

STATE OF NEW MEXICO  
BEFORE THE WATER QUALITY CONTROL COMMISSION



\_\_\_\_\_  
)  
)  
**In the Matter of:** )  
)

**PROPOSED AMENDMENT** )  
**TO 20.6.2 NMAC** )  
)  
\_\_\_\_\_ )

No.: 09-13 (R)

**NEW MEXICO ENVIRONMENT DEPARTMENT'S  
PETITION FOR REGULATORY CHANGE AND REQUEST FOR HEARING**

Pursuant to the New Mexico Water Quality Act ("WQA"), NMSA 1978 §§ 74-6-1 to 74-6-17 (2009); the *Schedule for Development of Dairy Facility Regulations* approved by the Water Quality Control Commission ("Commission") on July 14, 2009; and Section 301 of the *Guidelines for Water Quality Control Commission Regulation Hearings*, the New Mexico Environment Department ("NMED") petitions the Commission to amend the Ground and Surface Water Protection Regulations, 20.6.2 NMAC, to include new rules for the dairy industry.

NMED's proposed new rules for the dairy industry, attached as Attachment 1, consist of all new text. NMED proposes to insert the new rules for the dairy industry into sections 20.6.2.3200 through 20.6.2.3235 NMAC, which are reserved sections in 20.6.2 NMAC. NMED does not propose changes to existing sections of 20.6.2 NMAC.

**Statement of Reasons for the Rule Change**

A rule change is required by statute. During the first regular legislative session of 2009, the New Mexico legislature amended the WQA to require that the Commission adopt new rules for the dairy industry "to specify...the measures to be taken to prevent water pollution and to monitor water quality." NMSA 1978 §§ 74-6-4(K) (2009).

The WQA requires NMED, as the constituent agency for the Commission, to propose appropriate dairy industry rules for adoption by the Commission. *Id.* NMED developed its proposal for appropriate dairy industry rules through an extensive public and stakeholder process. As required by the WQA, NMED sought public input on the proposed rule change, established an advisory committee to seek advice on rules to propose and participated in stakeholder negotiations with representatives of the dairy industry, environmental organizations and groups of concerned citizens. The content of NMED's proposed new rules for the dairy industry is the product of this process.

Request for Hearing and Hearing Officer

NMED requests that the Commission schedule a rulemaking hearing to consider the proposed new rules for the dairy industry. Pursuant to the schedule approved by the Commission on July 14, 2009, NMED requests that the rulemaking hearing begin on March 9, 2010. NMED anticipates that the rulemaking hearing will take approximately five days. NMED also requests that Commissioner Steve Glass, who was appointed by the Commission as hearing officer for scheduling questions in this matter, be appointed by the Commission as hearing officer to conduct this rulemaking hearing. A proposed order to this effect accompanies this petition.

Respectfully submitted,

NEW MEXICO ENVIRONMENT DEPARTMENT



---

Adolfo J. Mendez II, Assistant General Counsel  
Office of General Counsel  
New Mexico Environment Department  
1190 St. Francis Drive  
PO Box 5469  
Santa Fe, New Mexico 87502  
Telephone: (505) 827-1031

CERTIFICATE OF SERVICE

I hereby certify that a copy of this New Mexico Environment Department's Petition for Regulatory Change and Request for Hearing was served on the following parties on December 22, 2009:

Joyce Medina  
Board Administrator  
NMED Boards and Commissions  
1190 St. Francis Dr., N2153  
Santa Fe, NM 87502

  
Melissa Mascareñas

# **ATTACHMENT 1**

**PROPOSED AMENDMENT TO  
20.6.2 NMAC**

1 **20.6.2.3200 SUPPLEMENTAL PERMITTING REQUIREMENTS FOR ALL DAIRY**  
2 **FACILITIES**

3 [20.6.2.3200 NMAC – N, effective date]  
4

5 **20.6.2.3201 PURPOSE:** The purpose of Sections 20.6.2.3200 through 20.6.2.3235 NMAC is to  
6 supplement the general permitting requirements of Sections 20.6.2.3000 through 20.6.2.3114 NMAC to  
7 control discharges specific to dairy facilities and their operations.  
8

9 **20.6.2.3202 DEFINITIONS:**

10 **A.** Terms defined in the Water Quality Act and Section 20.6.2.7 NMAC shall have the  
11 meaning as given in such.

12 **B.** Terms defined in this subsection shall have the meaning as given in such when used in  
13 Sections 20.6.2.3200 through 20.6.2.3235 NMAC, but not in other sections of this Part.

14 (1) “Adjacent” means lying near, but lacking actual contact along a boundary or at a point.

15 (2) “Applicant” means the person(s) applying for a new, renewed or modified discharge  
16 permit.

17 (3) “Construction quality assurance” or “CQA” means a planned system of activities  
18 necessary to ensure standards and procedures are adhered to and construction and installation meet design  
19 criteria, plans and specifications. A CQA includes inspections, verifications, audits, evaluations of material  
20 and workmanship necessary to determine and document the quality of the constructed impoundment or  
21 structure and corrective action when necessary.

22 (4) “Construction quality control” or “CQC” means a planned system of operational  
23 techniques and activities used to preserve the quality of materials and construction to specifications.  
24 Elements of a CQC include inspections, testing, data collection, data analysis and appropriate corrective  
25 actions.

26 (5) “Contiguous” means being in actual contact along a boundary or at a point.

27 (6) “CQA/CQC Report” means a report that summarizes all inspection, testing, data  
28 collection, data analysis and any corrective actions completed as part of CQA or CQC for a project.

29 (7) “Dairy facility” means the entire site where the discharge and associated activities will  
30 take place, including the production area and the land application area.

31 (8) “Discharge volume” means the maximum daily volume in gallons per day of wastewater  
32 authorized for discharge by a discharge permit.

33 (9) “EPA” means the United States Environmental Protection Agency.

34 (10) “Existing dairy facility” means a facility that is currently discharging, or has previously  
35 discharged and has not received a notice from the department verifying that closure and post-closure  
36 monitoring activities have been completed.

37 (11) “Expiration” means the date upon which the term of a discharge permit ends.

1 (12) "Field" means a unit of irrigated cropland within the land application area cultivated in  
2 the same manner to grow a specific crop for the uptake and removal of nutrients.

3 (13) "Flow meter" means a device used to measure the volume of water, wastewater or  
4 stormwater that passes a particular reference section in a unit of time.

5 (14) "Freeboard" means the vertical distance between the elevation at the lowest point of the  
6 top inside edge of the impoundment or spillway and the elevation of the water level in the impoundment.

7 (15) "Impoundment" means any structure used for storage or disposal by evaporation of  
8 wastewater, stormwater, or a combination of both wastewater and stormwater, or used for solids settling. A  
9 multiple-cell impoundment system having at least one shared berm or barrier whose smallest cells have a  
10 cumulative constructed capacity of 10 percent or less of the constructed capacity of the largest cell shall be  
11 considered a single impoundment for the purposes of these regulations.

12 (16) "Land application area" means irrigated and cultivated fields collectively authorized by  
13 the department through a discharge permit to receive wastewater or stormwater applications as a source of  
14 nutrients managed for crop production.

15 (17) "Land application data sheet" means a form used to report all nitrogen inputs applied to  
16 each field within the land application area, including the cropping status of the field at the time of  
17 application (i.e., fallow, corn, wheat, etc.).

18 (18) "New dairy facility" means a facility that has never before discharged wastewater.

19 (19) "Permittee" means any person who makes or controls a discharge and is responsible for  
20 compliance with the dairy facility's discharge permit.

21 (20) "Production area" means that part of the animal feeding operation that includes the  
22 animal confinement area, the manure, residual solids and compost storage area, the raw materials storage  
23 area, and the wastewater and stormwater containment areas. The animal confinement area includes but is  
24 not limited to open lots, housed lots, feedlots, confinement barns, stall barns, free stall barns, milkrooms,  
25 milk centers, cowyards, barnyards, hospital pens and barns, and animal walkways. The manure, residual  
26 solids and compost storage areas include, but are not limited to, storage sheds, stockpiles, static piles, and  
27 composting piles. The raw materials storage areas include, but are not limited, to feed silos, silage storage  
28 areas, feed storage barns, and liquid feed tanks. The wastewater and stormwater containment areas include,  
29 but are not limited to, settling separators, impoundments, sumps, runoff drainage channels, and areas within  
30 berms and diversions which prohibit uncontaminated stormwater from coming into contact with  
31 contaminants.

32 (21) "Spillway" means a structure used for controlled releases from an impoundment  
33 designed to receive stormwater, in a manner that protects the structural integrity of the impoundment.

34 (22) "Stormwater" means direct precipitation and runoff that comes into contact with water  
35 contaminants.

36 (23) "Unauthorized discharge" means a release of wastewater, stormwater or other  
37 substance containing water contaminants not approved by a discharge permit.

1 (24) “Wastewater” means water, except overflow from the drinking water system and  
2 stormwater, that has come into contact with water contaminants as a result from water being directly or  
3 indirectly used in the operation of the dairy facility for any of, but not limited to, the following: washing,  
4 cleaning, or flushing barns or other roof-covered production areas; washing of animals; spray-cooling of  
5 animals (except in open lots); and cooling or cleaning of feed mills and equipment.  
6

7 **20.6.2.3203 REQUIREMENTS FOR DISCHARGING FROM DAIRY FACILITIES:** A dairy  
8 facility shall not discharge without a discharge permit. All dairy facilities shall meet the requirements of  
9 Sections 20.6.2.3204, 20.6.2.3205, 20.6.2.3215, 20.6.2.3217, 20.6.2.3220, 20.6.2.3223, 20.6.2.3224,  
10 20.6.2.3227, 20.6.2.3230, 20.6.2.3233, 20.6.2.3234, and 20.6.2.3235 NMAC. In addition, the requirements  
11 of Sections 20.6.2.3101 through 20.6.2.3114 NMAC shall apply to all dairy facilities unless otherwise  
12 noted in Sections 20.6.2.3201 through 20.6.2.3235 NMAC. Dairy facilities that apply wastewater or  
13 stormwater to a land application area shall also meet the requirements of Sections 20.6.2.3221, 20.6.2.3225,  
14 and 20.6.2.3228 NMAC. Dairy facilities that dispose of wastewater or stormwater by evaporation shall  
15 also meet the requirements of Sections 20.6.2.3222, 20.6.2.3226, and 20.6.2.3229 NMAC. Dairy facilities  
16 submitting an application for a new discharge permit, shall meet the requirements of Sections 20.6.2.3205,  
17 20.6.2.3206, 20.6.2.3209, and 20.6.2.3216 NMAC. Dairy facilities submitting an application for a renewed  
18 or modified discharge permit, shall meet the requirements of Sections 20.6.2.3205 and 20.6.2.3207 NMAC.  
19 Dairy facilities submitting an application for a renewed discharge permit for closure, shall meet the  
20 requirements of Sections 20.6.2.3205 and 20.6.2.3208 NMAC. The requirements of this section do not  
21 relieve a dairy facility’s owner or operator from the requirement to comply with all applicable local, state  
22 and federal regulations or laws.  
23

24 **20.6.2.3204 FEES:** Notwithstanding the permit fee requirements of Subsection F of 20.6.2.3114  
25 NMAC:

26 **A.** A permit fee payment shall be remitted annually to the department no later than August 1  
27 of each year and shall continue until termination of the discharge permit. The annual permit fee payment  
28 amounts are specified in Table 1 of this section and are equal to one-fifth of the applicable permit fee,  
29 determined by the permitted discharge volume, specified in Table 1 of Section 20.6.2.3114 NMAC.

30 (1) The initial permit fee payment for any new or renewed discharge permit issued after the  
31 effective date of these regulations shall be remitted to the department no later than the first occurrence of  
32 August 1 following issuance of the new or renewed discharge permit. Subsequent permit fee payments  
33 shall be remitted pursuant to this subsection.

34 (2) After the effective date of these regulations, any dairy facility holding a discharge permit  
35 longer than the term of the discharge permit shall begin remitting annual permit fee payments pursuant to  
36 this subsection.

1 (3) For discharge permits which only authorize closure activities or post-closure monitoring,  
2 the annual permit fee payment amount shall be the lowest payment specified in Table 1 of this section.

3 **B.** The fee for a discharge permit modification as defined in Subsection C of 20.6.2.3114  
4 NMAC shall be remitted to the department within 30 days after the effective date of the discharge permit  
5 modification.

6 **C.** The filing fee for a discharge permit application as defined in Section 20.6.2.3114  
7 NMAC shall be remitted to the department at the time of submission of the application.

8 **20.6.2.3204 TABLE 1**

Permitted Discharge Volume	Annual Permit Fee Payment
Less than 10,000 gallons per day	\$230
10,000 to 49,999 gallons per day	\$460
50,000 to 99,999 gallons per day	\$690
100,000 gallons per day or greater	\$920

9  
10 **20.6.2.3205 GENERAL APPLICATION REQUIREMENTS FOR ALL DAIRY FACILITIES:**

11 **A.** Notwithstanding Subsection F of 20.6.2.3106 NMAC, an application for renewal of a  
12 discharge permit for existing dairy facilities shall be submitted to the department at least one year before  
13 the discharge permit expiration date. Notwithstanding Paragraph (11) of Subsection A of 20.6.2.3107  
14 NMAC, an existing discharge permit that will expire while a dairy facility is in the process of completing  
15 permanent closure measures or post-closure monitoring, shall submit a renewal application for closure.

16 **B.** In lieu of the information required by Subsection C of 20.6.2.3106 NMAC, a dairy  
17 facility applying for a new, renewed, or modified discharge permit shall submit the information and  
18 supporting technical documentation pursuant to this section and:

19 (1) For a new discharge permit, an application shall include the information required by  
20 Section 20.6.2.3206 NMAC;

21 (2) For a renewed or modified discharge permit, an application shall include the information  
22 required by Section 20.6.2.3207 NMAC; or

23 (3) For a renewed discharge permit for closure, an application shall include the information  
24 required by Section 20.6.2.3208 NMAC.

25 **C.** If a discharge permit for an existing dairy facility has expired on or before the effective  
26 date of this section and an application for renewal has not been submitted to the department, an application  
27 for a renewal, renewal and modification or closure for the dairy facility shall be submitted to the  
28 department within 90 days of the effective date of this section.

29 **D.** The department shall create a discharge permit application form specific to dairy facilities  
30 to collect the information required by this section. Applicants shall use the form to provide the information  
31 required by this section. An application shall consist of the form and required supporting documentation,  
32 regardless of previous submissions. The applicant shall attest to the truth of the information and supporting

1 documentation in the application, and sign the form. The form shall be signed in the presence of a notary  
2 and notarized.

3 E. The department shall, within 60 days of the department's receipt of proof of notice  
4 pursuant to Subsection D of 20.6.2.3108 NMAC, review the application for technical completeness. If  
5 proof of notice is not submitted to the department pursuant to Subsection D of 20.6.2.3108 NMAC, the  
6 department may deny the application.

7 F. For an application to be deemed technically complete, the application shall include the  
8 information required by Subsection B of this section. If the department determines that the application is  
9 not technically complete, the department shall provide notice of technical deficiency to the applicant by  
10 certified mail within 60 days of receipt of the applicant's proof of notice. The applicant shall have 30 days  
11 from the date of the notice of technical deficiency to provide the information required by this section.

12 (1) If an application is technically complete, then the department shall make available a  
13 proposed approval of a discharge permit (i.e., draft discharge permit) or denial of a discharge permit  
14 application, pursuant to Subsection H of 20.6.2.3108 NMAC.

15 (2) In the event that the applicant filing an application for a new discharge permit does not  
16 verify that the dairy facility complies with the setback requirements of Section 20.6.2.3216 NMAC,  
17 pursuant to Subsection D of 20.6.2.3206 NMAC, the application shall not be reviewed for technical  
18 completeness by the department, and shall be denied. The department shall provide notice of denial to the  
19 applicant by certified mail.

20 (3) In the event that the applicant filing an application for a new discharge permit does not  
21 provide to the department all information required by this section within 30 days of the date of the notice of  
22 technical deficiency, the application shall be denied. The department shall provide notice of denial to the  
23 applicant by certified mail.

24 (4) In the event that the applicant for a renewed or modified discharge permit does not  
25 provide to the department all information required by this section within 30 days of the date of the notice of  
26 technical deficiency, the department may deny the application or propose a discharge permit for approval  
27 consistent with the requirements of these regulations.

28 (a) If the department denies the application, the department shall provide notice of  
29 denial to the applicant by certified mail.

30 (b) If the department proposes approval of the discharge permit and the secretary  
31 approves the discharge permit, the permittee shall submit the required information in the notice of technical  
32 deficiency within 30 days of the effective date of the discharge permit.

33 (c) A request for a hearing on the proposed approval of a discharge permit (i.e., a draft  
34 discharge permit) regarding the inclusion of a discharge permit condition(s) requiring the submission of the  
35 information in the notice of technical deficiency shall be denied.

36 G. If the department proposes an additional condition in a discharge permit that is not  
37 included in these rules, the department shall include a written explanation of the reason for the additional

1 condition with the copy of the proposed approval sent to the applicant pursuant to Subsection H of  
2 20.6.2.3108 NMAC. Written comments or a request for hearing about the additional condition may be  
3 submitted to the department during the 30-day comment period provided by Subsection K of 20.6.2.3108  
4 NMAC.

5 **H.** With the exception of Paragraph (3) of Subsection C of 20.6.2.3109 NMAC and provided  
6 that the requirements of Section 20.6.2.3205 NMAC are met, the secretary shall approve the discharge  
7 permit or deny the application for a discharge permit pursuant to Section 20.6.2.3109 NMAC.

8  
9 **20.6.2.3206 APPLICATION REQUIREMENTS FOR NEW DISCHARGE PERMITS:**

10 **A.** An application for an initial discharge permit to be issued after the effective date of these  
11 regulations shall include the information in this section.

12 **B.** Contact Information:

13 (1) Applicant's name, title and affiliation with the dairy facility, mailing address, and phone  
14 number.

15 (2) Dairy facility manager's or operator's name, title and affiliation with the dairy facility,  
16 mailing address and phone number.

17 (3) Application preparer's name, title and affiliation with the dairy facility, mailing address,  
18 phone number and signature.

19 (4) The mailing address and phone number of any consultants contracted to assist the dairy  
20 facility with compliance.

21 **C.** Ownership and Real Property Agreements:

22 (1) Dairy facility owner's name, title, mailing address and phone number.

23 (a) If more than one person has an ownership interest in the dairy facility, then the  
24 applicant shall list all persons having an ownership interest in the dairy facility, including their names,  
25 titles, mailing addresses and phone numbers.

26 (b) If any corporate entity, including but not limited to a corporation or a limited  
27 liability company, holds an ownership interest in the dairy facility, then the applicant shall also list the  
28 name(s), as filed with the New Mexico Public Regulation Commission, of the corporate entity, the  
29 corporate entity's registered agent's name and address and the names of each of the corporate entity's  
30 owners, directors, officers, members or partners.

31 (2) If the applicant is not the owner of the real property upon which the dairy facility is or  
32 will be situated, or upon which dairy operations and land application will occur, then the applicant shall  
33 submit a copy of any lease agreement or other agreement which authorizes the use of the real property for  
34 the duration of the term of the requested permit. Lease prices or other price terms may be redacted.

35 **D. Setbacks:** Verification that the proposed layout of the dairy facility complies with the  
36 setback requirements of Section 20.6.2.3216 NMAC.

37 **E. Dairy Facility Information and Location:**

1 (1) Dairy facility name, physical address and county.

2 (2) Township, Range and Section for the entire dairy facility, which includes the production  
3 area and fields within the land application area.

4 **F. Public Notice Preparation:** The applicant shall identify a newspaper of general  
5 circulation for the future display ad publication, the proposed location(s) of the 2-foot by 3-foot sign, and  
6 the proposed off-site location of the 8.5-inch by 11-inch flyer, as required by Section 20.6.2.3108 NMAC.

7 **G. Pre-Discharge Total Dissolved Solids Concentration in Ground Water:** Pursuant to  
8 Paragraph (3) of Subsection C of 20.6.2.3106 NMAC, an application shall include the pre-discharge total  
9 dissolved solids concentration from analytical results of ground water obtained from the on-site test boring  
10 pursuant to Subsection Z of 20.6.2.3220 NMAC. A copy of the laboratory analysis shall be submitted.

11 **H. Discharge Volume:**

12 (1) Maximum daily discharge volume proposed, and a description of the methods and  
13 calculations used to determine the proposed daily discharge volume.

14 (2) Identification of all sources of wastewater which may include, but are not limited to,  
15 hospital barns, maternity barns, bottle-washing operations and parlor/equipment washdown.

16 (3) Animal washing method(s) employed and the estimated daily discharge volume for the  
17 method(s).

18 (4) Other wastewater discharges (i.e., domestic or industrial) at the dairy facility not  
19 generated by dairy operations. Permit identification numbers shall be submitted for those discharges that  
20 are already permitted.

21 **I. Wastewater Quality:** Applications shall include estimated concentrations of wastewater  
22 quality for total dissolved solids, chloride, sulfate, nitrate as nitrogen, total Kjeldahl nitrogen and other  
23 constituents of concern that may be included in the wastewater at the dairy facility based on data collected  
24 at other dairy facilities with similar discharge(s) volumes and wastewater management systems.

25 **J. Identification and Physical Description of the Dairy Facility:**

26 (1) A scaled map of the entire dairy facility pursuant to Subsection W of 20.6.2.3220  
27 NMAC.

28 (2) Identification of each proposed impoundment shall include information regarding its  
29 location; purpose to store wastewater or stormwater, or dispose of it by evaporation; liner material; and  
30 storage or evaporative disposal capacity.

31 (3) Identification of each field within the proposed land application area shall include  
32 information regarding its location; acreage; proposed method of wastewater and stormwater application;  
33 and proposed method of irrigation water application.

34 (4) Identification of proposed additional wastewater and stormwater system components  
35 such as, but not limited to, sumps and mix tanks shall include information for each component regarding its  
36 location; purpose; construction material; dimensions; and capacity.

1 (5) A description of the proposed location of all manure, silage and compost storage areas at  
2 the dairy facility; and a description of the proposed method(s) employed to protect the areas from  
3 stormwater runoff and run-on, and to minimize leachate.

4 **K. Flow Metering:** A flow metering system pursuant to Subsections K, L, M, N and O of  
5 20.6.2.3220 NMAC and Subsections I and J of 20.6.2.3221 NMAC including:

6 (1) Identification of method(s) (pumped versus gravity flow) of wastewater discharge,  
7 stormwater transfer and wastewater and stormwater land application.

8 (2) A description of the proposed flow measurement devices for each flow method.

9 (3) Identification of flow meter locations.

10 **L. Depth-to-Most-Shallow Ground Water and Ground Water Flow Direction:**

11 (1) Depth-to-most-shallow ground water shall be determined by one site-specific test boring  
12 pursuant to Subsection Z of 20.6.2.3220 NMAC.

13 (2) Ground water flow direction of the most-shallow ground water beneath the dairy facility  
14 shall be based on the most recent regional water level data or published hydrogeologic information. Survey  
15 data from nearby monitoring wells and a ground water elevation contour map indicating the direction of  
16 ground water flow may be included. The sources of all information used to determine ground water flow  
17 direction shall be provided with the application.

18 **M. Monitoring Wells:** The proposed monitoring well locations pursuant to Subsections A  
19 and B of 20.6.2.3223 NMAC.

20 **N. Surface Soil Survey and Vadose Zone Geology:**

21 (1) The most recent regional soil survey map and associated descriptions identifying surface  
22 soil type(s).

23 (2) The lithologic log obtained from the on-site test boring pursuant to Subsection Z of  
24 20.6.2.3220 NMAC to identify the geological profile of the vadose zone.

25 **O. Location Map:** A location map with topographic surface contours identifying all of the  
26 following features located within a one-mile radius of the dairy facility:

27 (1) Watercourses, lakebeds, sinkholes, playa lakes and springs (springs used to provide  
28 water for human consumption shall be so denoted).

29 (2) Wells supplying water for a public water system and private domestic water wells.

30 (3) Irrigation supply wells.

31 (4) Ditch irrigations systems, acequias, irrigation canals and drains.

32 **P. Flood Zone Map:** The most recent 100-year flood zone map developed by Federal  
33 Emergency Management Administration, FEMA, documenting flood potential for the dairy facility, and a  
34 description of any engineered measures used for flood protection.

35 **Q. Engineering and Surveying:** Pursuant to Section 20.6.2.3217 NMAC an application  
36 shall include:

37 (1) Plans and specifications for impoundments and associated liners.

1 (2) Plans and specifications for a manure solids separator(s).

2 (3) A grading and drainage report and plan.

3 **R. Land Application Areas:** For dairy facilities with a land application area, the  
4 application shall include:

5 (1) Documentation of irrigation water rights pursuant to Subsection D of 20.6.2.3221  
6 NMAC.

7 (2) A nutrient management plan (NMP) pursuant to Subsections K and L of 20.6.2.3221  
8 NMAC.

9 (3) A written description of the wastewater sampling location(s) between the manure solids  
10 separator(s) and wastewater impoundment(s) pursuant to Subsection C of 20.6.2.3225 NMAC.

11  
12 **20.6.2.3207 APPLICATION REQUIREMENTS FOR DISCHARGE PERMIT RENEWAL OR**  
13 **MODIFICATION:**

14 **A.** An application for a renewed or modified discharge permit shall include the information  
15 in this section.

16 **B. Contact Information:**

17 (1) Applicant's name, title and affiliation with the dairy facility, mailing address, and phone  
18 number.

19 (2) Dairy facility manager's or operator's name, title and affiliation with the dairy facility,  
20 mailing address and phone number.

21 (3) Application preparer's name, title and affiliation with the dairy facility, mailing address,  
22 phone number and signature.

23 (4) The mailing address and phone number of any consultants contracted to assist the dairy  
24 facility with compliance.

25 **C. Ownership and Real Property Agreements:**

26 (1) Dairy facility owner's name, title, mailing address and phone number.

27 (a) If more than one person has an ownership interest in the dairy facility, then the  
28 applicant shall list all persons having an ownership interest in the dairy facility, including their names,  
29 titles, mailing addresses and phone numbers.

30 (b) If any corporate entity, including but not limited to a corporation or a limited  
31 liability company, holds an ownership interest in the dairy facility, then the applicant shall also list the  
32 name(s), as filed with the New Mexico Public Regulation Commission, of the corporate entity, the  
33 corporate entity's registered agent's name and address and the names of each of the corporate entity's  
34 owners, directors, officers, members or partners.

35 (2) If the applicant is not the owner of the real property upon which the dairy facility is or  
36 will be situated, or upon which dairy operations and land application will occur, then the applicant shall

1 submit a copy of any lease agreement or other agreement which authorizes the use of the real property for  
2 the duration of the term of the requested permit. Lease prices or other price terms may be redacted.

3 **D. Dairy Facility Information and Location:**

- 4 (1) Dairy facility name, physical address and county.  
5 (2) Township, Range and Section for the entire dairy facility, which includes the production  
6 area and fields within the land application area.  
7 (3) Date of initial discharge at the dairy facility.

8 **E. Public Notice Preparation:**

9 (1) An application for a modified or renewed and modified discharge permit shall identify a  
10 newspaper of general circulation for the future display ad publication, the proposed location(s) of the 2-foot  
11 by 3-foot sign, and the proposed off-site location of the 8.5-inch by 11-inch flyer, as required by Subsection  
12 B of 20.6.2.3108 NMAC.

13 (2) An application for a renewed discharge permit without modification shall identify a  
14 newspaper of general circulation for the future display ad publication as required by Subsection C of  
15 20.6.2.3108 NMAC.

16 **F. Pre-Discharge Total Dissolved Solids Concentration in Ground Water:** Pursuant to  
17 Paragraph (3) of Subsection C of 20.6.2.3106 NMAC, an application shall include the pre-discharge total  
18 dissolved solids concentration in ground water, sample source (e.g., upgradient monitoring well, on-site  
19 supply well, nearby off-site supply well) and a copy of the laboratory analysis.

20 **G. Discharge Volume:**

- 21 (1) Maximum daily discharge volume proposed, and a description of the methods and  
22 calculations used to determine the proposed daily discharge volume.  
23 (2) Identification of all sources of wastewater which may include, but are not limited to,  
24 hospital barns, maternity barns, bottle-washing operations and parlor/equipment washdown.  
25 (3) Animal washing method(s) employed and the estimated daily discharge volume for the  
26 method(s).  
27 (4) Other wastewater discharges (i.e., domestic or industrial) at the dairy facility not  
28 generated by dairy operations. Permit identification numbers shall be submitted for those discharges that  
29 are already permitted.

30 **H. Identification and Physical Description of Dairy Facility:**

- 31 (1) A scaled map of the entire dairy facility pursuant to Subsection W of 20.6.2.3220  
32 NMAC.  
33 (2) Identification of each proposed, existing and closed impoundment, including previously  
34 utilized impoundments to which wastewater discharge or stormwater collection has ceased. Information  
35 for each impoundment shall be provided regarding its location; purpose to store wastewater or stormwater,  
36 or dispose of it by evaporation; date of original construction; past and existing liner material; date of  
37 current liner installation; and storage or evaporative disposal capacity.

1 (3) Identification of each field within the land application area, including existing, proposed,  
2 and previously utilized fields to which wastewater or stormwater application has ceased. Information for  
3 each field shall be provided regarding its location; date of initial application of wastewater or stormwater;  
4 acreage; status with regard to having received wastewater or stormwater (i.e. never, inactive, active);  
5 current method of backflow prevention employed; current method of wastewater and stormwater  
6 application; and current method of irrigation water application.

7 (4) The identification of additional wastewater and stormwater system components such as,  
8 but not limited to, sumps and mix tanks. Information for each component shall be provided regarding its  
9 location; purpose; date of original construction; construction material; dimensions; and capacity.

10 (5) Settled solids thickness measurements for each existing wastewater and combination  
11 wastewater/stormwater impoundment pursuant to Subsection D of 20.6.2.3220 NMAC.

12 (6) A description of proposed and existing method(s) of solids separation pursuant to  
13 Paragraph (5) of Subsection C of 20.6.2.3217 NMAC and Subsection F of 20.6.2.3220 NMAC.

14 (7) A description of the location of all manure, silage and compost storage areas at the dairy  
15 facility; and a description of the method(s) employed to protect the areas from stormwater runoff and run-  
16 on, and to minimize leachate.

17 **I. Flow Metering:** A flow metering system pursuant to Subsections K, L, M, N and O of  
18 20.6.2.3220 NMAC and Subsections I and J of 20.6.2.3221 NMAC including:

19 (1) Identification of method(s) of wastewater discharge and stormwater transfer or  
20 application (pumped versus gravity flow).

21 (2) A description of the existing and proposed flow measurement devices for each flow  
22 method.

23 (3) Identification of flow meter locations.

24 **J. Depth-to-Most-Shallow Ground Water and Ground Water Flow Direction:**

25 (1) Applications for existing dairy facilities shall provide depth-to-most-shallow ground  
26 water and indicate ground water flow direction beneath the dairy facility on a ground water elevation  
27 contour map which is developed based upon the most recent ground water levels obtained with a water  
28 level measuring device and survey data from on-site monitoring wells obtained from a survey, pursuant to  
29 Section 20.6.2.3223 NMAC.

30 (2) If a dairy facility does not have a monitoring well intersecting most-shallow ground  
31 water the applicant shall provide:

32 (a) The depth-to-most-shallow ground water determined by one site-specific test  
33 boring pursuant to Subsection Z of 20.6.2.3220 NMAC.

34 (b) The ground water flow direction of the most-shallow ground water beneath the  
35 dairy facility based upon the most recent regional water level data or published hydrogeologic information.  
36 Survey data from nearby monitoring wells and a ground water elevation contour map indicating the

1 direction of ground water flow may be included. The sources of all information used to determine ground  
2 water flow direction shall be provided with the application.

3 **K. Monitoring Wells:**

4 (1) Construction and lithologic logs of all existing monitoring wells that indicate the date of  
5 installation and well driller.

6 (2) Identification of monitoring well locations, proposed and existing, pursuant to  
7 Subsections A and B of 20.6.2.3223 NMAC.

8 **L. Surface Soil Survey and Vadose Zone Geology:**

9 (1) The most recent regional soil survey map and associated descriptions identifying surface  
10 soil type(s).

11 (2) An application shall include lithologic logs from on-site monitoring wells.

12 (3) If a dairy facility does not have a monitoring well intersecting most-shallow ground  
13 water, the application shall include the lithologic log obtained from the on-site test boring pursuant to  
14 Subsection Z of 20.6.2.3220 NMAC to identify the geological profile of the vadose zone.

15 **M. Location Map:** A location map with topographic surface contours identifying all of the  
16 following features located within a one-mile radius of the dairy facility:

17 (1) Watercourses, lakebeds, sinkholes, playa lakes and springs (springs used to provide  
18 water for human consumption shall be so denoted).

19 (2) Wells supplying water for a public water system and private domestic water wells.

20 (3) Irrigation supply wells.

21 (4) Ditch irrigations systems, acequias, irrigation canals and drains.

22 **N. Flood Zone Map:** The most recent 100-year flood zone map developed by Federal  
23 Emergency Management Administration, FEMA, documenting flood potential for the dairy facility, and a  
24 description of any engineered measures used for flood protection.

25 **O. Engineering and Surveying:**

26 (1) Plans and specifications for new or improved structures and associated liners proposed  
27 by the applicant pursuant to Section 20.6.2.3217 NMAC.

28 (2) Record drawings and final specifications for existing structures and associated liners.  
29 For existing impoundments where record drawings and final specifications do not exist, survey data and  
30 capacity calculations shall be submitted pursuant to Subsection C of 20.6.2.3220 NMAC.

31 (3) A grading and drainage report and plan pursuant to Paragraph (6) of Subsection C of  
32 20.6.2.3217 NMAC.

33 **P. Land Application Area:** For dairy facilities with a land application area, the application  
34 shall include:

35 (1) Documentation of irrigation water rights pursuant to Subsection D of 20.6.2.3221  
36 NMAC.

1 (2) Documentation confirming the existence of infrastructure necessary to distribute and  
2 apply wastewater and stormwater to the land application area pursuant to Subsection G of 20.6.2.3221  
3 NMAC.

4 (3) A nutrient management plan (NMP) pursuant to Subsections K and L of 20.6.2.3221  
5 NMAC.

6 (4) A written description of the wastewater sampling location(s) between the manure solids  
7 separator(s) and wastewater impoundment(s) pursuant to Subsection C of 20.6.2.3225 NMAC.

8  
9 **20.6.2.3208 APPLICATION REQUIREMENTS FOR DAIRY FACILITY CLOSURE:**

10 A. An application for closure shall include the information required by Subsections B, C, D,  
11 E, F, J, K, L, M and N of 20.6.2.3207 NMAC, Paragraphs (1), (2), (3) and (4) of Subsection H of  
12 20.6.2.3207 NMAC. For dairy facilities with or previously having a land application area, the application  
13 shall also include Paragraph (2) of Subsection P of 20.6.2.3207 NMAC, specifically pertaining to the past  
14 method(s) of wastewater discharge and stormwater application to the land application area.

15  
16 **20.6.2.3209 ADDITIONAL PUBLIC NOTICE REQUIREMENTS FOR DAIRY FACILITIES:**

17 A. The requirements of this section shall apply to dairy facilities whose application for a  
18 new discharge permit is received by the department after the effective date of these regulations.

19 B. In lieu of the requirement for public notice specified in Paragraph (2) of Subsection B of  
20 20.6.2.3108 NMAC, the applicant shall provide written notice of the discharge by mail to owners of record  
21 of all properties within a one-mile distance from the boundary of the property where the discharge site is  
22 located. If there are no properties other than properties owned by the discharger within a one-mile distance  
23 of the boundary of the property where the discharge site is located, the applicant shall provide notice to  
24 owners of record of the next nearest properties not owned by the discharger.

25 C. Proof of notice required by Subsection D of 20.6.2.3108 NMAC shall include an affidavit  
26 of mailing(s) and a list of property owner(s) notified pursuant to Subsection B of this section.

27  
28 **20.6.2.3210 – 20.6.2.3214: [RESERVED]**

29  
30 **20.6.2.3215 PROCEDURES FOR REQUESTING PUBLIC HEARINGS ON PERMITTING**  
31 **ACTIONS OF DAIRY FACILITIES:**

32 A. Requests for a hearing from any person, including the applicant for a discharge permit, on  
33 the proposed approval of a discharge permit or denial of a discharge permit application shall be postmarked  
34 on or before the end of the comment period and submitted to the department pursuant to Subsection K of  
35 20.6.2.3108 NMAC. Requests that do not meet all requirements of Subsection K of 20.6.2.3108 NMAC  
36 and this section shall be denied. The department shall provide notice of hearing denial by certified mail to  
37 the person(s) requesting a hearing.

1           B.       Requests for a hearing on the proposed approval of a discharge permit (i.e., a draft  
2 discharge permit) shall identify the specific discharge permit requirements or conditions being disputed and  
3 the reasons such requirements or conditions are being disputed. Hearings held upon the secretary's  
4 approval shall be limited in scope to the disputed requirements or conditions identified in the requests.  
5 Requests for a hearing that fail to identify requirements or conditions in dispute and the reasons for dispute  
6 shall be denied. The department shall provide notice of hearing denial by certified mail to the person(s)  
7 requesting a hearing.

8           C.       Requests for a hearing on the denial of a discharge permit application due to failure to  
9 provide information required by these regulations shall be denied. The department shall provide notice of  
10 hearing denial by certified mail to the person(s) requesting a hearing.

11  
12 **20.6.2.3216       SETBACK REQUIREMENTS FOR DAIRY FACILITIES:**

13           A.       The requirements of this section shall apply to dairy facilities whose application for a  
14 new discharge permit is received by the department after the effective date of these regulations.

15           B.       Setback requirements shall be measured as horizontal map distances.

16           C.       Setback requirements shall apply on the date of receipt by the department of the initial  
17 application.

18           D.       **Production Area Setback Requirements:**

19           (1)       The production area, excluding feed storage silos, feed storage barns and liquid feed  
20 tanks, shall be located:

21                   (a)       greater than 200 feet from the 100-year flood zone of any watercourse, or from the  
22 ordinary high-water mark of any watercourse for which no 100-year flood zone has been established. This  
23 setback distance shall not apply to ditch irrigations systems, acequias, irrigation canals and drains.

24                   (b)       greater than 200 feet (measured from the ordinary high-water mark) from a  
25 lakebed, sinkhole or playa lake.

26                   (c)       greater than 200 feet from any spring identified on a US Geological Survey  
27 (USGS) topographic map and not identified as a supply of water for human consumption.

28                   (d)       greater than 350 feet from a private domestic water well or spring that supplies  
29 water for human consumption.

30                   (e)       greater than 1000 feet from any water well or spring that supplies water for a  
31 public water system as defined by Part 20.7.10 NMAC, unless a wellhead protection program established  
32 by the public water system requires a greater distance.

33           (2)       The requirements of Subparagraph (d) of Paragraph (1) of this subsection shall not apply  
34 to wells or springs that supply water to the dairy facility for human consumption and are located on the  
35 dairy facility.

1 (3) Setback distances for impoundments shall be measured from the toe of the outside berm  
2 of above-grade impoundments or the top inside edge of the impoundment for sub-grade impoundments;  
3 distances for all other features shall be measured from the outer extent of the feature.

4 **E. Land Application Area Setback Requirements:**

5 (1) Any field within a land application area shall be located:

6 (a) greater than 100 feet from the 100-year flood zone of any watercourse, or from the  
7 ordinary high-water mark of any watercourse for which no 100-year flood zone has been established. This  
8 setback distance shall not apply to ditch irrigations systems, acequias, irrigation canals and drains.

9 (b) greater than 100 feet (measured from the ordinary high-water mark) from any  
10 lakebed, sinkhole or playa lake.

11 (c) greater than 100 feet from a private domestic water well or spring that supplies  
12 water for human consumption.

13 (d) greater than 200 feet from any water well or spring that supplies water for a public  
14 water system as defined by Part 20.7.10 NMAC, unless a wellhead protection program established by the  
15 public water system requires a greater distance.

16 (2) The requirements of Subparagraph (c) of Paragraph (1) of this subsection shall not apply  
17 to wells or springs that supply water for human consumption to the dairy facility and are located on the  
18 dairy facility.

19 (3) Setback distances for fields shall be measured from the outer edge of the field.  
20

21 **20.6.2.3217 ENGINEERING AND SURVEYING REQUIREMENTS FOR ALL DAIRY**  
22 **FACILITIES:**

23 **A. Practice of Engineering:** All plans and specifications, supporting design calculations,  
24 record drawings, final specifications, final capacity calculations, grading and drainage report and plan, and  
25 other work products requiring the practice of engineering shall bear the seal and signature of a licensed  
26 New Mexico professional engineer pursuant to the New Mexico Engineering and Surveying Practice Act,  
27 Sections 61-23-1 through 61-23-32 NMSA 1978, and the rules promulgated under that authority.

28 **B. Practice of Surveying:** All surveys of wastewater, stormwater, and combination  
29 wastewater/stormwater impoundments, monitoring well locations and casing elevations, and other work  
30 products requiring the practice of surveying shall bear the seal and signature of a licensed New Mexico  
31 professional surveyor pursuant to the New Mexico Engineering and Surveying Practice, Sections 61-23-1  
32 through 61-23-32 NMSA 1978, and the rules promulgated under that authority.

33 **C. Engineering Plans and Specifications Requirements:**

34 (1) **Impoundment Plans and Specifications:** Any applicant or permittee proposing or  
35 required to construct a new impoundment or to improve an existing wastewater, stormwater, or  
36 combination wastewater/stormwater impoundment, including relining of an existing impoundment, shall  
37 submit detailed and complete construction plans and specifications and supporting design calculations

1 developed pursuant to this section and Section 20.6.2.3220 NMAC. The applicant or permittee proposing  
2 or required to construct an impoundment shall document compliance with all requirements of the Dam  
3 Safety Bureau of the State Engineer pursuant to Section 72-5-32 NMSA 1978, and rules promulgated under  
4 that authority, unless exempt by law from such requirements. In the event of improvement(s) to an existing  
5 impoundment, the construction plans and specifications shall also address the management of wastewater  
6 or stormwater during preparation and construction of the improvements.

7 (a) Construction plans and specifications proposed by the applicant or permittee shall  
8 be submitted to the department with the application for a new, renewed or modified discharge permit.

9 (b) Construction plans and specifications not proposed by the applicant or permittee  
10 but required to achieve compliance with these regulations shall be submitted to the department within 90  
11 days of the effective date of the discharge permit.

12 (2) **Impoundment CQA/CQC:** Construction of a new impoundment or improvement to an  
13 existing impoundment shall be done in accordance with a Construction Quality Assurance/Construction  
14 Quality Control (CQA/CQC) Plan. A CQA/CQC Plan shall be included as part of the design plans and  
15 specifications. The CQA/CQC Plan shall outline the observations and tests to be used to ensure that  
16 construction of the impoundment meets or exceeds all design criteria, plans and specifications. All testing  
17 and evaluation reports shall be certified by a licensed New Mexico professional engineer experienced in  
18 lagoon construction and liner installation. The CQA/CQC Plan shall include, at a minimum, the following  
19 elements:

20 (a) Identity of persons responsible for overseeing the CQA/CQC program. The person  
21 responsible for compliance with the CQA/CQC plan shall be a licensed New Mexico professional engineer  
22 experienced in lagoon construction and liner installation, and have at least three years experience in lagoon  
23 construction and lining.

24 (b) Discussion of how inspections will be performed.

25 (c) Location, availability, applicability and calibration of testing equipment and  
26 facilities, both field and laboratory.

27 (d) Procedures for observing and testing the liner material.

28 (e) Procedures for reviewing inspection test results and laboratory and field sampling  
29 test results.

30 (f) Actions to be taken to replace or repair liner material should deficiencies be  
31 identified.

32 (g) Procedures for seaming synthetic liners.

33 (h) Reporting procedures for all inspections and test data.

34 (3) **Impoundment Improvement - Wastewater/Stormwater Management:** Any  
35 applicant or permittee proposing or required to improve an existing wastewater, stormwater, or  
36 combination wastewater/stormwater impoundment, including relining of an existing impoundment, shall  
37 submit a plan for wastewater or stormwater management during improvement of an existing impoundment

1 as part of the design plans and specifications. The plan for wastewater or stormwater management shall  
2 include the following minimum elements and be implemented upon department approval:

3 (a) A description of how on-going wastewater discharges or stormwater collection  
4 will be handled and disposed of during improvement to the impoundment.

5 (b) A description of how solids and wastewater or stormwater within the  
6 impoundment will be removed and disposed prior to beginning improvement to the impoundment.

7 (c) A schedule for implementation through completion of the project.

8 (d) Should the plan propose the use of a discharge location other than those authorized  
9 by the effective discharge permit, a request for temporary permission to discharge shall be submitted to the  
10 department.

11 (4) **Manure Solids Separation Plans and Specifications - New Wastewater System:** Any  
12 applicant or permittee proposing or required to construct a new manure solids separator as a component of  
13 a newly designed wastewater storage or disposal system shall submit construction plans and specifications  
14 and supporting design calculations to include the separator, pursuant to this section.

15 (a) Construction plans and specifications proposed by the applicant or permittee shall  
16 be submitted to the department with the application for a new, renewed or modified discharge permit.

17 (b) Construction plans and specifications not proposed by the applicant or permittee  
18 but required to achieve compliance with these regulations shall be submitted to the department within 90  
19 days of the effective date of the discharge permit.

20 (5) **Manure Solids Separation Plans and Specifications - Existing Wastewater System:**  
21 Any applicant or permittee proposing or required to construct a new manure solids separator as a  
22 component of an existing wastewater storage or disposal system shall submit a scaled design schematic and  
23 supporting documentation including design calculations. The separator shall be designed to accommodate,  
24 at a minimum, the maximum daily discharge volume authorized by the discharge permit, and the manure  
25 solids associated with the wastewater discharge. Components of the separator functioning to collect,  
26 contain or store manure solids prior to removal or land application shall be designed with an impervious  
27 material(s) to minimize generation and infiltration of leachate.

28 (a) A scaled design schematic and supporting documentation for a proposed separator  
29 shall be submitted to the department with the application for a new, renewed or modified discharge permit.

30 (b) A scaled design schematic and supporting documentation for a separator not  
31 proposed by the applicant or permittee but required to achieve compliance with these regulations shall be  
32 submitted to the department within 90 days of the effective date of the discharge permit.

33 (6) **Grading and Drainage Report and Plan:** The applicant or permittee shall submit with  
34 the application for a new, renewed or modified discharge permit, a grading and drainage report and a  
35 grading and drainage plan, including supplemental information associated with the plan.

36 (a) The grading and drainage report shall include, at a minimum, the following  
37 information: a description of the drainage concept for the dairy facility; a description of existing dairy

1 facility drainage conditions; a description of the proposed post-development drainage conditions; a  
2 description of the calculations performed to support the drainage analysis; and a map prepared from a 7.5  
3 minute quadrangle map showing the dairy facility location and drainage basin influences on drainage flows  
4 at the dairy facility from on-site and off-site locations.

5 (b) The grading and drainage plan shall include, at a minimum, the following  
6 information: north arrow and scale; property boundaries; delineation of off-site watersheds that contribute  
7 drainage to the dairy facility; permanent benchmark location, description and elevation; existing and  
8 proposed land contours; spot elevations at key points, grade breaks, critical locations, floors or pads of  
9 existing and proposed structures, and inverts of piping associated with the drainage system; identification  
10 of all existing and proposed on-site structures, including drainage features; identification of internal  
11 contributory drainage areas, including roof areas, parking lots, and other disturbed areas; flows in cubic  
12 feet/second and flow lines defined by arrows and spot elevations; and details of impoundments, inlets,  
13 rundowns, emergency spillways, impoundment outlets, slopes, and all other significant drainage structures  
14 with contours, cross-sections and spot elevations.

15 (c) Supplemental information supporting the grading and drainage plan shall be  
16 submitted to the department with the plan and shall include, at a minimum, the following information:  
17 calculations for both existing and post-development drainage conditions; hydraulic calculations  
18 demonstrating capacity or adequacy of existing and proposed stormwater impoundments; hydraulic  
19 calculations demonstrating capacity of existing and proposed conveyance channels to contain and transport  
20 runoff to the stormwater impoundment(s); and a description of computer software, documents, circulars,  
21 manuals, etc. used to develop the drainage calculations.

22 (7) **Flow Metering Plans and Specifications:** Any applicant or permittee proposing or  
23 required to install a flow meter(s) shall submit construction plans and specifications for the device.

24 (a) Construction plans and specifications proposed by the applicant or permittee shall  
25 be submitted to the department with the application for a new, renewed or modified discharge permit.

26 (b) Construction plans and specifications not proposed by the applicant or permittee  
27 but required to achieve compliance with these regulations shall be submitted to the department within 90  
28 days of the effective date of the discharge permit.

29 **D. Engineering Design Requirements:**

30 (1) **Impoundment Capacities – Wastewater or Wastewater/Stormwater Combination:**

31 (a) Capacity requirements for dairy facilities discharging to a land application area:  
32 (i) Wastewater impoundments intended to store wastewater prior to discharging  
33 to a land application area shall be designed to contain cumulatively the maximum daily discharge volume  
34 authorized by the discharge permit for a minimum period of 60 days to accommodate periods when land  
35 application is not feasible, while preserving two feet of freeboard.

36 (ii) Combination wastewater/stormwater impoundments intended to contain  
37 both wastewater and stormwater runoff for storage prior to discharging to a land application area shall be

1 designed to contain cumulatively the maximum daily discharge volume authorized by the discharge permit  
2 for a minimum period of 60 days to accommodate periods when land application is not feasible; and  
3 stormwater runoff and direct precipitation as specified by current EPA regulatory requirements for  
4 Concentrated Animal Feeding Operations pursuant to 40 Code of Federal Regulations, Parts 122 and 412, as  
5 amended, while preserving two feet of freeboard.

6 (b) Capacity requirements for dairy facilities discharging to an evaporative wastewater  
7 disposal system:

8 (i) Wastewater impoundments intended to dispose of wastewater by evaporation  
9 shall be designed to contain cumulatively the maximum daily discharge volume authorized by the  
10 discharge permit for disposal by evaporation, while preserving two feet of freeboard.

11 (ii) Combination wastewater/stormwater impoundments intended to dispose of  
12 both wastewater and stormwater runoff by evaporation shall be designed to contain cumulatively the  
13 maximum daily discharge volume authorized by the discharge permit; and stormwater runoff and direct  
14 precipitation as specified by current EPA regulatory requirements for Concentrated Animal Feeding  
15 Operations pursuant to 40 Code of Federal Regulations, Parts 122 and 412, as amended, while preserving two  
16 feet of freeboard.

17 (c) Impoundments designed and used for solids settling shall not be used to satisfy the  
18 impoundment capacity requirements of this subsection.

19 (2) **Impoundment Capacity - Stormwater:** Stormwater impoundments intended to contain  
20 only stormwater shall be designed to contain stormwater runoff and direct precipitation as specified by  
21 current EPA regulatory requirements for Concentrated Animal Feeding Operations pursuant to 40 Code of  
22 Federal Regulations, Parts 122 and 412, as amended.

23 (3) **Stormwater Conveyance Channels:** Stormwater conveyance channels shall be  
24 designed to contain and transport stormwater runoff and direct precipitation to stormwater impoundments  
25 as specified by current EPA regulatory requirements for Concentrated Animal Feeding Operations pursuant to  
26 40 Code of Federal Regulations, Parts 122 and 412, as amended.

27 (4) **Impoundment Design and Construction - General:** Impoundments shall meet the  
28 following design and construction requirements:

29 (a) Inside slopes shall be a maximum of three (horizontal) to one (vertical), and a  
30 minimum of four (horizontal) to one (vertical). Outside slopes shall be a maximum of three (horizontal) to  
31 one (vertical).

32 (b) Sub-grade shall be compacted to a minimum of 95 percent of standard proctor  
33 density.

34 (c) The finished grade of the floor of the impoundment shall be as uniform as possible  
35 and shall not have surface deviations which vary more than +/- 1.5 inches from the finished grade.

36 (d) The minimum dike width shall be eight feet to allow vehicle traffic for  
37 maintenance.

- 1 (5) **Impoundment Design and Construction - Liner:** Impoundments requiring a liner  
2 shall meet the following additional design and construction requirements:
- 3 (a) The liner shall be installed with sufficient slack in the liner material to  
4 accommodate shrinkage due to temperature changes. Folds in the liner material shall not be present in the  
5 completed liner.
- 6 (b) The sub-grade shall be free of sharp rocks, vegetation and stubble to a depth of at  
7 least six inches below the liner. Liners shall be placed on a sub-grade of sand or fine soil. The surface in  
8 contact with the liner shall be smooth to allow for good contact between liner and sub-grade. The surface  
9 shall be dry during liner installation.
- 10 (c) Liners shall be anchored in an anchor trench. The trench shall be a minimum of 12  
11 inches wide, 12 inches deep and shall be set back at least 24 inches from the top inside edge of the  
12 impoundment.
- 13 (d) Liner panels shall be oriented such that all sidewall seams are vertical.
- 14 (e) A liner vent system shall be installed if an impoundment is installed over areas of  
15 decomposing organic materials.
- 16 (f) Any opening in the liner through which a pipe or other fixture protrudes shall be  
17 sealed in accordance with the liner manufacturer's requirements. Liner penetrations shall be detailed in the  
18 construction plans and record drawings.
- 19 (g) The liner shall be installed by, or the installation supervised by, an individual that  
20 has the necessary training and experience as required by the liner manufacturer.
- 21 (h) All manufacturer's installation and field seaming guidelines shall be followed.
- 22 (i) All liner seams shall be field tested by the installer and verification of the adequacy  
23 of the seams shall be submitted to department along with the record drawings.
- 24 (j) Any concrete slabs installed on top of a liner for operational purposes shall be  
25 completed in accordance with manufacturer and installer recommendations to ensure liner integrity.
- 26 (6) **Impoundment Liner – Wastewater or Wastewater/Stormwater Combination:** Any  
27 applicant or permittee proposing or required to construct a new or to improve an existing wastewater or  
28 combination wastewater/stormwater impoundment, shall, at a minimum, utilize a liner meeting the  
29 following requirements:
- 30 (a) Where the vertical distance between the seasonal high ground water level and the  
31 finished grade of the floor of the impoundment is less than or equal to 50 feet as documented through the  
32 most recent ground water data obtained from an on-site test boring(s) or monitoring well(s), the  
33 impoundment shall, at a minimum, utilize an upper (primary) and lower (secondary) liner. The upper liner  
34 material shall be a minimum of 60-mil high density polyethylene (HDPE) or other material having  
35 equivalent characteristics with regard to permeability, resistance to degradation by ultraviolet light,  
36 compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and  
37 puncture resistance. The lower liner material shall be a minimum of 40-mil HDPE or other material having

1 equivalent characteristics with regard to permeability, compatibility with the liquids anticipated to be  
2 collected in the impoundment, tensile strength, and tear and puncture resistance. A leak detection system  
3 shall be constructed between the upper and lower liners and shall consist of a drainage layer, filter layer,  
4 fluid collection pipes, fluid collection sumps, and fluid removal system.

5 (i) A drainage layer shall be constructed of granular soil materials or  
6 geosynthetic drainage net (geonet). The drainage material shall have a hydraulic conductivity of  $10^{-2}$   
7 centimeters/second or greater. The drainage layer shall be constructed with a slope of at least two percent.

8 (ii) A filter layer shall be constructed above the drainage layer and below the  
9 upper liner. A filter layer above a granular drainage layer shall be composed of granular soil materials that  
10 are finer than the granular drainage layer or a geotextile filter fabric; a geotextile filter fabric shall be used  
11 as a filter layer above a geosynthetic drainage net. A filter layer shall provide for adequate flow of fluid  
12 through the filter while providing adequate retention of fine particles.

13 (iii) Perforated fluid collection pipes shall be installed to transmit fluid from the  
14 drainage layer to a fluid collection sump(s). Collection pipe material, diameter, wall thickness, and slot  
15 size and distribution shall be sufficient to prevent deflection, buckling, collapse or other failure. Collection  
16 pipes shall be installed with slopes equivalent to the slope of the drainage layer. Collection pipe systems  
17 shall be designed to allow for cleaning of all collection pipes with standard pipe cleaning equipment.

18 (iv) A fluid removal system shall be installed to remove fluid from the leak  
19 detection system. The fluid removal system shall consist of a sump(s), a dedicated pump(s), an automated  
20 pump activation system that activates the pump(s) when a specific fluid level is reached in a sump(s), a  
21 totalizing flow meter to measure the volume of leachate pumped from the system, and an  
22 automated alarm system that provides warning of pump failure.

23 (b) Where the vertical distance from the seasonal high ground water level and the  
24 finished grade of the floor of the impoundment is greater than 50 feet as documented through the most  
25 recent ground water data obtained from an on-site test boring(s) or monitoring well(s), the impoundment  
26 shall, at a minimum, utilize a single liner that has a minimum of 60-mil HDPE or other material having  
27 equivalent characteristics with regard to permeability, resistance to degradation by ultraviolet light,  
28 compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and  
29 puncture resistance.

30 (7) **Impoundment Liner - Stormwater:** Any applicant or permittee proposing or required  
31 to improve an existing stormwater impoundment shall, at a minimum, utilize a liner that has a minimum of  
32 60-mil HDPE or other material having equivalent characteristics with regard to permeability, resistance to  
33 degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the  
34 impoundment, tensile strength, and tear and puncture resistance.

35 (8) **Separation Between Impoundments and Ground Water:** Impoundments shall not be  
36 constructed in a location where the vertical distance between the seasonal high ground water level and the

1 finished grade of the floor of the impoundment is less than or equal to four feet as documented through the  
2 most recent ground water data obtained from an on-site test boring(s) or monitoring well(s).

3 (9) **Impoundment Spillways:** Impoundments intended to contain only wastewater shall not  
4 be designed with a spillway.

5  
6 **20.6.2.3218 ADDITIONAL ENGINEERING DESIGN REQUIREMENTS FOR DAIRY**  
7 **FACILITIES WITH A LAND APPLICATION AREA: [RESERVED]**

8  
9 **20.6.2.3219 ADDITIONAL ENGINEERING DESIGN REQUIREMENTS FOR DAIRY**  
10 **FACILITIES DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM:**  
11 **[RESERVED]**

12  
13 **20.6.2.3220 OPERATIONAL REQUIREMENTS FOR ALL DAIRY FACILITIES:**

14 **A. Notification of Presence of Livestock and Wastewater Discharge:** Written  
15 notification of the commencement, cessation, or recommencement of wastewater discharge or the  
16 placement, removal, or reintroduction of livestock shall be submitted to the department as follows:

17 (1) **For new dairy facilities:**

18 (a) **Placement of Livestock:** Written notification shall be submitted to the  
19 department a minimum of 90 days prior to the estimated date of placement of any livestock at the dairy  
20 facility. Written verification of the actual date of placement of any livestock shall be submitted to the  
21 department within 30 days of placement.

22 (b) **Commencement of Wastewater Discharge:** Written notification shall be  
23 submitted to the department a minimum of 90 days prior to the estimated initial wastewater discharge date  
24 indicating the date discharge is proposed to commence. Written verification of the actual date of discharge  
25 commencement shall be submitted to the department within 30 days of commencement.

26 (2) **For existing dairy facilities:**

27 (a) **Removal or Reintroduction of Livestock:** Written verification shall be  
28 submitted to the department indicating the date of removal of all livestock from the dairy facility or the date  
29 of reintroduction of any livestock at the dairy facility, if all livestock were previously removed, within 30  
30 days of livestock removal or reintroduction.

31 (b) **Cessation of Wastewater Discharge:** Written verification shall be submitted to  
32 the department indicating the date wastewater discharge ceased at the dairy facility within 30 days of the  
33 cessation of discharge.

34 (c) **Recommencement of Wastewater Discharge:** Written notification shall be  
35 submitted to the department a minimum of 90 days prior to the estimated date wastewater discharge is  
36 expected to recommence. Written verification of the actual date of discharge commencement shall be  
37 submitted to the department within 30 days of recommencement.

1           **B. Authorized Use of New and Existing Impoundments:** Impoundments shall comply  
2 with the liner, design, and construction requirements of Subsection D of 20.6.2.3217 NMAC; except  
3 impoundments in existence on the effective date of these regulations that do not meet the requirements of  
4 Paragraphs (2) through (9) of Subsection D of 20.6.2.3217 NMAC may continue to receive wastewater or  
5 stormwater provided the water contaminant concentration in a ground water sample and in any subsequent  
6 ground water sample collected from a monitoring well(s) intended to monitor an impoundment does not  
7 exceed:

8           (1) Any ground water standard of Section 20.6.2.3103 NMAC; or

9           (2) The water contaminant concentration in a ground water sample collected from the  
10 upgradient monitoring well, if the water contaminant concentration associated with the upgradient  
11 monitoring well exceeds the ground water standard(s) of Section 20.6.2.3103 NMAC.

12           **C. Constructed Capacity of Existing Impoundment – Determination:** In the event that  
13 record drawings are unavailable or have not been completed for impoundments constructed prior to the  
14 effective date of these regulations to indicate the impoundment capacity of each existing wastewater,  
15 stormwater, or combination wastewater/stormwater impoundment, an up-to-date survey and capacity  
16 calculations of each impoundment shall be completed. The survey data and capacity calculations shall be  
17 submitted to the department with the application for a renewed or modified discharge permit.

18           **D. Free-Liquid Capacity of Existing Impoundment – Determination:** The thickness of  
19 settled solids in each existing wastewater and combination wastewater/stormwater impoundment shall be  
20 measured period during twelve-month prior to the submission of an application for a renewed or modified  
21 discharge permit and in accordance with the following procedure:

22           (1) The total surface area of the impoundment shall be divided into nine equal sub-areas.

23           (2) A settled solids measurement device shall be utilized to obtain one settled solids  
24 thickness measurement (to the nearest half-foot) per sub-area. The nine settled solids measurements shall  
25 be taken on the same day and the date shall be recorded and submitted to the department with the  
26 measurements.

27           (3) The nine settled solids measurements shall be averaged.

28           (4) The total volume of settled solids in the impoundment shall be estimated by multiplying  
29 the average thickness of the solids layer by the area of the top of the settled solids layer. The area shall be  
30 calculated using the impoundment dimensions corresponding to the estimated surface of the settled solids  
31 layer.

32           (5) The estimated volume of settled solids shall be subtracted from the design capacity of the  
33 impoundment (less two feet of freeboard) to estimate the actual free-liquid capacity.

34           (6) The settled solids measurements, calculations, estimation of total settled solids volume  
35 and volume of the actual free-liquid capacity for each impoundment shall be submitted to the department  
36 with the application for a renewed or modified discharge permit.

1           **E.       Impoundment Construction or Improvement:** Construction of a new impoundment or  
2 improvements to an existing impoundment, including relining of an existing impoundment, shall be  
3 performed in accordance with the construction plans and specifications and supporting design calculations  
4 submitted with the application for a new, renewed or modified discharge permit, or those submitted after  
5 issuance of a discharge permit to achieve compliance with these regulations. The department shall be  
6 notified at least five working days prior to construction or improvement of an impoundment to allow for an  
7 inspection by department personnel. A Construction Certification Report shall be submitted bearing the  
8 seal and signature of a licensed New Mexico professional engineer verifying that installation and  
9 construction was completed pursuant to Subsection C of 20.6.2.3217 NMAC shall be submitted. The  
10 Construction Certification Report shall include: record drawings, final specifications, final capacity  
11 calculations and the CQA/CQC report.

12           (1) For new dairy facilities, impoundment construction shall be completed as follows:

13                   (a) Wastewater impoundment construction shall be completed and the Construction  
14 Certification Report shall be submitted to the department prior to discharging wastewater at the dairy  
15 facility.

16                   (b) Combination wastewater/stormwater impoundment construction shall be  
17 completed and the Construction Certification Report shall be submitted to the department prior to placing  
18 any livestock at the dairy facility.

19                   (c) Stormwater impoundment construction shall be completed and the Construction  
20 Certification Report shall be submitted to the department prior to placing any livestock at the dairy facility.

21           (2) For existing dairy facilities, impoundment construction shall be completed:

22                   (a) within one year of the effective date of the discharge permit, if construction of a  
23 new impoundment or improvement of an existing impoundment is required to achieve compliance with  
24 these regulations; or

25                   (b) in accordance with the timeframe specified in Subsection B of 20.6.2.3227  
26 NMAC, when invoked after the effective date of a discharge permit issued pursuant to these regulations.

27                   (c) The Construction Certification Report shall be submitted to the department within  
28 90 days of completion of impoundment construction.

29           **F.       Manure Solids Separator Installation:** Manure solids separation shall be employed  
30 prior to discharging to an impoundment intended to receive wastewater.

31           (1) New dairy facilities and dairy facilities installing a new wastewater storage or disposal  
32 system shall, prior to discharging to the new system, construct a manure solids separator(s) in accordance  
33 with the construction plans and specifications submitted with the application for a new, renewed or  
34 modified discharge permit, or those submitted after issuance of a discharge permit to achieve compliance  
35 with these regulations. Confirmation of solids separator construction, including separator type(s) and  
36 location(s), shall be submitted to the department prior to discharging to the new system.

1 (2) Existing dairy facilities that do not employ manure solids separation shall construct a  
2 manure solids separator(s) within 150 days of the effective date of the discharge permit. Confirmation of  
3 solids separator construction, including separator type(s) and location(s), shall be submitted to the  
4 department within 180 days of the effective date of the discharge permit.

5 **G. Grading and Drainage Report and Plan – Submittal and Implementation:**

6 Development of a new or improvements to an existing grading and drainage system shall be completed in  
7 accordance with the Grading and Drainage Report and Plan required by Subsection C of 20.6.2.3217  
8 NMAC and submitted with the application for a new, renewed, or modified discharge permit. A post-  
9 development drainage report, including record drawings, bearing the seal and signature of a licensed New  
10 Mexico professional engineer shall be submitted.

11 (1) For new dairy facilities, development of the grading and drainage system shall be  
12 completed and the post-development drainage report shall be submitted to the department prior to placing  
13 any livestock at the dairy facility.

14 (2) For existing dairy facilities, improvements to the grading and drainage system shall be  
15 completed within one year of the effective date of the discharge permit. The post-development drainage  
16 report shall be submitted to the department within 90 days of completion of improvements.

17 **H. Stormwater Conveyance and Collection:** Stormwater from the corrals and other  
18 applicable areas at the dairy facility (i.e., calf pens, alleys, feed storage and mixing, etc.) shall be diverted  
19 into the stormwater or combination wastewater/stormwater impoundment(s) in accordance with the grading  
20 and drainage plan required by Subsection C of 20.6.2.3217 NMAC and as specified by current EPA  
21 regulatory requirements for Concentrated Animal Feeding Operations pursuant to 40 Code of Federal  
22 Regulations, Parts 122 and 412, as amended. Conveyance channels shall be constructed and maintained to  
23 minimize ponding and infiltration of stormwater.

24 **I. Stormwater Management – Unlined Impoundment:** Stormwater collected in an  
25 unlined impoundment(s) shall be pumped to the wastewater impoundment(s) or the distribution system for  
26 the land application area after a storm event to minimize the potential for movement to ground water and to  
27 restore the necessary free capacity to contain the volume of stormwater runoff and direct precipitation as  
28 specified by current EPA regulatory requirements for Concentrated Animal Feeding Operations pursuant to 40  
29 Code of Federal Regulations, Parts 122 and 412, as amended. Operational pumps shall be maintained on-site  
30 at all times for the transfer of stormwater from stormwater impoundment(s) to the wastewater  
31 impoundment(s) or the distribution system for the land application area, as authorized by a discharge  
32 permit.

33 **J. Stormwater Management – Lined Impoundment:** Stormwater collected in a  
34 synthetically lined impoundment(s) shall be pumped to the wastewater impoundment(s) or the distribution  
35 system for the land application area after a storm event to restore the necessary free capacity to contain the  
36 volume of stormwater runoff and direct precipitation as specified by current EPA regulatory requirements for  
37 Concentrated Animal Feeding Operations pursuant to 40 Code of Federal Regulations, Parts 122 and 412, as

1 amended. Operational pumps shall be maintained on-site at all times for the transfer of stormwater from  
2 stormwater impoundment(s) to the wastewater impoundment(s) or the distribution system for the land  
3 application area, as authorized by a discharge permit.

4 **K. Flow Meter Installation:** A flow metering system shall be employed that utilizes flow  
5 measurement devices (flow meters) to measure the volume of wastewater discharged at the dairy facility.  
6 Flow meter(s) shall be installed in accordance with the plans and specifications submitted with the  
7 application for a new, renewed or modified discharge permit, or those submitted after issuance of a  
8 discharge permit to achieve compliance with these regulations, pursuant to this section, Subsection C of  
9 20.6.2.3217 NMAC, and Subsections I and J of 20.6.2.3221 NMAC. Flow meters shall be physically and  
10 permanently labeled with the discharge permit number, meter identification nomenclature as specified in a  
11 discharge permit, and the month and year of meter installation. Confirmation of installation shall include a  
12 description of the device type, manufacturer, meter identification, location, record drawings, and the results  
13 of the initial field calibration completed pursuant to Subsection E of 20.6.2.3224 NMAC.

14 (1) New dairy facilities shall install flow meters and submit confirmation of flow meter  
15 installation to the department prior to discharging at the dairy facility.

16 (2) Existing dairy facilities shall install flow meters within 150 days of the effective date of  
17 the discharge permit and submit confirmation of flow meter installation to the department within 180 days  
18 of the effective date of the discharge permit.

19 **L. Flow Metering Methods:** Flow metering shall be accomplished by the following  
20 methods:

21 (1) For pumped flow discharge or transfer situations, a closed-pipe velocity sensing  
22 totalizing flow meter(s) shall be installed on the pressurized discharge or transfer line(s).

23 (2) For gravity flow discharge or transfer situations, an open-channel primary flow  
24 measuring device(s) (flume or weir), equipped with head sensing and totalizing mechanisms, shall be  
25 installed on the discharge or transfer line(s).

26 **M. Flow Meter Locations:** Flow meter locations shall be identified in the application for a  
27 new, renewed or modified discharge permit. All flow meters shall be located pursuant to this section and  
28 Subsections I and J of 20.6.2.3221 NMAC, and indicated on the scaled map required by Subsection W of  
29 this section.

30 **N. Authorized Use of Existing Flow Meters:** An applicant or permittee proposing to use  
31 an existing flow meter(s) shall submit documentation demonstrating that the existing flow meter(s) is  
32 installed consistent with this section, and Subsections I and J of 20.6.2.3221 NMAC, as appropriate. The  
33 proposal shall be submitted with an application for a new, renewed and modified discharge permit and shall  
34 include the following documentation:

35 (1) The location of each existing flow meter indicated on the scaled map required by  
36 Subsection W of this section and identified relative to the wastewater discharge or stormwater application it  
37 is intended to measure.

1 (2) A copy of the record drawings or manufacturer plans and technical specifications  
2 specific to each existing flow meter.

3 (3) A field calibration report for each existing flow meter, completed pursuant to Subsection  
4 E of 20.6.2.3224 NMAC.

5 **O. Flow Metering - Wastewater to Impoundment:** A flow meter(s) shall be installed to  
6 measure the volume of wastewater discharged from all wastewater sources to the wastewater or  
7 combination wastewater/stormwater impoundment(s). The flow meter(s) shall be installed on the discharge  
8 line(s) from all wastewater sources to the wastewater impoundment(s). Meter installation and confirmation  
9 of meter installation shall be performed pursuant to this section.

10 **P. Flow Meter Inspection and Maintenance:** Flow meters shall be visually inspected on a  
11 daily basis for evidence of malfunction. In the event visual inspection indicates a flow meter(s) is not  
12 functioning to measure flow, the permittee shall repair or replace the meter within 30 days of discovery.  
13 The repaired or replaced flow meter(s) shall be installed and calibrated pursuant to these regulations.

14 (1) For repaired meters, the permittee shall submit a report to the department with the next  
15 quarterly monitoring report following the repair that includes a description of the malfunction; a statement  
16 verifying the repair; and a flow meter calibration report completed pursuant to Subsection E of 20.6.2.3224  
17 NMAC.

18 (2) For replacement meters, the permittee shall submit a report to the department with the  
19 next quarterly monitoring report following the replacement that includes plans and specifications for the  
20 device pursuant to Subsection C of 20.6.2.3217 NMAC, and a flow meter calibration report completed  
21 pursuant to Subsection E of 20.6.2.3224 NMAC.

22 **Q. Impoundment Inspection and Maintenance:** Impoundments shall be maintained to  
23 prevent conditions which could affect the structural integrity of the impoundments and associated liners.  
24 Such conditions include, but are not limited to erosion damage; animal burrows or other animal damage;  
25 the presence of vegetation including aquatic plants, weeds, woody shrubs or trees growing within five feet  
26 of the top inside edge of a sub-grade impoundment, within five feet of the toe of the outside berm of an  
27 above-grade impoundment, or within the impoundment itself; evidence of seepage; evidence of berm  
28 subsidence; and the presence of large debris or large quantities of debris in the impoundments.  
29 Impoundments and surrounding berms shall be inspected on a monthly basis to ensure proper condition and  
30 control vegetation growing around the impoundments in a manner that is protective of the liners. Any  
31 evidence of damage that threatens the structural integrity of a berm or liner of an impoundment or that may  
32 result in an unauthorized discharge shall be reported to the department within 24 hours of discovery.  
33 Routine berm maintenance shall not be required to be reported to the department.

34 **R. Leak Detection System Inspection and Maintenance:** Impoundments utilizing primary  
35 and secondary liners and equipped with leak detection systems shall be inspected and maintained as  
36 follows:

1 (1) Leachate accumulation within the leak detection system shall be returned to the  
2 respective impoundment utilizing an automatically activated pump to minimize hydraulic head on the  
3 secondary liner.

4 (2) The sump(s), dedicated pump(s), automated pump activation system, automated alarm  
5 system and totalizing flow meter shall be inspected on a monthly basis for evidence of malfunction. In the  
6 event inspection indicates malfunction of any of these components, the permittee shall repair the  
7 component(s) within 30 days of discovery. The permittee shall notify the department of component  
8 malfunctions and repairs made to components within 60 days of discovery.

9 **S. Pipe and Fixture Inspection and Maintenance:** Pipes and fixtures utilized for the  
10 conveyance or distribution of wastewater or stormwater at the dairy facility shall be maintained to prevent  
11 the unauthorized release of wastewater or stormwater. Pipes and fixtures shall be visually inspected on a  
12 daily basis for evidence of leaks or failure. Where pipes and fixtures cannot be visually inspected because  
13 they are buried, the area directly surrounding the features shall be inspected for evidence of leaks or failure  
14 (e.g., saturated surface soil, surfacing wastewater, etc.). In the event that evidence indicates an  
15 unauthorized discharge has resulted from damaged or faulty pipe(s) or fixture(s), the permittee shall repair  
16 or replace the pipe(s) or fixture(s) within 24 hours of discovery. The unauthorized discharge shall be  
17 reported to the department within 24 hours of discovery and pursuant to Section 20.6.2.1203 NMAC.

18 **T. Leachate Management - Manure Solids Separation System:** Solids captured by and  
19 removed from the manure solids separation system(s), and stored at the dairy facility prior to removal or  
20 land application shall be managed to minimize generation and infiltration of leachate. Leachate from  
21 manure solids shall be collected and contained on an impervious surface prior to disposal.

22 **U. Leachate Management – Manure and Compost Storage:** Manure solids and  
23 composted material, unless authorized by the discharge permit to be land applied at the dairy facility, shall  
24 be removed from the dairy facility. Management practices prior to removal of manure solids and  
25 composted material stored at the dairy facility shall minimize the generation and infiltration of leachate by  
26 diverting stormwater run-on and run-off and by preventing the ponding of water within areas used for  
27 manure and compost stockpiling.

28 **V. Leachate Management – Silage Storage:** Ponding of leachate from silage storage areas  
29 shall be minimized, and collected and contained on an impervious surface prior to disposal.

30 **W. Scaled Map of Dairy Facility:** A scaled map of the dairy facility shall be prepared and  
31 submitted to the department with the application for a new, renewed or modified discharge permit. The  
32 map shall be clear and legible, and drawn to a scale such that all necessary information is plainly shown  
33 and identified. The map shall show the scale in feet or metric measure, a graphical scale, a north arrow,  
34 and the effective date of the map. Documentation identifying the means used to locate the mapped objects  
35 (i.e., GPS, land survey, digital map interpolation, etc.) and the relative accuracy of the data (i.e., +/- XX  
36 feet or meters) shall be included with the map. Any object that cannot be directly shown due to its location

1 inside of existing structures or because it is buried without surface identification, shall be identified on the  
2 map in a schematic format and identified as such. The map shall include the following objects:

- 3 (1) Overall dairy facility layout (barns, feed storage areas, pens, etc.).
- 4 (2) Location of all sumps.
- 5 (3) Location of all manure solids separators.
- 6 (4) Location of all wastewater, stormwater, and combination wastewater/stormwater  
7 impoundments.
- 8 (5) Location of all mix tanks.
- 9 (6) Location and acreage of each field within the land application area.
- 10 (7) Location of all monitoring wells.
- 11 (8) Location of all irrigation wells.
- 12 (9) Location of all meters measuring wastewater discharges to and from impoundments.
- 13 (10) Location of all meters measuring stormwater applied to the land application area.
- 14 (11) Location of all pumps for discharge and transfer.
- 15 (12) Location of all wastewater and stormwater distribution pipelines.
- 16 (13) Location of each ditch irrigation system, acequia, irrigation canal and drain.
- 17 (14) Location of all backflow prevention.
- 18 (15) All wastewater sampling locations, with the exception of impoundments for disposal by  
19 evaporation.
- 20 (16) Location of all septic tanks and leachfields.

21 **X. Scaled Map of Dairy Facility - Updates:** The dairy facility map required by this section  
22 shall be updated and resubmitted to the department within 90 days of any additions or changes to the dairy  
23 facility layout which includes any of the items required by Subsection W of this section.

24 **Y. Animal Mortality Management:** All animal mortalities intended to be disposed of  
25 (buried or composted) on dairy facilities shall be managed in accordance with the following requirements:

- 26 (1) Only mortalities originating at the dairy facility shall be disposed of at the dairy facility.
- 27 (2) Mortalities shall not be stored or buried within 200 feet (measured as horizontal map  
28 distance) from private or public wells, or any watercourse; and at least 100 feet (measured as horizontal  
29 map distance) from the 100-year flood zone of any watercourse, as defined by the most recent Federal  
30 Emergency Management Administration, FEMA, map.
- 31 (3) Stormwater run-on to disposal areas shall be prevented by use of berms or other physical  
32 barriers.
- 33 (4) Mortalities disposed of by burial shall be placed in a pit(s) where the vertical distance  
34 between the seasonal high ground water level and the floor of the pit(s) is greater than 30 feet as  
35 documented through the most recent ground water data obtained from an on-site test boring(s) or  
36 monitoring well(s).

1 (5) Mortality composting shall be accomplished by an individual certified by and in  
2 accordance with the requirements of the Compost Facility Operator Certification Program and the Mortality  
3 and Butcher Waste Composting Guidelines, administered by the New Mexico Environment Department  
4 Solid Waste Bureau.

5 **Z. Determination of Depth-to-Most-Shallow Ground Water and Lithology – Test**

6 **Boring:** Dairy facilities without a monitoring well intersecting most-shallow ground water shall provide  
7 the depth-to-most-shallow ground water and a lithologic log determined by one site-specific test boring  
8 with the application for a new, renewed or modified discharge permit. The test boring shall be drilled in  
9 the area of lowest elevation within the production area. Depth-to-most-shallow ground water shall be  
10 measured immediately upon completion of the test boring and again 24 hours following completion of the  
11 boring. Lithology shall be characterized pursuant to American Society of Testing and Materials (ASTM)  
12 Test Method D 2487 or D 2488.

13 **AA. Domestic Wastewater:** Domestic wastewater shall not be commingled with wastewater  
14 or stormwater generated at a dairy facility. Domestic wastewater shall be treated or disposed pursuant to  
15 Part 20.7.3 NMAC or a discharge permit issued solely for the discharge of domestic wastewater, as  
16 appropriate.

17  
18 **20.6.2.3221 ADDITIONAL OPERATIONAL REQUIREMENTS FOR DAIRY FACILITIES**  
19 **WITH A LAND APPLICATION AREA:**

20 **A. Impoundment Storage Capacity Management – Wastewater and**  
21 **Wastewater/Stormwater Combination:** Wastewater or combination wastewater/stormwater  
22 impoundment(s) shall be operated and maintained for the purpose of storing wastewater prior to  
23 discharging to the land application area. Wastewater or combination wastewater/stormwater  
24 impoundment(s) shall be managed to maintain the free-liquid capacity required by Subsection D of  
25 20.6.2.3217 NMAC.

26 **B. Prohibition of Irrigation Water Storage in Permitted Impoundments:** Irrigation  
27 water shall not be introduced into any impoundment authorized for the storage of wastewater or stormwater  
28 by the department through a discharge permit.

29 **C. Authorized Land Application of Wastewater and Stormwater:** Wastewater and  
30 stormwater shall be applied to fields within the land application area and up to the maximum acreage of  
31 irrigated cropland specifically authorized by a discharge permit. Wastewater and stormwater shall be  
32 distributed evenly over the fields in which application is occurring, and ponding shall be minimized.

33 **D. Irrigation Water Rights – Documentation:** Documentation of irrigation water rights  
34 from the Office of the State Engineer for all fields within the land application area shall be submitted to the  
35 department with the application for a new, renewed or modified discharge permit. The documentation shall  
36 demonstrate adequate irrigation water is available to produce and harvest the crops necessary for the  
37 removal of nitrogen applied in wastewater and stormwater pursuant to this section.

1           **E. Land Application Area – Fresh Irrigation Water Required:** Wastewater shall only be  
2 applied to fields within the land application area receiving fresh irrigation water. Fresh irrigation water  
3 shall be used as the primary source to meet the water consumptive needs of the crop to support crop  
4 production and nutrient removal. Wastewater and stormwater are intended as sources of crop nutrients and  
5 shall not be used as a primary source to meet the water consumptive needs of the crop.

6           **F. Wastewater/Irrigation Water Blending:** Wastewater shall not be combined with  
7 irrigation water in the impoundment(s) or in the fresh irrigation water supply line(s). Wastewater may be  
8 blended in a mix-tank(s), or applied alternately in the same irrigation line which has been physically  
9 disconnected from supply wells or in a separate line, as authorized by a discharge permit.

10           **G. Land Application Area – Existing Infrastructure:** Documentation of the existing  
11 infrastructure necessary to transfer, distribute and apply wastewater or stormwater to all fields within the  
12 land application area that have previously received wastewater or stormwater shall be submitted to the  
13 department with the application for a new, renewed or modified discharge permit. A narrative statement  
14 and photographic documentation (for above ground infrastructure) shall be submitted and confirm the  
15 existing land application distribution system including the type(s) and location(s) of the systems, and the  
16 method(s) of backflow prevention employed.

17           **H. Land Application Area – New Infrastructure:** Prior to initial application of  
18 wastewater or stormwater to any field within the land application area that has not previously received  
19 wastewater or stormwater, a land application distribution system shall be installed to distribute wastewater  
20 and stormwater to all fields that will be actively receiving wastewater and stormwater. The land  
21 application distribution system shall be utilized to distribute and apply wastewater and stormwater to fields  
22 within the land application area to meet the requirements of this section. Prior to initial application of  
23 wastewater or stormwater to any field within the land application area, documentation confirming  
24 installation of the land application distribution system, including the type(s) and location(s) of the system,  
25 and the method(s) of backflow prevention employed shall be submitted to the department.

26           **I. Flow Metering - Wastewater to Land Application Area:** A flow meter(s) shall be  
27 installed to measure the volume of wastewater discharged from the wastewater or combination  
28 wastewater/stormwater impoundment(s) to the land application area. The flow meter(s) shall be installed  
29 on the discharge line(s) from the wastewater impoundment(s) to the distribution system for the land  
30 application area. Meter installation and confirmation of meter installation shall be performed pursuant to  
31 Subsection K, L, and N of 20.6.2.3220 NMAC.

32           **J. Flow Metering - Stormwater to Land Application Area:** For dairy facilities  
33 transferring stormwater from the stormwater impoundment(s) directly to the distribution system for the  
34 land application area, a flow meter(s) shall be installed to measure the volume of stormwater applied  
35 directly to the land application area. The flow meter(s) shall be installed on the transfer line(s) from the  
36 stormwater impoundment(s) to the distribution system for the land application area. Meter installation and  
37 confirmation of meter installation shall be performed pursuant to Subsection K, L, and N of 20.6.2.3220

1 NMAC.

2 **K. Nutrient Management Plan:** Nutrients and other constituents present in wastewater and  
3 stormwater shall be applied to irrigated cropland under cultivation in accordance with the requirements of a  
4 nutrient management plan (NMP) submitted to the department with the application for a new, renewed, or  
5 modified discharge permit. The amount of nitrogen from all combined nitrogen sources, including but not  
6 limited to wastewater, stormwater, manure solids, composted material, irrigation water and other additional  
7 fertilizer(s), along with residual soil nitrogen and nitrogen credits from leguminous crops, shall be applied  
8 to each field within the land application area in accordance with the NMP. The NMP shall contain all  
9 components identified in accordance with the Natural Resources Conservation Service General Manual  
10 Title 190, Part 402, and the Natural Resources Conservation Service Conservation Practice Standard 590  
11 for New Mexico. The NMP shall be signed and dated annually by an individual certified by the American  
12 Society of Agronomy as a Certified Crop Advisor (CCA) or Certified Professional Agronomist (CPAg) and  
13 by an individual certified by the New Mexico Natural Resources Conservation Service as a Nutrient  
14 Management Planner. Plant material and soil sampling shall be, at a minimum, equivalent to the  
15 requirements of Subsections I, K, and L of 20.6.2.3225 NMAC, and the method of crop removal to be  
16 employed shall be identified. The NMP shall be developed for the term of the discharge permit, updated  
17 annually, and implemented pursuant to these regulations. Annual updates to the NMP shall be submitted to  
18 the department in the monitoring report due by May 1 of each year.

19 **L. Crop Removal – Mechanical or Grazing:** Crop removal from fields within the land  
20 application area shall be accomplished by mechanical harvest unless an alternative proposal for the use of  
21 grazing is submitted with the application for a new, renewed, or modified discharge permit. If grazing is  
22 the method proposed for crop removal, the nutrient management plan (NMP) prepared pursuant to  
23 Subsection K of this section shall include a proposal for the use of grazing for crop removal by means of an  
24 actively managed rotational grazing system which promotes uniform grazing and waste distribution  
25 throughout the field(s) (and pastures within the field). Proposals shall quantify the degree of nitrogen  
26 removal expected to be achieved by grazing, and shall provide scientific documentation supporting the  
27 estimated nitrogen removal and justification for the selection of input parameters used in calculations or  
28 computer modeling. The NMP proposing grazing for crop removal shall be implemented in its entirety.  
29 Annual updates to the NMP shall include updates to the grazing plan as well as report actual weight gains,  
30 actual nitrogen uptake of the crop, and estimated crop and nutrient removal from the previous season. An  
31 NMP which proposes grazing for crop removal shall also include, at a minimum, the following elements:

- 32 (1) Length of grazing season.
- 33 (2) Size and number of animals to be grazed.
- 34 (3) Estimated weight gain of animals to be grazed.
- 35 (4) Calculations to determine stocking rates and total acreage needed.
- 36 (5) Plant species used to establish pastures and pasture renovation practices to be employed.
- 37 (6) Yield of plant species grown in each pasture and the forage supplied on a monthly basis.

1 (7) Grazing management system employed and a map indicating key features of the system  
2 including water tanks, fencing, and pasture layout with numbering system and acreage of each pasture.

3 **M. Crop Removal - Changes to Method(s):** In the event the permittee proposes to change  
4 the method(s) of crop removal on any field within the land application area authorized by the discharge  
5 permit, the discharge permit is required to be modified prior to implementation of the change(s). The  
6 permittee shall submit an application which includes the proposed change(s) pursuant to Subsection K and  
7 L of this section.

8 **N. Irrigation Ditches – Inspection and Maintenance:** For dairy facilities land applying  
9 wastewater and stormwater using irrigation ditches; all ditches shall be concrete-lined with sealed  
10 expansion joints. The ditch system shall be visually inspected on a monthly basis to ensure proper  
11 maintenance. Any damage to the lined ditches shall be repaired immediately. A log shall be kept on-site  
12 documenting the inspection findings and repairs made, and the log shall be made available to the  
13 department upon request.

14 **O. Backflow Prevention:** Each dairy facility shall install and maintain backflow prevention  
15 to protect all wells used within the land application distribution system from contamination by wastewater  
16 or stormwater backflow. Backflow prevention shall be achieved by a total disconnect (physical air gap)  
17 between the fresh irrigation water and wastewater and stormwater delivery systems.

18 (1) New dairy facilities shall install backflow prevention and submit written confirmation of  
19 installation to the department prior to discharging at the dairy facility.

20 (2) Existing dairy facilities lacking backflow protection as required by this subsection shall  
21 install backflow prevention within 90 days of the effective date of the discharge permit. Written  
22 confirmation of installation shall be submitted to the department within 180 days of the effective date of the  
23 discharge permit.

24 **P. Supply Well Protection:** With the exception of monitoring wells, all wells located on a  
25 dairy facility shall have a surface pad constructed in accordance with the recommendations of Subsection G  
26 of 19.27.4.29 NMAC and a permanent well cap or cover pursuant to Subsection I of 19.27.4.29 NMAC.

27  
28 **20.6.2.3222 ADDITIONAL OPERATIONAL REQUIREMENTS FOR DAIRY FACILITIES**  
29 **DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: Impoundment**  
30 **Evaporative Capacity – Wastewater and Wastewater/Stormwater Combination:** The wastewater or  
31 combination wastewater/stormwater impoundment(s) shall be operated and maintained for the purpose of  
32 disposing of wastewater or both wastewater and stormwater by evaporation. Capacity of the wastewater or  
33 combination wastewater/stormwater impoundment(s) shall be maintained pursuant to Subsection D of  
34 20.6.2.3217 NMAC.

35  
36 **20.6.2.3223 GROUND WATER MONITORING REQUIREMENTS FOR ALL DAIRY**  
37 **FACILITIES:**

1           A.       **Monitoring Wells – Required Locations:** Monitoring of ground water quality shall be  
2 required hydrologically downgradient of each source of ground water contamination, including but not  
3 limited to wastewater, stormwater, and combination wastewater/stormwater impoundments, and fields  
4 within the land application area. Monitoring wells shall be located pursuant to this section to detect  
5 exceedance(s) or trends towards exceedance(s) of the ground water standards at the earliest possible  
6 occurrence, so that source control or abatement may be implemented as soon as possible.

7           (1)       **Ground Water Monitoring – Wastewater Impoundments:** A minimum of one  
8 monitoring well shall be located hydrologically downgradient and within 75 feet (measured as horizontal  
9 map distance) of the top inside edge of each wastewater impoundment, including previously utilized  
10 impoundments to which wastewater discharge has ceased.

11                   (a)   For new dairy facilities, monitoring wells shall be installed prior to discharging at  
12 the dairy facility.

13                   (b)   For existing dairy facilities, monitoring wells shall be installed within 120 days of  
14 the effective date of the discharge permit.

15                   (c)   Existing dairy facilities constructing a new impoundment(s) shall install a  
16 monitoring well(s) prior to discharging wastewater in the impoundment(s).

17           (2)       **Ground Water Monitoring – Combination Wastewater/Stormwater**  
18 **Impoundments:** A minimum of one monitoring well shall be located hydrologically downgradient and  
19 within 75 feet (measured as horizontal map distance) of the top inside edge of each combination  
20 wastewater/stormwater impoundment, including previously utilized impoundments to which wastewater  
21 discharge or stormwater collection has ceased.

22                   (a)   For new dairy facilities, monitoring wells shall be installed prior to placing any  
23 livestock at the dairy facility or prior to discharging wastewater to the impoundment.

24                   (b)   For existing dairy facilities, monitoring wells shall be installed within 120 days of  
25 the effective date of the discharge permit.

26                   (c)   Existing dairy facilities constructing a new impoundment(s) shall install a  
27 monitoring well(s) prior to discharging wastewater to the impoundment(s).

28           (3)       **Ground Water Monitoring – Stormwater Impoundments:** A minimum of one  
29 monitoring well shall be located hydrologically downgradient and within 75 feet (measured as horizontal  
30 map distance) of the top inside edge of each stormwater impoundment, including previously utilized  
31 impoundments to which stormwater collection has ceased.

32                   (a)   For new dairy facilities, monitoring wells shall be installed prior to placing any  
33 livestock at the dairy facility.

34                   (b)   For existing dairy facilities, monitoring wells shall be installed within 120 days of  
35 the effective date of the discharge permit.

36                   (c)   Existing dairy facilities constructing a new impoundment(s) shall install a  
37 monitoring well(s) prior to collecting stormwater in the impoundment(s).

1           (4) **Ground Water Monitoring – Land Application Area:** Monitoring wells intended to  
2 monitor ground water hydrologically downgradient of fields within the land application area shall be  
3 installed as follows:

4           (a) **Flood Irrigation:** Ground water monitoring shall be performed hydrologically  
5 downgradient of each flood irrigated field or grouping of contiguous flood irrigated fields. For every 60  
6 acres or less of a single flood irrigated field or a single grouping of contiguous flood irrigated fields, a  
7 minimum of one monitoring well shall be located hydrologically downgradient and within 50 feet  
8 (measured as horizontal map distance) of the downgradient boundary of the single field or single grouping  
9 of contiguous fields, including previously utilized fields to which application of wastewater or stormwater  
10 has ceased. Flood irrigated fields separated by ditch irrigation systems, acequias and drains shall be  
11 considered contiguous for the purpose of this subsection.

12           (i) For new dairy facilities, monitoring wells shall be installed prior to  
13 discharging at the dairy facility.

14           (ii) For existing dairy facilities, monitoring well shall be installed within 120  
15 days of the effective date of the discharge permit.

16           (iii) Existing dairy facilities activating a new flood irrigated field(s) shall install  
17 a monitoring well(s) prior to applying wastewater or stormwater to the field(s).

18           (b) **Sprinkler or Drip Irrigation:** Ground water monitoring shall be performed  
19 hydrologically downgradient of each sprinkler or drip irrigated field, or grouping of contiguous sprinkler or  
20 drip irrigated fields. For every 125 acres or less of a single sprinkler or drip irrigated field, or a single  
21 grouping of 125 contiguous acres of sprinkler or drip irrigated fields, a minimum of one monitoring well  
22 shall be located hydrologically downgradient and within 50 feet (measured as horizontal map distance) of  
23 the downgradient boundary of the single field or single grouping of contiguous fields, including previously  
24 utilized fields to which application of wastewater or stormwater has ceased. Sprinkler or drip irrigated  
25 fields separated by ditch irrigation systems, acequias and drains shall be considered contiguous for the  
26 purpose of this subsection.

27           (i) For new dairy facilities, monitoring wells shall be installed prior to  
28 discharging at the dairy facility.

29           (ii) For existing dairy facilities, monitoring wells shall be installed within 120  
30 days of the effective date of the discharge permit.

31           (iii) Existing dairy facilities activating a new sprinkler or drip irrigated field(s)  
32 shall install a monitoring well(s) prior to applying wastewater or stormwater to the field(s).

33           (c) **Crop Harvest by Grazing:** Notwithstanding the requirements of Subparagraphs  
34 (a) and (b) of this paragraph, a minimum of one monitoring well(s) shall be located hydrologically  
35 downgradient and within 50 feet (measured as horizontal map distance) of the downgradient boundary of  
36 each field where grazing is proposed in an nutrient management plan (NMP) as an alternative to crop  
37 removal by mechanical harvest.

1           (5) **Ground Water Monitoring – Upgradient:** A minimum of one monitoring well shall  
2 be located hydrologically upgradient of all ground water contamination sources at the dairy facility in order  
3 to establish ground water quality conditions at a location not likely to be affected by contamination sources  
4 at the dairy facility.

5           (a) For new dairy facilities, monitoring wells shall be installed prior to discharging at  
6 the dairy facility.

7           (b) For existing dairy facilities, monitoring well shall be installed within 120 days of  
8 the effective date of the discharge permit.

9           (6) **Use of Existing Monitoring Wells:** A monitoring well in existence prior to the  
10 effective date of these regulations shall be approved for ground water monitoring at a dairy facility  
11 provided all of the following requirements are met:

12           (a) A monitoring well is located at the location previously approved by the department  
13 and is located no more than 100 feet hydrologically downgradient from the contamination source.

14           (b) A monitoring well intended to monitor ground water quality near a contamination  
15 source is downgradient of such a source based on current hydrologic conditions, and a monitoring well  
16 intended to monitor ground water quality at a location not likely to be affected by contamination sources at  
17 a dairy facility is located hydrologically upgradient of such sources.

18           (c) A monitoring well is constructed with a screen length consistent with the  
19 construction requirements of this section or an alternative screen length previously approved by the  
20 department.

21           (d) A monitoring well construction log, a scaled dairy facility map, and a ground  
22 water elevation contour map are submitted with the application for a renewed or renewed and modified  
23 discharge permit and verify that the requirements of Subparagraphs (a), (b), and (c) of this paragraph are  
24 met.

25           (7) **Exceptions to Monitoring Well Requirements:** When appropriate, based on the  
26 documented ground water flow direction, one monitoring well may be authorized by a discharge permit to  
27 monitor ground water hydrologically downgradient of more than one contamination source under the  
28 following circumstances:

29           (a) Contiguous impoundments are oriented along a line that is parallel or  
30 approximately parallel to the direction of ground water flow beneath the impoundments.

31           (b) Adjacent impoundments are oriented along a line that is parallel or approximately  
32 parallel to the direction of ground water flow beneath the impoundments and separated by a distance of 50  
33 feet or less as measured from the top inside edge of one impoundment to the nearest top inside edge of the  
34 adjacent impoundment.

35           (c) Adjacent or adjacent groupings of contiguous sprinkler or drip irrigated fields are  
36 oriented along a line that is parallel or approximately parallel to the direction of ground water flow beneath  
37 the fields provided the average depth-to-most-shallow ground water measured in on-site monitoring wells

1 pursuant to Subsection F of this section or the depth-to-most-shallow ground water measured in a site-  
2 specific test boring pursuant to Subsection Z of 20.6.2.3220 NMAC is 300 feet or greater. A monitoring  
3 well(s) installed hydrologically downgradient of a sprinkler or drip irrigated field or a grouping of sprinkler  
4 or drip irrigated fields pursuant to Paragraph (4) of this subsection may be authorized by a discharge permit  
5 to monitor ground water hydrologically downgradient of not more than two adjacent sprinkler or drip  
6 irrigated fields or adjacent groupings of sprinkler or drip irrigated fields.

7 (8) **Requirement for Third Monitoring Well:** In the event that fewer than three  
8 monitoring wells are needed to satisfy the ground water monitoring requirements of this section, a third  
9 monitoring well shall be installed within 75 feet of the contamination source and in a location alternate to  
10 the downgradient monitoring well required by this subsection. The third monitoring well shall be installed  
11 in an alternative location that allows for the determination of ground water flow direction pursuant to this  
12 section.

13 **B. Monitoring Wells – Location Proposals:** Monitoring well locations shall be identified  
14 in the application for a new, renewed or modified discharge permit pursuant to Subsection A of this section,  
15 and shall include the following information:

16 (1) The location of each monitoring well relative to the contamination source it is intended  
17 to monitor shall be indicated on the scaled map required by Subsection W of 20.6.2.3220 NMAC.

18 (2) A written description of the specific location for each monitoring well including the  
19 horizontal map distance in feet and compass bearing of each monitoring well from the top inside edge of  
20 the impoundment berm or edge of the field it is intended to monitor.

21 (3) Ground water flow direction beneath the dairy facility used to determine the monitoring  
22 well location(s), including supporting documentation used to determine ground water flow direction.

23 **C. Monitoring Wells – Identification Tags:** All monitoring wells required by these  
24 regulations shall be identified by a well identification tag. For above-grade wells, the tag shall be affixed to  
25 the exterior of the steel well shroud using rivets, bolts or a steel band. For wells finished below-grade, the  
26 tag shall be placed inside the well vault next to the well riser. The tag shall be:

27 (1) Made of aluminum.

28 (2) At least two inches by four inches in size.

29 (3) For monitoring wells installed after the effective date of these regulations, the tag shall  
30 be engraved with the discharge permit number; well identification nomenclature specified in a discharge  
31 permit; name of the well driller and New Mexico well driller license number; and the month and year of  
32 well installation.

33 (4) For monitoring wells installed before the effective date of these regulations and  
34 satisfying the requirements of Paragraph (6) of Subsection A of this section, the tag shall be engraved with  
35 the discharge permit number and well identification nomenclature specified in a discharge permit. If  
36 available, the name of the well driller and New Mexico well driller license number, and the month and year  
37 of well installation shall also be engraved on the tag.

1           **D. Monitoring Wells – Construction and Completion:** Monitoring wells shall be  
2 constructed pursuant to Part 19.27.4 NMAC and the following requirements:

3           (1) All well drilling activities shall be performed by an individual with a current and valid  
4 well driller license issued by the State of New Mexico pursuant to Part 19.27.4 NMAC.

5           (2) Drilling methods that allow for accurate determinations of water table locations shall  
6 be employed. All drill bits, drill rods, and down-hole tools shall be thoroughly cleaned immediately  
7 prior to the start of drilling. The bore hole diameter shall allow a minimum annular space of two inches  
8 between the outer circumference of the well materials (casing or screen) and the bore hole wall to allow  
9 for the emplacement of sand and sealant.

10          (3) After completion, the well shall be allowed to stabilize for a minimum of 12 hours  
11 before development is initiated.

12          (4) The well shall be developed so that formation water flows freely through the screen  
13 and is not turbid, and all sediment and drilling disturbances are removed from the well.

14          (5) Schedule 40 (or heavier) PVC pipe, stainless steel pipe, or carbon steel pipe shall be  
15 used as casing. The casing shall have an inside diameter not less than two inches. The casing material  
16 selected for use shall be compatible with the anticipated chemistry of the ground water and appropriate for  
17 the contaminants of interest at the dairy facility. The casing material and thickness selected for use shall  
18 have sufficient collapse strength to withstand the pressure exerted by grouts used as annular seals and  
19 thermal properties sufficient to withstand the heat generated by the hydration of cement-based grouts.

20          (6) Casing sections shall be joined using welded, threaded, or mechanically locking joints;  
21 the method selected shall provide sufficient joint strength for the specific well installation.

22          (7) The casing shall extend from the top of the screen to at least one foot above ground  
23 surface. The top of the casing shall be fitted with a removable cap, and the exposed casing shall be  
24 protected by a locking steel well shroud. The shroud shall be large enough in diameter to allow easy access  
25 for removal of the cap. Alternatively, monitoring wells may be completed below grade. In this case, the  
26 casing shall extend from the top of the screen to six to twelve inches below the ground surface; the  
27 monitoring wells shall be sealed with locking, expandable well plugs; a flush-mount, watertight well vault  
28 that is rated to withstand traffic loads shall be emplaced around the wellhead; and the cover shall be  
29 secured with at least one bolt. The vault cover shall indicate that the wellhead of a monitoring well is  
30 contained within the vault.

31          (8) A 20-foot section (maximum) of continuous well screen shall be installed across the  
32 water table. Screen shall consist of continuous-slot, machine slotted, or other manufactured Schedule 40  
33 (or heavier) PVC or stainless steel. Screens created by cutting slots into solid casing with saws or other  
34 tools shall not be used. The screen material selected for use shall be compatible with the anticipated  
35 chemistry of the ground water and appropriate for the contaminants of interest at the dairy facility. The  
36 screen slot size shall be selected to retain 90 percent of the filter pack.

*Attachment 1 – Proposed Amendment to 20.6.2 NMAC  
December 22, 2009*

1 (a) Requests for a 30-foot section of continuous well screen may be authorized by a  
2 discharge permit when the most recent two years of ground water level data demonstrates a declining water  
3 level trend of at least two feet per year. Data supporting ground water levels shall be specific to monitoring  
4 wells located at the dairy facility and obtained with a water level measuring device as required by  
5 Subsection F of this section.

6 (b) Requests for a 30-foot section of continuous well screen shall be submitted to the  
7 department in the application for a new, renewed or modified discharge permit.

8 (9) Screen sections shall be joined using welded, threaded, or mechanically locking  
9 joints; the method selected shall provide sufficient joint strength for the specific well installation and shall  
10 not introduce constituents that may reasonably be considered contaminants of interest at the dairy facility.  
11 A cap shall be attached to the bottom of the well screen. Sumps (i.e., casing attached to the bottom of a  
12 well screen) shall not be installed.

13 (10) The bottom of the screen shall be installed no more than 15 feet below the water  
14 table; or 25 feet below the water table when additional screen length is authorized by a discharge permit.  
15 The top of the well screen shall be positioned not less than five feet above the water table. The well screen  
16 slots shall be appropriately sized for the formation materials.

17 (11) Casing and well screen shall be centered in the borehole by installing centralizers  
18 near the top and bottom of the well screen.

19 (12) A filter pack shall be installed around the screen by filling the annular space from the  
20 bottom of the screen to two feet above the top of the screen with clean silica sand. The filter pack shall be  
21 properly sized to exclude the entrance of fine sand, silt, and clay from the formation into the monitoring  
22 well. For wells deeper than 30 feet, the sand shall be emplaced by a tremmie pipe. The well shall be  
23 surged or bailed to settle the filter pack and additional sand added, if necessary, before the bentonite seal is  
24 emplaced.

25 (13) A bentonite seal shall be constructed immediately above the filter pack by emplacing  
26 bentonite chips or pellets (three-eighths inch in size or smaller) in a manner that prevents bridging of the  
27 chips/pellets in the annular space. The bentonite seal shall be three feet in thickness and hydrated with  
28 clean water. Adequate time shall be allowed for expansion of the bentonite seal before installation of the  
29 annular space seal.

30 (14) The annular space above the bentonite seal shall be sealed with a bentonite-cement  
31 grout (five lbs. of powdered bentonite, 94 lbs. of Portland cement, and six and a half to eight and a half  
32 gallons of clean water), neat cement grout (94 lbs. of Portland cement and five to six gallons of clean  
33 water), or bentonite grout (20 percent solids, created by mixing 50 lbs. of bentonite grout with 24 gallons of  
34 clean water). Emplacement of the annular space seal shall be performed by using a tremmie pipe (flow by  
35 gravity or pumping through the pipe). Annular space seals shall extend from the top of the bentonite seal to  
36 the ground surface (for wells completed above grade) or to a level three to six inches below the top of  
37 casing (for wells completed below grade).

1 (15) A concrete pad (two-foot minimum radius, four-inch minimum thickness) shall be  
2 poured around the shroud or well vault and wellhead. The concrete and surrounding soil shall be sloped to  
3 direct rainfall and runoff away from the wellhead.

4 **E. Monitoring Wells – OSE Requirements:** Monitoring wells shall be installed pursuant  
5 to a well permit granted by the Office of the State Engineer prior to well drilling pursuant to Section 29  
6 of 19.27.4 NMAC, should a well permit for monitoring well installation be required by the Office of the  
7 State Engineer.

8 **F. Ground Water Sample Collection Procedure:** All ground water sample collection,  
9 preservation, transport and analysis shall be performed according to the following procedure:

10 (1) Depth-to-most-shallow ground water shall be measured from the top of well casing at  
11 point of survey to the nearest 0.01 feet using an electronic water level indicator consisting of dual  
12 conductor wire encased in a cable or tape graduated to 0.01 feet, a probe attached to the end of the  
13 conductor wire, and a visual or audible indicator.

14 (2) Monitoring wells shall be purged prior to sample collection by one of the following  
15 methods:

16 (a) Three well volumes of water shall be purged from the well prior to sample  
17 collection, or;

18 (b) The monitoring well shall be purged until measurements of indicator parameters  
19 (pH, specific conductance, and temperature) have stabilized. Indicator parameters shall be measured  
20 periodically during purging. A parameter stabilization log shall be kept during each sampling event for  
21 each monitoring well and include: date; water quality indicator parameter measurements; time for all  
22 measurements; and purge volume extracted. Indicator parameters are considered stable when three  
23 consecutive readings made no more than five minutes apart fall within the following ranges: temperature  $\pm$   
24 10 percent; pH  $\pm$  0.5 units; specific conductance  $\pm$  10 percent.

25 (3) Following purging and immediately prior to sample collection the following field  
26 parameters shall be measured and recorded: pH, specific conductance, and temperature.

27 (4) Samples from the well shall be obtained for analysis in accordance with the methods  
28 authorized by Subsection B of 20.6.2.3107 NMAC. In-line flow-through cells shall be disconnected or by-  
29 passed during sample collection if used during purging.

30 (5) Samples shall be prepared, preserved and transported to a qualified analytical laboratory  
31 for analysis in accordance with the methods authorized by Subsection B of 20.6.2.3224 NMAC.

32 **G. Ground Water Sampling and Reporting - Routine:** Ground water samples shall be  
33 collected quarterly from all monitoring wells required by Subsection A of this section and Subsection C of  
34 20.6.2.3227 NMAC. Samples shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride,  
35 sulfate and total dissolved solids pursuant to this Subsection B of 20.6.2.3224 NMAC. Depth-to-most-  
36 shallow ground water, field parameter measurements, parameter stabilization log (if applicable), analytical  
37 results, including laboratory quality assurance and quality control summary report, and a map showing the

1 location and number of each well in relation to the contamination source it is intended to monitor, shall be  
2 submitted to the department in the quarterly monitoring reports.

3 **H. Ground Water Sampling – New Monitoring Wells:** Ground water samples shall be  
4 collected in all newly installed monitoring wells. Samples shall be analyzed for nitrate as nitrogen, total  
5 Kjeldahl nitrogen, chloride, sulfate and total dissolved solids pursuant to this Subsection B of 20.6.2.3224  
6 NMAC.

7 (1) Samples shall be collected from the newly installed monitoring wells at new dairy  
8 facilities prior to discharging at the dairy facility.

9 (2) Samples shall be collected from the newly installed monitoring wells at existing dairy  
10 facilities within 120 days of the effective date of the discharge permit.

11 **I. Monitoring Well Survey and Ground Water Flow Determination:** All monitoring  
12 wells shall be surveyed to a U.S. Geological Survey (USGS) benchmark. Survey data shall include  
13 northing, easting and elevation to the nearest hundredth of a foot or in accordance with the "Minimum  
14 Standards for Surveying in New Mexico", Part 12.8.2 NMAC. A survey elevation shall be established at  
15 the top-of-casing, with a permanent marking indicating the point of survey. The survey shall be completed  
16 and bear the seal and signature of a licensed New Mexico professional surveyor. Depth-to-most-shallow  
17 ground water shall be measured from the point of survey to the nearest hundredth of a foot in all surveyed  
18 wells pursuant to Subsection F of this section, and the data shall be used to develop a map showing the  
19 location of all monitoring wells and the direction and gradient of ground water flow at the dairy facility.

20 (1) For new dairy facilities, all monitoring wells shall be surveyed prior to discharging at the  
21 dairy facility.

22 (2) For existing dairy facilities, monitoring wells not previously surveyed in a manner  
23 consistent with the requirements of this subsection and Subsection B of 20.6.2.3217 NMAC shall be  
24 surveyed within 150 days of the effective date of the discharge permit.

25 **J. Monitoring Well Completion Report:** A monitoring well completion report pertaining  
26 to all monitoring wells shall be submitted to the department. For new dairy facilities, the report shall be  
27 submitted prior to discharging at the dairy facility. For existing dairy facilities, the report shall be  
28 submitted within 180 days after the effective date of the discharge permit or within 60 days of completion  
29 as specified in a discharge permit. The report shall contain the following information:

30 (1) Construction and lithologic logs for the new monitoring wells including well record  
31 information specified by Part 19.27.4 NMAC.

32 (2) Depth-to-most-shallow ground water measured in each new and existing monitoring  
33 well.

34 (3) Survey data and a survey map showing the locations of each new and existing  
35 monitoring well and a ground water elevation contour map developed pursuant to Subsection L of this  
36 section.

1 (4) Analytical results of ground water samples collected from the new monitoring wells,  
2 including laboratory quality assurance and quality control summary reports, and field parameters  
3 measurements.

4 **K. Monitoring Well Survey Report – Existing Monitoring Wells:** For dairy facilities  
5 required to survey existing monitoring wells pursuant to this section, the monitoring well survey report  
6 shall be submitted to the department within 180 days of the effective date of the discharge permit. The  
7 report shall contain the depth-to-most-shallow ground water measured in each monitoring well, and a  
8 surveyed map showing the locations of the monitoring wells, and the direction and gradient of ground  
9 water flow at the dairy facility.

10 **L. Ground Water Elevation Contour Maps:** Ground water elevation contour maps shall  
11 be developed on a quarterly basis using data associated with all monitoring wells used for monitoring at the  
12 dairy facility. Top of casing elevation data obtained from monitoring well surveys completed pursuant to  
13 this section and quarterly depth-to-most-shallow ground water measurements in monitoring wells shall be  
14 used to calculate ground water elevations at monitoring well locations. Ground water elevations between  
15 monitoring well locations shall be estimated using common interpolation methods. Ground water  
16 elevations shall be expressed in feet and a contour interval appropriate to the data but no greater than two  
17 feet shall be used. Ground water elevation contour maps shall depict the ground water flow direction using  
18 arrows based on the orientation of the ground water elevation contours and the location and identification  
19 of each monitoring well, impoundment, and field within the land application area. Ground water elevation  
20 contour maps shall be submitted to the department in the quarterly monitoring reports.

21 **M. Monitoring Well Inspection:** The department shall have the option to perform  
22 downhole inspections of all monitoring wells. The department shall establish the inspection date, identify  
23 the monitoring wells to be inspected, and provide at least 60 days notice to the permittee by certified mail.  
24 All existing dedicated pumps shall be removed at least 48 hours prior to department inspection to allow  
25 adequate settling time of sediment agitated from pump removal. Should a dairy facility decide to install  
26 dedicated pumps in any of the monitoring wells, the department shall be notified prior to pump installation  
27 so that downhole well inspection(s) can be scheduled prior to pump installation.

28  
29 **20.6.2.3224 MONITORING REQUIREMENTS FOR ALL DAIRY FACILITIES:**

30 **A. Monitoring Reports – Schedule of Submittal:** Monitoring reports shall be submitted to  
31 the department on a quarterly schedule and shall contain monitoring data and information collected  
32 pursuant to these regulations. Quarterly monitoring reports shall be submitted according to the following  
33 schedule:

- 34 (1) January 1 through March 31 (first quarter) – report due by May 1.  
35 (2) April 1 through June 30 (second quarter) – report due by August 1.  
36 (3) July 1 through September 30 (third quarter) – report due by November 1.  
37 (4) October 1 through December 31 (fourth quarter) – report due by February 1.

1           **B. Sampling and Analysis Methods:** Sampling and analysis of water shall be conducted  
2 pursuant to Subsection B of 20.6.2.3107 NMAC, and sampling and analysis of soil shall be conducted in  
3 accordance with Methods of Soil Analysis: Part 1. Physical and Mineralogical Methods and Part 2.  
4 Chemical and Microbiological Properties, American Society of Agronomy.

5           **C. Discharge Volume Measurement and Reporting:** The daily volume of all wastewater  
6 discharged to the wastewater impoundment(s) shall be measured using a flow meter(s). Daily meter  
7 readings including the date, time and units of each measurement, and daily discharge volumes reported in  
8 gallons shall be submitted to the department in the quarterly monitoring reports.

9           **D. Stormwater Sampling and Reporting:** Stormwater samples shall be collected on a  
10 quarterly basis from each stormwater impoundment. The samples shall be collected as soon as possible  
11 after a storm event, prior to transferring to the wastewater impoundment(s) or the land application area.  
12 The samples shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, sulfate and total  
13 dissolved solids pursuant to this section. Analytical results, or a statement that stormwater runoff did not  
14 occur, shall be submitted to the department in the quarterly monitoring reports.

15           **E. Flow Meter Field Calibration:** All flow meters shall be capable of having their  
16 accuracy ascertained under actual working (field) conditions. A description of the field calibration method  
17 to be utilized shall be developed for each flow meter and that method shall be utilized to check the accuracy  
18 of each respective meter. Field calibrations shall be performed upon installation and, at a minimum,  
19 annually thereafter. Flow meters shall be calibrated to within +/- 10 percent of actual flow, as measured  
20 under field conditions. Field calibrations shall be performed by an individual knowledgeable in flow  
21 measurement and in the installation/operation of the particular device in use. The results of annual field  
22 calibrations shall be submitted to the department annually in the monitoring reports due by May 1. The  
23 flow meter calibration report shall include the following:

24           (1) The location and meter identification nomenclature identified by the department through  
25 a discharge permit.

26           (2) The method of flow meter calibration employed.

27           (3) The measured accuracy of each flow meter prior to adjustment indicating the positive or  
28 negative offset as a percentage of actual flow as determined by an in-field calibration check.

29           (4) The measured accuracy of each flow meter following adjustment, if necessary, indicating  
30 the positive or negative offset as a percentage of actual flow of the meter.

31           (5) Any flow meter repairs made during the previous year or during calibration.

32           **F. Primary Liner Leakage Measurement, Analysis and Reporting:** Impoundments  
33 utilizing primary and secondary liners and equipped with leak detection systems shall be monitored in the  
34 following manner:

35           (1) The monthly volume of leachate pumped from the leak detection system(s) back into the  
36 respective impoundment(s) shall be measured using a totalizing flow meter(s). Monthly meter readings

1 including units of measurement, and monthly volumes shall be submitted to the department in the quarterly  
2 monitoring reports.

3 (2) Monthly meter volumes of leachate shall be used to determine the average daily leakage  
4 rate for the respective impoundment. The average daily leakage rate shall be compared to the pump rate to  
5 assure that the automated pump system is capable of removing leachate at a rate sufficient to ensure  
6 leachate accumulation in the drainage layer is minimized. A report documenting that the pump system is  
7 operating effectively shall be submitted to the department in the quarterly monitoring reports.

8 (3) Upon initial discovery of leachate in the leak detection system(s), a leachate sample shall  
9 be collected from the system and analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, sulfate  
10 and total dissolved solids pursuant to this section. Analytical results shall be submitted to the department in  
11 the next quarterly monitoring report. Should leachate continue to accumulate in the leak detection system  
12 such that it is routinely pumped, a leachate sample shall be collected on a quarterly basis and analyzed as  
13 described above and the results shall be submitted to the department in the quarterly monitoring reports.  
14

15 **20.6.2.3225 ADDITIONAL MONITORING REQUIREMENTS FOR DAIRY FACILITIES**  
16 **WITH A LAND APPLICATION AREA:**

17 **A. Volume of Wastewater and Wastewater/Stormwater Land Applied – Measurement**  
18 **and Reporting:** All wastewater discharges from the wastewater or combination wastewater/stormwater  
19 impoundment(s) to each field within the land application area shall be measured using a flow meter(s) and  
20 recorded. A log shall be maintained indicating the date and location of each discharge, flow meter readings  
21 immediately prior to and after each discharge, and the calculated total volume of each discharge reported in  
22 gallons and acre-feet. A copy of the log entries including units of measurement shall be submitted to the  
23 department in the quarterly monitoring reports.

24 **B. Volume of Stormwater Land Applied – Measurement and Reporting:** All  
25 stormwater applications from the stormwater impoundment(s) to each field within the land application area  
26 shall be measured using a flow meter(s) and recorded. A log shall be maintained indicating the date and  
27 location of each application, flow meter readings immediately prior to and after each application, and the  
28 calculated total volume of each application reported in gallons and acre-feet. A copy of the log entries  
29 including units of measurement shall be submitted to the department in the quarterly monitoring reports.

30 **C. Wastewater to be Land Applied – Sampling and Reporting:** Wastewater samples  
31 shall be collected on a quarterly basis and analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride,  
32 sulfate and total dissolved solids pursuant to Subsection B of 20.6.2.3224 NMAC. Samples shall be  
33 collected during active milking from a location between the manure solids separator(s) and wastewater  
34 impoundment(s) for each separator associated with an individual parlor. Wastewater samples shall be  
35 collected from the sampling location(s) proposed in the application for a new, renewed and modified  
36 discharge permit, and specified in the discharge permit. Analytical results shall be submitted to the  
37 department in the quarterly monitoring reports.

1           **D. Manure Solids – Nitrogen Content:** The nitrogen content of the manure solids applied  
2 to each field within the land application area shall be estimated at 25 pounds of nitrogen per ton. Should  
3 the permittee choose to use actual nitrogen content values of on-site manure solids, a composite sample  
4 shall be collected on an annual basis. The composite sample shall consist of a minimum of 30 sub-samples  
5 collected on the same day and thoroughly mixed. Manure samples shall be analyzed for total Kjeldahl  
6 nitrogen and moisture content. The analytical results shall be submitted to the department in the quarterly  
7 monitoring reports.

8           **E. Irrigation Water – Sampling, Volume Applied, and Reporting:** Irrigation wells used  
9 to supply fresh water to the fields within the land application area shall be monitored to account for  
10 additional potential nitrogen supplied to the land application area in the following manner:

11           (1) Each irrigation well shall be identified in association with the field(s) to which it supplies  
12 fresh water.

13           (2) An annual sample of irrigation water supplied from each well shall be collected and  
14 analyzed for nitrate as nitrogen and total Kjeldahl nitrogen, pursuant to Subsection B of 20.6.2.3224  
15 NMAC.

16           (3) The annual volume of irrigation water applied to each field within the land application  
17 area shall be estimated for each well.

18           (4) Analytical results and the annual estimated volume of irrigation water applied from each  
19 well to each field within the land application area shall be submitted to the department in the monitoring  
20 reports due by May 1.

21           **F. Fertilizer Application Reporting:** A log shall be maintained of all additional  
22 fertilizer(s) applied to each field of the land application area. The log shall contain the date of fertilizer  
23 application, the type and form of fertilizer, fertilizer analysis, the amount of fertilizer applied in pounds per  
24 acre to each field, and the amount of nutrients applied in pounds per acre to each field. A copy of the log  
25 entries shall be submitted to the department in the quarterly monitoring reports.

26           **G. Land Application Data Sheets:** Land Application Data Sheets shall be completed for  
27 each field within the land application area, which document the crop grown and amount of total nitrogen  
28 applied from wastewater, stormwater, manure solids, composted material, irrigation water and other  
29 additional fertilizer(s), along with residual soil nitrogen and nitrogen credits from leguminous crops. The  
30 Land Application Data Sheet or a statement that land application did not occur shall be submitted to the  
31 department in the quarterly monitoring reports. The Land Application Data Sheet shall include the  
32 following elements:

33           (1) Information required by Paragraphs (2) through (8) of this subsection from the previous  
34 six quarters.

35           (2) The total monthly volume, reported in acre-feet, of wastewater and stormwater applied to  
36 each field of the land application area. Total monthly volumes shall be obtained from flow meter readings  
37 of each application pursuant to Subsections A and B of this section.

1 (3) The total nitrogen concentration of wastewater and stormwater obtained from the  
2 corresponding quarterly analyses collected pursuant to Subsection C of this section and Subsection D of  
3 20.6.2.3224 NMAC.

4 (4) The total monthly volume, reported in tons per acre, of manure solids applied to each  
5 field of the land application area.

6 (5) The total nitrogen content of the manure solids estimated at 25 pounds of nitrogen per  
7 ton or determined from analysis of manure solids samples collected pursuant to Subsection D of this  
8 section.

9 (6) The total nitrogen concentration within the irrigation water and the amount of irrigation  
10 water applied pursuant to Subsection E of this section.

11 (7) The amount of nitrogen reported in pounds per acre from additional fertilizer(s) applied  
12 pursuant to Subsection F of this section.

13 (8) The amount of residual soil nitrogen and nitrogen from leguminous crops credited to  
14 each field of the land application area pursuant to Subsections K and L of this section.

15 **H. Crop Yield Documentation:** Crop yield documentation and plant and harvest dates of  
16 each crop grown shall be submitted to the department in the quarterly monitoring reports. Crop yield  
17 documentation shall consist of copies of scale-weight tickets or harvest summaries based on scale-weights.

18 **I. Nitrogen Concentration of Harvested Crop:** The total nitrogen concentration of each  
19 harvested crop shall be determined. A composite sample consisting of 15 sub-samples of plant material  
20 shall be taken from each field during the final harvest of each crop grown per year. Samples shall be  
21 analyzed for percent total nitrogen and percent dry matter. Analytical reports shall be submitted to the  
22 department in the quarterly monitoring reports.

23 **J. Nitrogen Removal Summary of Harvested Crop:** A nitrogen removal summary shall  
24 be developed to determine total nitrogen removed by each crop grown on each field within the land  
25 application area. Nitrogen removal shall be determined utilizing crop yield and total nitrogen concentration  
26 information collected pursuant to Subsections H and I of this section. The summary shall be submitted to  
27 the department in the quarterly monitoring reports.

28 **K. Soil Sampling – Initial for Discharge Permit Term:** For the first soil sampling event  
29 following the effective date of the discharge permit, soil samples shall be collected from each field within  
30 the land application area. Composite soil samples shall be collected between September 1 and January 31  
31 for all fields regardless of whether the field is cropped, remains fallow, or has received wastewater or  
32 stormwater. One surface composite soil sample (first-foot) and two sub-surface composite soil samples  
33 (second-foot and third-foot) shall be collected from each field. Composite soil samples shall be collected  
34 and analyzed according to the following procedure:

35 (1) Each surface and sub-surface soil sample shall consist of a single composite of 15 soil  
36 cores collected randomly throughout each field. Should a field consist of different soil textures (i.e., sandy  
37 and silty clay); soil samples shall be collected from each soil texture within each field.

- 1 (2) Surface soil samples (first-foot) shall be collected from a depth of 0 to 12 inches.  
2 (3) Each second-foot sub-surface soil sample shall be collected from a depth of 12 to 24  
3 inches.  
4 (4) Each third-foot sub-surface soil sample shall be collected from a depth of 24 to 36  
5 inches.  
6 (5) Each surface and sub-surface composite sample shall be analyzed for pH, electrical  
7 conductivity, total Kjeldahl nitrogen, nitrate as nitrogen, chloride, organic matter, potassium, phosphorus,  
8 sodium, calcium, magnesium, sulfate, soil texture, and sodium adsorption ratio.  
9 (6) pH, electrical conductivity, sodium, calcium, magnesium, and sulfate shall be analyzed  
10 using a saturated paste extract in accordance with the analytical methodology required by Subsection B of  
11 20.6.2.3224 NMAC. Phosphorus shall be analyzed using the Olsen sodium bicarbonate method in  
12 accordance with the analytical methodology required by Subsection B of 20.6.2.3224 NMAC. Nitrate as  
13 nitrogen shall be analyzed by a 2 molar KCl extract in accordance with the analytical methodology required  
14 by Subsection B of 20.6.2.3224 NMAC. Total Kjeldahl nitrogen, chloride, organic matter, potassium, soil  
15 texture, and sodium adsorption ratio shall be analyzed in accordance with the analytical methodology  
16 required by Subsection B of 20.6.2.3224 NMAC.  
17 (7) The analytical results and a map showing the fields as well as the sampling locations  
18 within each field shall be submitted to the department in the monitoring report due by May 1 following the  
19 effective date of the discharge permit.

20 **L. Soil Sampling – Routine:** Following the initial soil sampling required by this section,  
21 annual soil samples shall be collected from each field within the land application area that has received or  
22 is actively receiving wastewater or stormwater. Composite soil samples shall be collected between  
23 September 1 and January 31. For those fields that have never before received wastewater, soil samples  
24 shall be collected immediately prior to initial wastewater application and annually thereafter. Once a field  
25 has received wastewater it shall be sampled annually regardless of whether the field is cropped, remains  
26 fallow, or has recently received wastewater or stormwater. One surface composite soil sample (first-foot)  
27 and two sub-surface composite soil samples (second-foot and third-foot) shall be collected from each field.  
28 Composite soil samples shall be collected and analyzed according to the following procedure:

- 29 (1) Each surface and sub-surface soil sample shall consist of a single composite of 15 soil  
30 cores collected randomly throughout each field. Should a field consist of different soil textures (i.e., sandy  
31 and silty clay); soil samples shall be collected from each soil texture within each field.  
32 (2) Surface soil samples (first-foot) shall be collected from a depth of 0 to 12 inches.  
33 (3) Each second-foot sub-surface soil sample shall be collected from a depth of 12 to 24  
34 inches.  
35 (4) Each third-foot sub-surface soil sample shall be collected from a depth of 24 to 36  
36 inches.  
37 (5) Surface soil samples shall be analyzed for pH, electrical conductivity, nitrate as nitrogen,

1 chloride, organic matter, potassium, phosphorus, sodium, calcium, magnesium, and sodium adsorption  
2 ratio.

3 (6) Sub-surface soil samples shall be analyzed for electrical conductivity, nitrate as nitrogen,  
4 and chloride.

5 (7) pH, electrical conductivity, sodium, calcium, and magnesium shall be analyzed using a  
6 saturated paste extract in accordance with the analytical methodology required by Subsection B of  
7 20.6.2.3224 NMAC. Phosphorus shall be analyzed using the Olsen sodium bicarbonate method in  
8 accordance with the analytical methodology required by Subsection B of 20.6.2.3224 NMAC. Nitrate as  
9 nitrogen shall be analyzed by a 2 molar KCl extract in accordance with the analytical methodology required  
10 by Subsection B of 20.6.2.3224 NMAC. Chloride, organic matter, potassium, and sodium adsorption ratio  
11 shall be analyzed in accordance with the analytical methodology required by Subsection B of 20.6.2.3224  
12 NMAC.

13 (8) The analytical results and a map showing the fields as well as the sampling locations  
14 within each field shall be submitted to the department in the monitoring report due by May 1.  
15

16 **20.6.2.3226 ADDITIONAL MONITORING REQUIREMENTS FOR DAIRY FACILITIES**

17 **DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: Wastewater to**  
18 **be Evaporated – Sampling and Reporting:** A composite wastewater sample shall be collected on a  
19 quarterly basis from each wastewater or combination wastewater/stormwater impoundment used for  
20 disposal by evaporation. The composite sample from each impoundment shall consist of a minimum of six  
21 sub-samples collected around the entire perimeter of each impoundment and thoroughly mixed. Samples  
22 shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, sulfate and total dissolved solids  
23 pursuant to Subsection B of 20.6.2.3224 NMAC. Analytical results shall be submitted to the department in  
24 the quarterly monitoring reports.  
25

26 **20.6.2.3227 CONTINGENCY REQUIREMENTS FOR ALL DAIRY FACILITIES:**

27 **A. Exceedance of Ground Water Standards – Any Monitoring Well:** In the event a  
28 ground water sample and any subsequent sample collected from the same monitoring well intended to  
29 monitor a contamination source indicate a water contaminant concentration that exceeds one or more of the  
30 ground water standards of Section 20.6.2.3103 NMAC, and exceeds the concentration of such  
31 contaminant(s) in a ground water sample collected from the upgradient monitoring well, the following  
32 actions shall be taken:

33 (1) For a monitoring well associated with an impoundment: Within 90 days of the  
34 subsequent sample analysis date, the permittee shall submit and implement a corrective action plan  
35 pursuant to Subsection B of this section.

36 (2) For a monitoring well not associated with an impoundment: Within 90 days of the  
37 subsequent sample analysis date, the permittee may investigate potential sources of contamination that may

1 have caused a standard(s) to be exceeded and shall submit a corrective action plan to the department and  
2 implementation of the plan shall be initiated within 30 days of department approval. The corrective action  
3 plan shall describe the results of the investigation of potential sources of the exceedance, describe any  
4 repairs made to address the cause of the exceedance, and propose source control measures and a schedule  
5 for implementation through completion of source control measures.

6 (3) In the event ground water monitoring shows that one or more standards of Section  
7 20.6.2.3103 NMAC continue to be exceeded at least 180 days after the subsequent sample analysis date,  
8 the permittee shall submit an abatement plan proposal pursuant to Section 20.6.2.4106 NMAC. Abatement  
9 shall be performed pursuant to Sections 20.6.2.4101, 20.6.2.4103, 20.6.2.4104, and 20.6.2.4106 through  
10 20.6.2.4115 NMAC.

11 **B. Exceedance of Ground Water Standards – Impoundment Monitoring Well:** In the  
12 event the constituent concentration in a ground water sample and in any subsequent ground water sample  
13 collected from a monitoring well intended to monitor an impoundment(s) exceeds one or more of the  
14 ground water standards of Section 20.6.2.3103 NMAC, and exceeds the concentration of such  
15 constituent(s) in a ground water sample collected from the upgradient monitoring well, the permittee shall  
16 submit within 90 days of the subsequent sample analysis date a corrective action plan proposing one or  
17 more of the following measures:

18 (1) For impoundments with a primary liner composed of material other than that required by  
19 Subsection D of 20.6.2.3217 NMAC, the corrective action plan shall include:

20 (a) A proposal for reconstruction and lining of an existing impoundment, or  
21 construction and lining of a new impoundment. Reconstruction and new construction shall be completed  
22 pursuant to Section 20.6.2.3217 NMAC within one year of the subsequent sample analysis date. In the  
23 event a new impoundment is constructed, the existing impoundment shall be permanently closed pursuant  
24 to Section 20.6.2.3230 NMAC.

25 (b) Construction plans and specifications for the proposal shall be completed pursuant  
26 to Section 20.6.2.3217 NMAC.

27 (2) For impoundments with a primary liner composed of material consistent with that  
28 required by Subsection D of 20.6.2.3217 NMAC, the corrective action plan shall include:

29 (a) A proposal for the repair of the existing liner consistent with Section 20.6.2.3217  
30 NMAC, if repair is practicable. Repairs shall be completed within 180 days of the subsequent sample  
31 analysis date. In the event repair is not practicable, the corrective action plan shall propose liner  
32 replacement pursuant to Section 20.6.2.3217 NMAC, or a new lined impoundment shall be proposed and  
33 constructed pursuant to Section 20.6.2.3217 NMAC within one year of the subsequent sample analysis  
34 date. In the event a new impoundment is constructed, the existing impoundment shall be permanently  
35 closed pursuant to Section 20.6.2.3230 NMAC.

36 (b) Construction plans and specifications for the proposal shall be completed pursuant  
37 to Section 20.6.2.3217 NMAC.

1           **C.       Monitoring Well Replacement:** In the event that information available to the  
2 department indicates that a monitoring well(s) required by Section 20.6.2.3223 NMAC is not located  
3 hydrologically downgradient of the contamination source it is intended monitor, is not completed pursuant  
4 to Section 20.6.2.3223 NMAC or contains insufficient water to effectively monitor ground water quality, a  
5 replacement monitoring well(s) shall be installed. The replacement monitoring well(s) shall be installed  
6 within 120 days of notification from the department and a survey of the replacement monitoring well(s)  
7 shall be performed within 150 days of notification from the department. The replacement monitoring  
8 well(s) shall be located, installed, completed, surveyed and sampled pursuant to Section 20.6.2.3223  
9 NMAC. A monitoring well completion report shall be developed pursuant to Subsection J of 20.6.2.3223  
10 NMAC and submitted to the department within 180 days of notification from the department.

11           **D.       Exceedances of Permitted Discharge Volume:** In the event the daily discharge volume  
12 reported pursuant to Subsection C of 20.6.2.3224 NMAC exceeds the maximum daily discharge volume  
13 authorized by the discharge permit by more than ten percent for any 30 daily measurements within any 90  
14 consecutive days, the permittee shall complete and submit within 60 days of the thirtieth exceedance: a  
15 corrective action plan for reducing the discharge volume; or an application for a modified or renewed and  
16 modified discharge permit pursuant to Section 20.6.2.3205 NMAC. Implementation of the corrective  
17 action plan shall be initiated within 30 days of department approval.

18           **E.       Insufficient Impoundment Capacity:** In the event the survey or capacity calculations,  
19 or settled solids thickness measurements, indicate an existing wastewater, stormwater, or combination  
20 wastewater/stormwater impoundment is not capable of meeting the capacity requirements required by  
21 Subsection D of 20.6.2.3217 NMAC, a corrective action plan shall be submitted for department approval  
22 within 90 days of the effective date of the discharge permit. The plan may include, but is not limited to,  
23 proposals for constructing an additional impoundment, reducing the maximum daily discharge volume,  
24 removing accumulated solids, changing wastewater or stormwater management practices, or installing an  
25 advanced treatment system. The corrective action plan shall include a schedule for implementation through  
26 completion of corrective actions not to exceed one year from the submittal date of the initial corrective  
27 action plan. Implementation of the corrective action plan shall be initiated within 30 days of department  
28 approval. Should the corrective action plan include removal of accumulated solids, solids shall be removed  
29 from the impoundment in a manner that is protective of the impoundment liner. The plan shall include the  
30 method of removal, and locations and methods for storage and disposal of the solids-slurry. In the event  
31 the plan proposes land application of the solids-slurry, the plan must also include analytical results of total  
32 Kjeldahl nitrogen and chloride obtained from a representative sample of the solids-slurry to be applied.

33           **F.       Inability to Preserve Required Freeboard:** In the event that a minimum of two feet of  
34 freeboard cannot be preserved in the wastewater impoundment, a corrective action plan shall be submitted  
35 for department approval within 30 days of the date of the initial exceedance of the freeboard requirement.  
36 The plan may include, but is not limited to, proposals for constructing an additional impoundment,  
37 reducing the maximum daily discharge volume, changing wastewater management practices, or installing

1 an advanced wastewater treatment system. The corrective action plan shall include actions to be  
2 immediately implemented to regain and maintain the two feet of freeboard until permanent corrective  
3 actions have been completed, and a schedule for implementation through completion of corrective actions  
4 not to exceed one year from the submittal date of the initial corrective action plan. Implementation of the  
5 corrective action plan shall be initiated within 30 days of department approval.

6 **G. Impoundment – Structural Integrity Comprised:** In the event that damage to the  
7 berms or the liner of an impoundment occurs or conditions exist that may comprise the structural integrity  
8 of the impoundment, the damage or condition shall be reported to the department within 24 hours of  
9 discovery. A corrective action plan describing any actions taken or proposed to be taken to repair the  
10 damage or condition shall be submitted to the department within 15 days of the reported discovery. The  
11 department shall respond to the proposed corrective action plan within 30 days of receipt. Repairs to the  
12 impoundment liner or berms shall be completed pursuant to Section 20.6.2.3217 NMAC. A-proposed  
13 corrective action plan shall include a schedule for implementation through completion of corrective actions  
14 not to exceed one year from the submittal date of the initial corrective action plan. The schedule of  
15 corrective actions shall be commensurate to the magnitude and scope of the activities to be completed.  
16 Implementation of the corrective action plan shall be initiated within 30 days of department approval.

17 **H. Impoundments Utilizing Primary and Secondary Liners - Primary Liner Leakage:**  
18 In the event that the leakage rate of the leak detection system is found to be increasing or the functioning  
19 automated pump system is unable to keep the interstitial space between the liners free of fluids, a corrective  
20 action plan shall be submitted for department approval within 30 days of the date of the initial discovery.  
21 The corrective action plan shall include a schedule for implementation through completion of corrective  
22 actions not to exceed one year from the submittal date of the initial corrective action plan. Implementation  
23 of the corrective action plan shall be initiated within 30 days of department approval.

24 **I. Unauthorized Discharge - Reporting and Correction:** In the event of a spill or release  
25 that is not authorized by the discharge permit, notifications and corrective actions shall be initiated pursuant  
26 to Section 20.6.2.1203 NMAC. Wastewater or stormwater shall be contained and pumped to a permitted  
27 sump, impoundment, or land application area pursuant to these regulations. Wastewater or stormwater  
28 applied to the land application area shall conform to the requirements of Sections 20.6.2.3221 and  
29 20.6.2.3225 NMAC. Failed components shall be repaired or replaced within 48 hours from the time of  
30 failure or as soon as possible.

31  
32 **20.6.2.3228 ADDITIONAL CONTINGENCY REQUIREMENTS FOR DAIRY FACILITIES**  
33 **WITH A LAND APPLICATION AREA: Excessive Nitrogen Accumulation in Soil:** In the event that  
34 soil sampling conducted pursuant to Subsections K and L of 20.6.2.3225 NMAC indicates that excessive  
35 nitrogen accumulation has occurred within a field(s) within the land application area, the nutrient  
36 management plan (NMP) shall be revised to remove excessive nitrogen from the soil. Revisions to the  
37 NMP shall be made by a certified professional, pursuant to Subsection K of 20.6.2.3221 NMAC. The

1 NMP revisions to address excessive nitrogen accumulations within a field(s) shall be incorporated into the  
2 subsequent annual update to the NMP and shall be submitted to the department pursuant to Subsection K of  
3 20.6.2.3221 NMAC.

4  
5 **20.6.2.3229 ADDITIONAL CONTINGENCY REQUIREMENTS FOR DAIRY FACILITIES**  
6 **DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: Inability to**  
7 **Maintain Required Freeboard:** In the event that a combination wastewater/stormwater impoundment  
8 used for disposal by evaporation does not have free capacity below the two-foot freeboard level to contain  
9 the volume of stormwater runoff and direct precipitation as specified by current EPA regulatory requirements  
10 for Concentrated Animal Feeding Operations pursuant to 40 Code of Federal Regulations, Parts 122 and 412,  
11 as amended, a corrective action plan shall be submitted for department approval within seven days of the  
12 date of discovery of insufficient free capacity. The plan shall include, but is not limited to, a request for  
13 temporary permission to discharge to allow immediate removal and disposal of combined wastewater and  
14 stormwater, a proposal for long-term corrective actions which may include constructing an additional  
15 impoundment, reducing the maximum daily discharge volume, changing wastewater or stormwater  
16 management practices, or installing an advanced treatment system. The corrective action plan shall also  
17 include a schedule for implementation through completion not to exceed one year from the submittal date  
18 of the initial corrective action plan. The corrective action plan shall be implemented upon department  
19 approval.

20  
21 **20.6.2.3230 CLOSURE REQUIREMENTS FOR ALL DAIRY FACILITIES:**

22 **A. Permanent Closure of Dairy Facility or Impoundments:** The following closure  
23 actions shall be performed at dairy facilities:

24 (1) For permanent closure of a dairy facility:

25 (a) The department shall be notified no later than 30 days after wastewater discharge  
26 has permanently ceased and all livestock have been removed from the dairy facility.

27 (b) Installation of all monitoring wells shall be completed pursuant to Section  
28 20.6.2.3223 NMAC.

29 (c) All impoundments shall be emptied of wastewater and stormwater within six  
30 months of permanently ceasing wastewater discharge and removing all livestock from the dairy facility.  
31 Wastewater and stormwater removed from impoundments shall be applied to the designated land  
32 application area, as authorized by a discharge permit. In the event that land application is not authorized by  
33 a discharge permit, a disposal plan shall be submitted for department approval and the plan implemented  
34 upon department approval.

35 (d) Complete removal of manure solids from the impoundment(s) shall be achieved  
36 within two years of permanently ceasing wastewater discharge and removing all livestock from the dairy  
37 facility. Manure solids shall be applied to the designated land application area, as authorized by a

1 discharge permit. In the event that land application is not authorized by a discharge permit, a disposal plan  
2 shall be submitted for department approval and the plan implemented upon department approval.

3 (e) All manure solids and compost shall be removed from the dairy facility and  
4 applied to the designated land application area, as authorized by a discharge permit, or transferred off-site  
5 for proper disposal within one year of permanently ceasing wastewater discharge and removing all  
6 livestock from the facility.

7 (f) Impoundment liner(s) shall be perforated or removed and the impoundment shall  
8 be re-graded with clean fill to blend with surface topography to prevent ponding within two years of  
9 permanently ceasing wastewater discharge and removing all livestock from the facility.

10 (2) For closure of existing impoundments upon replacement with new impoundments:

11 (a) Existing impoundments shall be emptied of wastewater and stormwater within six  
12 months of completion of the new impoundments. Wastewater and stormwater removed from  
13 impoundments shall be applied to the designated land application area, as authorized by a discharge permit.  
14 In the event that land application is not authorized by a discharge permit, a disposal plan shall be submitted  
15 for department approval and the plan implemented upon department approval.

16 (b) Complete removal of manure solids from impoundments shall be achieved within  
17 two years of completion of the new impoundments. Manure solids shall be applied to the designated land  
18 application area, as authorized by a discharge permit. In the event that land application is not authorized by  
19 a discharge permit, a disposal plan shall be submitted for department approval and the plan implemented  
20 upon department approval.

21 (c) Impoundment liners shall be perforated or removed and the impoundments shall be  
22 re-graded with clean fill to blend with surface topography to prevent ponding within two years of  
23 completion of the new impoundments.

24 **B. Post-Closure Ground Water Sampling and Reporting:** Following completion and  
25 confirmation by the department of the requirements of Subsection A of this section, ground water  
26 monitoring shall continue pursuant to Section 20.6.2.3223 NMAC until a minimum of eight consecutive  
27 ground water sampling events confirm that the standards of Section 20.6.2.3103 NMAC are not exceeded  
28 and the total nitrogen concentration in ground water is less than or equal to 10 milligrams per liter. If  
29 monitoring results show that one or more of the standards of Section 20.6.2.3103 NMAC is exceeded or the  
30 total nitrogen concentration in ground water is greater than 10 milligrams per liter, contingency  
31 requirements shall be implemented pursuant to Section 20.6.2.3227 NMAC. Upon notification from the  
32 department that post-closure ground water monitoring may cease, all monitoring wells shall be abandoned  
33 and a report shall be submitted to the department pursuant to Subsection C of this section.

34 **C. Monitoring Well Abandonment:** Upon notification from the department, monitoring  
35 wells shall be abandoned pursuant to Part 19.27.4 NMAC and the following requirements:

1 (1) The well casing shall be removed and bentonite-cement grout, neat cement grout, or  
2 bentonite grout, prepared as specified in this section, shall be placed from the bottom of the borehole to the  
3 ground surface using a tremmie pipe.

4 (2) In the event the casing cannot be removed, bentonite-cement grout, neat cement grout,  
5 or bentonite grout shall be emplaced in the well using a tremmie pipe from the bottom of the well to the  
6 ground surface.

7 (3) A well abandonment report shall be prepared by the permittee and shall provide  
8 information equivalent to the plugging record requirements of Part 19.27.4 NMAC. The well abandonment  
9 report shall be submitted to the department within 60 days of completion of well plugging activities.

10

11 **20.6.2.3231 ADDITIONAL CLOSURE REQUIREMENTS FOR DAIRY FACILITIES WITH**  
12 **A LAND APPLICATION AREA: [RESERVED]**

13

14 **20.6.2.3232 ADDITIONAL CLOSURE REQUIREMENTS FOR DAIRY FACILITIES**  
15 **DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: [RESERVED]**

16

17 **20.6.2.3233 RECORD RETENTION REQUIREMENTS FOR ALL DAIRY FACILITIES:**

18 **A.** A written record shall be retained at the dairy facility of all data and information related  
19 to field measurements, sampling, and analysis conducted pursuant to this part and the discharge permit.  
20 The following information shall be recorded and shall be made available to the department upon request:

- 21 (1) The dates, exact place and times of sampling or field measurements;
- 22 (2) The name and job title of the individuals who performed each sample collection or field  
23 measurement;
- 24 (3) The date of the analysis of each sample;
- 25 (4) The name and address of the laboratory and the name and job title of the person that  
26 performed the analysis of each sample;
- 27 (5) The analytical technique or method used to analyze each sample or take each field  
28 measurement;
- 29 (6) The results of each analysis or field measurement, including raw data;
- 30 (7) The results of any split, spiked, duplicate or repeat sample; and
- 31 (8) A description of the quality assurance and quality control procedures used.

32 **B.** A written record shall be retained at the dairy facility of any spills, seeps, or leaks of  
33 effluent, and of leachate or process fluids not authorized by the discharge permit. Records shall be made  
34 available to the department upon request.

35 **C.** A written record shall be retained at the dairy facility of the operation, maintenance, and  
36 repair of all features/equipment used to treat, store or dispose of wastewater, measure flow rates, monitor  
37 water quality, or collect other data. Records shall include repair, replacement or calibration of any

1 monitoring equipment and repair or replacement of any equipment used in the waste or wastewater  
2 treatment and disposal system. Records shall be made available to the department upon request.

3 **D.** Records of all monitoring information shall be retained at the dairy facility, including all  
4 calibration and maintenance records, copies of all reports, and the application for the discharge permit.  
5 Records shall be retained for a period of at least 10 years from the date of the sample collection,  
6 measurement, report or application.

7  
8 **20.6.2.3234 TRANSFER OF DAIRY DISCHARGE PERMITS:**

9 **A.** Transfer of discharge permits for dairy facilities shall be made pursuant to Subsections A,  
10 B, and E of 20.6.2.3111 NMAC and this section. Subsections C and D of 20.6.2.3111 NMAC shall not  
11 apply to the transfer of discharge permits for dairy facilities.

12 **B.** The transferee(s) shall notify the department, in writing, of the date of transfer of  
13 ownership and provide contact information for the new owner(s) pursuant to Subsection C of 20.6.2.3207  
14 NMAC. Notification shall be submitted to the department of the transfer within 30 days of the ownership  
15 transfer date.

16  
17 **20.6.2.3235 CONTINUING EFFECT OF PRIOR ACTIONS DURING TRANSITION:**

18 **A.** A discharge permit issued pursuant to Section 20.6.2.3109 NMAC that has not expired on  
19 or before the effective date of Sections 20.6.2.3200 through 20.6.2.3235 NMAC shall remain in effect and  
20 enforceable pursuant to the terms and conditions of the discharge permit.

21 **B.** Sections 20.6.2.3200 through 20.6.2.3235 NMAC shall apply, unless otherwise specified  
22 in these regulations, to any discharge permit issued after the effective date of these regulations. An  
23 application for a new discharge permit submitted to the department prior to the effective date of these  
24 regulations, shall be accepted by the department if the application has been deemed administratively  
25 complete and the requirements of Subsection D of 20.6.2.3108 NMAC have been satisfied. An application  
26 for a renewed or modified discharge permit submitted to the department prior to the effective date of these  
27 regulations, shall be accepted by the department if the application has been deemed administratively  
28 complete, the requirements of Subsection D of 20.6.2.3108 NMAC have been satisfied, and the expiration  
29 date of the existing discharge permit is prior to the effective date of these regulations.

30 **C.** Proposed approval or disapproval of previously-submitted applications that are accepted  
31 by the department shall be made in accordance with the following schedule and are subject to the public  
32 notice requirements of Section 20.6.2.3108 NMAC. The permittee shall have ninety days from the date of  
33 the discharge permit issuance to submit all the necessary information to comply with Sections 20.6.2.3205  
34 through 20.6.2.3208 NMAC.

35 (1) For new discharge permit applications and discharge permits whose terms end prior to  
36 calendar year 2006, proposed approval of a discharge permit or disapproval of an application shall be  
37 mailed to the applicants within 90 days of the effective date of these regulations.

1 (2) For discharge permits whose terms end in calendar year 2006, proposed approval of a  
2 discharge permit or disapproval of an application shall be mailed to the applicants within 180 days of the  
3 effective date of these regulations.

4 (3) For discharge permits whose terms end in calendar year 2007, proposed approval of a  
5 discharge permit or disapproval of an application shall be mailed to the applicants within 270 days of the  
6 effective date of these regulations.

7 (4) For discharge permits whose terms end in calendar year 2008, proposed approval of a  
8 discharge permit or disapproval of an application shall be mailed to the applicants within 360 days of the  
9 effective date of these regulations.

10 (5) For discharge permits whose terms end in calendar year 2009, proposed approval of a  
11 discharge permit or disapproval of an application shall be mailed to the applicants within 450 days of the  
12 effective date of these regulations.

13 (6) For discharge permits whose terms end between January 1, 2010 and the effective date  
14 of this section, proposed approval of a discharge permit or disapproval of an application shall be mailed to  
15 the applicants within 540 days of the effective date of these regulations.

16 **D.** Any dairy facility discharging, capable of recommencing discharging, or that has ceased  
17 discharging within the term of its most recent discharge permit shall continue all monitoring and submittal  
18 of monitoring reports as prescribed in the most recent discharge permit until the department issues a  
19 renewed or renewed and modified discharge permit.

20 **E.** Any discharge permit proposed for approval (i.e., draft discharge permit) by the  
21 department pursuant to Section 20.6.2.3109 NMAC, but not made final prior to the effective date of these  
22 regulations, is hereby withdrawn. Any permit fee submitted prior to the department's withdrawal of such a  
23 draft discharge permit shall be applied towards the assessed permit fee for the initial permit issued pursuant  
24 to these regulations.