

GROUND WATER DISCHARGE PERMIT
Savoy Travel Center, DP-1204

I. INTRODUCTION

The New Mexico Environment Department (NMED) issues this Discharge Permit, DP-1204, to Sean Curtis (permittee) pursuant to the New Mexico Water Quality Act (WQA), NMSA 1978 §§74-6-1 through 74-6-17, and the New Mexico Water Quality Control Commission (WQCC) Regulations, 20.6.2 NMAC.

NMED's purpose in issuing this Discharge Permit, and in imposing the requirements and conditions specified herein, is to control the discharge of water contaminants from Savoy Travel Center into ground and surface water, so as to protect ground and surface water for present and potential future use as domestic and agricultural water supply and other uses and protect public health. In issuing this Discharge Permit, NMED has determined that the requirements of Subsection C of 20.6.2.3109 NMAC have been met.

The activities which produce the discharge, the location of the discharge, and the quantity, quality and flow characteristics of the discharge are briefly described as follows:

Up to 10,000 gallons per day (gpd) of domestic wastewater is discharged from a restaurant and fuel services facility through a 1,500-gallon grease interceptor, a 20,000 gallon septic tank, and a 2,000 gallon dosing tank with final disposal to a 1.5-acre four-celled synthetically lined total evaporation lagoon system. The discharge contains water contaminants or toxic pollutants which may be elevated above the standards of Section 20.6.2.3103 NMAC. The facility is located at 14150 Highway 418 SW, approximately 13 miles west of Deming, in Sections 5 & 8, T24S, R11W, Luna County. Ground water most likely to be affected is at a depth of approximately 169 feet and has a total dissolved solids concentration of approximately 235 mg/L.

The permittee's application consists of the materials submitted by Sean Curtis dated December 10, 2007 and additional information received on January 29, 2008, November 19, 2008, February 25, 2009 and materials as applicable. The discharge shall be managed in accordance with all conditions and requirements of this Discharge Permit.

Pursuant to Section 20.6.2.3109 NMAC, NMED reserves the right to require a Discharge Permit Modification in the event NMED determines that the requirements of 20.6.2 NMAC are being or may be violated or the standards of Section 20.6.2.3103 NMAC are being or may be violated. This may include a determination that structural controls and/or management practices approved under this Discharge Permit are not protective of ground water quality, and that more stringent requirements to protect and/or remediate ground water quality may be required by NMED. These requirements may include: relining of the lagoon; changing waste management practices; expanding monitoring requirements; installing an advanced treatment system; and/or implementing abatement of water pollution.

Issuance of this Discharge Permit does not relieve Sean Curtis of the responsibility to comply with the WQA, WQCC Regulations, and any other applicable federal, state and/or local laws and regulations, such as zoning requirements and nuisance ordinances.

The following abbreviations may be used in this Discharge Permit:

Abbreviation	Explanation	Abbreviation	Explanation
BOD ₅	biochemical oxygen demand (5-day)	NMSA	New Mexico Statutes Annotated
CFR	Code of Federal Regulations	NO ₃ -N	nitrate-nitrogen
CFU	colony forming units	NTU	nephelometric turbidity units
Cl	chloride	TDS	total dissolved solids
LADS	land application data sheet(s)	TKN	total Kjeldahl nitrogen
mg/L	milligrams per liter	TSS	total suspended solids
mL	milliliters	total nitrogen	TKN+NO ₃ -N
NMAC	New Mexico Administrative Code	WQCC	Water Quality Control Commission
NMED	New Mexico Environment Department	TRC	Total Residual Chlorine

II. FINDINGS

In issuing this Discharge Permit, NMED finds:

1. Sean Curtis is discharging effluent or leachate from the Savoy Travel Center so that such effluent or leachate may move directly or indirectly into ground water within the meaning of Section 20.6.2.3104 NMAC.
2. Sean Curtis is discharging effluent or leachate from the Savoy Travel Center so that such effluent or leachate may move into ground water of the State of New Mexico which has an existing concentration of 10,000 milligrams per liter or less of total dissolved solids within the meaning of Subsection A of 20.6.2.3101 NMAC.
3. The discharge from the Savoy Travel Center is not subject to any of the exemptions of Section 20.6.2.3105 NMAC.

III. CONDITIONS

The following conditions shall be complied with by Sean Curtis and are enforceable by NMED. Sean Curtis is permitted to discharge water contaminants subject to the following conditions:

OPERATIONAL PLAN

#	Terms and Conditions
1.	The permittee shall implement the following operational plan to ensure compliance with Title 20, Chapter 6, Parts 1 and 2 NMAC. [20.6.2.3106.C NMAC, 20.6.2.3107 NMAC]
2.	The permittee shall operate in a manner such that standards and requirements of Sections 20.6.2.3101 and 20.6.2.3103 NMAC are not violated. [20.6.2.3101 NMAC, 20.6.2.3103 NMAC]

3.	The permittee is authorized to discharge up to 10,000 gallons per day of wastewater to a 1.5-acre four-celled synthetically lined total evaporation lagoon system. Wastewater is conveyed through a grease interceptor, septic tank, and dosing tank prior to final disposal in the evaporation lagoon. [20.6.2.3104 NMAC]
4.	Until such time when the facility is able to discharge to the newly constructed wastewater treatment and disposal system, the permittee shall continue to follow all corrective actions and reporting schedules as outlined in Paragraph 30 of the Administrative Compliance Order issued to Sean Curtis dba Savoy Travel Center on August 30, 2007 (copy enclosed). [NMSA 1978 §74-6-10F]
5.	The permittee shall maintain a minimum of two feet of freeboard in the lagoon at all times. In the event that a minimum of two feet of freeboard cannot be maintained at all times, the permittee shall submit a corrective action plan for NMED approval to modify the management of discharge volumes. [20.6.2.3107 NMAC, 20.6.2.3109 NMAC]
6.	Within 90 days of the effective date of this Discharge Permit (by [date]), the permittee shall construct and begin discharging to the proposed wastewater treatment system according to the final construction plans and specification submitted to NMED on November 19, 2008 and as amended on February 25, 2009. The permittee shall notify NMED at the commencement of construction to allow NMED personnel to be onsite for inspection during the construction phase. Record drawings of the finished wastewater treatment facility shall be submitted to NMED within 30 days of completion. A licensed New Mexico professional engineer shall certify all construction plans and specifications, supporting design calculations, and record drawings of the wastewater treatment system. [20.6.2.3109 NMAC]
7.	Prior to discharging to the newly constructed wastewater treatment and disposal system (i.e., total evaporation lagoon), the permittee shall give written notification to NMED stating the date the discharge is to commence. [20.6.2.3109.H NMAC]
8.	Within 90 days of the effective date of this Discharge Permit, by (date), the permittee shall install a grease interceptor sized and designed according to Uniform Plumbing Code (UPC) specifications to accommodate the discharge from the restaurant kitchen. The sizing of the grease interceptor shall be approved by NMED prior to installation. Record drawings of the grease interceptor shall be submitted to NMED within 30 days of completion. [20.6.2.3109 NMAC]
9.	Within 90 days of the effective date of this Discharge Permit (by [date]), the permittee shall install fences around the entire wastewater treatment facility. The fences shall be constructed in a manner which prevents access by the general public and animals such as dogs (e.g., chain link or field fencing) and shall be maintained throughout the term of this Discharge Permit. [20.6.2.3109 NMAC]
10.	Within 90 days of the effective date of this Discharge Permit (by [date]) the permittee shall post signs in English and Spanish at the facility entrance and other areas where public contact is possible indicating that the water is not potable. All signs shall remain visible and legible for the term of this Discharge Permit. [20.6.2.3109 NMAC]
11.	The permittee shall visually inspect the lagoon and surrounding berms on a monthly basis to ensure proper maintenance. Any conditions that could damage the lagoon liner or affect the structural integrity of the lagoon shall be corrected. Such conditions include but are not limited to erosion damage, animal activity/damage, the presence of potentially harmful

	vegetation such as woody shrubs or uncontrolled weeds, evidence of seepage, or the presence of large pieces or quantities of debris. The permittee shall keep a log of the inspection findings and repairs made. In the event that inspection findings reveal significant damage likely to affect the ability of the lined lagoon to contain contaminants, the permittee shall submit a corrective action plan to NMED for approval. [20.6.2.3107 NMAC]
12.	The permittee shall utilize operators, certified by the State of New Mexico at the appropriate level, to operate the wastewater collection, treatment, and disposal systems. All operations and maintenance of all or any part of the wastewater system shall be performed by, or under the direct supervision of, a certified operator. [20.7.4 NMAC]

MONITORING, REPORTING, AND OTHER REQUIREMENTS

#	Terms and Conditions
13.	The permittee shall conduct the following monitoring, reporting, and other requirements listed below. [20.6.2.3107 NMAC]
14.	METHODOLOGY - Unless otherwise approved in writing by NMED, the permittee shall conduct sampling and analysis in accordance with the most recent edition of the following documents: <ol style="list-style-type: none"> a) American Public Health Association, Standard Methods for the Examination of Water and Wastewater (18th, 19th or current); b) U.S. Environmental Protection Agency, Methods for Chemical Analysis of Water and Waste; c) U.S. Geological Survey, Techniques for Water Resources Investigations of the U.S. Geological Survey; d) American Society for Testing and Materials, Annual Book of ASTM Standards, Part 31. Water; e) U.S. Geological Survey, et al., National Handbook of Recommended Methods for Water Data Acquisition; and f) Methods of Soil Analysis: Part 1. Physical and Mineralogical Methods and Part 2. Chemical and Microbiological Properties, American Society of Agronomy. [20.6.2.3107.B NMAC]
15.	The permittee shall submit semi-annual monitoring reports to NMED by January 15 and July 15 of each year. Monitoring requirements detailed in this Discharge Permit are summarized on the sheet titled <i>Summary of Required Actions, Monitoring and Reporting</i> . [20.6.2.3107 NMAC]
16.	The permittee shall estimate the monthly volume of wastewater discharged to the lagoons by multiplying the total monthly operating time of the dosing tank effluent sump pumps by the pumping rate. The record of the monthly operating time for the pumps and estimated monthly discharge volumes shall be submitted to NMED in the semi-annual monitoring reports. The equipment hours meters used to track the operating time of the pumps shall be kept functional at all times. [20.6.2.3107 NMAC]
17.	The permittee shall sample wastewater from a representative location within the lagoon treatment system on a semi-annual basis and analyze the samples for TKN, NO ₃ -N, TDS and Cl. Analytical results shall be submitted to NMED in the semi-annual monitoring

	reports. [20.6.2.3107 NMAC]
18.	The permittee shall inspect the grease interceptor on a quarterly basis and pump it as needed. Inspection records shall be kept on-site. Pumping invoices shall be submitted to NMED in the semi-annual monitoring reports. [20.6.2.3109 NMAC]
19.	The permittee shall inspect the septic tank semi-annually for the accumulation of scum and solids. In the event that the scum layer exceeds three inches or the settled solids occupy 50% of the tank or more, the contents of the tank shall be pumped by a licensed hauler. The inspection and pumping records shall be submitted to NMED in the semi-annual monitoring reports. [20.6.2.3107 NMAC]
20.	The permittee shall inspect the dosing tank on a quarterly basis, and clean it as needed. The inspection and cleaning records shall be submitted to NMED in the semi-annual monitoring reports. [20.6.2.3107 NMAC]
21.	<p>Within 90 days of the effective date of this Discharge Permit (by DATE), the permittee shall install 1 new monitoring well. The permittee shall install:</p> <ul style="list-style-type: none"> • One monitoring well (MW-8) located 20 to 50 feet hydrologically downgradient of the lagoon. <p>All monitoring well locations shall be approved by NMED prior to installation. The wells shall be completed in accordance with the attachment titled <i>Ground Water Discharge Permit Monitoring Well Construction and Abandonment Conditions</i>, Revision 1.0, June 2008. Construction and lithologic logs for all monitoring wells shall be submitted to NMED within 30 days of well completion. [20.6.2.3107 NMAC]</p>
22.	<p>Within 120 days of the effective date of this Discharge Permit (by DATE), the permittee shall survey all wells approved by NMED for Discharge Permit monitoring purposes to a U.S. Geological Survey (USGS) or other permanent benchmark. Survey data shall include northing, easting and elevation to the nearest hundredth of a foot or in accordance with the "Minimum Standards for Surveying in New Mexico" (12.8.2 NMAC). A survey elevation shall be established at the top-of-casing, with a permanent marking indicating the point of survey. The survey shall be completed and certified by a licensed New Mexico professional surveyor. Depth-to-water shall be measured to the nearest hundredth of a foot in all surveyed wells, and the data shall be used to develop a map showing the location of all monitoring wells and the direction and gradient of ground water flow at the facility. The data and map of ground water flow direction at the facility shall be submitted to NMED within 30 days of survey completion. If ground water flow information determined from the monitoring well survey indicates that the monitoring wells were not installed hydrologically downgradient of the intended discharge locations, well replacement or additional wells may be required. [20.6.2.3107 NMAC]</p>
23.	<p>The permittee shall perform semi-annual ground water sampling in 3 wells used for monitoring. The permittee shall sample:</p> <ul style="list-style-type: none"> • MW-7, intended to be located hydrologically upgradient of the facility (i.e., 150 feet northwest of facility at 450875 Northing and 2676698 Easting); • MW-2, intended to be located cross gradient from MW-7 and adjacent to the facility at 450966 Northing and 2676541 Easting; • MW-8, intended to be located 20 to 50 feet hydrologically downgradient of the lagoon; and <p>The ground water sampling shall be performed according to the following procedure:</p>

	<p>a) measure the depth-to-ground water from the top of well casing to the nearest hundredth of a foot;</p> <p>b) purge three well volumes of water from the well prior to sample collection; and</p> <p>c) obtain samples from the well to be analyzed for NO₃-N, TKN, Cl, and TDS.</p> <p>Depth-to-water measurements, analytical results, and a facility layout map showing the location and number of each well shall be submitted to NMED immediately after the initial sampling and in the semi-annual monitoring reports. [20.6.2.3107 NMAC]</p>
--	--

CONTINGENCY PLAN

#	Terms and Conditions
24.	In the event that monitoring indicates ground water standards are violated during the term of this Discharge Permit, upon closure of the facility or during post-closure monitoring, the permittee shall collect a confirmatory sample from the monitoring well within 15 days to confirm the initial sampling results. Within 15 days of confirmation of ground water contamination, the permittee shall submit to NMED a corrective action plan that proposes measures to mitigate damage from the discharge including, at a minimum, source control measures and an implementation schedule. The permittee may be required to abate water pollution pursuant to Sections 20.6.2.4000 through 20.6.2.4115 NMAC, if the corrective action plan will not result in compliance with the standards and requirements set forth in Section 20.6.2.4103 NMAC within 180 days of confirmation of ground water contamination. [20.6.2.1203 NMAC, 20.6.2.4105.A(8) NMAC]
25.	In the event of a spill or release that is not authorized under this Discharge Permit, the permittee shall initiate the notifications and corrective actions as required in Section 20.6.2.1203 NMAC. The permittee shall take immediate corrective action to contain and remove or mitigate the damage caused by the discharge. Within 24 hours after discovery of the discharge, the permittee shall verbally notify NMED and provide the information required by Paragraph (1) of Subsection A of 20.6.2.1203 NMAC. Within 7 days of discovering the discharge, the permittee shall submit a written report to NMED verifying the oral notification and providing any additional information or changes. The permittee shall submit a corrective action report within 15 days after discovery of the discharge. [20.6.2.1203 NMAC]
26.	In the event NMED or the permittee identifies any other failures of the Discharge Permit or system not specifically noted herein, NMED may require the permittee to develop for NMED approval contingency plans and schedules to cope with the failures. [20.6.2.3107.A(10) NMAC]

CLOSURE PLAN

#	Terms and Conditions
27.	<p>Upon closure of the facility, the permittee shall perform the following closure measures:</p> <p>a) Remove or plug all lines leading to the lagoon, grease interceptor, septic tank, and dosing tank so that a discharge can no longer occur.</p> <p>b) Pump and/or evaporate all liquids from the lagoon, grease interceptor, septic tank, and dosing tank and dispose of all sludge in accordance with all local, state, and federal (40</p>

	<p>CFR Part 503) regulations.</p> <p>c) Backfill the grease interceptor, septic tank, and dosing tank with clean fill or sand or remove from the site.</p> <p>d) Perforate or remove the lagoon liner and re-grade the lagoon with clean fill to blend with surface topography and prevent ponding.</p> <p>e) Continue ground water monitoring as required by this Discharge Permit for two years after closure to confirm the absence of ground water contamination. If monitoring results show that the ground water standards in Section 20.6.2.3103 NMAC are being violated, the permittee shall implement the contingency plan required by this Discharge Permit.</p> <p>f) Following notification from NMED that post-closure monitoring may cease, the permittee shall plug and abandon the monitoring well(s) in accordance with the attachment titled <i>Ground Water Discharge Permit Monitoring Well Construction and Abandonment Conditions</i>, Revision 1.0, June 2008.</p> <p>When all post-closure requirements have been met, the permittee may request to terminate the Discharge Permit. [20.6.2.3107.A(11) NMAC]</p>
--	--

GENERAL TERMS AND CONDITIONS

#	Terms and Conditions
28.	<p>RECORD KEEPING - The permittee shall maintain at its facility a written record of all data and information related to field measurements, sampling, and analysis conducted pursuant to this Discharge Permit. The following information shall be recorded and shall be made available to NMED upon request:</p> <p>a) The dates, exact place and times of sampling or field measurements;</p> <p>b) The name and job title of the individuals who performed each sample collection or field measurement;</p> <p>c) The date of the analysis of each sample;</p> <p>d) The name and address of the laboratory and the name and job title of the person that performed the analysis of each sample;</p> <p>e) The analytical technique or method used to analyze each sample or take each field measurement;</p> <p>f) The results of each analysis or field measurement, including raw data;</p> <p>g) The results of any split sampling, spikes or repeat sampling; and</p> <p>h) A description of the quality assurance and quality control procedures used.</p> <p>[20.6.2.3107.A NMAC]</p>
29.	<p>RECORD KEEPING - The permittee shall maintain a written record of any spills, seeps, and/or leaks of effluent, and of leachate and/or process fluids not authorized by this Discharge Permit. [20.6.2.3107.A NMAC]</p>
30.	<p>RECORD KEEPING - The permittee shall maintain a written record of the operation, maintenance, and repair of all facilities/equipment used to treat, store or dispose of wastewater; to measure flow rates, to monitor water quality, or to collect other data required by this Discharge Permit. This record shall include repair, replacement or calibration of any monitoring equipment and repair or replacement of any equipment used in the permittee's waste or wastewater treatment and disposal system. [20.6.2.3107.A</p>

	NMAC]
31.	RECORD KEEPING - The permittee shall maintain a written record of the amount of wastewater, effluent, leachate or other wastes discharged pursuant to this Discharge Permit. [20.6.2.3107.A NMAC]
32.	RECORD KEEPING - The permittee shall retain records of all monitoring information, including all calibration and maintenance records, copies of all reports required by this Discharge Permit, and records of all data used to complete the application for this Discharge Permit for a period of at least five years from the date of the sample collection, measurement, report or application. This period may be extended by request of the Secretary at any time. [20.6.2.3107.A NMAC]
33.	INSPECTION and ENTRY - The permittee shall allow the Secretary or an authorized representative, upon the presentation of credentials, to: <ul style="list-style-type: none"> a) Enter at regular business hours or at other reasonable times upon the permittee's premises or other location where records must be kept under the conditions of this Discharge Permit, or under any federal or WQCC regulation. b) Inspect and copy, during regular business hours or at other reasonable times, any records required to be kept under the conditions of this Discharge Permit, or under any federal or WQCC regulation. c) Inspect, at regular business hours or at other reasonable times, any facility, equipment (including monitoring and control equipment or treatment works), practices or operations regulated or required under this Discharge Permit, or under any federal or WQCC regulation. d) Sample or monitor, at reasonable times for the purpose of assuring compliance with this Discharge Permit or as otherwise authorized by the New Mexico Water Quality Act, any effluent, water contaminant, or receiving water at any location before or after discharge. [20.6.2.3107.D NMAC, 74-6-9(B) & (E) WQA]
34.	INSPECTION and ENTRY - Nothing in this Discharge Permit shall be construed as limiting in any way the inspection and entry authority of NMED under the WQA, the WQCC Regulations, or any other applicable law or regulation. [20.6.2.3107 NMAC, 74-6-9(B) & (E) WQA]
35.	DUTY to PROVIDE INFORMATION - The permittee shall furnish to NMED, within a reasonable time, any documents or other information which it may request to determine whether cause exists for modifying, terminating and/or renewing this Discharge Permit or to determine compliance with this Discharge Permit. The permittee shall also furnish to NMED, upon request, copies of documents required to be kept by this Discharge Permit. [20.6.2.3107.D NMAC, 74-6-9(B) & (E) WQA]
36.	SPILLS, LEAKS, and OTHER UNAUTHORIZED DISCHARGES - This Discharge Permit authorizes only those discharges specified herein. Any unauthorized discharges violate Section 20.6.2.3104 NMAC and must be reported to NMED and remediated as required by Section 20.6.2.1203 NMAC. [20.6.2.1203 NMAC]
37.	MODIFICATIONS and/or AMENDMENTS - The permittee shall notify NMED of any changes to the permittee's wastewater treatment and disposal system, including any changes in the wastewater flow rate or the volume of wastewater storage, or of any other changes to operations or processes that would result in any significant change in the

	discharge of water contaminants. The permittee shall obtain NMED's approval, as a modification to this Discharge Permit pursuant to Subsections E, F, or G of 20.6.2.3109 NMAC, prior to any increase in the quantity discharged, or any increase in the concentration of water contaminants discharged, above those levels approved in this Discharge Permit. [20.6.2.3107.C NMAC]
38.	ENFORCEMENT - Any violation of the requirements and conditions of this Discharge Permit, including any failure to allow NMED staff to enter and inspect records or facilities, or any refusal or failure to provide NMED with records or information, may subject the permittee to an enforcement action. Pursuant to WQA 74-6-10(A) and (B), such action may include a compliance order requiring compliance immediately or in a specified time, assessing a civil penalty, modifying or terminating the Discharge Permit, or any combination of the foregoing; or an action in district court seeking injunctive relief, civil penalties, or both. Pursuant to WQA 74-6-10(C) and 74-6-10.1, civil penalties of up to \$15,000 per day of noncompliance may be assessed for each violation of the WQA 74-6-5, the WQCC Regulations, or this Discharge Permit, and civil penalties of up to \$10,000 per day of noncompliance may be assessed for each violation of any other provision of the WQA, or any regulation, standard, or order adopted pursuant to such other provision. For certain violations specified in WQA 74-6-10.2, criminal penalties may also apply. In any action to enforce this Discharge Permit, the permittee waives any objection to the admissibility as evidence of any data generated pursuant to this Discharge Permit. [74-6 WQA]
39.	COMPLIANCE WITH OTHER LAWS - Nothing in this Discharge Permit shall be construed in any way as relieving the permittee of the obligation to comply with all applicable federal, state, and local laws, regulations, permits or orders. [20.6.2 NMAC]
40.	RIGHT to APPEAL - The permittee may file a petition for review before the WQCC on this Discharge Permit. Such petition shall be in writing to the WQCC within thirty (30) days of the receipt of this Discharge Permit. Unless a timely petition for review is made, the decision of NMED shall be final and not subject to judicial review. [74-6-5(O) WQA]
41.	TRANSFER of DISCHARGE PERMIT - Prior to the transfer of any ownership, control, or possession of this permitted facility or any portion thereof, the permittee shall notify the proposed transferee in writing of the existence of this Discharge Permit and include a copy of this Discharge Permit with the notice. The permittee shall deliver or send by certified mail to NMED a copy of the notification and proof that such notification has been received by the proposed transferee. [20.6.2.3111 NMAC]
42.	TERM - Pursuant to WQA 74-6-5(I) and Subsection H of 20.6.2.3109 NMAC, the term of this Discharge Permit is five years from its effective date. To renew this Discharge Permit, the permittee must submit an application for renewal at least 180 days before the termination date. [20.6.2.3109.H NMAC, 74-6-5(I) WQA]
43.	Payment of permit fees is due at the time of Discharge Permit approval. Permit fees shall be paid in a single payment or shall be paid in equal installments on a yearly basis over the term of the Discharge Permit. Single payments shall be remitted to NMED no later than 30 days after the Discharge Permit effective date. Initial installment payments shall be remitted to NMED no later than 30 days after the Discharge Permit effective date; subsequent installment payments shall be remitted to NMED no later than the anniversary of the Discharge Permit effective date. An approved Discharge Permit shall be suspended

	or terminated if the facility fails to remit an installment payment by its due date. [20.6.2.3114.F NMAC, 74-6-5(K) WQA]
--	---

EFFECTIVE DATE: effective date

EXPIRATION DATE: expiration date

WILLIAM C. OLSON
Chief, Ground Water Quality Bureau
New Mexico Environment Department

draft