

**ATTACHMENT M2**  
**GEOLOGIC REPOSITORY**

(This page intentionally blank)

## ATTACHMENT M2

### GEOLOGIC REPOSITORY

#### TABLE OF CONTENTS

List of Tables .....	<a href="#">M2-ii</a>
List of Figures .....	<a href="#">M2-ii</a>
M2-1 <u>Description of the Geologic Repository</u> .....	<a href="#">M2-1</a>
M2-2 <u>Geologic Repository Design and Process Description</u> .....	<a href="#">M2-2</a>
M2-2a <u>Geologic Repository Design and Construction</u> .....	<a href="#">M2-2</a>
M2-2a(1) <u>CH TRU Mixed Waste Handling Equipment</u> .....	<a href="#">M2-3</a>
M2-2a(2) <u>Shafts</u> .....	<a href="#">M2-5</a>
M2-2a(3) <u>Subsurface Structures</u> .....	<a href="#">M2-6</a>
M2-2a(4) <u>RH TRU Mixed Waste Handling Equipment</u> .....	<a href="#">M2-10</a>
M2-2b <u>Geologic Repository Process Description</u> .....	<a href="#">M2-11</a>
M2-3 <u>Waste Characterization</u> .....	<a href="#">M2-13</a>
M2-4 <u>Treatment Effectiveness</u> .....	<a href="#">M2-13</a>
M2-5 <u>Maintenance, Monitoring, and Inspection</u> .....	<a href="#">M2-14</a>
M2-5a <u>Maintenance</u> .....	<a href="#">M2-14</a>
M2-5a(1) <u>Ground-Control Program</u> .....	<a href="#">M2-14</a>
M2-5b <u>Monitoring</u> .....	<a href="#">M2-14</a>
M2-5b(1) <u>Groundwater Monitoring</u> .....	<a href="#">M2-14</a>
M2-5b(2) <u>Geomechanical Monitoring</u> .....	<a href="#">M2-14</a>
M2-5b(2)(a) <u>Description of the Geomechanical Monitoring System</u> .....	<a href="#">M2-14</a>
M2-5b(2)(b) <u>System Experience</u> .....	<a href="#">M2-15</a>
M2-5b(3) <u>Volatile Organic Compound Monitoring</u> .....	<a href="#">M2-16</a>
M2-5c <u>Inspection</u> .....	<a href="#">M2-16</a>
References .....	<a href="#">M2-17</a>

## List of Tables

<b>Table</b>	<b>Title</b>
M2-1	CH TRU Mixed Waste Handling Equipment Capacities
M2-2	Instrumentation used in Support of the Geomechanical Monitoring System
M2-3	RH TRU Mixed Waste Handling Equipment Capacities

## List of Figures

<b>Figure</b>	<b>Title</b>
M2-1	Repository Horizon
M2-2	Spatial View of the Miscellaneous Unit and Waste Handling Facility
M2-3	Facility Pallet for Seven-Pack of Drums
M2-5	Typical Backfill Sacks Emplaced on Drum Stacks
M2-5a	Potential MgO Emplacement Configurations
M2-6	Waste Transfer Cage to Transporter
M2-7	Push-Pull Attachment to Forklift to Allow Handling of Waste Containers
M2-8	Typical RH and CH Transuranic Mixed Waste Container Disposal Configuration
M2-9	Underground Ventilation System Airflow
M2-11	Typical Room Barricade
M2-12	WIPP Facility Surface and Underground CH Transuranic Mixed Waste Process Flow Diagram
M2-13	Layout and Instrumentation - As of 1/96
M2-14	Facility Cask Transfer Car (Side View)
M2-15	Horizontal Emplacement and Retrieval Equipment
M2-16	RH TRU Waste Facility Cask Unloading from Waste Shaft Conveyance
M2-17	Facility Cask Installed on the Horizontal Emplacement and Retrieval Equipment
M2-18	Installing Shield Plug
M2-19	Shield Plug Supplemental Shielding Plate(s)
M2-20	Shielding Layers to Supplement RH Borehole Shield Plugs
M2-21	Shield Plug Configuration

## ATTACHMENT M2

### GEOLOGIC REPOSITORY

#### 1 M2-1 Description of the Geologic Repository

2 Management, storage, and disposal of transuranic (**TRU**) mixed waste in the Waste Isolation  
3 Pilot Plant (**WIPP**) geologic repository is subject to regulation under Title 20 of the New Mexico  
4 Administrative Code, Chapter 4, Part 1 (20.4.1 NMAC), Subpart V. The WIPP is a geologic  
5 repository mined within a bedded salt formation, which is defined in 20.4.1.101 NMAC  
6 (incorporating 40 CFR §260.10) as a miscellaneous unit. As such, HWMUs within the repository  
7 are eligible for permitting according to 20.4.1.101 NMAC (incorporating 40 CFR §260.10), and  
8 are regulated under 20.4.1.500 NMAC, Miscellaneous Units.

9 As required by 20.4.1.500 NMAC (incorporating 40 CFR §264.601), the Permittees shall ensure  
10 that the environmental performance standards for a miscellaneous unit, which are applied to the  
11 Underground Hazardous Waste Disposal Units (**HWDUs**) in the geologic repository, will be met.

12 The Disposal Phase will consist of receiving contact-handled (**CH**) and remote-handled  
13 (**RH**) TRU mixed waste shipping containers, unloading and transporting the waste containers to  
14 the Underground HWDUs, emplacing the waste in the Underground HWDUs, and subsequently  
15 achieving closure of the Underground HWDUs in compliance with applicable State and Federal  
16 regulations.

17 The WIPP geologic repository is mined within a 2,000-foot (ft) (610-meters (m))-thick bedded-  
18 salt formation called the Salado Formation. The Underground HWDUs (miscellaneous units) are  
19 located 2,150 ft (655 m) beneath the ground surface. TRU mixed waste management activities  
20 underground will be confined to the southern portion of the 120-acre (48.5 hectares) mined area  
21 during the Disposal Phase. During the initial term of this Permit, disposal of containers of CH  
22 TRU mixed waste will occur only in the seven HWDUs designated as Panels 1-7 (See Figure  
23 M2-1). RH TRU mixed waste disposal may begin in Panel 4. In the future, the Permittees may  
24 request a Permit to dispose of containers of CH and RH TRU mixed waste in additional panels  
25 that meet the definition of the HWDU in Permit Module IV. In addition, the Permittees may also  
26 request in the future a Permit to allow disposal of containers of TRU mixed waste in the north-  
27 south entries marked as E-300, E-140, W-30, and W-170, between S-1600 and S-3650. These  
28 areas are referred to as the disposal area access drifts and have been designated as Panels 9  
29 and 10 in Figure M2-1. This Permit, during its initial 10-year term, authorizes the excavation of  
30 Panels 2 through 10 and the disposal of waste in Panels 1 through 7.

31 Panels 1 through 7 will consist of seven rooms and two access drifts each. Access drifts  
32 connect the rooms and have the same cross section (see Section M2-2a(3)). The closure  
33 system installed in each HWDU after it is filled will prevent anyone from entering the HWDU and  
34 will stop ventilation airflow. The point of compliance for air emissions from the Underground is  
35 Sampling Station VOC-A, as defined in Permit Attachment N (Confirmatory Volatile Organic  
36 Compound Monitoring Plan). Sampling Station VOC-A is the location where the concentration of  
37 volatile organic compounds (VOCs) in the air emissions from the Underground HWDUs will be

1 measured and then compared to the VOC concentration of concern as required by Permit  
2 Module IV.

3 Four shafts connect the underground area with the surface. The Waste Shaft Conveyance  
4 headframe and hoist are located within the Waste Handling Building (**WHB**) and will be used to  
5 transport containers of TRU mixed waste, equipment, and materials to the repository horizon.  
6 The waste hoist can also be used to transport personnel. The Air Intake Shaft and the Salt  
7 Handling Shaft provide ventilation to all areas of the mine except for the Waste Shaft Station.  
8 This area is ventilated by the Waste Shaft itself. The Salt Handling Shaft is also used to hoist  
9 mined salt to the surface and serves as the principal personnel transport shaft. The Exhaust  
10 Shaft serves as a common exhaust air duct for all areas of the mine. The relationship between  
11 the WIPP surface facility, the four shafts, and the geologic repository horizon is shown on  
12 Figure M2-2.

13 The HWDUs identified as Panels 1 through 7 (Figure M2-1) provide room for up to 4,582,750  
14 cubic feet (ft<sup>3</sup>) ( 129,750 meters (m<sup>3</sup>)) of CH TRU mixed waste. The CH TRU mixed waste  
15 containers (typically, 7-packs and standard waste boxes (**SWBs**)) may be stacked three-high  
16 across the width of the room.

17 Panels 4 through 7 provide room for up to 70,100 ft<sup>3</sup> ( 1,985 m<sup>3</sup>) of RH TRU mixed waste. RH  
18 TRU mixed waste may be disposed of in up to 730 boreholes per panel. At a minimum, these  
19 boreholes shall be drilled on nominal eight-foot centers, horizontally, about mid-height in the ribs  
20 of a disposal room. The thermal loading from RH TRU mixed waste shall not exceed 10  
21 kilowatts per acre when averaged over the area of a panel, as shown in Permit Attachment M3,  
22 plus one hundred feet of each of a Panel's adjoining barrier pillars.

23 Detailed studies and evaluations of the natural environmental setting of the repository area have  
24 been part of the site selection and characterization process. Detailed information regarding the  
25 climatic, geologic, and hydrologic characteristics of the WIPP facility and local vicinity was  
26 provided in Section D-9a, and numerous Chapter D Appendices, of the WIPP RCRA Part B  
27 Permit Application (DOE, 1997).

28 The WIPP facility is located in a sparsely populated area with site conditions favorable to  
29 isolation of TRU mixed waste from the biosphere. Geologic and hydrologic characteristics of the  
30 site related to its TRU mixed waste isolation capabilities are discussed in Section D-9a(1) of the  
31 WIPP RCRA Part B Permit Application (DOE, 1997). Hazard prevention programs are described  
32 in Permit Attachment E. Contingency and emergency response actions to minimize impacts of  
33 unanticipated events, such as spills, are described in Permit Attachment F. The closure plan for  
34 the WIPP facility is described in Permit Attachment I.

## 35 M2-2 Geologic Repository Design and Process Description

### 36 M2-2a Geologic Repository Design and Construction

37 The WIPP facility, when operated in compliance with the Permit, will ensure safe operations and  
38 be protective of human health and the environment.

1 As a part of the design validation process, geomechanical tests were conducted in SPDV test  
2 rooms. During the tests, salt creep rates were measured. Separation of bedding planes and  
3 fracturing were also observed. Consequently, a ground-control strategy was implemented. The  
4 ground-control program at the WIPP facility mitigates the potential for roof or rib falls and  
5 maintains normal excavation dimensions, as long as access to the excavation is possible.

#### 6 M2-2a(1) CH TRU Mixed Waste Handling Equipment

7 The following are the major pieces of equipment used to manage CH TRU waste in the geologic  
8 repository. A summary of equipment capacities, as required by 20.4.1.500 NMAC is included in  
9 Table M2-1.

#### 10 Facility Pallets

11 The facility pallet is a fabricated steel unit designed to support 7-packs, 3-packs, or 4-packs of  
12 drums, SWBs, or ten-drum overpacks (**TDOPs**), and has a rated load of 25,000 pounds (lbs.)  
13 (11,430 kilograms (kg)). The facility pallet will accommodate up to four 7-packs, four 3-packs, or  
14 four 4-packs of drums, four SWBs (in two stacks of two units), or two TDOPs. Loads are  
15 secured to the facility pallet during transport to the emplacement area. Facility pallets are shown  
16 in Figure M2-3. Fork pockets in the side of the pallet allow the facility pallet to be lifted and  
17 transferred by forklift to prevent direct contact between TRU mixed waste containers and forklift  
18 tines. This arrangement reduces the potential for puncture accidents. WIPP facility operational  
19 documents define the operational load of the facility pallet to ensure that the rated load of a  
20 facility pallet is not exceeded.

#### 21 Backfill

22 Magnesium oxide (**MgO**) will be used as a backfill in order to provide chemical control over the  
23 solubility of radionuclides in order to comply with the requirements of 40 CFR §191.13. The  
24 MgO backfill will be purchased prepackaged in the proper containers for emplacement in the  
25 underground. Purchasing prepackaged backfill eliminates handling and placement problems  
26 associated with bulk materials, such as dust creation. In addition, prepackaged materials will be  
27 easier to emplace, thus reducing potential worker exposure to radiation. Should a backfill  
28 container be breached, MgO is benign and cleanup is simple. No hazardous waste would result  
29 from a spill of backfill.

30 The MgO backfill will be managed in accordance with Specification D-0101 (MgO Backfill  
31 Specification) and WP05-WH1025 (CH Waste Downloading and Emplacement). These  
32 documents are kept on file at the WIPP facility by the Permittees.

33 Backfill will be handled in accordance with standard operating procedures. Typical  
34 emplacement configurations are shown in Figures M2-5 and M2-5a.

35 Quality control will be provided within standard operating procedures to record that the correct  
36 number of sacks are placed and that the condition of the sacks is acceptable.

37 Backfill placed in this manner is protected until exposed when sacks are broken during creep  
38 closure of the room and compaction of the backfill and waste. Backfill in sacks utilizes existing

1 techniques and equipment and eliminates operational problems such as dust creation and  
2 introducing additional equipment and operations into waste handling areas. There are no mine  
3 operational considerations (e.g. ventilation flow and control) when backfill is placed in this  
4 manner.

### 5 The Waste Shaft Conveyance

6 The hoist systems in the shafts and all shaft furnishings are designed to resist the dynamic  
7 forces of the hoisting system and to withstand a design-basis earthquake of 0.1 g. Appendix D2  
8 of the WIPP RCRA Part B Permit Application (DOE, 1997) provided engineering design-basis  
9 earthquake report which provides the basis for seismic design of WIPP facility structures. The  
10 waste hoist is equipped with a control system that will detect malfunctions or abnormal  
11 operations of the hoist system (such as overtravel, overspeed, power loss, circuitry failure, or  
12 starting in a wrong direction) and will trigger an alarm that automatically shuts down the hoist.

13 The waste hoist moves the Waste Shaft Conveyance and is a multirope, friction-type hoist. A  
14 counterweight is used to balance the waste shaft conveyance. The waste shaft conveyance  
15 (outside dimensions) is 30 ft (9 m) high by 10 ft (3 m) wide by 15 ft (4.5 m) deep and can carry a  
16 payload of 45 tons (40,824 kg). During loading and unloading operations, it is steadied by fixed  
17 guides. The hoist's maximum rope speed is 500 ft (152.4 m) per min.

18 The Waste Shaft hoist system has two sets of brakes, with two units per set, plus a motor that is  
19 normally used to stop the hoist. The brakes are designed so that either set, acting alone, can  
20 stop a fully loaded conveyance under all emergency conditions.

### 21 The Underground Waste Transporter

22 The underground waste transporter is a commercially available diesel-powered tractor. The  
23 trailer was designed specifically for the WIPP for transporting facility pallets from the waste shaft  
24 conveyance to the Underground HWDU in use. This transporter is shown in Figure M2-6.

### 25 Underground Forklifts

26 CH TRU mixed waste containers loaded on slipsheets will be removed from the facility pallets  
27 using forklifts with a push-pull attachment (Figure M2-7) attached to the forklift-truck front  
28 carriage. The push-pull attachment grips the edge of the slipsheet (on which the waste  
29 containers sit) to pull the containers onto the platen. After the forklift moves the waste  
30 containers to the emplacement location, the push-pull attachment pushes the containers into  
31 position. The use of the push-pull attachment prevents direct contact between waste containers  
32 and forklift tines. SWBs and TDOPs may also be removed from the facility pallet by using  
33 forklifts equipped with special adapters for these containers. These special adapters will prevent  
34 direct contact between SWBs or TDOPs and forklift tines. In addition, the low clearance forklift  
35 that is used to emplace MgO may be used to emplace waste if necessary.

1 M2-2a(2) Shafts

2 The WIPP facility uses four shafts: the Waste Shaft, the Salt Handling Shaft, the Air Intake  
3 Shaft, and the Exhaust Shaft. These shafts are vertical openings that extend from the surface to  
4 the repository level.

5 The Waste Shaft is located beneath the WHB and is 19 to 20 ft (5.8 to 6.1 m) in diameter. The  
6 Salt Handling Shaft, located north of the Waste Shaft beneath the salt handling headframe, is  
7 10 to 12 ft (3 to 3.6 m) in diameter. Salt mined from the repository horizon is removed through  
8 the Salt Handling Shaft. The Salt Handling Shaft is the main personnel and materials hoist and  
9 also serves as a secondary-supply air duct for the underground areas. The Air Intake Shaft,  
10 northwest of the WHB, varies in diameter from 16 ft 7 in. (4.51 m) to 20 ft 3 in. (6.19 m) and is  
11 the primary source of fresh air underground. The Exhaust Shaft, east of the WHB, is 14 to 15 ft  
12 (4.3 to 4.6 m) in diameter and serves as the exhaust duct for the underground air.

13 Openings excavated in salt experience closure because of salt creep (or time-dependent  
14 deformation at constant load). The closure affects the design of all of the openings discussed in  
15 this section. Underground excavation dimensions, therefore, are nominal, because they change  
16 with time. The unlined portions of the shafts have larger diameters than the lined portions, which  
17 allows for closure caused by salt creep. Each shaft includes a shaft collar, a shaft lining, and a  
18 shaft key section. The Final Design Validation Report in Appendix D1 of the WIPP RCRA Part B  
19 Permit Application (DOE, 1997) discusses the shafts and shaft components in greater detail.

20 The reinforced-concrete shaft collars extend from the surface to the top of the underlying  
21 consolidated sediments. Each collar serves to retain adjacent unconsolidated sands and soils  
22 and to prevent surface runoff from entering the shafts. The shaft linings extend from the base of  
23 the collar to the top of the salt beds approximately 850 ft (259 m) below the surface. Grout  
24 injected behind the shaft lining retards water seeping into the shafts from water-bearing  
25 formations, and the liner is designed to withstand the natural water pressure associated with  
26 these formations. The shaft liners are concrete, except in the Salt Handling Shaft, where a steel  
27 shaft liner has been grouted in place.

28 The shaft key is a circular reinforced concrete section emplaced in each shaft below the liner in  
29 the base of the Rustler and extending about 50 ft (15 m) into the Salado. The key functions to  
30 resist lateral pressures and assures that the liner will not separate from the host rocks or fail  
31 under tension. This design feature also aids in preventing the shaft from becoming a route for  
32 groundwater flow into the underground facility.

33 On the inside surface of each shaft, excluding the Salt Handling Shaft, there are three water-  
34 collection rings: one just below the Magenta, one just below the Culebra, and one at the  
35 lowermost part of the key section. These collection rings will collect water that may seep into the  
36 shaft through the liner. The Salt Handling Shaft has a single water collection ring in the lower  
37 part of the key section. Water collection rings are drained by tubes to the base of the shafts  
38 where the water is accumulated.

39 WIPP shafts and other underground facilities are, for all practical purposes, dry. Minor quantities  
40 of water (which accumulate in some shaft sumps) are insufficient to affect the waste disposal

1 area. This water is collected, brought to the surface, and disposed of in accordance with current  
2 standards and regulations.

3 The Waste Shaft is protected from precipitation by the roof of the waste shaft conveyance  
4 headframe tower. The Exhaust Shaft is configured at the top with a 14 ft- (4.3 m-) diameter duct  
5 that diverts air into the exhaust filtration system or to the atmosphere, as appropriate. The Salt  
6 Handling and Air Intake Shaft collars are open except for the headframes. Rainfall into the  
7 shafts is evaporated by ventilation air.

### 8 M2-2a(3) Subsurface Structures

9 The subsurface structures in the repository, located at 2,150 ft (655 m) below the surface,  
10 include the HWDUs, the northern experimental areas, and the support areas. Appendix D3 of  
11 the WIPP RCRA Part B Permit Application (DOE, 1997) provided details of the underground  
12 layout. Figure M2-8 shows the proposed waste emplacement configuration for the HWDUs.

13 The status of important underground equipment, including fixed fire-protection systems, the  
14 ventilation system, and contamination detection systems, will be monitored by a central  
15 monitoring system, located in the Support Building adjacent to the WHB. Backup power will be  
16 provided as discussed in Permit Attachment E. The subsurface support areas are constructed  
17 and maintained to conform to Federal mine safety codes.

### 18 Underground Hazardous Waste Disposal Units (HWDUs)

19 During the initial term of this Permit, the volume of CH TRU mixed waste emplaced in the  
20 repository will not exceed 4,582,750 ft<sup>3</sup> (129,750 m<sup>3</sup>) and the volume of RH TRU mixed waste  
21 shall not exceed 70,100 ft<sup>3</sup> (1,985 m<sup>3</sup>). CH TRU mixed waste will be disposed of in up to 7  
22 Underground HWDUs identified as Panels 1 through 7. RH TRU mixed waste may be disposed  
23 of in Panels 4 through 7.

24 Main entries and cross cuts in the repository provide access and ventilation to the HWDUs. The  
25 main entries link the shaft pillar/service area with the TRU mixed waste management area and  
26 are separated by pillars. Normal entries are 12 ft (3.7 m) to 13 ft (4.0 m) high and 14 ft (4.3 m) to  
27 16 ft (4.9) wide. Each of the Underground HWDUs labeled Panels 1 through 7 will have seven  
28 rooms. The locations of these HWDUs are shown in Figure M2-1. The rooms will have nominal  
29 dimensions of 13 ft (4.0 m) high by 33 ft (10 m) wide by 300 ft (91 m) long and will be supported  
30 by 100 ft- (30 m-) wide pillars.

31 As currently planned, future Permits may allow disposal of TRU mixed waste containers in three  
32 additional panels, identified as Panels 8, 9, and 10. Disposal of TRU mixed waste in Panels 8,  
33 9, and 10 is prohibited under this Permit. If waste volumes disposed of in the eight panels fail to  
34 reach the stated design capacity, the Permittees may request a Permit to allow disposal of TRU  
35 mixed waste in the four main entries and crosscuts adjacent to the waste panels (referred to as  
36 the disposal area access drifts). These areas are labeled Panels 9 and 10 in Figure M2-1. This  
37 Permit allows only the construction of Panels 9 and 10 and prohibits disposal of TRU mixed  
38 waste in Panels 9 and 10. A permit modification or future permit would be submitted describing  
39 the condition of those drifts and the controls exercised for personnel safety and environmental

1 protection while disposing of waste in these areas. These areas have the following nominal  
2 dimensions:

3 E-300 will be mined to be 14 ft (4.3 m) to 16 ft (4.9 m) wide and 12 ft (3.7 m) to 13 ft (4.0  
4 m) high

5 E-140 is mined to 25 ft (7.6 m) wide by 13 ft (4 m) high

6 W-030 and W-170 will be similar to E-300.

7 All extend from S-1600 to S-3650 (i.e., 2050 ft long [625 m]). Crosscuts (east-west entries) will  
8 be 20 ft (6.1 m) wide by 13 ft (4 m) high by 470 ft (143 m) long. The layout of these excavations  
9 is shown on Figure M2-1.

10 Panel 1 is the first HWMU to be used for waste disposal and was excavated from 1986 through  
11 1988. The panels may be mined in the following order:

12 Panel 10 (disposal area access drift)

13 Panel 2

14 Panel 9 (disposal area access drift)

15 Panel 3

16 Panel 4

17 Panel 5

18 Panel 6

19 Panel 7

20 Panel 8

## 21 Underground Facilities Ventilation System

22 The underground facilities ventilation system will provide a safe and suitable environment for  
23 underground operations during normal WIPP facility operations. The underground system is  
24 designed to provide control of potential airborne contaminants in the event of an accidental  
25 release or an underground fire.

26 The main underground ventilation system is divided into four separate flows (Figure M2-9): one  
27 flow serving the mining areas, one serving the northern experimental areas, one serving the  
28 disposal areas, and one serving the Waste Shaft and station area. The four main airflows are  
29 recombined near the bottom of the Exhaust Shaft, which serves as a common exhaust route  
30 from the underground level to the surface.

## 31 Underground Ventilation System Description

32 The underground ventilation system consists of six centrifugal exhaust fans, two identical  
33 HEPA-filter assemblies arranged in parallel, isolation dampers, a filter bypass arrangement, and  
34 associated ductwork. The six fans, connected by the ductwork to the underground exhaust shaft  
35 so that they can independently draw air through the Exhaust Shaft, are divided into two groups.  
36 One group consists of three main exhaust fans, two of which are utilized to provide the nominal  
37 air flow of 425,000 standard ft<sup>3</sup> per min (SCFM) throughout the WIPP facility underground during  
38 normal operation. One main fan may be operated in the alternate mode to provide 260,000  
39 SCFM underground ventilation flow. These fans are located near the Exhaust Shaft. The

1 second group consists of the remaining three filtration fans, and each can provide 60,000 SCFM  
2 of air flow. These fans, located at the Exhaust Filter Building, are capable of being employed  
3 during the filtration mode, where exhaust is diverted through HEPA filters, or in the reduced or  
4 minimum ventilation mode where air is not drawn through the HEPA filters. In order to ensure  
5 the miscellaneous unit environmental performance standards are met, a minimum running  
6 annual average exhaust rate of 260,000 SCFM will be maintained.

7 The underground mine ventilation is designed to supply sufficient quantities of air to all areas of  
8 the repository. During normal operating mode (simultaneous mining and waste emplacement  
9 operations), approximately 140,000 actual ft<sup>3</sup> (3,962 m<sup>3</sup>) per min can be supplied to the panel  
10 area. This quantity is necessary in order to support the level of activity and the pieces of diesel  
11 equipment that are expected to be in operation.

12 At any given time during waste emplacement activities, there may be significant activities in  
13 multiple rooms in a panel. For example, one room may be receiving CH TRU mixed waste  
14 containers, another room may be receiving RH TRU mixed waste canisters, and the drilling of  
15 RH TRU mixed waste emplacement boreholes may be occurring in another room. The  
16 remaining rooms in a panel will either be completely filled with waste; be idle, awaiting waste  
17 handling operations; or being prepared for waste receipt. A minimum ventilation rate of 35,000  
18 ft<sup>3</sup> (990 m<sup>3</sup>) per minute will be maintained in each room where waste disposal is taking place  
19 when workers are present in the room. This quantity of air is required to support the numbers  
20 and types of diesel equipment that are expected to be in operation in the area, to support the  
21 underground personnel working in that area, and to exceed a minimum air velocity of 60 ft  
22 (18 m) per minute as specified in the WIPP Ventilation Plan. The remainder of the air is needed  
23 in order to account for air leakage through inactive rooms.

24 Air will be routed into a panel from the intake side. Air is routed through the individual rooms  
25 within a panel using underground bulkheads and air regulators. Bulkheads are constructed by  
26 erecting framing of rectangular steel tubing and screwing galvanized sheet metal to the framing.  
27 Bulkhead members use telescoping extensions that are attached to framing and the salt which  
28 adjust to creep. Rubber or sheet metal attached to the bulkhead on one side and the salt on the  
29 other completes the seal of the ventilation. Where controlled airflow is required, a louver-style  
30 damper on a slide-gate (sliding panel) regulator is installed on the bulkhead. Personnel access  
31 is available through most bulkheads, and vehicular access is possible through selected  
32 bulkheads. Vehicle roll-up doors in the panel areas are not equipped with warning bells or  
33 strobe lights since these doors are to be used for limited periodic maintenance activities in the  
34 return air path. Flow is also controlled using brattice cloth barricades. These consist of chainlink  
35 fence that is bolted to the salt and covered with brattice cloth; and are used in instances where  
36 the only flow control requirement is to block the air. A brattice cloth air barricade is shown in  
37 Figure M2-11. Ventilation will be maintained only in all active rooms within a panel until waste  
38 emplacement activities are completed and the panel-closure system is installed. The air will be  
39 routed simultaneously through all the active rooms within the panel. The rooms that are filled  
40 with waste will be isolated from the ventilation system, while the rooms that are actively being  
41 filled will receive a minimum of 35,000 SCFM of air when workers are present to assure worker  
42 safety. After all rooms within a panel are filled, the panel will be closed using a closure system  
43 described Permit Attachment I and Permit Attachment I1.

1 Once a disposal room is filled and is no longer needed for emplacement activities, it will be  
2 barricaded against entry and isolated from the mine ventilation system by removing the air  
3 regulator bulkhead and constructing chain link/brattice cloth barricades at each end. There is no  
4 requirement for air for these rooms since personnel and/or equipment will not be in these areas.

5 The ventilation path for the waste disposal side is separated from the mining side by means of  
6 air locks, bulkheads, and salt pillars. A pressure differential is maintained between the mining  
7 side and the waste disposal side to ensure that any leakage is towards the disposal side. The  
8 pressure differential is produced by the surface fans in conjunction with the underground air  
9 regulators.

#### 10 Underground Ventilation Modes of Operation

11 The underground ventilation system is designed to perform under two types of operation:  
12 normal (the HEPA exhaust filtration system is bypassed), and filtered (the exhaust is filtered  
13 through the HEPA filtration system, if radioactive contaminants are detected or suspected.

14 Overall, there are six possible modes of exhaust fan operation:

- 15 ● 2 main fans in operation
- 16 ● 1 main fan in operation
- 17 ● 1 filtration fan in filtered operation
- 18 ● 1 filtration fan in unfiltered operation
- 19 ● 2 filtration fans in unfiltered operation
- 20 ● 1 main and 1 filtration fan (unfiltered) in operation

21 Under some circumstances (such as power outages and maintenance activities, etc.), all mine  
22 ventilation may be discontinued for short periods of time.

23 In the normal mode, two main surface exhaust fans, located near the Exhaust Shaft, will provide  
24 continuous ventilation of the underground areas. All underground flows join at the bottom of the  
25 Exhaust Shaft before discharge to the atmosphere.

26 Outside air will be supplied to the mining areas and the waste disposal areas through the Air  
27 Intake Shaft, the Salt Handling Shaft, and access entries. A small quantity of outside air will flow  
28 down the Waste Shaft to ventilate the Waste Shaft station. The ventilation system is designed to  
29 operate with the Air Intake Shaft as the primary source of fresh air. Under these circumstances,  
30 sufficient air will be available to simultaneously conduct all underground operations (e.g., waste  
31 handling, mining, experimentation, and support). Ventilation may be supplied by operating one  
32 main exhaust fan, or one or two filtration exhaust fans, or a combination of the three.

33 If the nominal flow of 425,000 cfm (12,028 m<sup>3</sup>/min) is not available (i.e., only one of the main  
34 ventilation fans is available) underground operations may proceed, but the number of activities  
35 that can be performed in parallel may be limited depending on the quantity of air available.  
36 Ventilation may be supplied by operating one or two of the filtration exhaust fans. To accomplish  
37 this, the isolation dampers will be opened, which will permit air to flow from the main exhaust  
38 duct to the filter outlet plenum. The filtration fans may also be operated to bypass the HEPA  
39 plenum. The isolation dampers of the filtration exhaust fan(s) to be employed will be opened,

1 and the selected fan(s) will be switched on. In this mode, underground operations will be limited,  
2 because filtration exhaust fans cannot provide sufficient airflow to support the use of diesel  
3 equipment.

4 In the filtration mode, the exhaust air will pass through two identical filter assemblies, with only  
5 one of the three Exhaust Filter Building filtration fans operating (all other fans are stopped). This  
6 system provides a means for removing the airborne particulates that may contain radioactive  
7 and hazardous waste contaminants in the reduced exhaust flow before they are discharged  
8 through the exhaust stack to the atmosphere. The filtration mode is activated manually or  
9 automatically if the radiation monitoring system detects abnormally high concentrations of  
10 airborne radioactive particulates (an alarm is received from the continuous air monitor in the  
11 exhaust drift of the active waste panel) or a waste handling incident with the potential for a  
12 waste container breach is observed. The filtration mode is not initiated by the release of gases  
13 such as VOCs.

#### 14 Underground Ventilation Normal Mode Redundancy

15 The underground ventilation system has been provided redundancy in normal ventilation mode  
16 by the addition of a third main fan. Ductwork leading to that new fan ties into the existing main  
17 exhaust duct. Documentation for this addition of a third fan and associated ductwork will be  
18 submitted to NMED before receipt of TRU mixed waste.

#### 19 Electrical System

20 The WIPP facility uses electrical power (utility power) supplied by the regional electric utility  
21 company. If there is a loss of utility power, TRU mixed waste handling and related operations  
22 will cease.

23 Backup, alternating current power will be provided on site by two 1,100-kilowatt diesel  
24 generators. These units provide 480-volt power with a high degree of reliability. Each of the  
25 diesel generators can carry predetermined equipment loads while maintaining additional power  
26 reserves. Predetermined loads include lighting and ventilation for underground facilities, lighting  
27 and ventilation for the TRU mixed waste handling areas, and the Air Intake Shaft hoist. The  
28 diesel generator can be brought on line within 30 minutes either manually or from the control  
29 panel in the Central Monitoring Room (CMR).

30 Uninterruptible power supply units are also on line providing power to predetermined monitoring  
31 systems. These systems ensure that the power to the radiation detection system for airborne  
32 contamination, the local processing units, the computer room, and the CMR will always be  
33 available, even during the interval between the loss of off-site power and initiation of backup  
34 diesel generator power.

#### 35 M2-2a(4) RH TRU Mixed Waste Handling Equipment

36 The following are the major pieces of equipment used to manage RH TRU mixed waste in the  
37 geologic repository. A summary of equipment capacities is included in Table M2-3.

## The Facility Cask Transfer Car

The Facility Cask Transfer Car is a self-propelled rail car (Figure M2-14) that operates between the Facility Cask Loading Room and the geologic repository. After the Facility Cask is loaded, the Facility Cask Transfer Car moves onto the waste shaft conveyance and is then transported underground. At the underground waste shaft station, the Facility Cask Transfer Car proceeds away from the waste shaft conveyance to provide forklift access to the Facility Cask.

## Horizontal Emplacement and Retrieval Equipment

The Horizontal Emplacement and Retrieval Equipment (**HERE**) (Figure M2-15) emplaces canisters into a borehole in a room wall of an Underground HWDU. Once the canisters have been emplaced, the HERE then fills the borehole opening with a shield plug.

## M2-2b Geologic Repository Process Description

Prior to receipt of TRU mixed waste at the WIPP facility, waste operators will be thoroughly trained in the safe use of TRU mixed waste handling and transport equipment. The training will include both classroom training and on-the-job training.

## RH TRU Mixed Waste Emplacement

The Facility Cask Transfer Car is loaded onto the waste shaft conveyance and is lowered to the waste shaft station underground. At the waste shaft station underground, the Facility Cask is moved from the waste shaft conveyance by the Facility Cask Transfer Car (Figure M2-16). A forklift is used to remove the Facility Cask from the Facility Cask Transfer Car and to transport the Facility Cask to the Underground HWDU. There, the Facility Cask is placed on the HERE (Figure M2-17). The HERE is used to emplace the RH TRU mixed waste canister into the borehole. The borehole will be visually inspected for obstructions prior to aligning the HERE and emplacement of the RH TRU mixed waste canister. The Facility Cask is moved forward to mate with the shield collar, and the transfer carriage is advanced to mate with the rear Facility Cask shield valve. The shield valves on the Facility Cask are opened, and the transfer mechanism advances to push the canister into the borehole. After retracting the transfer mechanism into the Facility Cask, the forward shield valve is closed, and the transfer mechanism is further retracted into its housing. The transfer mechanism is moved to the rear, and the shield plug carriage containing a shield plug is placed on the emplacement machine. The transfer mechanism is used to push the shield plug into the Facility Cask. The front shield valve is opened, and the shield plug is pushed into the borehole (Figure M2-18). The transfer mechanism is retracted, the shield valves close on the Facility Cask, and the Facility Cask is removed from the HERE.

A shield plug is a concrete filled cylindrical steel shell (Figure M2-21) approximately 61 in. long and 29 in. in diameter, made of concrete shielding material inside a 0.24 in. thick steel shell with a removable pintle at one end. Each shield plug has integral forklift pockets and weighs approximately 3,750 lbs. The shield plug is inserted with the pintle end closest to the HERE to provide the necessary shielding, limiting the borehole radiation dose rate at 30 cm to less than 10 mrem per hour for a canister surface dose rate of 100 rem/hr. Additional shielding is provided at the direction of the Radiological Control Technician based on dose rate surveys following shield plug emplacement. This additional shielding is provided by the manual

1 emplacement of one or more shield plug supplemental shielding plates and a retainer (Figures  
2 M2-19 and M2-20).

3 The amount of RH TRU mixed waste disposal in each panel is limited based on thermal and  
4 geomechanical considerations and shall not exceed 10 kilowatts per acre as described in  
5 Permit Attachment M2-1. RH TRU mixed waste emplacement boreholes shall be drilled in the  
6 ribs of the panels at a nominal spacing of 8 ft (2.4 m) center-to-center, horizontally.

7 Figures M1-26 and M1-27 are flow diagrams of the RH TRU mixed waste handling process for  
8 the RH-TRU 72-B and CNS 10-160B casks, respectively.

### 9 CH TRU Mixed Waste Emplacement

10 CH TRU mixed waste containers will arrive by tractor-trailer at the WIPP facility in sealed  
11 shipping containers (e.g., TRUPACT-IIs or HalfPACTs), at which time they will undergo security  
12 and radiological checks and shipping documentation reviews. The trailers carrying the shipping  
13 containers will be stored temporarily at the Parking Area Container Storage Unit (Parking Area  
14 Unit). A forklift will remove the Contact Handled Packages from the transport trailers and will  
15 transport them into the Waste Handling Building Container Storage Unit for unloading of the  
16 waste containers. Each TRUPACT-II may hold up to two 7-packs, two 4-packs, two 3-packs,  
17 two SWBs, or one TDOP. Each HalfPACT may hold up to seven 55-gal (208 L) drums, one  
18 SWB, or four 85-gal (321 L) drums. An overhead bridge crane will be used to remove the waste  
19 containers from the Contact Handled Packaging and place them on a facility or containment  
20 pallet. Each facility pallet has two recessed pockets to accommodate two sets of 7-packs, two  
21 sets of 3-packs, two sets of 4-packs, two SWBs stacked two-high, or two TDOPs. Each stack of  
22 waste containers will be secured prior to transport underground (see Figure M2-3). A forklift or  
23 the facility transfer vehicle will transport the loaded facility pallet to the conveyance loading  
24 room adjacent to the Waste Shaft. The facility transfer vehicle will be driven onto the waste shaft  
25 conveyance deck, where the loaded facility pallet will be transferred to the waste shaft  
26 conveyance, and the facility transfer vehicle will be backed off. Containers of CH TRU mixed  
27 waste (55-gal (208 L) drums, SWBs, 85-gal (321 L) drums, 100-gal (379 L) drums, and TDOPs)  
28 can be handled individually, if needed, using the forklift and lifting attachments (i.e., drum  
29 handlers, parrot beaks).

30 The waste shaft conveyance will lower the loaded facility pallet to the underground. At the waste  
31 shaft station, the CH TRU underground transporter will back up to the waste shaft conveyance,  
32 and the facility pallet will be transferred from the waste shaft conveyance onto the transporter  
33 (see Figure M2-6). The transporter will then move the facility pallet to the appropriate  
34 Underground HWDU for emplacement.

35 A forklift in the HWDU near the waste stack will be used to remove the waste containers from  
36 the facility pallets and to place them in the waste stack using a push-pull attachment. The waste  
37 will be emplaced room by room in Panels 1 through 7. Each panel will be closed off when filled.  
38 If a waste container is damaged during the Disposal Phase, it will be immediately overpacked or  
39 repaired. CH TRU mixed waste containers will be continuously vented. The filter vents will allow  
40 aspiration, preventing internal pressurization of the container and minimizing the buildup of  
41 flammable gas concentrations.

1 Once a waste panel is mined and any initial ground control established, flow regulators will be  
2 constructed to assure adequate control over ventilation during waste emplacement activities.  
3 The first room to be filled with waste will be Room 7, which is the one that is farthest from the  
4 main access ways. A ventilation control point will be established for Room 7 just outside the  
5 exhaust side of Room 6. This ventilation control point will consist of a bulkhead with a ventilation  
6 regulator. When RH TRU mixed waste canister emplacement is completed in a room, CH TRU  
7 mixed waste emplacement can begin in that room. Stacking of CH waste will begin at the  
8 ventilation control point and proceed down the access drift, through the room and up the intake  
9 access drift until the entrance of Room 6 is reached. At that point, a brattice cloth and chain link  
10 barricade will be emplaced. This process will be repeated for Room 6, and so on until Room 1 is  
11 filled. At that point, the panel closure system will be constructed.

12 The emplacement of CH TRU mixed waste into the HWDUs will typically be in the order  
13 received and unloaded from the Contact Handled Packaging. There is no specification for the  
14 amount of space to be maintained between the waste containers themselves, or between the  
15 waste containers and the walls. Containers will be stacked in the best manner to provide  
16 stability for the stack (which is up to three containers high) and to make best use of available  
17 space. It is anticipated that the space between the wall and the container could be from 8 to 18  
18 in. (20 to 46 cm). This space is a function of disposal room wall irregularities, container type,  
19 and sequence of emplacement. Bags of backfill will occupy some of this space. Space is  
20 required over the stacks of containers to assure adequate ventilation for waste handling  
21 operations. A minimum of 16 in. (41 cm) was specified in the Final Design Validation Report  
22 (Appendix D1, Chapter 12 of the WIPP RCRA Part B Permit Application (DOE, 1997)) to  
23 maintain air flow. Typically, the space above a stack of containers will be 36 to 48 in. (90 to 122  
24 cm). However 18 in. (0.45 m) will contain backfill material consisting of bags of Magnesium  
25 Oxide (MgO). Figure M2-8 shows a typical container configuration, although this figure does not  
26 mix containers on any row. Such mixing, while inefficient, will be allowed to assure timely  
27 movement of waste into the underground. No aisle space will be maintained for personnel  
28 access to emplaced waste containers. No roof maintenance behind stacks of waste is planned.

29 The anticipated schedule for the filling of each of the Underground HWDUs known as Panels 1  
30 through 7 is shown in Permit Attachment I, Table I-1. Panel closure in accordance with the  
31 Closure Plan in Permit Attachment I and Permit Attachment I1 is estimated to require an  
32 additional 150 days.

33 Figure M2-12 is a flow diagram of the CH TRU mixed waste handling process.

### 34 M2-3 Waste Characterization

35 TRU mixed waste characterization is described in Permit Attachment B.

### 36 M2-4 Treatment Effectiveness

37 TRU mixed waste treatment, as defined in 20.4.1.101 NMAC (incorporating 40 CFR §260.10),  
38 for which a permit is required, will not be performed at the WIPP facility.

1     M2-5 Maintenance, Monitoring, and Inspection

2     M2-5a Maintenance

3     M2-5a(1) Ground-Control Program

4     The ground-control program at the WIPP facility will ensure that any room in an HWDU in which  
5     waste will be placed will be sufficiently supported to assure compliance with the applicable  
6     portions of the Land Withdrawal Act (**LWA**), which requires a regular review of roof-support  
7     plans and practices by the Mine Safety and Health Administration (**MSHA**). Support is installed  
8     to the requirements of 30 CFR §57, Subpart B.

9     M2-5b Monitoring

10    M2-5b(1) Groundwater Monitoring

11    Groundwater monitoring for the WIPP Underground HWDUs will be conducted in accordance  
12    with Module V and Permit Attachment L of this permit.

13    M2-5b(2) Geomechanical Monitoring

14    The geomechanical monitoring program at the WIPP facility is an integral part of the ground-  
15    control program (See Figure M2-13). HWDUs, drifts, and geomechanical test rooms will be  
16    monitored to provide confirmation of structural integrity. Geomechanical data on the  
17    performance of the repository shafts and excavated areas will be collected as part of the  
18    geotechnical field-monitoring program. The results of the geotechnical investigations will be  
19    reported annually. The report will describe monitoring programs and geomechanical data  
20    collected during the previous year.

21    M2-5b(2)(a) Description of the Geomechanical Monitoring System

22    The Geomechanical Monitoring System (**GMS**) provides in situ data to support the continuous  
23    assessment of the design for underground facilities. Specifically, the GMS provides for:

- 24       •     Early detection of conditions that could affect operational safety
- 25       •     Evaluation of disposal room closure that ensures adequate access
- 26       •     Guidance for design modifications and remedial actions
- 27       •     Data for interpreting the behavior of underground openings, in comparison with  
28            established design criteria

29    The instrumentation in Table M2-2 is available for use in support of the geomechanical program.

30    The minimum instrumentation for each of the eight panels will be one borehole extensometer  
31    installed in the roof at the center of each disposal room. The roof extensometers will monitor the

1 dilation of the immediate salt roof beam and possible bed separations along clay seams.  
2 Additional instrumentation will be installed as conditions warrant.

3 Remote polling of the geomechanical instrumentation will be performed at least once every  
4 month. This frequency may be increased to accommodate any changes that may develop.

5 The results from the remotely read instrumentation will be evaluated after each scheduled  
6 polling. Documentation of the results will be provided annually in the Geotechnical Analysis  
7 Report.

8 Data from remotely read instrumentation will be maintained as part of a geotechnical  
9 instrumentation system. The instrumentation system provides for data maintenance, retrieval,  
10 and presentation. The Permittees will retrieve the data from the instrumentation system and  
11 verify data accuracy by confirming the measurements were taken in accordance with applicable  
12 instructions and equipment calibration is known. Next, the Permittees will review the data after  
13 each polling to assess the performance of the instrument and of the excavation. Anomalous  
14 data will be investigated to determine the cause (instrumentation problem, error in recording,  
15 changing rock conditions). The Permittees will calculate various parameters such as the change  
16 between successive readings and deformation rates. This assessment will be reported to the  
17 Permittees' cognizant ground control engineer and operations personnel. The Permittees will  
18 investigate unexpected deformation to determine if remediation is needed.

19 The stability of an open panel excavation is generally determined by the rock deformation rate.  
20 The excavation may be unstable when there is a continuous increase in the deformation rate  
21 that cannot be controlled by the installed support system. The Permittees will evaluate the  
22 performance of the excavation. These evaluations assess the effectiveness of the roof support  
23 system and estimate the stand-up time of the excavation. If an open panel shows the trend is  
24 toward adverse (unstable) conditions, the results will be reported to determine if it is necessary  
25 to terminate waste disposal activities in the open panel. This report of the trend toward adverse  
26 conditions in an open HWDU will also be provided to the Secretary of the NMED within seven  
27 (7) calendar days of issuance of the report.

#### 28 M2-5b(2)(b) System Experience

29 Much experience in the use of geomechanical instrumentation was gained as the result of  
30 performance monitoring of Panel 1, which began at the time of completion of the panel  
31 excavation in 1988. The monitoring system installed at that time involved simple measurements  
32 and observations (e.g., vertical and horizontal convergence rates, and visual inspections).  
33 Minimal maintenance of instrumentation is required, and the instrumentation is easily replaced if  
34 it malfunctions. Conditions throughout Panel 1 are well known. The monitoring program  
35 continues to provide data to compare the performance of Panel 1 with that established  
36 elsewhere in the underground. Panel 1 performance is characterized by the following:

- 37 ● The development of bed separations and lateral shifts at the interfaces of the salt  
38 and the clays underlying the anhydrites "a" and "b."
- 39 ● Room closures. A closure due only to the roof movement will be separated from  
40 the total closure.

- 1           ●       The behavior of the pillars.
- 2           ●       Fracture development in the roof and floor.
- 3           ●       Distribution of load on the support system.

4       Roof conditions are assessed from observation boreholes and extensometer measurements.  
5       Measurements of room closure, rock displacements, and observations of fracture development  
6       in the immediate roof beam are made and used to evaluate the performance of a panel. A  
7       description of the Panel 1 monitoring program was presented to the members of the  
8       Geotechnical Experts Panel (in 1991) who concurred that it was adequate to determine  
9       deterioration within the rooms and that it will provide early warning of deteriorating conditions.

10       The assessment and evaluation of the condition of WIPP excavations is an interactive,  
11       continuous process using the data from the monitoring programs. Criteria for corrective action  
12       are continually reevaluated and reassessed based on total performance to date. Actions taken  
13       are based on these analyses and planned utilization of the excavation. Because WIPP  
14       excavations are in a natural geologic medium, there is inherent variability from point to point.  
15       The principle adopted is to anticipate potential ground control requirements and implement them  
16       in a timely manner rather than to wait until a need arises.

17       M2-5b(3) Volatile Organic Compound Monitoring

18       The volatile organic compound monitoring for the WIPP Underground HWDUs will be conducted  
19       in accordance with Module IV and Permit Attachment N of this permit.

20       M2-5c Inspection

21       The inspection of the WIPP Underground HWDUs will be conducted in accordance with Module  
22       II and Permit Attachment D of this permit.

1

## References

2 DOE, 1997. Resource Conservation and Recovery Act Part B Permit Application, Waste  
3 Isolation Pilot Plant (WIPP), Carlsbad, New Mexico, Revision 6.5, 1997.

(This page intentionally blank)

1

## **TABLES**

(This page intentionally blank)

**TABLE M2-1**  
**CH TRU MIXED WASTE HANDLING EQUIPMENT CAPACITIES**

<b>CAPACITIES FOR EQUIPMENT</b>	
Facility Pallet	25,000 lbs.
Facility Transfer Vehicle	26,000 lbs.
Underground transporter	28,000 lbs.
Underground fork lift	12,000 lbs.
<b>MAXIMUM GROSS WEIGHTS OF CONTAINERS</b>	
Seven-pack of 55-gallon drums	7,000 lbs.
Four-pack of 85-gallon drums	4,500 lbs.
Three-pack of 100-gallon drums	3,000 lbs.
Ten-drum overpack	6,700 lbs.
Standard waste box	4,000 lbs.
<b>MAXIMUM NET EMPTY WEIGHTS OF EQUIPMENT</b>	
TRUPACT-II	13,140 lbs.
HalfPACT	10,500 lbs.
Facility pallet	4,120 lbs.

**TABLE M2-2  
 INSTRUMENTATION USED IN SUPPORT OF THE  
 GEOMECHANICAL MONITORING SYSTEM**

INSTRUMENT TYPE	FEATURES	PARAMETER MEASURED	RANGE
Borehole Extensometer	The extensometer provides for monitoring the deformation parallel to the borehole axis. Units suitable for up to 5 measurements anchors in addition to the reference head. Maximum borehole depths shall be 50 feet.	Cumulative Deformation	0-2 inches
Borehole Television Camera	Closed circuit television may be used for monitoring areas otherwise inaccessible, such as boreholes or shafts.	Video Image	N/A
Convergence Points and Tape Extensometers	Mechanically anchored eyebolts to which a portable tape extensometer is attached.	Cumulative Deformation	2-50 feet
Convergence Meters	Includes wire and sonic meters. Mounted on rigid plates anchored to the rock surface.	Cumulative Deformation	2-50 feet
Inclinometers	Both vertical and horizontal inclinometers are used. Traversing type of system in which a probe is moved periodically through casing located in the borehole whose inclination is being measured.	Cumulative Deformation	0-30 degrees
Rock Bolt Load Cells	Spool type units suitable for use with rock bolts. Tensile stress is inferred from strain gauges mounted on the surface of the spool.	Load	0-300 kips
Earth Pressure Cells	Installed between concrete keys and rock. Preferred type is a hydraulic pressure plate connected to a vibrating wire transmitter.	Lithostatic Pressure	0-1000 psi
Piezometer Pressure Transducers	Located in shafts and of robust design and construction. Periodic checks on operability required.	Fluid Pressure	0-500 psi
Strain Gauges	Installed within the concrete shaft key. Suitably sealed for the environment. Two types used-- surface mounted and embedded.	Cumulative Deformation	0-3000 $\mu\text{in/in}$ (embedded) 0-2500 $\mu\text{in/in}$ (surface)

1  
2  
3  
4  
5  
6  
7  
8  
9  
10

TABLE M2-3  
RH TRU MIXED WASTE HANDLING EQUIPMENT CAPACITIES

<b>CAPACITIES FOR EQUIPMENT</b>	
41-Ton Forklift	82,000 lbs
<b>MAXIMUM GROSS WEIGHTS OF RH TRU CONTAINERS</b>	
RH TRU Facility Canister	10,000 lbs
55-Gallon Drum	1,000 lbs
RH TRU Canister	8,000 lbs
<b>MAXIMUM NET EMPTY WEIGHTS OF EQUIPMENT</b>	
Facility Cask	67,700 lbs

(This page intentionally blank)

1

**FIGURES**

(This page intentionally blank)




Figure M2-1  
 Repository Horizon




Figure M2-2  
Spatial View of the Miscellaneous Unit and Waste Handling Facility




Figure M2-3  
Facility Pallet for Seven-Pack of Drums





Figure M2-5  
Typical Backfill Sacks Emplaced on Drum Stacks




Figure M2-5a  
Potential MgO Emplacement Configurations




Figure M2-6  
Waste Transfer Cage to Transporter




Figure M2-7  
Push-Pull Attachment to Forklift to Allow Handling of Waste Containers




Figure M2-8  
 Typical RH and CH Transuranic Mixed Waste Container Disposal Configuration




Figure M2-9  
Underground Ventilation System Airflow




Figure M2-11  
Typical Room Barricade




Figure M2-12  
 WIPP Facility Surface and Underground CH Transuranic Mixed Waste Process Flow Diagram




Figure M2-12  
 WIPP Facility Surface and Underground CH Transuranic Mixed Waste Process Flow Diagram  
 (Continued)






Figure M2-14  
Facility Cask Transfer Car (Side View)




Figure M2-15  
Horizontal Emplacement and Retrieval Equipment




Figure M2-16  
RH TRU Waste Facility Cask Unloading from Waste Shaft Conveyance




Figure M2-17  
Facility Cask Installed on the Horizontal Emplacement and Retrieval Equipment

FACILITY CASK AGAINST SHIELD COLLAR, TRANSFER CARRIAGE RETRACTED,  
SHIELD PLUG CARRIAGE ON STAGING PLATFORM, SHIELD PLUG BEING INSTALLED




Figure M2-18  
Installing Shield Plug




Figure M2-19  
Shield Plug Supplemental Shielding Plate(s)





Figure M2-20  
Shielding Layers to Supplement RH Borehole Shield Plugs



TYPICAL DIMENSION: APPROXIMATELY 29 INCHES DIAMETER X 61 INCHES SHIELDING LENGTH

Composition: Cylindrical steel shell filled with concrete  
Weight: Approximately 3750 pounds

Figure M2-21  
Shield Plug Configuration