

Environmental Protection Division Water Quality & RCRA Group (ENV-RCRA) P.O. Box 1663, Mail Stop K490 Los Alamos, New Mexico 87545 (505) 667-0666



National Nuclear Security Administration Los Alamos Site Office, A316 3747 West Jemez Road Los Alamos, New Mexico 87545 (505) 667-5794/FAX (505) 667-5946

Date: SEP 2 0 2012 Refer To: ENV-RCRA-12-0202 LAUR: 12-24131

Mr. John E. Kieling, Bureau Chief RCRA Permits Management Program Hazardous Waste Bureau New Mexico Environment Department 2905 Rodeo Park Drive East, Building 1 Santa Fe, NM 87505-6303

Dear Mr. Kieling:

SUBJECT: REQUEST FOR CLASSIFICATION DETERMINATION FOR PROPOSED MODIFICATION TO THE LOS ALAMOS NATIONAL LABORATORY (LANL) HAZARDOUS WASTE FACILITY PERMIT, EPA ID NO. NM0890010515

The purpose of this letter is to request a classification determination from the New Mexico Environment Department – Hazardous Waste Bureau (NMED-HWB) for proposed changes to the Los Alamos National Laboratory (LANL) Hazardous Waste Facility Permit (Permit), as described below. In July 2012 NMED-HWB requested that the U.S. Department of Energy and Los Alamos National Security, LLC (collectively the Permittees) submit a formal request for a classification determination to modify the Permit to add macroencapsulation treatment. The Permittees believe that such a modification would qualify as a Class 1 permit modification requiring prior NMED-HWB approval pursuant to the criteria outlined in 20.4.1.900 NMAC (incorporating 40 CFR §270.42(a)(2)). Pursuant to 40 CFR 270.42, classification decisions are based on two criteria: (1) the similarity of the modification to those modifications in Appendix I of 40 CFR § 270.42; and (2) application of the general definitions of Class 1, 2, or 3 (see 270.42(d)(2)). Under Appendix I, Item F.1.c, a modification or addition of a treatment process to treat waste restricted from land disposal to meet the treatment standards qualifies as a Class 1 permit modification requiring prior NMED-HWB approval (see 54 Fed. Reg. 9596, 9598, 9603 (Mar. 7, 1989)).

For the following reasons, the Permittees believe that macroencapsulation is a treatment process that meets the criteria for a Class 1 permit modification requiring prior NMED-HWB approval under Appendix I, Item F.1.c. Macroencapsulation is an EPA-approved treatment process as described in 40 CFR §§ 268.40 and 268.45 and meets the criteria under Item F.1.c as a "treatment process to treat waste restricted from land disposal to meet all or some of the treatment standards". The Permittees would like to use macroencapsulation for on-site treatment of hazardous waste stored at permitted storage units at Technical Area (TA-54), Area G. On-site treatment will also serve to expedite off-site disposal and facilitate the compliance commitments under the Federal Facility Compliance Order (Los Alamos National Laboratory, 1995) and the Compliance Order on Consent (2005, as revised).

Enclosure 1 contains a detailed description of the macroencapsulation technology and its applicability to treat radioactive lead solids and hazardous debris waste stored at TA-54, Area G. Also included are details about land disposal restriction (LDR) requirements as they apply to this waste stream and a discussion of how this macroencapsulation technology meets those requirements.

The types of regulated waste stored and generated at TA-54, Area G, include contaminated or suspect contaminated lead, glove boxes with contaminated or suspect contaminated lead, and debris waste from repackaging fiberglass reinforced plywood (FRP) boxes and drums. These waste streams are restricted from land disposal and must be treated to meet LDR treatment standards prior to disposal.

The macroencapsulation treatment process will not add to or change the permitted units, does not require an increase in the storage capacity, and does not add different waste to those already managed at the permitted units. Benefits of adding this treatment include increased worker safety, limited need for size reduction and repackaging, increased cost savings by eliminating the need to transport untreated waste off-site for treatment, and decreased processing time.

Mr. John E. Kieling ENV-RCRA-12-0202

If you have comments or questions regarding this request, please contact Gene E. Turner (LASO-EPO) at (505) 667-5794 or Mark P. Haagenstad (ENV-RCRA) at (505) 665-2014.

Sincerely,

A R Gneggs

(1)

Anthony R. Grieggs Group Leader Water Quality & RCRA Group (ENV-RCRA) Los Alamos National Security, LLC Sincerely,

Gene E. Turner Environmental Permitting Manager Environmental Projects Office Los Alamos Site Office U.S. Department of Energy

ARG:GET:TD/lm

- Enclosure:
- Proposed Macroencapsulation of Hazardous Waste at Technical Area 54 (TA-54), Area G
- Cy: Laurie King, USEPA/Region 6, Dallas, TX, w/enc. Tim Hall, NMED/HWB, Santa Fe, NM, w/o enc., Pete Maggiore, LASO-EPO, w/o enc., (E-File) Gene E. Turner, LASO-EPO, w/o enc., (E-File) George C. Henckel, LSSO-EPPO, w/o enc., (E-File) Carl A. Beard, PADOPS, w/o enc., A102 Michael T. Brandt, ADESH, w/o enc., (E-File) Alison M. Dorries, ENV-DO, w/o enc., (E-File) Charles O. Lenoie, PMFS-DO, LANL, w/o enc., (E-File) Mike J. Romero, LTP-OCP, LANL, w/o enc., (E-File) Mark P. Haagenstad, ENV-RCRA, w/o enc., (E-File) Tammy Diaz, ENV-RCRA, w/o enc., (E-File) Robert A. Lechel, ENV-ES, w/o enc., (E-File) LASO Records Center, w/enc., A316 IRM-RMMSO, w/enc., (E-File) ENV-RCRA Correspondence File, w/enc., K490

ENCLOSURE 1

MACROENCAPSULATION OF HAZARDOUS WASTE

AT TECHNICAL AREA 54, AREA G

ENV-RCRA-12-0202

LAUR-12-24131

Date: SEP 2 0 2012

Introduction

Per conversation with the New Mexico Environment Department – Hazardous Waste Bureau (NMED-HWB) staff in July 2012, it was requested that the US Department of Energy/ National Nuclear Security Administration (DOE/NNSA) and Los Alamos National Security, LLC (LANS) (collectively the Permittees) submit a white paper explaining the macroencapsulation processes proposed for use at Technical Area 54 (TA-54). The following discussion explains how macroencapsulation meets land disposal restriction (LDR) treatment standards for hazardous and mixed low level waste (MLLW) debris and radioactive lead solids (RLS) as defined in Title 40 of the Code of Federal Regulations (40 CFR) §§ 268.40, 268.42, and 268.45.

Background

The Permittees propose requesting approval from the NMED-HWB for a permit modification to allow treatment by macroencapsulation for appropriate mixed low-level waste streams. The proposed modification is necessary to achieve closure of Area G and its nine permitted storage units by the end of 2015 as required by Compliance Order on Consent (2005, as revised). In the Los Alamos National Laboratory (LANL) Framework Agreement (2012), the Permittees committed to removing all uncemented legacy and newly generated (as of October 1, 2011) transuranic (TRU) waste containers, stored above-ground at Area G, by June 30, 2014. A schedule for below-ground retrievable TRU waste will be developed by December 31, 2012.

The wastes stored at TA-54, Area G include TRU wastes, mixed TRU (MTRU) waste, low-level waste (LLW), and MLLW. Many of the waste containers do not meet U.S. Department of Transportation (DOT) or off-site waste disposal facility packaging requirements and must undergo processing and repackaging to render them acceptable for offsite shipment or disposal. Proposed waste processing may include segregation, decontamination (when possible), size reduction (if necessary), and repackaging according to waste composition (i.e. the waste matrix), chemical and physical characterization, and determination of compatibility, reactivity, and likely disposal destination. The waste may also be further treated to meet LDRs, void space requirements, and other waste acceptance criteria before they can be shipped to an approved off-site disposal facility. After approval of the modification, the processing will be completed within existing storage units at TA-54, Area G. The domes will provide containment, fire suppression, heat and cooling, and power requirements.

Macroencapsulation is a viable treatment option to meet LDRs for hazardous debris waste and radioactive lead solids (RLS) resulting from these operations. Commercially available macro-liner encapsulation systems (macro liners) are available and in use at other DOE/NNSA sites for treatment of both hazardous debris waste and RLS. Descriptions of the systems and their compliance with regulatory treatment standards are presented in the following discussion.

Compliance with RCRA Land Disposal Restrictions and Regulations

In order to meet LDR treatment standards for off-site disposal of wastes from TA-54, the Permittees propose to use commercially available macro-liners for macroencapsulation of hazardous debris waste and RLS. The proposed macroencapsulation systems consist of stainless steel (SS) macro-liners for debris, and high density polyethylene (HDPE) macro-liners for RLS. The macro-liners are inserted into or directly cast inside DOT and accepting waste facility compliant packages (e.g. DOT Type-A drums or

boxes). In both cases, the macro-liner is separate from the container, is not a structural component of the container, and is not integral to the DOT certification of the container. Once sealed, the macro-liner becomes an item shipped in the container.

The alternative treatment standard for hazardous debris is specified in 40 CFR § 268.45, Table 1, as: "Macroencapsulation: Application of surface coating materials such as polymeric organics (e.g., resins and plastics) or use of a jacket of inert inorganic materials to substantially reduce surface exposure to potential leaching media." The performance and/or design and operating standard is that the "(E)ncapsulating material must completely encapsulate debris and be resistant to degradation by the debris and its contaminants and materials into which it may come into contact after placement (leachate, other waste, microbes)." The standard for hazardous debris differs from the standard for RLS, which is identified in 40 CFR § 268.40 as a special subcategory under the D008 definition of regulated lead waste.

"Radioactive Lead Solids Subcategory (Note: These lead solids include, but are not limited to, all forms of lead shielding and other elemental forms of lead. These lead solids do not include treatment residuals such as hydroxide sludges, other wastewater treatment residuals, or incinerator ashes that can undergo conventional pozzolanic stabilization, nor do they include organolead materials that can be incinerated and stabilized as ash. This subcategory consists of non-wastewaters only.)"

EPA specifies the treatment standard for RLS waste as "MACRO" (macroencapsulation) in Table 1 of 40 CFR § 268.42, "Technology Codes and Descriptions for Technology-Based Standards:"

"Macroencapsulation with surface coating materials such as polymeric organics (e.g., resins and plastics) or with a jacket of inert inorganic materials to substantially reduce surface exposure to potential leaching media. Macroencapsulation specifically does not include any material that would be classified as a tank or container according to 40 CFR § 260.10". (40 CFR 260.10 – "Container means any portable device in which a material is stored, transported, treated, disposed of, or otherwise handled.")

The standard for hazardous debris differs from the standard for RLS in that the use of "any material that would be classified as a tank or container according to 40 CFR § 260.10" is allowed for macroencapsulation of hazardous debris, but it is not allowed for macroencapsulation of RLS. Macroliners must not meet the definition of a container, in order to be used for the treatment of RLS to meet Land Disposal Restrictions.

Treatment Standard Compliance

The distinction between a waste container liner or jacket for macroencapsulation and the waste container itself, as identified in the applicable regulations for macroencapsulation of RLS, was an important issue for the State of Nevada, Division of Environmental Protection (NDEP), which is the permitting authority for the Nevada National Security Site (NNSS) – a likely destination for some of the LANL MLLW following macroencapsulation treatment. In 2007, NDEP explicitly accepted that the HDPE liners used in the macroencapsulation process, discussed below, are not equivalent to containers according to the EPA definition in 40 CFR §260.10.

On November 1, 2007, the NDEP approved an UltraTech macro-liner macroencapsulation system (as described in Attachment 1) as complying with the requirements for macroencapsulation of RLS, and also stated that the technology can be used for wastes sent to the NNSS for disposal (Attachment 2). In 2012,

the NDEP also approved the use of a Product Drum Model (PD) Macro Pack, a 1/2" thick external HDPE liner, as an alternative method for compliance with LDRs for all National Nuclear Security Administration (NNSA) generators (Attachment 3). NDEP's approval acknowledged that the PD Macro Pack provides equivalent performance to the specified method in 40 CFR § 268.42, and meets the 40 CFR § 268.45 "Treatment Standard for Hazardous Debris and Radioactive Cadmium and Mercury Batteries," as well as the 40 CFR § 268.40 "Treatment Standard for Radioactive Lead Solids." In so doing, NDEP explicitly accepted that the HDPE liners used in the macroencapsulation process are not containers, and do not meet the description of a container as specified in 40 CFR §260.10.

Discussion

In the NDEP-approved treatment process for RLS (as noted in Attachment 1), an HDPE liner is placed or molded within a DOT-approved container; waste is placed into the macro-liner; and a non-biodegradable filler material meeting offsite disposal facility requirements (e.g. vermiculite, polyurethane expansion foam, etc.) is added in the liner to eliminate void space. The HDPE liner and filler materials that are used in the process have been proven to be effective and are inert, impermeable, resistant to potentially leaching media, compatible with the waste types, and nonreactive with the waste. After void space is filled and verified, the HDPE liner lid is put in place and bonded to the liner, completely sealing the waste in the liner. The bonding process is verified, and the DOT-container lid is put in place and secured. The chemically inert, HDPE liner jackets the waste, totally isolating the waste from the environment and from any potential leaching media, while the outer container meets the necessary requirements for shipping and off-site disposal.

The HDPE liner used in this method acts as a "coating or jacket of inert material" that is completely sealed, thus substantially reducing the potential for leaching materials to come into contact with the surface of the lead waste. The liner is the encapsulating material (i.e., it meets the RCRA definition of a "jacket of inert inorganic material"); it is separate from, but inside, the DOT approved container for the waste; and the liner is not considered in the DOT certification of the container. Therefore, the liners do not meet the description of "containers" or "tanks" as defined in 40 CFR 260.10.

Two EPA letters elucidate EPA's original intent regarding macroencapsulation. The first is a July 30, 1990 letter to the Naval Nuclear Propulsion program [RCRA Online number 9554.1990(07)], in which the EPA Director of the Office of Solid Waste provided an explanation of macroencapsulation as it applies to RLS:

"....The key to assuring compliance with the standard is the stipulation in the regulatory language that the "jacket of inert inorganic materials" (i.e., the steel surrounding the lead) "substantially re duce(s) surface exposure to potential leaching media". The key to this decision is whether the steel is indeed sealed and thereby minimizing potential exposure to any leaching material."

The July 30, 1990 letter further states:

"......EPA felt that it was necessary to add the language to the definition of macroencapsulation to prevent the "jacket of inorganic material" from being interpreted as including materials that are merely containers or drums."

EPA stated that the "key" was "minimizing potential exposure to any leaching material," and that the "jacket of inorganic material" cannot include materials that "are merely containers or drums."

EPA's position regarding the definition of macroencapsulation was reemphasized in a letter dated December 27, 1990 [RCRA Online number 9554, 1990(14)]:

".....Paraphrasing the regulatory language, compliance with the macroencapsulation standard explicitly prohibits containerization of wastes or material in a tank or container meeting the regulatory criteria under the 40 CFR § 260.10.EPA purposely modified the proposed standard for D008 radioactive lead solids to include "jackets of inorganic materials" in order to specifically account for these submarine reactor compartments. EPA felt that it was necessary to add the language to the definition of macroencapsulation to prevent the "jacket of inorganic material" from being interpreted as including materials that are merely containers or drums."

These documents show that EPA's intent for a macroencapsulation treatment system was, and is, to protect the environment from lead or other hazards that could be leached from RLS. This is achieved by reducing the potential of a leaching material, such as infiltrating water or a dilute acid, from coming in contact with the surface of the contaminated lead. The encapsulating inert media must be "sealed" and, when applied to RLS, the macroencapsulation system cannot "merely" be a simple container or tank.

The December 27, 1990 letter also stated that EPA would recognize SS as meeting the MACRO treatment requirements:

".....With regards to the lead weights in Question 2, the wastes may be considered to meet the specified method of "MACRO", as generated, provided the stainless steel surrounding the lead weights does not meet the definition of a tank or container and provided a substantial reduction in surface exposure to potential leaching media can be determined."

In this response, EPA reiterated that the macroencapsulation methodology must significantly protect the contaminated lead solids from exposure to leaching media by completely sealing them in the protective material and that the protective material cannot be considered a container or tank.

The macro-liners proposed for use at LANL will be housed within DOT compliant containers, and act as a jacket of inert material that is completely sealed, thus, substantially reducing the potential for leaching materials to come into contact with the surface of the waste. The key for the macro-liner to meet the requirements of 40 CFR § 268.42 is that the liner cannot be construed as a "container" or "tank" and given that the liner is within, yet separate from a DOT approved container, and is not integral to the DOT certification, it is not a container or a tank. Therefore, the proposed, commercially available macro-liners meet the "MACRO" definition in 40 CFR § 268.42. SS macro-liners offer an appropriate treatment process for hazardous debris waste, and HDPE macro-liners offer an appropriate treatment process for RLS.

Conclusion

After careful evaluation of the regulations, available EPA guidance, and past precedents, the Permittees believe that the proposed macro-liner macroencapsulation systems clearly comply with the EPA definitions of "MACRO," for the following reasons.

U1201872

- 1. As applied to RLS, the HDPE liners meet the requirements of 40 CFR § 268.42 because they do not meet the description of a tank or container;
- 2. As applied to hazardous debris, the SS liners likewise meet the requirements of 40 CFR § 268.45.

This conclusion is in agreement with positions adopted by EPA and the State of Nevada. Therefore, the Permittees intend to request addition of macroencapsulation to the Permit as a minor permit modification for appropriate, LDR-compliant treatment of applicable waste streams generated from processing legacy wastes at TA-54.

Attachments:

Attachment 1 – Request for Nevada Division of Environmental Protection (NDEP) Approval of Alternative Treatment Standard for Radioactive Lead Solids, E. Frank Di Sanza, Federal Project Director, Waste Management Project, Department of Energy, National Nuclear Security Administration, Nevada Site Office, Las Vegas, NV, October 22 2007 (with enclosure).

Attachment 2 – Re: Request for Nevada Division of Environmental Protection (NDEP) Approval of Alternative Treatment Standard for Radioactive Lead Solids, T. H. Murphy, Chief, Bureau of Federal Facilities, Nevada Division of Environmental Protection, Las Vegas, NV, November 1, 2007.

Attachment 3 – Re: Request for Nevada Division of Environmental Protection (NDEP) Approval of Alternative Treatment Standard for Radioactive Lead Solids, Tim Murphy, Chief, Bureau of Federal Facilities, Nevada Division of Environmental Protection, Las Vegas, NV, May 22, 2012. (Also includes the original request from NNSA.)

Attachment 1 August 2012



Department of Energy National Nuclear Security Administration Nevada Site Office P.O. Box 98518 Las Vegas, NV 89193-8518



OCT 2 2 2007

Timothy Murphy, Chief Nevada Division of Environmental Protection Bureau of Federal Facilities 2030 E. Flamingo Road, Suite 230 Las Vegas, Nevada 89119

REQUEST FOR NEVADA DIVISION OF ENVIRONMENTAL PROTECTION (NDEP) APPROVAL OF ALTERNATIVE TREATMENT STANDARD FOR RADIOACTIVE LEAD SOLIDS

The National Nuclear Security Administration, Nevada Site Office, Waste Management Project (WMP) requests NDEP's review of the enclosed macroencapsulation method as a treatment method for radioactive lead solids. The WMP finds the method compelling and feels it would be a useful method for generators wanting to dispose Mixed Low-Level Waste (MLLW) at the Nevada Test Site (NTS). If the NDEP agrees, would the NDEP provide written approval to the NSO to allow the NTS generators to use the technology for disposing of their waste at the NTS.

E. Frank Di Sanza Federal Project Director Waste Management Project

WMP: 3562.JC

Enclosures: As stated

cc w/out encl via email: J. K. Wrapp, NSTec, Las Vegas, NV Carlos Ramirez, NSTec, Las Vegas, NV S. K. Krenzien, NREI, Las Vegas, NV

Energy Control Control

EnergX Macroencapsulation Process Compliance Evaluation

August 2007

Summary

After carefully comparing the EnergX macroencapsulation process to the Environmental Protection Agency (EPA) definition of macroencapsulation as a treatment for radioactive lead solids, we have concluded that the macroencapsulation processes being deployed by EnergX meets the definition of macroencapsulation for radioactive lead solid, and as such can be used to treat both contaminated debris and lead solids without having to use an alternative method or seeking an equivalency from the EPA.

Issue

It is readily accepted that the UltraTech Macroencapsulation systems meet the EPA definition of macroencapsulation as applied to hazardous debris waste. However, the UltraTech macroencapsulation systems have not, as of yet, been recognized as a compliant means of treating radioactive lead solids, as defined by the EPA.

This evaluation was performed to determine if the UltraTech macroencapsulation systems, as being deployed by EnergX at the TRU Waste Processing Center (TWPC) and other sites, meets the EPA definition of macroencapsulation as applied to the treatment of radioactive lead solids.

Requirements/Regulations

40 CFR 268.40 identifies radioactive lead solids as a special subcategory under the D008 definition of regulated lead waste.

"Radioactive Lead Solids Subcategory (Note: These lead solids include, but are not limited to, all forms of lead shielding and other elemental forms of lead. These lead solids do not include treatment residuals such as hydroxide sludges, other wastewater treatment residuals, or incinerator ashes that can undergo conventional pozzolanic stabilization, nor do they include organolead materials that can be incinerated and stabilized as ash. This subcategory consists of nonwastewaters only.)"

This section further defines the treatment standard for radioactive lead solids as "MACRO" (macroencapsulation). Table 1, Technology Codes and Descriptions for Technology-Based Standard, of 40 CFR 268.42 defines "MACRO" as:

"Macroencapsulation with surface coating materials such as polymeric organics (e.g., resins and plastics) or with a jacket of inert inorganic materials to substantially reduce surface exposure to potential leaching media. *Macroencapsulation specifically does not include any material that would be* classified as a tank or container according to 40 CFR 260.10. [emphasis added]

Macroencapsulation Systems

EnergX is employing the use of the latest UltraTech International (UltraTech) macroencapsulation macro-liner systems (macro-liner), which are comprised of highdensity/low-density polyethylene (PE) macro-liners housed within DOT compliant packages, such as DOT Type-A drum or box. Macro-liners can be customized to fit into almost any container. UltraTech macro-liners are inserted inside the DOT containers in one of two fashions. Typically for drums, UltraTech uses the cast-in-place process to insert the liner directly into the drum. In this case, the drum itself functions as part of the roto-molding process to cast the liner in place. The box liners are cast in standalone molds and are later slipped into the DOT box. In either case, even though the liners are in intimate contact with the DOT package they are not integral to the DOT certification. Photo 1 show the profiles of the two liners with lids bonded on.



UltraTech also produces robust heavy-duty (nominally 1 ½ inches thick) stand-alone macro tubes, which also qualify as a DOT strong-tight or IP-1 container, and can even be qualified as a high integrity container (HIC). These are typically referred to as macro-containers and can be produced in a large array of diameters and lengths. Photo 2 shows the 63" HDPE macrocontainer that qualifies as a DOT IP1 container. These macro-containers can be transported as standalone packages while the macro liner must be packaged within a DOT compliant container in order to be transported.

Photo 2 - UltraTech 63" macroencapsulation container

EnergX Macroencapsulation Process

EnergX is currently using the macro-liner systems in both the drum and the box configurations, but are not using any of the macro-containers (tubes) at this time.

The EnergX macroencapsulation process typically consists of the following steps (see photos 3 - 8); the waste is placed into the UltraTech PE macro-liner and a filler material (e.g. polyurethane expansion foam, vermiculite, etc.) is pumped into the liner in a continuous fashion to eliminate

all void space within the macro liner. Once filled, the half-inch thick PE macro lid is put in place and bonded to the PE liner body (nominally a half-inch thick) using a patented bonding process, which yields a highly durable, completely sealed liner. At this point the waste is now totally isolated from the environment and any potential leaching media by the half-inch thick, chemically inert, PE coating or jacket.

Once verified that the macroencapsulation bonding process has been successfully completed the drum or box lid is put in place and bolted closed, which further protects the waste from the environment and facilitates transportation.





3 - Drums being placed in macro box



5 - Void space filled



4 - Foam being added to fill void



6 - Macro liner being placed onto macro body





7 - Macro liner being sealed

8 - Type-A Box lid being bolted

Evaluation

Since the definition and performance requirements for macroencapsulation are open to interpretation additional research into the EPA's basis for the definition of "MACRO" as applied to radioactive lead solids was conducted. Two EPA letters were found that provided some insight into the EPA's original thoughts as applied to macroencapsulation. The first was the July 30 1990 letter to the Naval Nuclear Propulsion Program¹. As shown in the below excerpts from this letter, the EPA Director of the Office of Solid Waste essentially provides an explanation of macroencapsulation as it applies to radioactive lead solids and also explains how and why the EPA expanded the original definition of macroencapsulation to cover the defueled submarine reactor compartments.

"In summary, EPA determined that the practice of direct land disposal of these compartments may meet the "Macroencapsulation" BDAT treatment standard for D008 radioactive lead solids. The key to assuring compliance with the standard is the stipulation in the regulatory language that the "jacket of inert inorganic materials" (i.e., the steel surrounding the lead) "substantially reduce(s) surface exposure to potential leaching media". Since the information in your letter and your comments appears to indicate that this is true, the Agency believes that the practice probably complies with the BDAT standard for D008 radioactive lead solids. The compartments probably are considered to meet BDAT "as generated", because the lead shielding (as originally constructed) is surrounded in a thick, sealed steel jacket. The key to this decision is whether the steel is indeed sealed and thereby minimizing potential exposure to any leaching material." [emphasis added]

It further states:

"EPA purposely modified the proposed standard for D008 radioactive lead solids to include "jackets of inorganic materials" in order to specifically account for the submarine reactor compartments. However, EPA felt that it was necessary to add the language to the definition of macroencapsulation to prevent the "jacket of inorganic material" from being interpreted as including materials that are merely containers or drums. Thus, we concur with your

¹ Letter to Richard A. Guida, Associate Director, Naval Nuclear Propulsion Program, Department of Navy, from Sylvia K. Lowrance, Director, Office of Solid Waste, EPA, July 30 1990, Submarine Reactor Compartments – Land Disposal Restrictions, 9554.1990(07).

interpretation that the submarine compartment does not meet the definition of either a drum or a container." [emphasis added]

Even though the allowance for the use of a jacket of inorganic material was specifically added to allow the Navy to credit the steel housing surrounding the reactor compartments, it appears that the EPA did not intend to limit its application only to the reactor compartments, otherwise they would have simply granted the Navy an exemption or equivalency and would not have expanded and codified a new definition.

On December 27 1990, EPA issued another letter that reemphasized EPA's position regarding the reactor compartments and the definition of macroencapsulation²:

"This letter is in response to your letter dated November 16, 1990 requesting clarification on certain issues regarding treatment standards for certain mixed radioactive wastes.

With regards to Question 1 (as referred to in your letter), "placement in a heavy stainless steel box and welding the box closed" would not be considered to comply with the standard identified as "MACRO" in 268.42 Table 1 (55 FR 22693 (June 1, 1990). This standard is quite clearly described in regulatory language in Table 1 as "Macroencapsulation with surface coating materials such as polymeric organics (e.g., resins and plastics) or with a jacket of inert inorganic materials to substantially reduce surface exposure to potential leaching media. Macroencapsulation specifically does not include any material that would be classified as a tank or container according to 40 CFR 260.10" (emphasis added). Paraphrasing the regulatory language, compliance with the macroencapsulation standard explicitly prohibits containerization of wastes or materials in a tank or container meeting the regulatory criteria under the 40 CFR 260.10. [emphasis added]

This is not the same situation as where the U.S. Naval Nuclear Propulsion Program wanted to land dispose defueled submarine reactor compartments. The information provided by the Navy indicated that the "Jacket of inert inorganic materials" (i.e., the stool surrounding the lead) could "substantially reduce surface exposure to potential leaching media" and that due to their size and structure these compartments would not be classified as a tank or container according to the definitions in 40 CFR 260.10. EPA purposely modified the proposed standard for D008 radioactive lead solids to include "Jackets of inorganic materials" in order to specifically account for these submarine reactor compartments. EPA felt that it was necessary to add the language to the definition of macroencapsulation to prevent the "jacket of inorganic material" from being interpreted as including materials that are merely containers or drums."

It is obvious from these two letters that the EPA's intent for a macroencapsulation system was (is) to protect the environment from lead or other hazards that could be leached off contaminated lead solids. This can be achieved by reducing the potential of a leaching material, such as a dilute acid, to come into contact with the exposed surface of the contaminated lead. Critical to their position is that the protective media must be "sealed" and when applied to radioactive lead solids the macroencapsulation system cannot be a simple container or tank ["containerization of wastes or materials in a tank or container"].

² Letter to Kevin S. Dunn, Project Manager, Environmental Policy Center, Law Companies Environmental Group from Sylvia K. Lawrence, Director, Office of Solid Waste, EPA, December 27 1990, Treatment Standards for Certain Mixed Radioactive Waste, 9554, 1990(14).

The EPA provides further insight into their thoughts of macroencapsulation in the December 27 1990 letter when they stated that they would recognize the simple plastic coating covering lead lined gloves as macroencapsulation:

"With regards to the plastic coated, lead lined gloves in Question 2 of your letter, they would be considered to comply with the standard identified as "MACRO" provided that none of the lead is exposed (i.e., the entire surface of the lead is coated) and provided that the coating provides a substantial reduction in surface exposure to potential leaching media (i.e., the gloves should not be expected to be exposed to physical, chemical, or thermal conditions where the integrity of the surface coating could likely be breached). With regards to the lead weights in Question 2, the wastes may be considered to meet the specified method of "MACRO", as generated, provided the stainless steel surrounding the lead weights does not meet the definition of a tank or container and provided a substantial reduction in surface exposure to potential leaching media can be determined."

One can interpret this response to say that the macroencapsulation methodology does not have to be an extremely robust mechanism, such as metal shielding around the naval containment vessels, as long as the contaminated lead solids are significantly protected from the exposure to leaching media by being completely sealed by the protective material and that the protective material is not considered a container or tank.

These two key elements were used to review the two UltraTech macroencapsulation systems to determine compliance with the requirements of 40 CFR 268. 42. The macro-liners and the macro-containers were evaluated separately due to the unique differences between the two systems.

Macro-Liners

In this case, the macro-liners, which are housed in a DOT complaint container, act as a coating or jacket of inert material that are completely sealed, thus substantially reducing the potential for leaching materials to come into contact with the surface of the contaminated lead. One can equate this scenario to the lead lined glove scenario. Since the liners are housed inside a DOT approved container, and are not integral to the DOT certification, the liners cannot be construed as a "container" or a "tank", which are specifically excluded under the "MACRO" definition in 40 CFR 268.42. As such, the macro-liner systems are an appropriate treatment for both debris and radioactive lead solids.

Macro-Containers

Based on verbatim compliance, one must conclude that the use of the macro-containers do not meet the EPA definition of "MACRO" as applied to radioactive lead solids, simply because the tube can function as a container.

Conclusion

After careful evaluation of the requirements as applied to the EnergX macroencapsulation process it has been concluded that the EnergX macroencapsulation process using UltraTech macro-liners macroencapsulation systems clearly complies with the definitions of "macro" as applied to radioactive lead solids. However, the UltraTech macro-containers (tubes) cannot be used to treat radioactive lead solids without seeking an equivalency or a variance from the EPA requirements.



STATE OF NEVADA Department of Conservation & Natural Resources

DIVISION OF ENVIRONMENTAL PROTECTION

Brian Sandoval, Governor Leo M. Drozdoff, P.E., Director

WMD.120524.0001

Attachment 2 August 2012

Colleen Cripps, Ph.D., Administra

May 22, 2012

Janet L. Appenzeller-Wing Deputy Assistant Manager for Environmental Management National Nuclear Security Administration (NNSA/NSO) Nevada Site Office P. O. Box 98518 Las Vegas, NV 89193-8518

RE: Request for Nevada Division of Environmental Protection (NDEP) Approval of Alternative Treatment Standard for Radioactive Lead Solids

Dear Ms. Appenzeller-Wing:

The NDEP staff has received and reviewed the NNSA/NSO request to permit NNSS generators to use the Product Drum Model (PD Macro Pack) as a treatment method for radioactive lead solids. NDEP concurs that this alternative method for compliance with the Land Disposal Restrictions is equivalent in performance to the specified method in 40 CFR 268.42, and meets the Land Disposal Restrictions of 40 CFR 268.45 (Treatment Standard for Hazardous Debris and Radioactive Cadmium and Mercury Batteries), and 40 CFR 268.40 (Radioactive Lead Solids).

NNSS generators may use this technology for disposal of applicable waste at the NNSS.

If you have any questions regarding this matter contact Jeff MacDougall at (702) 486-2850 ext 233, or me ext. 231.

Sincerely Tim Murphy Chief

Bureau of Federal Facilities

THM/JJM/JW/SP/TZ/KC

U1201872



Attachment 2 August 2012

cc: R. G. Geisinger, NSTec, Las Vegas, NV NSTec Correspondence Control, MS NLV008
J. J. Cebe, WMP, NNSA/NSO, Las Vegas, NV
K. K. Snyder, PSG, NNSA/NSO, Las Vegas, NV
S. A. Hejazi, SC, NNSA/NSO, Las Vegas, NV
D. J. Morgan, OPA, NNSA/NSO, Las Vegas, NV

		14 M 42 L

동안 가는 것을 알고 있는 것은 한 것을 것 같아요. 안전 가지 않는 것은 것 같아요. 것이 같아요. 것이 같아요. 같이 있는 것이 같아요. 같이 있는 것이 같아요. 동안 그리고 가지 않는 것은 것이 같아요. 한 것이 같아요. 같이 같아요. 같이 있는 것이 같아요. 같이 있는 것이 같아요. 같이 같아요. 같이 같이 같아요. 것이는 동안

와 모두 가지 않는 사람들은 것은 모두 바람을 들었다. '김 같은 가슴과 한 것들은 것 같은 것을 줄었다. "무슨 ------ (" 나는 것이라는 "

The second se

Attachment 3 August 2012



Department of Energy National Nuclear Security Administration Nevada Site Office P.O. Box 98518 Las Vegas, NV 89193-8518



MAY 1 7 2012

Timothy Murphy, Chief Nevada Division of Environmental Protection Bureau of Federal Facilities 2030 East Flamingo Road, Suite 230 Las Vegas, NV 89119

REQUEST FOR NEVADA DIVISION OF ENVIRONMENTAL PROTECTION (NDEP) APPROVAL OF ALTERNATIVE TREATMENT STANDARD FOR RADIOACTIVE LEAD SOLIDS

The National Nuclear Security Administration Nevada Site Office (NNSA/NSO), Waste Management Project requests NDEP's review of the enclosed macroencapsulation method as a treatment method for radioactive lead solids. The Advance Mixed Waste Treatment Project is anticipating using this method to macroencapsulate radioactive lead solids under waste profile AMWP000000005 for disposal at the Nevada National Security Site (NNSS). If NDEP agrees, please provide written approval to NNSA/NSO to permit NNSS generators to use this technology for disposal of waste at the NNSS.

If you have any questions or comments, please contact James J. Cebe, Waste Management Project, at (702) 295-0957.

Janet L. Appenzeller-Wing Deputy Assistant Manager for Environmental Management

WMP:8588.JJC

Enclosure: As stated

Timothy Murphy

MAY 1 7 2012

cc w/encl. via e-mail:

J. J. MacDougall, NDEP, Las Vegas, NV R. G. Geisinger, NSTec, Las Vegas, NV NSTec Correspondence Control, MS NLV008 J. J. Cebe, WMP, NNSA/NSO, Las Vegas, NV K. K. Snyder, PSG, NNSA/NSO, Las Vegas, NV S. A. Hejazi, SC, NNSA/NSO, Las Vegas, NV D. J. Morgan, OPA, NNSA/NSO, Las Vegas, NV NNSA/NSO Read File

Macroencapsulation using the HDPE Macro Pack - Product Drum Model

At the Advanced Mixed Waste Treatment Project, super compaction is used to significantly reduce the volume of both transuranic (TRU) and low-level waste debris which will ultimately be treated and disposed. Mixed Low-Level Waste (MLLW) debris that can be processed in the AMWTP facility may be inspected, sorted, assayed and compacted. Some 55-gallon drums of MLLW debris are "direct feed into the Super Compactor, for super compaction resulting in "pucks", after RTR and assay are performed. The compacted waste pucks are placed into 100-gallon drums called product drums. If radiological characterization shows the final compacted waste containers, and each inner puck are < 100 nCi/g concentration of alpha emitting TRU nuclides and do not contain prohibited items, then they are candidates for macroencapsulation treatment and disposal.

Product drums are US DOT Type A containers which are processed and packaged in accordance with 40 CFR 264.315 (b), Special Requirements for Containers and loaded to the maximum extent practical and are considered full.

After filling the product drum, it is then placed into a Product Drum Model (PD Macro Pack); a ½" thick external High Density Polyethylene (HDPE) liner. Void space filler (e.g. vermiculite) is added to fill the PD Macro Pack to 90% full or greater. An HDPE lid is placed onto the PD Macro Pack. Using macro sealing wires imbedded in the lid, a control unit is connected to the wires to bond the HDPE lid to the PD Macro Pack. This process macroencapsulates the waste container thus meeting the Land Disposal Restrictions of 40 CFR 268.45, Treatment Standard for Hazardous Debris, radioactive Cadmium and Mercury batteries, and 40 CFR 268.40 Radioactive Lead Solids.



P.C.

Signature/Review/Coordination Sheet

This form is to accompany all documents requiring review, approval, or signature by the Laboratory Director or Designee.

Date	Deadline				
8/21/2012	September 14, 2012	Is this a response to a	an action item?	Yes 🖵	No 🖾
From: ENV-RCRA		Call for Pick-up			
Name:	MS: K490	Name: Linda M.	Salazar	Phone:	7-7407
Title: Identify docum	ant briefly describing subject ma	attor			
				1 NT	
Laboratory Hazardous	Waste Facility Permit (Permit) for	macroencapsulation treatment	ation to the Los A at TA-54, Area G	Permitted U	nal nits.
Action	nformation Only				
Background/Issues					
Letter to request a class	ification determination regarding the	he addition of a macroencapsul	ation treatment pr	rocess to the	Permit.
ACTION requested	of Laboratory Director or Desig	gnee:			
Review and Endorse					
		erengenn i setti aven			
PAD Endorsement	Circulture		[F		
Name (print)	Signature		L	Jale	
Carl A. Be	ard ha				
AD Endorsement	0.2				
Name (print)	Signature			Date	
Michael T. E	na				
Wilchael I. E	Jandt				
Coordinated with	0.000		TP	N	
T. Name (print)	Signature	$\tau_{\rm L}$	L		12
Alison M. D	orries Un	- MD-		9/11/	12
2. Name (print)	Signature		C	Date / /	
Authority	A	DE	6	9/1/12	
Anthony R. (Sichature	comp		Vato /	
o. Name (print)	Signature	1 2/1 5/1	4	2 and 1	0(1)
Mark P. Haa	genstad	Testing Mer		0/29/0	12
4. Name (print)	Signatúre		C	Date /	
Kathron M	Roberts Coo	for 3			
5. Name (print)	Signature	ing		Date	
·····		Par IL			
Kathryn W. Joh	ns-Hughs	lase T			

Please ensure appropriate inter/intra Directorate/Divisional coordination and review prior to submittal to the Director's Office. Form 1824 (1/07) 1824 Coordination sheet (continued)

Name (print)	Signature	Date	
Tammy A. Diaz	ar G. K	8/27/12	
Name (print)	Signature	Date	
Name (print)	Signature	Date	
Name (print)	Signature	Date	
Name (print)	Signature	Date	
Name (print)	Signature	Date	

2



Signature/Review/Coordination Sheet

This form is to accompany all documents requiring review, approval, or signature by the Laboratory Director or Designee.

8/21/2012	September 14, 2012	Is this a response to an a	ction item? Yes 🖬 No 🖾
From: ENV-RCRA		Call for Pick-up	
Name:	MS: K490	Name: Linda M. Sala	zar Phone: 7-7407
ENV-RCRA-12-000 Laboratory Hazardon Action Background/Issue Letter to request a cla	0 Request for a Classification Determ us Waste Facility Permit (Permit) for Information Only se: assification determination regarding t	nination for a proposed modification macroencapsulation treatment at T/	a to the Los Alamos National A-54, Area G Permitted Units.
ACTION requested Review and Endorse	d of Laboratory Director or Desig	gnee:	
AD Endorsement			
Name (print)	Signature		Date
Carl A. 1	Beard		
D Endorsement			
Name (print)	Signature		Date
Michael T.	Brandt		
Michael T.	Brandt		
Michael T. pordinated with 1. Name (print)	Brandt Signature		Date
Michael T. pordinated with 1. Name (print)	Brandt Signature		Date
Michael T. cordinated with I. Name (print) Alison M. 2. Name (print)	Brandt Signature Dorries Signature		Date
Michael T. pordinated with 1. Name (print) Alison M. 2. Name (print) Anthony B	Brandt Signature Dorries Signature	26	Date Date 9/1/12
Michael T. perdinated with 1. Name (pdnt) Alison M. 2. Name (print) Anthony R 3. Name (print)	Brandt Signature Dorries Grieggs Signature	26,1	Date Date 9/11/12 Date
Michael T. perdinated with 1. Name (print) Alison M. 2. Name (print) Anthony R. 3. Name (print) Mark P. Ha	Brandt Signature Dorries Grieggs Signature agenstad	2 <i>G</i> 7/1	Date Date 9/11/12 Date B/29/2012
Michael T. pordinated with 1. Name (print) Alison M. 2. Name (print) Anthony R 3. Name (print) Mark P. Ha 4. Name (print)	Brandt Dorries Grieggs Signature agenstad Signature Signature Signature Signature	26 7. fl-7. A	Date Date 9/11/12 Pate 8/29/2012 Date
Michael T. portinated with 1. Name (print) Alison M. 2. Name (print) Anthony R 3. Name (print) Mark P. Ha 4. Name (print)	Brandt Dorries Grieggs agenstad Behate	2G Zforth	Date Date 9////2 Pate 8/29/2012 Date 9 / 11// 2
Michael T. perdinated with 1. Name (print) Alison M. 2. Name (print) Anthony R. 3. Name (print) Mark P. Ha I. Name (print) Kathryn M 3. Name (print)	Brandt Dorries Grieggs Grieggs Signature agenstad Signature Signature	2G Zflyth they Abete	Date Date 9/1//2 Pate 8/29/2012 Date 9/11//2 Date
Michael T. condinated with Alison M. Alison M. Name (print) Anthony R Name (print) Mark P. Ha Name (print) Kathryn M Name (print)	Brandt Dorries Signature Grieggs Signature agenstad Signature Kat Signature Signature	26 Pflyth they Roberts	Date Date 9/11/12 Pate 8/29/2012 Date 9 / 11/12 Date

Please ensure appropriate Inter/Intra Directorate/Divisional coordination and review prior to submittal to the Director's Office. Form 1824 (1/07)

3



Signature/Review/Coordination Sheet

This form is to accompany all documents requiring review, approval, or signature by the Laboratory Director or Designee.

Date	Deadline	le this a reasonable to an action item?		
8/21/2012	September 14, 2012	is this a response to an action item?		
From: ENV-RCRA		🛛 Call for Pick-up		
Name:	MS: K490	Name: Linda M. Salazar	Phone: 7-7407	
Title: Identify docume	nt briefly describing subject matter			
ENTV DCDA 12 0000 D	an, oneny describing subject matter.	n fan e menered medification to the I as A	Inmaa Matianal	
Laboratory Hazardous V	Vaste Facility Permit (Permit) for macro	bencapsulation treatment at TA-54, Area G	Permitted Units.	
Action 🛛 In	formation Only			
Background/Issues:				
Letter to request a classi	fication determination regarding the add	lition of a macroencapsulation treatment p	rocess to the Permit.	
ACTION requested o	f Laboratory Director or Designee:			
Review and Endorse				
PAD Endorsement				
Name (print)	Signature	(C	Date	
Carl A. Bea	rd			
AD Endorsement				
Name (print)	Signature		Date	
Michael T. Dr	andt			
Michael I. Bi				
Coordinated with				
1. Name (print)	Signature		late	
Alison M. Do	rries			
2 Name (print)	Signature		late /	
Anthony R. G	rieggs H-121	J 1	1/1/2	
3. Name (print)	Signature		ate	
	N. P		2/19/2012	
Mark P. Haage	enstad Usk lig	hey NOV	Uprofesso	
4. Name (print)	Signature		ate (
Kathrvn M R	oberts			
5. Name (print)	Signature		ate	
	14.001		a lugla in	
Kathryn W. John	s-Hughs	. Kugus	7 1 18 2012	

Please ensure appropriate inter/intra Directorate/Divisional coordination and review prior to submittal to the Director's Office. Form 1824 (1/07)

From:	Medina, Louella B
To:	locatesteam
Subject:	REQUEST FOR CLASSIFICATION DETERMINATION FOR PROPOSED MODIFICATION TO LANL'S HAZARDOUS WASTE FACILITY PERMIT, EPA ID NO. NM0890010515
Date:	Thursday, September 20, 2012 8:34:52 AM
Attachments:	12-0202 Sept-20 Classification Determination Proposed Mod to LANL's HWF Permit NM0890010515.pdf