

**STATE OF NEW MEXICO
BEFORE THE WATER QUALITY CONTROL COMMISSION**



In the Matter of:
PROPOSED AMENDMENT
TO 20.6.6 NMAC (Dairy Rule)

No. WQCC ¹³~~12~~- 08 (R)

**SECOND PETITION TO AMEND 20.6.6 NMAC (DAIRY RULE)
AND REQUEST FOR HEARING**

I. INTRODUCTION

Pursuant to the New Mexico Water Quality Act ("WQA"), NMSA 1978, §§ 74-6-1 to 74-6-17 (2009), and Section 301 of the *Guidelines for Water Quality Control Commission Regulation Hearings*, the Dairy Industry Group for a Clean Environment ("DIGCE") petitions the Commission to amend the Ground Water Protection – Supplemental Permitting Requirements for Dairy Facilities Regulations, 20.6.6 NMAC (Dairy Rule).

DIGCE represents a coalition of dairy industry representatives, including the Dairy Farmers of America, Dairy Producers of New Mexico, and various individual dairy producers, who comprise its Board of Directors. DIGCE participated as the party representing the dairy industry in the original rulemaking proceedings regarding the Dairy Rule and in proceedings held before the Commission in 2011 regarding amendments to the Dairy Rule.

The Dairy Rule was adopted by the Commission in December 2010 and published in the New Mexico Register on January 15, 2011. DIGCE filed an appeal of the rules in the Court of Appeals, and implementation of the Dairy Rule was postponed while the parties to the rulemaking engaged in settlement discussions. Those settlement discussions resulted in a set of

proposed amendments to the Dairy Rule which were adopted by the Commission in November 2011 and became effective on December 31, 2011

On September 4, 2012, DIGCE filed a petition to amend the Dairy Rule with respect to three particular topics: flow meter calibration, acceptable backflow prevention devices, and nutrient management plans. Written direct and rebuttal testimony has been filed by DIGCE and a group of parties who oppose the amendments, and these proposed rule amendments currently are set for hearing before the Commission on September 10, 2013. As discussed below, DIGCE is willing to have the hearing on the amendments proposed through the September 2012 Petition be consolidated for hearing with the amendments proposed with this Petition.

As discussed in more detail below, since DIGCE filed its September 2012 Petition, a large number of draft discharge permits under the Dairy Rules have been published for comment. According to the latest report from NMED to the Commission dated June 2013, 92 draft discharge permits were published between September 2012 and June 2013 of a total of 128 draft discharge permits published since the Dairy Rule came into effect. As of June 2013, 18 discharge permits had been issued as final permits. With regard to those final permits, variance petitions had been filed and acted upon for two dairies, and there were five pending variance petitions. There were two other pending variance petitions, one regarding a draft permit and another regarding a permit issued before the Dairy Rule was in effect.

One of the primary reasons for this Petition is to avoid an unintended consequence of the Dairy Rule for the majority of permits to require variances from the Commission. DIGCE has polled dairy permittees to determine how many additional variance petitions could be expected regarding the 128 draft discharge permits. The results indicate that over 100 variance petitions are likely. Based on discussions with producers and their consultants, one of the most common

reasons for variance petitions are that the prescriptive rule requirements regarding the number and locations of monitoring wells result in a very large and unreasonable number of monitoring wells. Additional variance petitions are anticipated to address prescriptive liner requirements. Variance petitions also are expected to address a wide variety of other Dairy Rule provisions. DIGCE believes that the Commission's action on this Petition could avert the need for many, if not the large majority, of the expected variance petitions by providing the Department with a reasoned range of discretion and flexibility to establish reasonable permit requirements that can be put in place without the need for variances.

II. SUMMARY OF PROPOSAL

Exhibit "A" to this Second Petition shows the amendments that DIGCE now proposes. In Exhibit "A," existing rule language proposed for deletion is shown by strikeout, and new language proposed to be included in an amended Dairy Rule is underlined. Exhibit "A" also shows the amendments proposed in DIGCE's September 2012 Petition, which DIGCE continues to support, although they are shown in Exhibit "A" for convenience only. The following list summarizes the proposed amendments:

1. Amend the definition of "impoundment," section 20.6.6.7.B(18) NMAC, to exclude structures used for solids settling.
2. Amend the engineering design requirements for solids separators, section 20.6.6.17.C(5) NMAC, eliminate the requirement to submit a design schematic for a separator not proposed by the applicant or permittee within 90 days of the effective date of the permit.
3. Amend the engineering design requirements for new or improved impoundments, to section 20.6.6.17.D(5), (6) and (7) NMAC, to replace the minimum requirement for a

- 60 mil synthetic liner with a requirement for a two-foot thick compacted soil liner with a maximum demonstrated permeability of 1×10^{-7} cm/sec.
4. Amend the requirements for manure solids separators to eliminate the requirement for existing dairies to install separators. Section 20.6.6.20.F NMAC.
 5. Amend the flow meter installation requirements, section 20.6.6.20.J NMAC, to eliminate the requirement for a “physical and permanent” label. Note: additional amendments to this subsection were proposed in the September 2012 Petition.
 6. Amend the flow metering methods requirements, section 20.6.6.20.K NMAC, to allow for a closed pipe totalizing flow meter in gravity flow situations and to allow the Department discretion to accept a proposal to meter flow by metering the water supply.
 7. Amend the impoundment capacity management requirements, section 20.6.6.21.A NMAC, and corresponding flow meter requirements, 20.6.6.21.G, to allow for a tank to store wastewater.
 8. Amend the requirement for fresh water to be used in a land application area, 20.6.6.21.C NMAC, to allow the Department discretion to accept a proposal for land application of wastewater in the absence of fresh water.
 9. Amend the requirements for crop removal methods, 20.6.6.21.J NMAC, to eliminate some of the prescriptive requirements for demonstrations of grazing as a crop removal method.
 10. Amend the requirement for Department approval of changes to crop removal methods, 20.6.6.21.K NMAC, by eliminating the requirement.

11. Amend the monitoring well location requirements, 20.6.6.23.A and .B NMAC, to reduce the prescriptive monitoring well location requirements requiring a well downgradient of each “source” and to eliminate other prescriptive requirements specifying the location and number of monitoring wells. Instead, require an appropriate monitoring well system for the dairy facility with a minimum of one upgradient and two downgradient wells. Provide for acceptance of the continued use of previously approved existing monitoring wells.
12. Amend the monitoring well identification tag requirements, 20.6.6.23.C NMAC to allow for printed adhesive or metal labels.
13. Amend the construction and completion requirements for monitoring wells, 20.6.6.23.D NMAC, to clarify they apply to new monitoring wells.
14. Amend the ground water sampling requirements, 20.6.6.23.H(3) NMAC, to allow the Department to extend the time for sample collection.
15. Amend the monitoring well inspection requirements, 20.6.6.23.M NMAC, to eliminate the provisions on performance of downhole inspections.
16. Amend the wastewater volume measurement and reporting requirements, 20.6.6.24.C NMAC to allow for monthly rather than weekly recording of flow meter readings.
17. Amend the stormwater sampling and reporting requirements, 20.6.6.24.D NMAC, to eliminate the need to sample stormwater if it will first be sent to a wastewater impoundment before land application.
18. Amend the sampling and reporting requirements for wastewater to be land applied, 20.6.6.25.C NMAC, to provide for annual, rather than quarterly sampling and to allow the Department to approve an alternative sampling method for good cause.

19. Amend the sampling requirements for irrigation wells, 20.6.6.25.E NMAC, to allow sampling from a group of wells rather than each individual well and for sampling once every five years rather than annually.
20. Amend the land application data sheet requirement, 20.6.6.25.G, to eliminate the requirement to repeat data from the previous six quarters.
21. Amend the soil sampling requirement, 20.6.6.25.K and .L, to eliminate the specified five month period for sample collection.
22. Amend the requirements for sampling of wastewater from an evaporative system, 20.6.6.26, to eliminate the requirement for collection of six-subsamples.
23. Amend the contingency requirements regarding exceedance of ground water standards, 20.6.6.27.A and .B, to reflect the proposed modified engineering design requirements for new liners and to consolidate similar sections.
24. Amend the monitoring well replacement contingency requirements, 20.6.6.27.C NMAC [proposed to change to .B], to allow the Department discretion to extend the time to install replacement wells for good cause shown.
25. Amend the contingency requirements for impoundments, 20.6.6.27.G NMAC [proposed to change to .F], to reflect changes to the monitoring well requirements.
26. Amend the requirements for permanent closure, 20.6.6.30.A NMAC, to clarify what monitoring wells have to be installed and to change triggering event for certain activities from the removal of all livestock to the cessation of regulated discharges.
27. Amend the closure requirements regarding discontinuing of ground water monitoring, 20.6.6.30.D and E NMAC, by eliminating these subsections.

III. STATEMENT OF REASONS & PROPOSED REGULATORY CHANGES

A copy of the proposed regulatory changes, indicating any language proposed to be added or deleted, is included as Attachment A. DIGCE requests that the Commission hear and adopt the regulatory changes identified in Attachment A for the reasons indicated below.

DIGCE's reasons for the regulatory changes in Attachment A will be more fully supported by testimony to be submitted as part of the hearing process.

The general reasons for the proposed regulatory changes are to address issues regarding permits proposed for issuance under the Dairy Rule which, if the Dairy Rule is not amended, likely would result in petitions for variances to be heard before the Commission regarding the majority of the pending permit actions, and would be unduly burdensome on dairy operators. Specific reasons for each proposed change are set forth below.

1. Amend the definition of "impoundment," section 20.6.6.7.B(18) NMAC, to exclude structures used for solids settling.

The Dairy Rule currently requires solids settling structures for dairies originally permitted under the Dairy Rule and the addition of solids settling structure for existing dairies already permitted. The Dairy Rule allows the dairy operator to choose the type of solids settling structure to be used. One approach to solids settling is to have a settling basin, which must be designed to allow for removal of solids. Solids removal generally is not feasible for synthetically-lined impoundments because of the high risk of tearing the liner. The definition in the Dairy Rule, however, can be read to treat certain solids settling structures as "impoundments" subject to the prescriptive liner requirements. This proposed rule amendments would clarify that solids settling structures are not "impoundments" and may be constructed in a manner appropriate for solids settling and removal.

- 2. Amend the engineering design requirements for solids separators, section 20.6.6.17.C(5) NMAC, eliminate the requirement to submit a design schematic for a separator not proposed by the applicant or permittee within 90 days of the effective date of the permit.**

The purpose of this amendment is to eliminate the requirement for an existing dairy operating under an existing discharge permit to be retrofitted with a solids separator. Most existing dairies do not have solids separators, but some dairies were originally designed and permitted without solids separators. Retrofitting an existing dairy to install a separate solids separator can be costly and impracticable, and these existing dairies already are functioning without the need for a separate solids separator.

- 3. Amend the engineering design requirements for new or improved impoundments, to section 20.6.6.17.D(5), (6) and (7) NMAC, to replace the minimum requirement for a 60 mil synthetic liner with a requirement for a two-foot thick compacted soil liner with a maximum demonstrated permeability of 1×10^{-7} cm/sec.**

The Dairy Rule currently requires a single 60 mil HDPE liner or an equivalent liner. The Commission adopted the single synthetic liner requirement as a compromise between a double synthetic liner system with leak collection, as originally proposed by the Department, and a compacted soil liner system as proposed by DIGCE. Further technical evaluation of the synthetic liner system prescribed by the current Dairy Rule indicates that the single synthetic liner system as prescribed in the Dairy Rule likely will not be as effective in preventing or reducing discharges to ground water as would a two foot thick compacted soil liner with a demonstrated permeability of 1×10^{-7} or less. As DIGCE's witnesses testified in the original Dairy Rule hearing, a compacted soil liner system has several other advantages over a synthetic liner system. A compacted soil liner system can be less costly than a synthetic liner system, but, depending upon the nature of the soils at the site, can be more costly in some instances. DIGCE

proposes this amendment based primarily on the superior expected performance of a compacted soil liner system compared to a single synthetic liner.

- 4. Amend the requirements for manure solids separators to eliminate the requirement for existing dairies to install separators. Section 20.6.6.20.F NMAC.**

See reasons for this amendment as discussed in item 2 above.

- 5. Amend the flow meter installation requirements, section 20.6.6.20.J NMAC, to eliminate the requirement for a “physical and permanent” label. Note: additional amendments to this subsection were proposed in the September 2012 Petition.**

While this is a relatively minor issue, DIGCE believes that the current requirement for an engraved metal label is overly prescriptive and unduly burdensome, so DIGCE proposes to allow for labeling that can be more easily accomplished.

- 6. Amend the flow metering methods requirements, section 20.6.6.20.K NMAC, to allow for a closed pipe totalizing flow meter in gravity flow situations and to allow the Department discretion to accept a proposal to meter flow by metering the water supply.**

The current Dairy Rule would not allow a closed pipe totalizing flow meter in gravity flow situations and can be read to mandate an open pipe weir device. The amendment would allow the use of a closed-pipe totalizing flow meter when practicable. The amendment also allows for the use of metering the water supply as an alternative to flow meters for wastewater. Flow meters on the water supply are easier to maintain and are more reliable, and methods are available to allow for relatively easy calculation of wastewater discharge rates based on water use rates.

- 7. Amend the impoundment capacity management requirements, section 20.6.6.21.A NMAC, and corresponding flow meter requirements, 20.6.6.21.G, to allow for a tank to store wastewater.**

A few dairies utilize tanks to store wastewater rather than impoundments, particularly for relatively low-volume wastewater discharges. Tanks generally provide superior containment to impoundments, and there is no reason to preclude the use of tanks or to require a variance to allow the use of a tank.

8. Amend the requirement for fresh water to be used in a land application area, 20.6.6.21.C NMAC, to allow the Department discretion to accept a proposal for land application of wastewater in the absence of fresh water.

A few dairies have been permitted to operate land application systems without concurrent use of fresh water for irrigation. These typically are very small dairies who have successfully demonstrated their ability to land-apply dairy wastewater while maintaining crops. This approach may actually reduce the likelihood of discharges to groundwater, as long as crops are maintained, because of the much lower total volume of water applied to the crops. This amendment would allow the Department to review and approve this approach without the need for a variance.

9. Amend the requirements for crop removal methods, 20.6.6.21.J NMAC, to eliminate the need for Department-approved demonstrations to allow for grazing as a crop removal method.

Grazing as a means of harvesting crops can be an efficient means of crop removal. The current Dairy Rule allows the Department to accept grazing as a crop removal method subject to a number of prescriptive requirements. The proposed amendment would keep the minimum data requirements needed to calculate nitrogen removal by crops grazing, but would eliminate the need for a technical proposal and demonstration requiring Department approval.

10. Amend the requirement for Department approval of changes to crop removal methods, 20.6.6.21.K NMAC, by eliminating the requirement.

Changes to crop removal methods can be dictating by weather, the success of a particular crop in a particular season or year, and crops prices. For example, a farmer may plant a crop

with the intention of mechanical harvesting to produce grain, but failure of a crop due to hail or lack of precipitation can result in the need to change to a different crop and different crop removal method, such as harvesting for forage rather than grain or grazing rather than mechanical harvesting. These changes occur during the course of a growing season and are dictated by events outside the farmer's control, and it is not practicable to obtain Department approval for these changes. The potential for change can be accounted for in a nutrient management plan, with a simple switch to a different data collection and accounting method when crop removal methods change.

- 11. Amend the monitoring well location requirements, 20.6.6.23.A and .B NMAC, to reduce the prescriptive monitoring well location requirements requiring a well downgradient of each "source" and to eliminate other prescriptive requirements specifying the location and number of monitoring wells. Instead, require an appropriate monitoring well system for the dairy facility with a minimum of one upgradient and two downgradient wells. Provide for acceptance of the continued use of previously approved existing monitoring wells.**

The prescriptive requirements for monitoring well locations and numbers is the most common Dairy Rule requirement that will cause permittees to seek variances. The prescriptive requirements for monitoring well locations in the Dairy Rule can arbitrarily require replacement of existing monitoring wells for slight changes in location. They can require replacement of a monitoring well system previously approved by the Department that is functioning properly to monitor groundwater based on a site-specific conditions. The prescriptive requirements specify the location of monitoring wells without considering site-specific conditions in locations that could cause a monitoring well itself to be a conduit for contamination, such as placement in a playa lake bed or in a heavily-used area where a well is susceptible to damage. These requirements to not allow for experts to consider site specific conditions, such as surface topography, hydrology and geology in considering how to properly design an effective

monitoring well system. The prescriptive requirements do not take into account U.S. Environmental Protection Agency guidance on how to properly design a monitoring well system. The prescriptive requirements would require hundreds, perhaps over a thousand, new monitoring wells for dairies at great cost, and there is not sufficient drilling capacity to construct the required number of wells, even if it were reasonable and necessary to install all of these wells.

The proposed amendment would return the approach to developing appropriate monitoring well systems similar to the general Commission discharge permit regulations, where a monitoring well system would be designed for an entire facility, not individual sources, and the number and locations of wells would be considered based upon site-specific conditions. The consideration of professional interpretations and opinions based upon site-specific conditions is accomplished for facilities by the retention of subsection N of the current Dairy Rule, which provides for dispute resolution to consider differences in professional opinions and to provide a forum for resolution of disputes without resort to appeals to the Commission.

12. Amend the monitoring well identification tag requirements, 20.6.6.23.C NMAC to allow for printed adhesive or metal labels.

This is a minor change similar to item 5 to eliminate overly prescriptive requirements for labeling.

13. Amend the construction and completion requirements for monitoring wells, 20.6.6.23.D NMAC, to clarify they apply to new monitoring wells.

The Dairy Rule contains prescriptive design requirements for monitoring wells. DIGCE's proposed amendments would retain these requirements as is for new monitoring wells, but would clarify that they do not apply to existing monitoring wells previously approved for use

by the Department. This will allow for continued use of existing, previously approved and functioning monitoring wells.

14. Amend the ground water sampling requirements, 20.6.6.23.H(3) NMAC, to allow the Department to extend the time for sample collection.

This is a simple amendment allowing the Department to approve an extension of time to collect samples from newly-installed monitoring wells. An extension may be appropriate for a number of reasons, including the status of the dairy facility, issues with well development, and other limitations on sampling within the specified time frame.

15. Amend the monitoring well inspection requirements, 20.6.6.23.M NMAC, to eliminate the provisions on performance of downhole inspections.

This change corresponds to the change in item 13. Downhole inspections are costly, disruptive, and pose a risk of damage a monitoring well. DIGCE contends they are rarely needed, and are likely unnecessary if the Commission clarifies that the new well construction requirements do not apply retroactively to existing monitoring wells.

16. Amend the wastewater volume measurement and reporting requirements, 20.6.6.24.C NMAC to allow for monthly rather than weekly recording of flow meter readings.

The frequency of flow meter readings is not of high importance. It is easy to calculate daily discharge volumes regardless of the frequency of meter readings by simple arithmetic. Flow meter readings typically are taken by consultants to ensure proper recording of data, and a weekly meter reading requirement can require excessive consultant visits at considerable cost. Monthly readings were allowed in the past and are reasonable going forward.

17. Amend the stormwater sampling and reporting requirements, 20.6.6.24.D NMAC, to eliminate the need to sample stormwater if it will first be sent to a wastewater impoundment before land application.

When stormwater is sent for land application, it is simpler for purposes of nutrient management plans and data management and calculations to measure nutrient values for the combination wastewater and stormwater sent to a common pond. Separate measurements for stormwater impoundments can require considerable additional sampling and data handling and management with no benefit to nutrient management planning or groundwater protection.

18. Amend the sampling and reporting requirements for wastewater to be land applied, 20.6.6.25.C NMAC, to provide for annual, rather than quarterly sampling and to allow the Department to approve an alternative sampling method for good cause.

Frequent sampling of wastewater ponds can be dangerous to samplers attempting to obtain multiple samples from a wastewater pond. Annual sampling is believed to be of sufficient frequency to provide reasonably accurate data for use in nutrient management planning and would reduce the potential danger to samplers and the cost of sampling and data management.

19. Amend the sampling requirements for irrigation wells, 20.6.6.25.E NMAC, to allow sampling from a group of wells rather than each individual well and for sampling once every five years rather than annually.

Sampling individual irrigation wells to provide data on nitrogen levels for use in nutrient management planning is not necessarily representative of the quality of water applied for irrigation when multiple wells are used at the same time to supply an irrigation system. This amendment would simplify and reduce sampling and data management requirements while still providing reasonably accurate data.

20. Amend the land application data sheet requirement, 20.6.6.25.G, to eliminate the requirement to repeat data from the previous six quarters.

The current Dairy Rule requirement is to repeat land application data from the previous six quarters in a land application data sheet. Previous data will be available from previously submitted land application data sheets, and repeating the submission of data will increase paperwork and the potential for errors.

21. Amend the soil sampling requirement, 20.6.6.25.K and .L, to eliminate the specified five month period for sample collection.

It is not always practical or optimal to collect soil samples within the specified period due to changes in crop rotation, weather, and other factors. Soil collection can be addressed as specified in a nutrient management plan based upon individual farm and site circumstances as appropriate. The current rule is overly prescriptive.

22. Amend the requirements for sampling of wastewater from an evaporative system, 20.6.6.26, to eliminate the requirement for collection of six-subsamples.

Data from the sampling of wastewater in an evaporative system is of limited use, since it need not be used for nutrient management planning. Taking six subsamples from an evaporative pond is not necessary and simply adds to the danger of sample collection for samplers and the cost of data collection and management.

23. Amend the contingency requirements regarding exceedance of ground water standards, 20.6.6.27.A and .B, to reflect the proposed modified engineering design requirements for new liners and to consolidate similar sections.

The current Dairy Rule has a complex set of contingency requirements that vary based upon slightly different liner types. This approach is unnecessarily complex and there is less need

for such an approach if the Commission adopts the changes to standard wastewater impoundment liner design requirements as proposed above.

24. Amend the monitoring well replacement contingency requirements, 20.6.6.27.C NMAC [proposed to change to .B], to allow the Department discretion to extend the time to install replacement wells for good cause shown.

As discussed above, there are substantial constraints on available capacity to install monitoring wells given the large number of dairy permits that may require new wells and the large number of wells. Consequently, there is a serious question whether it is possible for dairies to meet the deadlines for installation of new wells. This change would give the Department discretion to grant an extension for good cause.

25. Amend the contingency requirements for impoundments, 20.6.6.27.G NMAC [proposed to change to .F], to reflect changes to the monitoring well requirements.

This proposed change reflects the proposed changes to reduce the prescriptive monitoring well requirements that currently require a downgradient monitoring well for each potential “source.”

26. Amend the requirements for permanent closure, 20.6.6.30.A NMAC, to clarify what monitoring wells have to be installed and to change triggering event for certain activities from the removal of all livestock to the cessation of regulated discharges.

The prescriptive monitoring well requirements have unduly burdened the number of dairies that are being closed due to economic constraints to the industry. These proposed changes generally correspond to the reduction in prescriptive requirements for installation of new monitoring wells under the Dairy Rules and will facilitate closure of existing dairies. Dairies

that are closing also may be used for other purposes, such as feeding heifers or beef cattle, from which discharges are not regulated. Part of this amendment changes the timing of certain closure activities so they occur sooner, on cessation of regulated dairy discharges, rather than waiting if the dairy has been put to another productive use.

27. Amend the closure requirements regarding discontinuing of ground water monitoring, 20.6.6.30.D and E NMAC, by eliminating these subsections.

This proposed amendment is intended to reduce overly prescriptive requirements regarding cessation of groundwater monitoring following closure. It is intended to facilitate closeout of permits for closed dairies by providing additional flexibility for cessation of monitoring when it is no longer necessary.

IV. REQUEST FOR HEARING

Petitioner requests that the Commission schedule a rulemaking hearing to consider these proposed amendments as soon as possible and that the Commission appoint a hearing officer to conduct this rulemaking hearing. Upon appointment of a hearing officer, DIGCE requests the Commission grant the hearing officer authority to set a schedule for submission of written direct testimony and responses prior to the hearing. It is anticipated that the rulemaking hearing will take approximately five days. DIGCE reserves the right to supplement the statement of reasons with additional reasons in support of the proposed regulatory changes and to change the language set forth in Attachment A.

A hearing already is scheduled to take place at the Commission's September 2013 meeting regarding the Petition filed in September 2012. Petitioner would agree to the consolidation of this Second Petition with the September 2012 Petition for hearing, allowing the Commission to hold one hearing covering both Petitions.

In order to avoid the need for dairies that currently have permit deadlines to take actions that would be affected by the proposed rule amendments, Petitioner has requested that the Department suspend enforcement of deadlines for actions that may be affected by the proposed rule amendments pending the Commission's consideration of this Petition. Suspension of enforcement pending the Commission's consideration of this Petition also will avoid the potential need for permittees to request variances from these requirements pending the Commission's consideration of the rule amendments, saving substantial commitments of resources by permittees, the Department and the Commission.

In addition, if amendments can be considered and adopted while the majority of the permits remain in draft form, any Dairy Rule amendments adopted by the Commission can be addressed by changes to the draft permits, reducing the need for permit modification proceedings should the Dairy Rule amendments not be adopted until after many additional final permits are issued. That will conserve resources for both the Department and permittees.

For the foregoing reasons, DIGCE respectfully requests that the Commission set a hearing on the amendments proposed in this Second Petition.

Respectfully submitted,

DAIRY INDUSTRY GROUP FOR A CLEAN
ENVIRONMENT, INC.



Dalva L. Mochlenberg, Esq.
Anthony (T.J.) J. Trujillo, Esq.
Gallagher & Kennedy, P.A.
1233 Paseo de Peralta
Santa Fe, New Mexico 87501
Phone: (505) 982-9523
Fax: (505) 983-8160
DLM@gknet.com
AJT@gknet.com

CERTIFICATE OF SERVICE

I hereby certify that a copy of this Petition to Amend 20.6.6 NMAC (Dairy Rule) and Request for Hearing was served via email and regular U.S. mail on the following parties this Monday, August 05, 2013:

Felicia Orth
Acting Board Administrator
NMED Boards and Commissions
1190 St. Francis Dr., N2153
Santa Fe, NM 87502
Felicia.Orth@state.nm.us

Jeff Kendall
General Counsel
Office of General Counsel
New Mexico Environment Department
1190 St. Francis Drive
Santa Fe, NM 87502
jeff.kendall@state.nm.us

Jonathan Block, Staff Attorney
New Mexico Environmental Law Center
1405 Luisa St. #5
Santa Fe, NM 87505
Jblock@nmelc.org



Anthony (T.J.) J. Trujillo, Esq.

ATTACHMENT A TO DIGCE'S SECOND PETITION TO AMEND DAIRY RULE



PROPOSED DAIRY RULE AMENDMENTS

KEY: Proposed elimination of language in current Dairy Rule shown by ~~strikeout~~.
Proposed new language to be inserted in current Dairy Rule shown by underline.
New language~~stricken language~~ = change proposed in DIGCE petition filed September 2012, not included in this Petition but included for convenience.

TITLE 20 ENVIRONMENTAL PROTECTION
CHAPTER 6 WATER QUALITY
PART 6 GROUND WATER PROTECTION - SUPPLEMENTAL PERMITTING REQUIREMENTS FOR DAIRY FACILITIES

20.6.6.1 ISSUING AGENCY: Water Quality Control Commission.
[20.6.6.1 NMAC - N, 01/31/2011]

20.6.6.2 SCOPE: All persons subject to the Water Quality Act, NMSA 1978, Sections 74-6-1 et seq and specifically to dairy facilities and their operations.
[20.6.6.2 NMAC - N, 01/31/2011]

20.6.6.3 STATUTORY AUTHORITY: Standards and regulations are adopted by the commission under the authority of the Water Quality Act, NMSA 1978, Sections 74-6-1 through 74-6-17.
[20.6.6.3 NMAC - N, 01/31/2011]

20.6.6.4 DURATION: Permanent.
[20.6.6.4 NMAC - N, 01/31/2011]

20.6.6.5 EFFECTIVE DATE: 01/31/2011, unless a later date is cited at the end of a section.
[20.6.6.5 NMAC - N, 01/31/2011]

20.6.6.6 OBJECTIVE: The purpose of 20.6.6 NMAC is to supplement the general permitting requirements of 20.6.2.3000 through 20.6.2.3114 NMAC to control discharges specific to dairy facilities and their operations.
[20.6.6.6 NMAC - N, 01/31/2011]

20.6.6.7 DEFINITIONS:

A. Terms defined in the Water Quality Act and 20.6.2.7 NMAC shall have the meanings as given in such.

B. As used in 20.6.6 NMAC, but not in other sections of 20.6.2 NMAC, a term defined in this part shall have the following meaning.

- (1) "Adjacent" means lying near, but lacking actual contact along a boundary or at a point.
- (2) "Applicant" means the person applying for a new, renewed or modified discharge permit.
- (3) "Construction quality assurance" or "CQA" means a planned system of activities necessary to ensure that standards and procedures are adhered to and that construction and installation meet design criteria, plans and specifications. A CQA includes inspections, verifications, audits, evaluations of material and workmanship necessary to determine and document the quality of the constructed impoundment or structure, and corrective actions when necessary.

- (4) "Construction quality control" or "CQC" means a planned system of operational techniques and activities used to preserve the quality of materials and ensure construction to specifications. Elements of a CQC include inspections, testing, data collection, data analysis and appropriate corrective actions.
- (5) "Contiguous" means being in actual contact along a boundary or at a point.
- (6) "CQA/CQC Report" means a report that summarizes all inspection, testing, data collection, data analysis and any corrective actions completed as part of CQA or CQC for a project.
- (7) "Dairy facility" means the production area and the land application area, where the discharge and associated activities will or do take place.
- (8) "Dairy rule" means 20.6.6 NMAC, as amended.
- (9) "Date of postal notice" means the date when the United States postal service (USPS) first makes notice to the applicant or permittee of its possession of certified mail addressed to the applicant or permittee.
- (10) "Discharge volume" means the measured daily volume of wastewater actually discharged within the production area. This definition does not include the volume of wastewater discharged to the land application area.
- (11) "EPA" means the United States environmental protection agency.
- (12) "Existing dairy facility" means a dairy facility that is currently discharging, or has previously discharged and has not been issued a notice from the department verifying that closure and post-closure monitoring activities have been completed.
- (13) "Existing impoundment" means an impoundment that is currently receiving or has ever received wastewater or collected stormwater and that has not been closed pursuant to a discharge permit.
- (14) "Expiration" means the date upon which the term of a discharge permit ends.
- (15) "Field" means a unit of irrigated cropland within the land application area cultivated in the same manner to grow a specific crop for the uptake and removal of nutrients.
- (16) "Flow meter" means a device used to measure the volume of water, wastewater or stormwater that passes a particular reference section in a unit of time.
- (17) "Freeboard" means the vertical distance between the elevation at the lowest point of the top inside edge of the impoundment and the design high water elevation of the water level in the impoundment.
- (18) "Impoundment" means any structure designed and used for storage or disposal by evaporation of wastewater, stormwater, or a combination of both wastewater and stormwater, ~~or used for solids settling~~. A multiple-cell impoundment system having at least one shared berm or barrier whose smallest cells have a cumulative constructed capacity of 10 percent or less of the constructed capacity of the largest cell shall be considered a single impoundment for the purposes of the dairy rule. A wastewater or stormwater transfer sump or a solids settling separator is not an impoundment.
- (19) "Land application area" means irrigated and cultivated fields collectively authorized by a discharge permit to receive wastewater or stormwater applications as a source of nutrients managed for crop production.
- (20) "Land application data sheet" means a form used to report all nitrogen inputs applied to each field within the land application area, including the cropping status of the field at the time of application (i.e., fallow, corn, wheat, etc.).
- (21) "Manure" means an agricultural waste composed of excreta of animals, and residual bedding materials, waste feed or other materials that have contacted excreta from such animals.
- (22) "Maximum daily discharge volume" means the total daily volume of wastewater (expressed in gallons per day) authorized for discharge by a discharge permit. This definition does not include the volume of wastewater discharged to the land application area.
- (23) "New dairy facility" means a dairy facility that has never before discharged wastewater.
- (24) "Permittee" means a person who is issued or receives by transfer a discharge permit for a dairy facility or, in the absence of a discharge permit, a person who makes or controls a discharge at a dairy facility.
- (25) "Production area" means that part of the animal feeding operation that includes the following: the animal confinement areas; the manure, residual solids and compost storage areas; the raw materials storage areas; and the wastewater and stormwater containment areas. The animal confinement areas include but are not limited to open lots, housed lots, feedlots, confinement barns, stall barns, free stall barns, milkrooms, milk centers, cowyards, barnyards, hospital pens and barns, and animal walkways. The manure, residual solids and compost storage areas include, but are not limited to, storage sheds, stockpiles, static piles, and composting piles. The raw materials storage areas include, but are not limited, to feed silos, silage storage areas, feed storage barns, and liquid feed tanks. The wastewater and stormwater containment areas include, but are not limited to, settling separators,

impoundments, sumps, runoff drainage channels, and areas within berms and diversions which prohibit uncontaminated stormwater from coming into contact with contaminants.

(26) "Spillway" means a structure used for controlled releases from an impoundment designed to receive stormwater, in a manner that protects the structural integrity of the impoundment.

(27) "Stormwater" means direct precipitation and runoff that comes into contact with water contaminants within the production area of a dairy facility.

(28) "Unauthorized discharge" means a release of wastewater, stormwater or other substances containing water contaminants not approved by a discharge permit.

(29) "Wastewater" means water, that has come into contact with water contaminants as a result of being directly or indirectly used in the operations of a dairy facility including, but not limited to, the following: washing, cleaning, or flushing barns or other roof-covered production areas; washing of animals; spray-cooling of animals (except in open lots); and cooling or cleaning of feed mills and equipment. Wastewater does not include overflow from the drinking water system or stormwater unless overflow or stormwater that is collected is comingled with wastewater, or it comes into contact with water contaminants as a result of being directly or indirectly used in dairy facility operations.

[20.6.6.7 NMAC - N, 01/31/2011]

20.6.6.8 REQUIREMENTS FOR DISCHARGING FROM DAIRY FACILITIES:

A. No person shall discharge from a dairy facility without a discharge permit. A person intending to discharge from a dairy facility shall submit an application for a discharge permit pursuant to 20.6.6.10 NMAC and remit fees pursuant to 20.6.6.9 NMAC.

B. Permittees, owners of record of a dairy facility and holders of an expired permit are responsible for complying with the dairy rule.

C. Unless otherwise noted in 20.6.6 NMAC, the requirements of 20.6.2.3101 through 20.6.2.3114 NMAC apply to a dairy facility.

D. Complying with the requirements of 20.6.6 NMAC does not relieve a dairy facility's owner, operator or permittee from complying with the requirements of other applicable local, state and federal regulations or laws.

[20.6.6.8 NMAC - N, 01/31/2011]

20.6.6.9 FEES: In lieu of paying fees under the requirements of 20.6.2.3114 NMAC, an applicant or permittee shall pay fees to the department pursuant to this section.

A. An applicant for a discharge permit or a discharge permit renewal for a dairy facility shall remit with the application to the department a filing fee in the amount of one hundred dollars (\$100) and one-half of the applicable permit fee from table 1 of 20.6.2.3114 NMAC. The filing fee and the permit fee payment remitted with the application are not refundable and may not be applied toward future discharge permit applications. If the department issues a discharge permit, the permittee shall remit a permit fee payment equal to one-tenth of the applicable permit fee from table 1 of 20.6.2.3114 NMAC on the first occurrence of August 1 after the effective date of the discharge permit, and annually thereafter until the expiration or termination of the discharge permit.

B. An applicant for a discharge permit modification separate from a discharge permit renewal shall remit a filing fee of one hundred dollars (\$100) and a permit modification fee with the application. The permit modification fee shall be equal to one-half of the applicable permit fee from table 1 of 20.6.2.3114 NMAC. The filing fee and the permit modification fee payment remitted with the application are not refundable and may not be applied toward future discharge permit applications. Payment of the permit modification fee shall not relieve a permittee from remitting the permit fee payments required by Subsection A of this section. If the discharge permit modification is required by the secretary outside the context of an enforcement action, a permit modification fee is not required.

C. A permittee requesting temporary permission to discharge pursuant to Subsection B of 20.6.2.3106 NMAC shall pay the fee specified in 20.6.2.3114 NMAC.

[20.6.6.9 NMAC - N, 01/31/2011]

20.6.6.10 GENERAL APPLICATION REQUIREMENTS FOR ALL DAIRY FACILITIES: This section specifies the general requirements for discharge permit applications for all types of dairy facilities.

A. In lieu of Subsection F of 20.6.2.3106 NMAC, a permittee shall submit an application for renewal of a discharge permit for a dairy facility to the department at least one year before the discharge permit expiration date, unless closure of the facility is approved by the department before that date. At least 180 days before the due

date for an application for renewal, a permittee may request a pre-application meeting with the department. The pre-application meeting shall be held in Santa Fe, unless otherwise agreed by the department. Requests shall be made in writing and submitted to the department by certified mail. If a permittee requests a pre-application meeting, the department shall contact the permittee to discuss and schedule a date for the pre-application meeting. The department shall respond to the permittee's request in writing by certified mail to confirm the pre-application meeting date. The pre-application meeting shall occur no less than 60 days before the application due date. If the permittee or his representative fails to participate in the scheduled pre-application meeting, the permittee forfeits the opportunity for a pre-application meeting.

B. For a dairy facility that has not been constructed or operated, a permittee shall submit to the department at least one year before the discharge permit expiration date an application for renewal pursuant to Subsection A of this section or a statement certifying that the dairy facility has not been and will not be constructed or operated and that no discharges have occurred or will occur. Upon the department's verification of the certification, the department shall terminate the discharge permit, if necessary, and retire the discharge permit number from use.

C. Instead of the information required by Subsection C of 20.6.2.3106 NMAC, an applicant:

(1) for a new discharge permit, shall provide the information and supporting technical documentation pursuant to this section and 20.6.6.11 NMAC;

(2) for a renewed or modified discharge permit, shall provide the information and supporting technical documentation pursuant to this section and 20.6.6.12 NMAC; or

(3) for a renewed discharge permit for closure, shall provide the information and supporting technical documentation pursuant to this section and 20.6.6.13 NMAC.

D. The department shall create a discharge permit application form for dairy facilities applying for a new discharge permit, for dairy facilities applying for a renewed, modified or renewed and modified discharge permit, and for dairy facilities applying for a discharge permit for closure to collect the information required by this section. The information requested on the form(s) shall be limited to the information required by this section. An applicant shall use the department's form to provide the information required by this section. An application shall consist of the appropriate form and required supporting documentation, regardless of previous submissions. The applicant shall attest to the truth of the information and supporting documentation in the application, and sign the form. The form shall be signed in the presence of a notary and notarized. The applicant shall provide to the department a hard copy (paper format) of the original signed and notarized completed application form and all supporting documentation. The applicant shall also provide an electronic copy of the original signed and notarized application and all supporting documentation in portable document format (PDF) on a compact disc (CD) or digital versatile disc (DVD).

E. If an applicant filing an application for a new discharge permit does not certify that the dairy facility complies with the setback requirements of 20.6.6.16 NMAC, as required by Subsection D of 20.6.6.11 NMAC, the department shall reject the application. The department shall provide notice of the rejection to the applicant by certified mail.

F. Within 60 days of the department's receipt of proof of notice pursuant to Subsection D of 20.6.2.3108 NMAC, the department shall review the application for technical completeness. If proof of notice is not submitted to the department pursuant to Subsection D of 20.6.2.3108 NMAC, the department shall notify the applicant by certified mail of the violation and provide 15 days from the date of postal notice for the applicant to submit the proof pursuant to Subsection D of 20.6.2.3108 NMAC. If proof of notice is not submitted to the department following the issuance of a notice of violation, the department may deny the application.

G. For an application to be deemed technically complete, an application shall include the information required by Subsection C of this section. Submittals or supporting documentation that require the certification of persons specified in the dairy rule are deemed technically complete if the documentation is prepared in accordance with the dairy rule and is certified by persons specified in the dairy rule. If the department determines that an application is not technically complete, the department shall provide notice of technical deficiency to the applicant by certified mail within 60 days of receipt of the applicant's proof of notice. The applicant shall have 60 days from the date of postal notice of the technical deficiency correspondence to provide the information required by this section.

(1) If an application is technically complete, the department shall make available a proposed approval of a discharge permit (i.e., draft discharge permit) or denial of a discharge permit application, pursuant to Subsection H of 20.6.2.3108 NMAC.

(2) If an applicant filing an application for a new discharge permit does not provide all information required by this section to the department within 60 days of the date of postal notice of the technical deficiency

correspondence, the department shall deny the application. The department shall provide notice of denial to the applicant by certified mail.

(3) If an applicant for a renewed or modified discharge permit does not provide all information required by this section to the department within 60 days of the date of postal notice of the technical deficiency correspondence, the department may deny the application or may propose a discharge permit for approval consistent with the requirements of the dairy rule. If the department denies the application, the department shall provide notice of denial to the applicant by certified mail.

H. The department may impose additional conditions on a discharge permit in accordance with Section 74-6-5 NMSA 1978. If the department proposes an additional condition in a discharge permit that is not included in the dairy rule, the department shall include a written explanation of the reason for the additional condition with the copy of the proposed approval sent to the applicant pursuant to Subsection H of 20.6.2.3108 NMAC. Written comments about the additional condition may be submitted to the department during the 30-day comment period provided by Subsection K of 20.6.2.3108 NMAC. A hearing may be requested about the additional condition as provided by 20.6.6.15 NMAC.

I. The secretary shall approve a discharge permit provided that it poses neither a hazard to public health nor undue risk to property, and:

- (1) the requirements of the dairy rule are met;
 - (2) the provisions of 20.6.2.3109 NMAC are met, with the exception of Subsection C of 20.6.2.3109 NMAC; and
 - (3) denial of an application for a discharge permit is not required pursuant to Subsection E of 74-6-5 NMSA 1978.
- [20.6.6.10 NMAC - N, 01/31/2011]

20.6.6.11 APPLICATION REQUIREMENTS FOR NEW DISCHARGE PERMITS:

A. An application for a new discharge permit shall include the information in this section.

B. Contact information. An application shall include:

- (1) applicant's name, title and affiliation with the dairy facility, mailing address, and phone number;
- (2) dairy facility manager's or operator's name, title and affiliation with the dairy facility, mailing address and phone number;
- (3) application preparer's name, title and affiliation with the dairy facility, mailing address, phone number and signature; and
- (4) mailing address and phone number of any consultants authorized to assist the dairy facility with compliance with the Water Quality Act and 20.6.2 and 20.6.6 NMAC.

C. Ownership and real property agreements.

(1) An application shall include the dairy facility owner's name, title, mailing address and phone number.

(a) If more than one person has an ownership interest in the dairy facility or a partnership exists, then the applicant shall list all persons having an ownership interest in the dairy facility, including their names, titles, mailing addresses and phone numbers.

(b) If any corporate entity, including but not limited to a corporation or a limited liability company, holds an ownership interest in the dairy facility, then the applicant shall also list the name(s), as filed with the New Mexico public regulation commission, of the corporate entity, and the corporate entity's registered agent's name and address.

(2) If the applicant is not the owner of record of the real property upon which the dairy facility is or will be situated, or upon which dairy operations and land application will occur, then the applicant shall submit a copy of any lease agreement or other agreement which authorizes the use of the real property for the duration of the term of the requested permit. Lease prices or other price terms may be redacted.

D. Setbacks. The applicant shall certify that the setback requirements of 20.6.6.16 NMAC are met. An application shall include a scaled map of the dairy facility layout demonstrating that the proposed layout of the dairy facility meets the setback requirements of 20.6.6.16 NMAC.

E. Dairy facility information and location. An application shall include:

- (1) the dairy facility name, physical address and county; and
- (2) the township, range and section for the entire dairy facility, which includes the production area and fields within the land application area.

F. Public notice preparation. An application shall include the name of a newspaper of general circulation in the location of the dairy facility for the future display advertisement publication, the proposed public

location(s) for posting of the 2-foot by 3-foot sign, and the proposed off-site public location for posting of the 8.5-inch by 11-inch flyer, as required by 20.6.2.3108 NMAC.

G. Pre-discharge total dissolved solids concentration in ground water. Pursuant to Paragraph (3) of Subsection C of 20.6.2.3106 NMAC, an application shall include the pre-discharge total dissolved solids concentration from analytical results of ground water obtained from the on-site test boring pursuant to Subsection X of 20.6.6.20 NMAC, if applicable, or from the nearest well within a one-mile radius of the dairy facility. A copy of the laboratory analysis stating the pre-discharge total dissolved solids concentration shall be submitted with the application.

H. Determination of maximum daily discharge volume. An application shall include the following information.

(1) The proposed maximum daily discharge volume and a description of the methods and calculations used to determine that volume.

(2) The identification of all sources of wastewater which may include, but are not limited to, hospital barns, maternity barns, bottle-washing operations and parlor/equipment washdown.

(3) The animal washing method(s) employed and the estimated daily wastewater volume generated by the method(s).

(4) Information regarding other wastewater discharges (i.e., domestic or industrial) at the dairy facility not generated by dairy operations. Permit identification numbers shall be submitted for those discharges that are already permitted.

I. Wastewater quality. An application shall include estimated concentrations of wastewater quality for total dissolved solids, chloride, total sulfur, nitrate as nitrogen, and total Kjeldahl nitrogen.

J. Identification and physical description of the dairy facility. An application shall include the following information.

(1) A scaled map of the entire dairy facility pursuant to Subsection U of 20.6.6.20 NMAC.

(2) The identification of each proposed impoundment, including information about its location, purpose (i.e., to store wastewater or stormwater, or dispose of it by evaporation), liner material and storage or evaporative disposal capacity.

(3) The identification of each field within the proposed land application area, including information about its location, acreage, proposed method of wastewater and stormwater application and proposed method of irrigation water application.

(4) The identification of proposed sumps and mix tanks, including information for each component regarding its location, purpose, construction material, dimensions and capacity.

(5) A description of the proposed method(s) employed to protect each area from stormwater runoff and run-on, and to minimize leachate.

K. Flow metering. An application shall describe a dairy facility's flow metering system pursuant to Subsections J, K, L, M, N and O of 20.6.6.20 NMAC and Subsections G and H of 20.6.6.21 NMAC, including:

(1) the identification of the method(s) (i.e., pumped versus gravity flow) of wastewater discharge, stormwater transfer, and wastewater and stormwater land application;

(2) the proposed flow measurement devices for each flow method; and

(3) the identification of flow meter locations.

L. Depth-to-most-shallow ground water and ground water flow direction. An application shall include the following information.

(1) The depth-to-most-shallow ground water pursuant to Subsection X of 20.6.6.20 NMAC.

(2) The ground water flow direction of the most-shallow ground water beneath the dairy facility based on the most recent regional water level data or published hydrogeologic information. Survey data from nearby monitoring wells and a ground water elevation contour map indicating the direction of ground water flow may be included. The sources of all information used to determine ground water flow direction shall be provided with the application.

M. Monitoring wells. An application shall include the proposed monitoring well locations pursuant to Subsections A and B of 20.6.6.23 NMAC.

N. Surface soil survey and vadose zone geology. An application shall include:

(1) the most recent regional soil survey map and associated descriptions identifying surface soil type(s); and

(2) if applicable, the lithologic log obtained from the on-site test boring pursuant to Subsection X of 20.6.6.20 NMAC to identify the geological profile of the vadose zone.

O. Location map. An application shall include a location map with topographic surface contours identifying all of the following features located within a one-mile radius of the dairy facility:

- (1) watercourses, lakebeds, sinkholes, playa lakes and springs (springs used to provide water for human consumption shall be so denoted);
- (2) wells supplying water for a public water system and private domestic water wells;
- (3) irrigation supply wells; and
- (4) ditch irrigations systems, acequias, irrigation canals and drains.

P. Flood zone map. An application shall include the most recent 100-year flood zone map developed by the federal emergency management administration, FEMA, documenting flood potential for the dairy facility, and a description of any engineered measures used for flood protection.

Q. Engineering and surveying. Pursuant to 20.6.6.17 NMAC an application shall include:

- (1) plans and specifications for impoundments and associated liners;
- (2) plans and specifications for a manure solids separator(s); and
- (3) a grading and drainage report and plan.

R. Land application area. For a dairy facility with a land application area, an application shall include the following information.

- (1) A nutrient management plan (NMP) pursuant to Subsections I and J of 20.6.6.21 NMAC.
- (2) A written description of the wastewater sampling location(s) pursuant to Subsection C of 20.6.6.25 NMAC.

[20.6.6.11 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.12 APPLICATION REQUIREMENTS FOR DISCHARGE PERMIT RENEWAL OR MODIFICATION:

A. An application for a renewed or modified discharge permit shall include the information in this section.

B. Contact information. An application shall include the:

- (1) applicant's name, title and affiliation with the dairy facility, mailing address, and phone number;
- (2) dairy facility manager's or operator's name, title and affiliation with the dairy facility, mailing address and phone number;
- (3) application preparer's name, title and affiliation with the dairy facility, mailing address, phone number and signature; and
- (4) mailing address and phone number of any consultants authorized to assist the dairy facility with compliance with the Water Quality Act and 20.6.2 and 20.6.6 NMAC.

C. Ownership and real property agreements.

(1) An application shall include the dairy facility owner's name, title, mailing address and phone number.

(a) If more than one person has an ownership interest in the dairy facility or a partnership exists, then the applicant shall list all persons having an ownership interest in the dairy facility, including their names, titles, mailing addresses and phone numbers.

(b) If any corporate entity, including but not limited to a corporation or a limited liability company, holds an ownership interest in the dairy facility, then the applicant shall also list the name(s), as filed with the New Mexico public regulation commission, of the corporate entity and the corporate entity's registered agent's name and address.

(2) If the applicant is not the owner of record of the real property upon which the dairy facility is or will be situated, or upon which dairy operations and land application will occur, then the applicant shall submit a copy of any lease agreement or other agreement which authorizes the use of the real property for the duration of the term of the requested permit. Lease prices or other price terms may be redacted.

D. Dairy facility information and location. An application shall include:

- (1) the dairy facility name, physical address and county;
- (2) the discharge permit identification number as designated on the most recent discharge permit for the dairy facility;
- (3) the township, range and section for the entire dairy facility, which includes the production area and fields within the land application area; and
- (4) the date of initial discharge at the dairy facility.

E. Public notice preparation.

(1) An application for a modified or renewed and modified discharge permit shall include the name of a newspaper of general circulation in the location of the dairy facility for the future display advertisement publication, the proposed public location(s) for posting of the 2-foot by 3-foot sign, and the proposed off-site public location for posting of the 8.5-inch by 11-inch flyer, as required by Subsection B of 20.6.2.3108 NMAC.

(2) An application for a renewed discharge permit without modification shall include the name of a newspaper of general circulation in the location of the dairy facility for the future display advertisement publication as required by Subsection C of 20.6.2.3108 NMAC.

F. Pre-discharge total dissolved solids concentration in ground water. Pursuant to Paragraph (3) of Subsection C of 20.6.2.3106 NMAC, an application shall include the pre-discharge total dissolved solids concentration in ground water, sample source (e.g., upgradient monitoring well, on-site supply well, nearest well within a one-mile radius of the dairy facility) and a copy of the laboratory analysis.

G. Determination of maximum daily discharge volume. An application shall include the following information.

(1) The proposed maximum daily discharge volume and a description of the methods and calculations used to determine that volume.

(2) The identification of all sources of wastewater which may include, but are not limited to, hospital barns, maternity barns, bottle-washing operations and parlor/equipment washdown.

(3) The animal washing method(s) employed and the estimated daily wastewater volume generated by the method(s).

(4) Information regarding other wastewater discharges (i.e., domestic or industrial) at the dairy facility not generated by dairy operations. Permit identification numbers shall be submitted for those discharges that are already permitted.

H. Identification and physical description of dairy facility. An application shall include the following information.

(1) A scaled map of the entire dairy facility pursuant to Subsection U of 20.6.6.20 NMAC.

(2) The identification of each proposed, existing and closed impoundment, including information for each impoundment regarding its location, purpose (i.e., to store wastewater or stormwater, or dispose of it by evaporation), date of original construction, past and existing liner material, date of current liner installation and storage or evaporative disposal capacity.

(3) The identification of each existing, proposed, and previously used field within the land application area, including information for each field about its location, date of initial application of wastewater or stormwater, acreage, status with regard to having received wastewater or stormwater (i.e. never, inactive, active), current method of backflow prevention employed, current method of wastewater and stormwater application and current method of irrigation water application.

(4) The identification of sumps and mix tanks, including information for each component regarding its location, purpose, date of original construction, construction material, dimensions and capacity.

(5) The settled solids thickness measurements for each existing wastewater and combination impoundment pursuant to Subsection D of 20.6.6.20 NMAC.

(6) A description of proposed and existing method(s) of solids separation pursuant to Paragraph (5) of Subsection C of 20.6.6.17 NMAC and Subsection F of 20.6.6.20 NMAC.

(7) A description of the method(s) employed to protect each manure, silage and compost storage area from stormwater runoff and run-on, and to minimize leachate.

I. Flow metering. An application shall describe a dairy facility's flow metering system pursuant to Subsections J, K, L, M, N and O of 20.6.6.20 NMAC and Subsections G and H of 20.6.6.21 NMAC including:

(1) the identification of the method(s) (i.e. pumped versus gravity flow) of wastewater discharge, stormwater transfer and wastewater and stormwater land application;

(2) a description of the existing and proposed flow measurement devices for each flow method; and

(3) the identification of flow meter locations.

J. Depth-to-most-shallow ground water and ground water flow direction.

(1) An application for renewal or modification shall provide the depth-to-most-shallow ground water and indicate ground water flow direction beneath the dairy facility on a ground water elevation contour map. The ground water elevation contour map shall be developed based upon the most recent ground water levels obtained with a water level measuring device and survey data from on-site monitoring wells obtained from a survey, pursuant to 20.6.6.23 NMAC.

(2) If a dairy facility does not have a monitoring well intersecting most-shallow ground water, an applicant shall provide the following information.

(a) The depth-to-most-shallow ground water pursuant to Subsection X of 20.6.6.20 NMAC.
(b) The ground water flow direction of the most-shallow ground water beneath the dairy facility based upon the most recent regional water level data or published hydrogeologic information. Survey data from nearby monitoring wells and a ground water elevation contour map indicating the direction of ground water flow may be included. The sources of all information used to determine ground water flow direction shall be provided with the application.

K. Monitoring wells. An application shall include:

(1) the construction logs for all existing, on-site monitoring wells, which indicate the date of installation and well driller; and
(2) the identification of monitoring well locations, proposed and existing, pursuant to Subsections A and B of 20.6.6.23 NMAC.

L. Surface soil survey and vadose zone geology. An application shall include:

(1) the most recent regional soil survey map and associated descriptions identifying surface soil type(s);
(2) the lithologic logs from all existing, on-site monitoring wells, if available; and
(3) if applicable, where a dairy facility does not have a monitoring well intersecting most-shallow ground water, the application shall include the lithologic log obtained from the on-site test boring pursuant to Subsection X of 20.6.6.20 NMAC to identify the geological profile of the vadose zone.

M. Location map. An application shall include a location map with topographic surface contours identifying all of the following features located within a one-mile radius of the dairy facility:

(1) watercourses, lakebeds, sinkholes, playa lakes and springs (springs used to provide water for human consumption shall be so denoted);
(2) wells supplying water for a public water system and private domestic water wells;
(3) irrigation supply wells; and
(4) ditch irrigations systems, acequias, irrigation canals and drains.

N. Flood zone map. An application shall include the most recent 100-year flood zone map developed by the federal emergency management administration, FEMA, documenting flood potential for the dairy facility, and a description of any engineered measures used for flood protection.

O. Engineering and surveying. An application shall include the following information.

(1) Plans and specifications for new or improved structures and associated liners proposed by the applicant pursuant to 20.6.6.17 NMAC.
(2) Record drawings and final specifications for existing structures and associated liners. For existing impoundments where record drawings and final specifications do not exist, survey data and capacity calculations shall be submitted pursuant to Subsection C of 20.6.6.20 NMAC.

P. Land application area. For a dairy facility with a land application area, an application shall include the following information.

(1) Documentation confirming the existence of infrastructure necessary to distribute and apply wastewater and stormwater to the land application area pursuant to Subsection E of 20.6.6.21 NMAC.
(2) A nutrient management plan (NMP) pursuant to Subsections I and J of 20.6.6.21 NMAC.
(3) A written description of the wastewater sampling location(s) pursuant to Subsection C of 20.6.6.25 NMAC.

[20.6.6.12 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.13 APPLICATION REQUIREMENTS FOR A DISCHARGE PERMIT FOR CLOSURE: An application for a discharge permit for closure shall include the information required by Subsections B, C, D, E, F, J, K, L, M and N of 20.6.6.12 NMAC and Paragraphs (1), (2), (3) and (4) of Subsection H of 20.6.6.12 NMAC. For dairy facilities with or previously having a land application area, the application shall also include Paragraph (1) of Subsection P of 20.6.6.12 NMAC, specifically pertaining to the past method(s) of wastewater discharge and stormwater application to the land application area.

[20.6.6.13 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.14 ADDITIONAL PUBLIC NOTICE REQUIREMENTS FOR APPLICATIONS FOR NEW DISCHARGE PERMITS:

A. The requirements of this section shall apply to dairy facilities whose application for a new discharge permit is received by the department after the effective date of the dairy rule.

B. Instead of the requirement for public notice specified in Paragraph (2) of Subsection B of 20.6.2.3108 NMAC, the applicant shall provide written notice of the discharge and a copy of the map referenced in Subsection O of 20.6.6.11 NMAC by mail to owners of record of all properties within a one-mile distance from the boundary of the property where the discharge site is located. If there are no properties other than properties owned by the discharger within a one-mile distance of the boundary of the property where the dairy facility is located, the applicant shall provide notice to owners of record of the next nearest properties not owned by the discharger.

C. Proof of notice required by Subsection D of 20.6.2.3108 NMAC shall include an affidavit of mailing(s) and a list of property owner(s) notified pursuant to Subsection B of this section.
[20.6.6.14 NMAC - N, 01/31/2011]

20.6.6.15 PROCEDURES FOR REQUESTING PUBLIC HEARINGS ON PERMITTING ACTIONS FOR DAIRY FACILITIES:

A. Requests for a hearing from any person, including the applicant for a discharge permit, on the proposed approval of a discharge permit (i.e., a draft discharge permit) or denial of a discharge permit application shall be postmarked on or before the end of the comment period, and submitted to the department pursuant to Subsection K of 20.6.2.3108 NMAC. The secretary shall deny requests that do not meet the requirements of Subsection K of 20.6.2.3108 NMAC and this section. The secretary shall provide notice of hearing denial by certified mail to the person(s) requesting a hearing.

B. The secretary shall deny a request for a hearing on the proposed approval of a discharge permit for a dairy facility (i.e., a draft discharge permit) disputing conditions contained in the dairy rule. Requests for a hearing on the proposed approval of a discharge permit for a dairy facility shall identify the specific additional discharge permit conditions being disputed or requested and the reasons such additional discharge permit conditions are being disputed or requested. Hearings held upon the secretary's approval shall be limited in scope to the disputed or requested additional discharge permit conditions identified in the request for hearing. The secretary shall deny requests for a hearing that fail to identify disputed or requested additional discharge permit conditions and the reasons why the additional discharge permit conditions are disputed or requested. The secretary shall provide notice of hearing denial by certified mail to the person(s) requesting a hearing.
[20.6.6.15 NMAC - N, 01/31/2011]

20.6.6.16 SETBACK REQUIREMENTS FOR DAIRY FACILITIES APPLYING FOR NEW DISCHARGE PERMITS:

A. The setback requirements of this section apply to a dairy facility whose application for a new discharge permit is received by the department after the effective date of the dairy rule.

B. The setback requirements shall be measured as horizontal map distances.

C. The required setback distances shall be met as certified by the applicant as of the receipt date of the application.

D. If the setback requirements apply to a dairy facility, a permittee shall not propose or construct structures that violate the setback as determined as of the receipt date of the application for a new discharge permit by the department.

E. Production area setback requirements.

(1) The production area, excluding feed storage silos, feed storage barns and liquid feed tanks, shall be located:

(a) greater than 200 feet from the 100-year flood zone of any watercourse, or from the ordinary high-water mark of any watercourse for which no 100-year flood zone has been established (this setback distance shall not apply to ditch irrigations systems, acequias, irrigation canals and drains);

(b) greater than 200 feet (measured from the ordinary high-water mark) from a lakebed, sinkhole or playa lake;

(c) greater than 200 feet from any spring identified on a U.S. geological survey (USGS) topographic map and not identified as a supply of water for human consumption;

(d) greater than 350 feet from a private domestic water well or spring that supplies water for human consumption; and

(e) greater than 1000 feet from any water well or spring that supplies water for a public water system as defined by 20.7.10 NMAC, unless a wellhead protection program established by the public water system requires a greater distance.

(2) The requirements of Subparagraph (d) of Paragraph (1) of this subsection shall not apply to wells or springs that supply water to the dairy facility for human consumption and are located on the dairy facility.

(3) Setback distances for impoundments shall be measured from the top inside edge of the impoundment; distances for all other features shall be measured from the outer extent of the feature.

F. Land application area setback requirements.

(1) Any field within a land application area shall be located:

(a) greater than 100 feet from the 100-year flood zone of any watercourse, or from the ordinary high-water mark of any watercourse for which no 100-year flood zone has been established (this setback distance shall not apply to ditch irrigations systems, acequias, irrigation canals and drains);

(b) greater than 100 feet (measured from the ordinary high-water mark) from any lakebed, sinkhole or playa lake;

(c) greater than 100 feet from a private domestic water well or spring that supplies water for human consumption; and

(d) greater than 200 feet from any water well or spring that supplies water for a public water system as defined by 20.7.10 NMAC, unless a wellhead protection program established by the public water system requires a greater distance.

(2) The requirements of Subparagraph (c) of Paragraph (1) of this subsection shall not apply to wells or springs that supply water for human consumption to the dairy facility and are located on the dairy facility.

(3) Setback distances for fields shall be measured from the outer edge of the field.

[20.6.6.16 NMAC - N, 01/31/2011]

20.6.6.17 ENGINEERING AND SURVEYING REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. Practice of engineering. All plans and specifications, supporting design calculations, record drawings, final specifications, final capacity calculations, grading and drainage reports and plans, and other work products requiring the practice of engineering shall bear the seal and signature of a licensed New Mexico professional engineer pursuant to the New Mexico Engineering and Surveying Practice Act, NMSA 1978, Sections 61-23-1 through 61-23-32, and the rules promulgated under that authority.

B. Practice of surveying. All surveys of wastewater, stormwater, and combination wastewater/stormwater impoundments, monitoring well locations and casing elevations, and other work products requiring the practice of surveying shall bear the seal and signature of a licensed New Mexico professional surveyor pursuant to the New Mexico Engineering and Surveying Practice, NMSA 1978, Sections 61-23-1 through 61-23-32, and the rules promulgated under that authority.

C. Engineering plans and specifications requirements.

(1) **Impoundment plans and specifications.** An applicant or permittee proposing or required to construct a new impoundment or to improve an existing impoundment, including relining of an existing impoundment, shall submit detailed and complete construction plans and specifications and supporting design calculations developed pursuant to this section and 20.6.6.20 NMAC. The applicant or permittee proposing or required to construct an impoundment shall document compliance with the requirements of the dam safety bureau of the state engineer pursuant to Section 72-5-32 NMSA 1978, and rules promulgated under that authority, unless exempt by law from such requirements. The construction plans and specifications for an improvement(s) to an existing impoundment shall address the management of wastewater or stormwater during preparation and construction of the improvements.

(a) Construction plans and specifications proposed by the applicant or permittee shall be submitted to the department with the application for a new, renewed or modified discharge permit.

(b) Construction plans and specifications not proposed by the applicant or permittee but required to achieve compliance with the dairy rule shall be submitted to the department within 90 days of the effective date of the discharge permit.

(2) **Impoundment CQA/CQC.** Construction of a new impoundment or improvement to an existing impoundment shall be done in accordance with a construction quality assurance/construction quality control (CQA/CQC) plan. A CQA/CQC plan shall be included as part of the design plans and specifications. The CQA/CQC plan shall outline the observations and tests to be used to ensure that construction of the impoundment meets, at a minimum, all design criteria, plans and specifications. All testing and evaluation reports shall be signed and sealed by a licensed New Mexico professional engineer experienced in lagoon construction and liner installation. The CQA/CQC plan shall include, at a minimum, the following elements.

(a) The identity of persons responsible for overseeing the CQA/CQC program. The person responsible for overseeing with the CQA/CQC plan shall be a licensed New Mexico professional engineer experienced in lagoon construction and liner installation.

(b) A discussion of how inspections will be performed.

(c) The location, availability, applicability and calibration of testing equipment and facilities, both field and laboratory.

(d) The procedures for observing and testing the liner material.

(e) The procedures for reviewing inspection test results and laboratory and field sampling test results.

(f) The actions to be taken to replace or repair liner material should deficiencies be identified.

(g) The procedures for seaming synthetic liners.

(h) The reporting procedures for all inspections and test data.

(3) **Impoundment improvement - wastewater/stormwater management.** An applicant or permittee proposing or required to improve an existing impoundment, including relining of an existing impoundment, shall submit a plan for managing wastewater or stormwater during the improvement as part of the design plans and specifications. The plan for wastewater or stormwater management shall include the following minimum elements and be implemented upon department approval.

(a) A description of how on-going wastewater discharges or stormwater collection will be handled and disposed of during improvement to the impoundment.

(b) A description of how solids and wastewater or stormwater within the impoundment will be removed and disposed of prior to beginning improvement to the impoundment.

(c) A schedule for implementation through completion of the project.

(d) If the plan proposes temporary use of a location for the discharge of wastewater not authorized by the effective discharge permit, the applicant or permittee shall request temporary permission to discharge from the department.

(4) **Manure solids separation plans and specifications - new wastewater system.** An applicant or permittee proposing or required to construct a new manure solids separator as a component of a newly designed wastewater storage or disposal system shall submit construction plans and specifications and supporting design calculations that include the separator, pursuant to this section.

(a) Construction plans and specifications proposed by the applicant or permittee shall be submitted to the department with the application for a new, renewed or modified discharge permit.

(b) Construction plans and specifications not proposed by the applicant or permittee but required to achieve compliance with the dairy rule shall be submitted to the department within 90 days of the effective date of the discharge permit.

(5) **Manure solids separation plans and specifications - existing wastewater system.** An applicant or permittee proposing or required to construct a new manure solids separator as a component of an existing wastewater storage or disposal system shall submit a scaled design schematic and supporting documentation, including design calculations. The separator shall be designed to accommodate, at a minimum, the maximum daily discharge volume authorized by the discharge permit, and the volume of manure solids associated with the wastewater discharge. Components of the separator that collect, contain or store manure solids prior to removal or land application shall be designed with an impervious material(s) to minimize generation and infiltration of leachate.

~~(a) A scaled design schematic and supporting documentation for a proposed separator shall be submitted to the department with the application for a new, renewed or modified discharge permit.~~

~~(b) A scaled design schematic and supporting documentation for a separator not proposed by the applicant or permittee but required to achieve compliance with the dairy rule shall be submitted to the department within 90 days of the effective date of the discharge permit.~~

(6) **Grading and drainage report and plan.** An applicant shall submit with the application for a new discharge permit, a grading and drainage report and a grading and drainage plan, including supplemental information associated with the plan. The submittal shall include, at a minimum, the following information.

(a) A scaled map showing:

(i) the dairy facility and the property boundaries of the dairy facility;

(ii) all existing and proposed structures at the dairy facility, with the associated finished floor elevations;

(iii) existing and proposed ground surface contours at two foot vertical intervals; and

(iv) all existing and proposed stormwater management structures at the dairy facility including construction materials, size, type, slope, capacity and inlet and invert elevation of the structures, as applicable.

(b) A copy of the relevant federal emergency management administration, FEMA, flood insurance rate map (FIRM) or flood boundary and floodway map with the dairy facility clearly identified along with all flood zones.

(c) A description of existing drainage conditions at the dairy facility.

(d) A description of the proposed post-development drainage conditions.

(e) Supplemental information supporting the grading and drainage plan shall be submitted to the department with the plan and shall include, at a minimum, the following information:

(i) all hydrologic and hydraulic calculations for design storm events used;

(ii) hydraulic calculations demonstrating capacity or adequacy of existing and proposed stormwater impoundments;

(iii) hydraulic calculations demonstrating capacity of existing and proposed conveyance channels to contain and transport runoff to the stormwater impoundment(s); and

(iv) a description of computer software, documents, circulars, manuals, etc. used to develop the hydrologic and hydraulic calculations.

(7) **Flow metering plans [and specifications].** An applicant or permittee proposing or required to install a flow meter(s) shall submit documentation to support the selection of the proposed device as appropriate for the expected flow rate along with a description of the location and information on the installation or construction of each device.

(a) Such information proposed by the applicant or permittee shall be submitted to the department with the application for a new, renewed or modified discharge permit.

(b) Such information not proposed by the applicant or permittee but required to achieve compliance with the dairy rule shall be submitted to the department within 90 days of the effective date of the discharge permit.

D. Engineering design requirements.

(1) **Impoundment capacity requirements.** Impoundments designed to store wastewater prior to discharging to a land application area or to dispose of wastewater by evaporation shall meet the capacity requirements specified in the dairy rule. The dairy rule does not specify capacity requirements for the containment of stormwater. However, the dairy rule does not exempt a dairy facility from other applicable local, state and federal regulations or laws, including the EPA regulatory requirements for concentrated animal feeding operations pursuant to 40 Code of Federal Regulations, Parts 122 and 412, as amended.

(2) **Impoundment capacities - wastewater or wastewater/stormwater combination.**

(a) Capacity requirements for dairy facilities discharging wastewater to a land application area.

(i) The wastewater impoundments intended to store wastewater prior to discharging to a land application area shall be designed to contain the maximum daily discharge volume authorized by the discharge permit for a minimum period of ~~60~~21 days to accommodate periods when land application is not feasible, while preserving two feet of freeboard. This capacity requirement may be satisfied by a single wastewater impoundment or by the collective capacity of multiple impoundments intended to store wastewater.

(ii) The combination wastewater/stormwater impoundments intended to contain both wastewater and stormwater runoff for storage prior to discharging to a land application area shall be designed to contain the sum of the maximum daily discharge volume authorized by the discharge permit for a minimum period of ~~60~~21 days to accommodate periods when land application is not feasible and the additional volume intended for the containment of stormwater runoff and direct precipitation, while preserving two feet of freeboard. This capacity requirement may be satisfied by a single combination wastewater/stormwater impoundment or by the collective capacity of multiple impoundments intended to store wastewater or wastewater/stormwater.

(b) Capacity requirements for dairy facilities discharging to an evaporative wastewater or combination wastewater/stormwater disposal system.

(i) The wastewater impoundments intended to dispose of wastewater by evaporation shall be designed to contain the maximum daily discharge volume authorized by the discharge permit for disposal by evaporation, while preserving two feet of freeboard. This capacity requirement may be satisfied by a single wastewater impoundment or by the collective capacity of multiple impoundments intended to dispose of wastewater by evaporation.

(ii) The combination wastewater/stormwater impoundments intended to dispose of both wastewater and stormwater runoff by evaporation shall be designed for disposal by evaporation, the sum of the maximum daily discharge volume authorized by the discharge permit and the additional volume intended for the containment of stormwater runoff and direct precipitation while preserving two feet of freeboard. This capacity

requirement may be satisfied by a single combination wastewater/stormwater impoundment or by the collective capacity of multiple impoundments intended to dispose of wastewater or wastewater/stormwater by evaporation.

(c) An impoundment designed and used for solids settling shall not be used to satisfy the impoundment capacity requirements of this subsection.

(d) Notwithstanding Subparagraphs (a) and (b) of this paragraph, a wastewater impoundment or system of wastewater impoundments existing as of the effective date of the dairy rule may continue to be operated based upon the design capacity required under the applicable discharge permit as last issued or amended before the effective date of the dairy rule.

(3) **Stormwater conveyance channels.** Stormwater conveyance channels shall be designed in accordance with the grading and drainage report and plan required by this section.

(4) **Impoundment design and construction - general.** Impoundments required to be ~~synthetically~~ lined shall meet the following design and construction requirements.

(a) The inside slopes of an impoundment shall be a maximum of three (horizontal) to one (vertical), and a minimum of four (horizontal) to one (vertical).

(b) The outside slopes of an impoundment shall be a maximum of three (horizontal) to one (vertical).

(c) The sub-grade of an impoundment shall be compacted to a minimum of 90 percent of standard proctor density. If the existing material is unsuitable for compaction, a minimum depth of 18 inches of suitable material shall be used as sub-grade.

(d) The sub-grade of an impoundment shall provide a firm, unyielding surface with no sharp changes or abrupt breaks in grade.

(e) The minimum dike width of an impoundment shall be 12 feet to allow vehicle traffic for maintenance.

(5) **Impoundment design and construction - ~~synthetic~~ liner.** An applicant or permittee proposing or required to construct a new or to improve an existing impoundment liner, shall, at a minimum, use a 2' thick compacted soil liner with a maximum demonstrated permeability of 1×10^{-7} cm/sec or other materials having equivalent performance characteristics with regard to permeability, resistance to degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and puncture resistance.

Synthetic impoundment liners shall include a liner component that is at least 60 mil HDPE and meet the following additional design and construction requirements.

(a) The liner shall be installed with sufficient slack in the liner material to accommodate shrinkage due to temperature changes. Folds in the liner material shall not be present in the completed liner.

(b) The sub-grade shall be free of sharp rocks, vegetation and stubble to a depth of at least six inches below the liner. The surface in contact with the liner shall be smooth to allow for good contact between liner and sub-grade. The surface shall be dry during liner installation. The liner installer shall provide the owner with a sub-grade acceptance certificate prior to installing the liner indicating acceptance of the earthwork.

(c) The liner shall be anchored in an anchor trench. The trench shall be a minimum of 12 inches wide, 12 inches deep and shall be set back at least 24 inches from the top inside edge of the impoundment.

(d) The liner panels shall be oriented such that all sidewall seams are vertical.

(e) If practicable, decomposing organic materials shall be removed from areas over which a liner will be installed. If such materials remain, a liner vent system shall be installed.

(f) Any opening in the liner through which a pipe or other fixture protrudes shall be sealed in accordance with the liner manufacturer's requirements. Liner penetrations shall be detailed in the construction plans and record drawings.

(g) The liner shall be installed by, or the installation supervised by, an individual that has the necessary training and experience as required by the liner manufacturer.

(h) Manufacturer's installation and field seaming guidelines shall be followed.

(i) Liner seams shall be field tested by the installer and verification of the adequacy of the seams shall be submitted to department along with the record drawings.

(j) Concrete slabs installed on top of a liner for operational purposes shall be completed in accordance with manufacturer and installer recommendations to ensure liner integrity.

(6) **Impoundment liner - wastewater or wastewater/stormwater combination.** An applicant or permittee proposing or required to construct a new or to improve an existing wastewater or combination wastewater/stormwater impoundment, shall, at a minimum, use a single liner that is at least 60 mil HDPE liner that meets the requirements of paragraph (5) of this subsection ~~or other materials having equivalent characteristics with~~

regard to permeability, resistance to degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and puncture resistance.

(7) **Impoundment liner - stormwater.** Any applicant or permittee required to improve an existing stormwater impoundment pursuant to Subsection ~~AB~~ of 20.6.6.27 NMAC shall, at a minimum, use a liner that ~~is at least 60 mil HDPE or other material having equivalent characteristics with regard to permeability, resistance to degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and puncture resistance~~ meets the requirements in paragraph (6) of this subsection.

(8) **Separation between impoundments and ground water.** Impoundments shall not be constructed in a location where the vertical distance between the seasonal high ground water level and the finished grade of the floor of the impoundment is less than or equal to four feet as documented through the most recent ground water data obtained from an on-site test boring(s) or monitoring well(s).

(9) **Impoundment spillways.** Impoundments intended to contain only wastewater shall not be designed with a spillway.

[20.6.6.17 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.18 VARIANCES:

A. A petition for variance from the dairy rule shall be submitted in accordance with Subsection A of 20.6.2.1210 NMAC.

B. In addition to any other criteria offered by the petitioner, the commission may consider as an unreasonable burden upon the petitioner's activity that the requirements of the dairy rule are unnecessary to prevent ground water pollution due to site-specific conditions.

C. In addition to any other information required under Paragraph (7) of that subsection, the petition shall, if applicable, identify any alternative facility design, alternative measuring device, or other variation from the requirements of the dairy rule and describe why variation from the dairy rule is warranted based upon site-specific conditions.

D. Notwithstanding Subsection C of 20.6.2.1210 NMAC, a variance from the requirements of the dairy rule may be granted for a period of time in excess of five years through the period of the expected useful life of the feature for which a variance is granted.

E. The department may review a variance every five years in conjunction with the discharge permit renewal to determine whether the variance is achieving its designed purpose and whether the variance has caused an exceedance of the standards of 20.6.2.3103 NMAC. If a five year review demonstrates that the variance cannot meet these criteria, the department may request a hearing before the commission to revoke the variance.

[20.6.6.18 NMAC - N, 12/31/2011]

20.6.6.19 [RESERVED]

20.6.6.20 OPERATIONAL REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. **Notice of presence of lactating cows and wastewater discharge.** A permittee shall provide written notice to the department of the commencement, cessation, or recommencement of wastewater discharge or the placement, removal, or reintroduction of lactating cows as follows.

(1) For new dairy facilities.

(a) **Placement of lactating cows.** A permittee shall provide written notice to the department a minimum of 30 days before the placement of lactating cows at the dairy facility. A permittee shall provide written verification to the department of the actual date of placement of lactating cows within 30 days of placement.

(b) **Commencement of wastewater discharge.** A minimum of 30 days prior to the estimated initial wastewater discharge date a permittee shall provide written notice to the department indicating the date discharge is proposed to commence. A permittee shall provide written verification to the department of the actual date of discharge commencement within 30 days of commencement.

(2) For existing dairy facilities.

(a) **Removal or reintroduction of lactating cows.** A permittee shall provide written notice to the department indicating the date of removal of all lactating cows from the dairy facility or the date of reintroduction of any lactating cows at the dairy facility, if all lactating cows were previously removed, within 30 days of lactating cow removal or reintroduction.

(b) **Cessation of wastewater discharge.** A permittee shall provide written notice to the department indicating the date wastewater discharge ceased at the dairy facility within 30 days of the cessation of discharge.

(c) **Recommendation of wastewater discharge.** Written notification shall be submitted to the department a minimum of 30 days prior to the date wastewater discharge is expected to recommence. A permittee shall provide written notice to the department of the actual date of discharge commencement within 30 days of commencement.

B. Authorized use of new and existing impoundments. Impoundments shall meet the liner, design, and construction requirements of Subsection D of 20.6.6.17 NMAC; except an impoundment in existence on the effective date of the dairy rule that does not meet the requirements of Paragraphs (4) through (9) of Subsection D of 20.6.6.17 NMAC may continue to receive wastewater or stormwater provided the requirements of Paragraphs (1) or (2) of this subsection are met. If the requirements of Paragraph (1) and (2) of this subsection are not met, such an impoundment may continue to receive wastewater or stormwater provided the requirements of Subsection B of 20.6.6.27 NMAC are met.

(1) The water contaminant concentration in a ground water sample and in any subsequent ground water sample collected from a monitoring well(s) intended to monitor the impoundment does not exceed any ground water standard of 20.6.2.3103 NMAC.

(2) The water contaminant concentration in a ground water sample and in any subsequent ground water sample collected from a monitoring well(s) intended to monitor the impoundment does not exceed the water contaminant concentration in a ground water sample collected from the upgradient monitoring well, if the water contaminant concentration associated with the upgradient monitoring well exceeds the ground water standard(s) of 20.6.2.3103 NMAC. For the purpose of this subsection, ground water samples obtained from the impoundment monitoring well and the upgradient monitoring well that are used for comparison of water contaminant concentrations shall be collected within two days of each other. In the event ground water quality data for the upgradient monitoring well are not submitted by the permittee, the ground water standard(s) of 20.6.2.3103 NMAC shall be the applicable standard(s) used to assess compliance with the requirements of this subsection.

C. Constructed capacity of existing impoundment - determination. If record drawings are unavailable or have not been completed for an impoundment constructed before the effective date of the dairy rule to indicate the impoundment capacity of each existing wastewater or combination wastewater/stormwater impoundment, the permittee shall complete an up-to-date survey and capacity calculation for each impoundment. The permittee shall submit the survey data and capacity calculations to the department with the application for a renewed or modified discharge permit.

D. Free-liquid capacity of existing impoundment - determination. An applicant or permittee shall measure the thickness of settled solids in each existing wastewater and combination wastewater/stormwater impoundment during the twelve-month period prior to the submission of an application for a renewed or modified discharge permit and in accordance with one of the following procedures.

(1) Measure settled solids when the impoundment contains water using the following method:

(a) The total surface area of the impoundment shall be divided into nine equal sub-areas.

(b) A settled solids measurement device shall be used to obtain one settled solids thickness measurement (to the nearest half-foot) per sub-area. The nine settled solids measurements shall be taken on the same day and the date shall be recorded and submitted to the department with the measurements.

(c) The nine settled solids measurements shall be averaged.

(d) The total volume of settled solids in the impoundment shall be estimated by multiplying the average thickness of the solids layer by the area of the top of the settled solids layer. The area shall be calculated using the impoundment dimensions corresponding to the estimated surface of the settled solids layer.

(e) The estimated volume of settled solids shall be subtracted from the design capacity of the impoundment (less two feet of freeboard) to estimate the actual free-liquid capacity.

(f) The settled solids measurements, calculations, estimation of total settled solids volume and volume of the actual free-liquid capacity for each impoundment shall be submitted to the department with the application for a renewed or modified discharge permit.

(2) Measure settled solids when the impoundment has been drained of water to its lowest seasonal level using the following method:

(a) Place a visible mark on each of the sidewalls of the pond showing the design depth allowed for sludge accumulation, or establish at least two vertical staff gauges marked to show the design depth allowed for sludge accumulation. The design depth shall be determined based upon the design capacity approved in the most recent discharge permit.

(b) When the pond is drained to its lowest seasonal level, such that the marks showing the depths described above are visible (or would be visible except for sludge accumulation), photograph each of the markings and submit the photographs with the application.

E. Impoundment construction or improvement. Construction of a new impoundment or improvements to an existing impoundment, including relining of an existing impoundment, shall be performed in accordance with the construction plans and specifications and supporting design calculations submitted with the application for a new, renewed or modified discharge permit, or those submitted after issuance of a discharge permit to achieve compliance with the dairy rule. An applicant or permittee shall notify the department at least five working days before starting construction or improvement of an impoundment to allow for an inspection by department personnel. An applicant or permittee shall submit to the department a construction certification report bearing the seal and signature of a licensed New Mexico professional engineer verifying that installation and construction was completed pursuant to Subsection C of 20.6.6.17 NMAC. The construction certification report shall include: record drawings, final specifications, final capacity calculations and the CQA/CQC report.

(1) For new dairy facilities, impoundment construction shall be completed as follows.

(a) Wastewater impoundment construction shall be completed and the construction certification report shall be submitted to the department before discharging wastewater at the dairy facility.

(b) Combination wastewater/stormwater impoundment construction shall be completed and the construction certification report shall be submitted to the department before placing any livestock at the dairy facility.

(2) For existing dairy facilities, impoundment construction shall be completed:

(a) within one year of the effective date of the discharge permit, if construction of a new impoundment or improvement of an existing impoundment is required to achieve compliance with the dairy rule, or pursuant to the contingency timeframe specified in Subsection B of 20.6.6.27 NMAC when invoked after the effective date of a discharge permit issued pursuant to the dairy rule; and

(b) the construction certification report shall be submitted to the department within 90 days of completion of impoundment construction.

F. Manure solids separator installation – New Wastewater system. A permittee shall employ manure solids separation. ~~All wastewater discharges to an impoundment shall be made through a manure solid separator.~~

(1) A permittee installing a new wastewater storage or disposal system shall, before discharging to the new system, construct a manure solids separator(s) in accordance with the construction plans and specifications submitted with the application for a new, renewed or modified discharge permit, or those submitted after issuance of a discharge permit to achieve compliance with the dairy rule. Before discharging to the new system, the permittee shall submit to the department confirmation of solids separator construction, including separator type(s) and location(s).

~~(2) If an existing dairy facility does not employ manure solids separation, the permittee shall construct a manure solids separator(s) within 150 days of the effective date of the discharge permit. The permittee shall submit confirmation of solids separator construction, including separator type(s) and location(s), to the department within 180 days of the effective date of the discharge permit.~~

G. Grading and drainage report and plan - submittal and implementation. A permittee shall complete a new grading and drainage system, in accordance with the grading and drainage report and plan required by Subsection C of 20.6.6.17 NMAC and submitted with the application for a new discharge permit. A permittee shall submit a post-development drainage report, including record drawings, bearing the seal and signature of a licensed New Mexico professional engineer. The grading and drainage system shall be completed and the post-development drainage report shall be submitted to the department before placing any livestock at the dairy facility.

H. Stormwater conveyance. A permittee shall divert stormwater from the corrals and other applicable areas at the dairy facility (i.e., calf pens, alleys, feed storage and mixing, etc.) in accordance with the grading and drainage plan required by Subsection C of 20.6.6.17 NMAC. Stormwater shall be conveyed in a manner that minimizes ponding and infiltration of stormwater.

I. Stormwater management - unlined impoundment. A permittee shall transfer stormwater collected in an unlined impoundment(s) to the wastewater impoundment(s) or the distribution system for the land application area after a storm event to minimize the potential for movement to ground water. Operational pumps shall be available at the dairy facility at all times for the transfer of stormwater from stormwater impoundment(s) to the wastewater impoundment(s) or the distribution system for the land application area, as authorized by a discharge permit.

J. Flow meter installation. A permittee shall employ a flow metering system that uses flow measurement devices (flow meters) to measure the volume of wastewater discharged at the dairy facility. Flow meters shall be installed in accordance with the plans submitted with the application for a new, renewed or modified discharge permit, or those submitted after issuance of a discharge permit to achieve compliance with the dairy rule,

pursuant to this section, Subsection C of 20.6.6.17 NMAC, and Subsections G and H of 20.6.6.21 NMAC. Flow meters shall be ~~physically and permanently~~ labeled with the discharge permit number, meter identification nomenclature as specified in a discharge permit, and the month and year of meter installation. All flow meters shall be calibrated in accordance with the manufacturer's requirements prior to installation or reinstallation following repair. The permittee shall maintain copies of the manufacturer's certificate of calibration and the manufacturer's recommended maintenance schedule. Confirmation of installation shall include a description of the device type, manufacturer, meter identification, location, record drawings, and ~~the results of the initial field~~ a copy of the manufacturer's certificate of calibration and a copy of the manufacturer's recommended maintenance schedule completed pursuant to Subsection E of 20.6.6.24 NMAC.

(1) An applicant or permittee for a new dairy facility shall install flow meters and submit confirmation of flow meter installation to the department before discharging at the dairy facility.

(2) An applicant or permittee for an existing dairy facility shall install flow meters within 150 days of the effective date of the discharge permit and submit confirmation of flow meter installation to the department within 180 days of the effective date of the discharge permit.

K. Flow metering methods. Flow metering shall be accomplished by the following methods.

(1) For pumped flow discharge or transfer situations, an applicant or permittee shall install a closed-pipe velocity sensing totalizing flow meter(s) on the pressurized discharge or transfer line(s).

(2) For gravity flow discharge or transfer situations, an applicant or permittee shall install a closed pipe totaling flow meter or an open-channel primary flow measuring device(s) (flume or weir), equipped with head sensing and totalizing mechanisms, on the discharge or transfer line(s).

(3) An applicant may propose and the department may accept a proposal to meter flows by metering the water supply. The proposal shall provide specific detail regarding the flow meter to be used and the relationship between the volume of water supplied and wastewater volume.

L. Flow meter locations. An applicant or permittee shall identify flow meter locations in the application for a new, renewed or modified discharge permit. All flow meters shall be located pursuant to this section and Subsections G and H of 20.6.6.21 NMAC, and indicated on the scaled map required by Subsection U of this section.

M. Authorized use of existing flow meters. An applicant or permittee proposing to use an existing flow meter(s) shall submit documentation demonstrating that the existing flow meter(s) is installed consistent with this section, and Subsections G and H of 20.6.6.21 NMAC, as appropriate. The proposal shall be submitted with an application for a new, renewed and modified discharge permit and shall include the following documentation.

(1) The location of each existing flow meter indicated on the scaled map required by Subsection U of this section and the identification of the wastewater discharge, or wastewater or stormwater application it is intended to measure.

(2) A copy of the record drawings or manufacturer plans and technical specifications specific to each existing flow meter, if available.

~~(3) A field calibration report for each existing flow meter, completed pursuant to Subsection E of 20.6.6.24 NMAC.~~

N. Flow metering - wastewater to impoundment. A permittee shall install flow meters to measure the volume of wastewater discharged from all wastewater sources to the wastewater or combination wastewater/stormwater impoundment(s). The flow meter(s) shall be installed on the discharge line(s) from all wastewater sources to the wastewater impoundment(s). Meter installation and confirmation of meter installation shall be performed pursuant to this section. Alternatively, a dairy existing on the effective date of the dairy rule that does not utilize flow meters meeting the requirements of the preceding sentence may install a flow meter(s) on the water supply line(s) that serves all wastewater sources. Readings from flow meter(s) on water supply lines shall be used to estimate wastewater volumes discharged to wastewater or combination wastewater/stormwater impoundment(s) without adjustments or deductions to the meter readings.

O. Flow meter inspection and maintenance. A permittee shall visually inspect flow meters on a weekly basis for evidence of malfunction. If a visual inspection indicates a flow meter is not functioning to measure flow, the permittee shall initiate repair or replacement of the meter within ~~30~~ seven days of discovery. The repaired or replaced flow meter shall be installed and calibrated pursuant to ~~the dairy rule subsection J of this section.~~

(1) For repaired meters, the permittee shall submit a report to the department with the next quarterly monitoring report following the repair that includes a description of the malfunction; a statement verifying the repair, and a copy of the manufacturer's or repairer's certificate of calibration; and a flow meter field calibration report completed pursuant to Subsection E of 20.6.6.24 NMAC.

(2) For replacement meters, the permittee shall submit a report to the department with the next quarterly monitoring report following the replacement that includes plans for the device pursuant to Subsection C of 20.6.6.17 NMAC, a copy of the manufacturer's certificate of calibration, and a copy of the manufacturer's recommended maintenance schedule and a flow meter field calibration report completed pursuant to Subsection E of 20.6.6.24 NMAC.

P. Impoundment inspection and maintenance. A permittee shall maintain impoundments to prevent conditions which could affect the structural integrity of the impoundments and associated liners. Such conditions include, but are not limited to, erosion damage; animal burrows or other animal damage; the presence of vegetation including aquatic plants, weeds, woody shrubs or trees growing within five feet of the top inside edge of a sub-grade impoundment, within five feet of the toe of the outside berm of an above-grade impoundment, or within the impoundment itself; evidence of seepage; evidence of berm subsidence; and the presence of large debris or large quantities of debris in the impoundments. A permittee shall inspect impoundments and surrounding berms on a monthly basis to ensure proper condition and control vegetation growing around the impoundments in a manner that is protective of the liners. Within 24 hours of discovery, a permittee shall report to the department any evidence of damage that threatens the structural integrity of a berm or liner of an impoundment or that may result in an unauthorized discharge. A permittee is not required to report routine berm maintenance to the department.

Q. Pipe and fixture inspection and maintenance. A permittee shall maintain pipes and fixtures used for the conveyance or distribution of wastewater or stormwater at the dairy facility to prevent the unauthorized release of wastewater or stormwater. The permittee shall visually inspect pipes and fixtures on a weekly basis for evidence of leaks or failure, and shall maintain written records at the dairy facility of all such inspections including repairs to the pipes and fixtures. Where pipes and fixtures cannot be visually inspected because they are buried, the permittee shall inspect the area directly surrounding the features for evidence of leaks or failure (e.g., saturated surface soil, surfacing wastewater, etc.). If there is evidence an unauthorized discharge has resulted from damaged or faulty pipe(s) or fixture(s), the permittee shall repair or replace the pipe(s) or fixture(s) within 72 hours of discovery. The permittee shall report the unauthorized discharge to the department pursuant to 20.6.2.1203 NMAC.

R. Leachate management - manure solids separation system. A permittee shall manage the solids captured by and removed from the manure solids separation system(s) and stored at the dairy facility before removal or land application to minimize generation and infiltration of leachate. The manure solids removed from the manure solids separation system and leachate generated from those solids shall be collected and contained on an impervious surface before disposal.

S. Leachate management - manure and compost storage. Unless land application of manure solids and composted materials is authorized by a discharge permit, a permittee shall remove manure solids and composted material from the dairy facility. A permittee shall minimize the generation and infiltration of leachate from stockpiled manure solids and composted material before removal from the dairy facility by diverting stormwater run-on and run-off, and preventing ponding within areas used for manure and compost stockpiling.

T. Leachate management - silage storage. A permittee shall minimize the generation and infiltration of leachate from silage storage areas and prevent ponding within silage storage areas. Leachate generated from the silage storage areas shall be collected and contained on an impervious surface or the stormwater impoundment before disposal.

U. Scaled map of dairy facility. An applicant or permittee shall submit a scaled map of the dairy facility to the department with an application for a new, renewed or modified discharge permit. The map shall be clear and legible, and drawn to a scale such that all necessary information is plainly shown and identified. The map shall show the scale in feet or metric measure, a graphical scale, a north arrow, and the effective date of the map. Multiple maps showing different portions of the facility may be provided using different scales as appropriate to represent the facility. Documentation identifying the means used to locate the mapped objects (i.e., global positioning system (GPS), land survey, digital map interpolation, etc.) and the relative accuracy of the data (i.e., within a specified distance expressed in feet or meters) shall be included with the map. Any object that cannot be directly shown due to its location inside of existing structures, or because it is buried without surface identification, shall be identified on the map in a schematic format and identified as such. The map shall include the following objects:

- (1) the overall dairy facility layout (barns, feed storage areas, pens, etc.);
- (2) the location of all sumps;
- (3) the location of all manure solids separators;
- (4) the location of all wastewater, stormwater, and combination impoundments;
- (5) the location of all mix tanks;
- (6) the location and acreage of each field within the land application area;

- (7) the location of all monitoring wells;
- (8) the location of all irrigation wells;
- (9) the location of all meters measuring wastewater discharges to and from impoundments;
- (10) the location of all meters measuring stormwater applied to the land application area;
- (11) the location of all fixed pumps for discharge and transfer of wastewater or stormwater;
- (12) the location of all wastewater and stormwater distribution pipelines;
- (13) the location of each ditch irrigation system, acequia, irrigation canal and drain;
- (14) the location of all backflow prevention methods or devices;
- (15) all wastewater sampling locations, with the exception of impoundments for disposal by evaporation; and
- (16) location of all septic tanks and leachfields.

V. Scaled map of dairy facility - updates. Following completion of additions or changes to the dairy facility layout which affects items required by Subsection U of this section, a permittee shall update and resubmit to the department the dairy facility map required by this section within 90 days of any additions or changes to the dairy facility layout which affects items required by Subsection U of this section.

W. Animal mortality management. All animal mortalities that may legally be disposed of (buried or composted) on a dairy facility shall be managed in accordance with the following requirements.

- (1) Only mortalities originating at the dairy facility may be disposed of at the dairy facility.
- (2) Mortalities shall not be stored or buried within 200 feet (measured as horizontal map distance) from private or public wells, or any watercourse.
- (3) Mortalities shall not be stored or buried within 100 feet (measured as horizontal map distance) from the 100-year flood zone of any watercourse, as defined by the most recent federal emergency management administration, FEMA, map.
- (4) Stormwater run-on to disposal areas shall be prevented by use of berms or other physical barriers.
- (5) Mortalities disposed of by burial shall be placed in a pit(s) where the vertical distance between the seasonal high ground water level and the floor of the pit(s) is greater than 30 feet as documented through the most recent ground water data obtained from an on-site test boring(s) or monitoring well(s).

X. Determination of ground water conditions. An applicant or permittee for a dairy facility without a monitoring well from which depth-to-most-shallow ground water can be measured in accordance with the procedure required by Paragraph (1) of Subsection F of 20.6.6.23 NMAC shall evaluate ground water conditions by the following methods.

(1) The applicant or permittee shall obtain records from the office of the state engineer for all wells on file with the office of the state engineer located within one mile of the boundary of the dairy facility. The applicant or permittee shall submit to the department in tabular format the following information obtained from the office of the state engineer records: the well identification information; location of each well by latitude/longitude and township, range, and section; use of each well; depth to ground water in each well; and total depth of each well.

(2) If any well record information submitted pursuant to Paragraph (1) of this subsection indicates that depth to ground water is less than 100 feet, or in lieu of the requirement of Paragraph (1) of this subsection, the applicant or permittee shall conduct the following activities.

(a) The applicant or permittee shall drill one site-specific test boring to the depth of most-shallow ground water or a depth of 75 feet (measured from the ground surface), whichever is encountered first. The test boring shall be drilled in an area of low elevation within the production area outside of an existing or proposed impoundment.

(b) The applicant or permittee shall describe the lithology from the ground surface to the completed borehole depth and document the depth of most-shallow ground water or the absence of ground water within 75 feet of the ground surface. If ground water is encountered within 75 feet of the ground surface, the depth of most-shallow ground water shall be measured immediately upon ceasing drilling of the boring and again 24 hours following ceasing drilling. Lithology shall be characterized pursuant to American society of testing and materials (ASTM) test method D 2487 or D 2488 or characterized using standard visual geologic or soils descriptions that shall include lithology, grain size, color (Munsell soil color charts may be used), texture, sorting, percent gravel and degree of induration. The lithologic log and most-shallow ground water information shall be submitted to the department with the application for a new, renewed or modified discharge permit.

(c) Upon completion of ground water measurements, unless the borehole is completed as a monitoring or production well, the borehole shall be immediately abandoned by emplacing neat cement grout, bentonite based plugging material, or other sealing material approved by the state engineer in accordance with 19.27.4 NMAC in the borehole from the bottom of the borehole to the ground surface. A written record of borehole

abandonment shall be submitted to the department with the application for a new, renewed or modified discharge permit and shall describe the type of grout used and the depth interval sealed with grout. If a monitoring well is constructed in the borehole, the monitoring well shall be constructed in accordance with Subsection D of 20.6.6.23 NMAC, and a construction log including well record information specified by 19.27.4 NMAC shall be submitted to the department with the application for a new, renewed or modified discharge permit.

Y. Domestic wastewater. Domestic wastewater shall not be commingled with wastewater or stormwater generated at a dairy facility. Domestic wastewater shall be treated or disposed of pursuant to 20.7.3 NMAC or a discharge permit issued solely for the discharge of domestic wastewater, as appropriate. [20.6.6.20 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.21 ADDITIONAL OPERATIONAL REQUIREMENTS FOR DAIRY FACILITIES WITH A LAND APPLICATION AREA:

A. Impoundment storage capacity management - wastewater and wastewater/stormwater combination. A permittee shall operate and maintain a wastewater or combination wastewater/stormwater impoundment(s) or a tank for the purpose of storing wastewater prior to discharging to the land application area. A permittee shall manage wastewater or combination wastewater/stormwater impoundments to maintain the capacity and two feet of freeboard required by Subsection D of 20.6.6.17 NMAC.

B. Authorized land application of wastewater and stormwater. A permittee shall apply wastewater and stormwater to fields within the land application area, up to the maximum acreage of irrigated cropland specifically authorized by a discharge permit. Wastewater and stormwater shall be distributed uniformly over the field at the planned rate consistent with the nutrient management plan (NMP); ponding shall be minimized.

C. Land application area - fresh irrigation water required. Wastewater shall only be applied to fields within the land application area receiving fresh irrigation water. Fresh irrigation water shall be used as the primary source to meet the water consumptive needs of the crop to support crop production and nutrient removal. Wastewater and stormwater are intended as sources of crop nutrients and shall not be used as a primary source to meet the water consumptive needs of the crop. An applicant may propose and the department may accept a proposal to apply wastewater to crops or grazing land without using fresh water for irrigation if the proposal demonstrates to the department's satisfaction that crops or plants to be grazed can be successfully maintained without fresh irrigation water.

D. Wastewater/irrigation water blending. Wastewater may be blended in-line (i.e., fresh irrigation water supply lines) when fresh water irrigation lines are equipped with a reduced pressure principle backflow prevention assembly (RP). Wastewater may also be blended in a mix-tank(s), applied alternately in the same irrigation line which has been physically disconnected from supply wells, or applied in a separate line, as authorized by a discharge permit. Wastewater may be blended with fresh water in a wastewater impoundment prior to land application so long as:

(1) the permittee maintains an accurate written record of the volume of fresh water added to the wastewater and that volume is accounted for in determining the volumes of wastewater applied for purposes of the nutrient management plan;

(2) fresh water is introduced in a safe manner to prevent scouring of the liner;

(3) the impoundment capacity requirements of this rule are met.

E. Land application area - existing infrastructure. An applicant or permittee shall submit documentation for the existing infrastructure necessary to transfer, distribute and apply wastewater or stormwater to fields within the land application area that will receive wastewater or stormwater to the department with the application for a new, renewed or modified discharge permit. The documentation shall consist of a narrative statement and photographic documentation that confirm the existing land application distribution system including the type(s) and location(s) of the systems, and the method(s) of backflow prevention employed.

F. Land application area - new infrastructure. Before the initial application of wastewater or stormwater to any field within the land application area that has not previously received wastewater or stormwater, an applicant or permittee shall install a land application distribution system to distribute wastewater and stormwater to those fields. The land application distribution system shall be used to distribute and apply wastewater and stormwater to fields within the land application area to meet the requirements of this section. Before the initial application of wastewater or stormwater to any field within the land application area, an applicant or permittee shall submit documentation confirming installation of the land application distribution system. The documentation shall consist of a narrative statement and photographic documentation that confirms the new land application system including the type(s) and location(s) of the system(s), and the method(s) employed for backflow prevention.

G. Flow metering - wastewater to land application area. A permittee shall install flow meters to measure the volume of wastewater discharged from the wastewater or combination wastewater/stormwater impoundments to the land application area. The flow meter(s) shall be installed on the discharge line(s) from the wastewater impoundment(s) or tank to the distribution system for the land application area. Meter installation and confirmation of meter installation shall be performed pursuant to Subsections J, K and M of 20.6.6.20 NMAC.

H. Flow metering - stormwater to land application area. For a dairy facility transferring stormwater from a stormwater impoundment directly to a distribution system for the land application area, a permittee shall install flow meters to measure the volume of stormwater applied directly to the land application area. The flow meter(s) shall be installed on the transfer line(s) from the stormwater impoundment(s) to the distribution system for the land application area. Meter installation and confirmation of meter installation shall be performed pursuant to Subsections J, K and M of 20.6.6.20 NMAC.

I. Nutrient management plan. Nutrients and other constituents required to be monitored under section 20.6.6.25.C and present in wastewater and stormwater shall be applied to irrigated cropland under cultivation in accordance with the requirements of a nutrient management plan (NMP) submitted to the department with the application for a new, renewed, or modified discharge permit. The NMP shall provide for development of a nutrient budget for nitrogen on an annual basis that accounts for the amount of nitrogen from all combined nitrogen sources, including but not limited to wastewater, stormwater, manure solids, composted material, irrigation water and other additional fertilizer(s), along with residual soil nitrogen and nitrogen credits from leguminous crops and that considers estimated and measured nitrogen removal by harvested crops and other losses, considering the monitoring data required to be collected under section 20.6.6.25 NMAC. The NMP shall describe how planned total nitrogen application rates shall be determined each year based upon realistic yield goals for the planned crops. The information used to set the crop yield goals shall be identified in the NMP. The NMP shall address how nitrogen application rates will be adjusted based upon the results of soil tests required by section 20.6.6.25, subsections K and L, consistent with applicable Natural Resource Conservation Service guidance for normal, high and excessive soil nitrogen levels. The NMP shall specify the maximum application rates for wastewater applied through irrigation so as not to exceed the soil intake/infiltration rate., shall be applied to- The application of nitrogen to each field within the land application area shall be in accordance with the NMP, and any departures from the NMP due to growing conditions or other factors shall be addressed in the update to the NMP for the following year. The NMP shall be developed through utilization of the U.S. department of agriculture natural resources conservation service (USDA-NRCS) national comprehensive nutrient management plan development templates as adopted by the New Mexico office of the USDA NRCS and in accordance with the USDA-NRCS conservation practice standard for New Mexico, nutrient management - code 590. The NMP shall be developed, signed and dated annually by an individual certified by the American society of agronomy as a certified crop advisor (CCA) or certified professional agronomist (CPAg) and by an individual certified by the New Mexico office of the USDA-NRCS as a nutrient management planner. Plant material and soil sampling protocols in the NMP shall be, at a minimum, equivalent to the requirements of Subsections I, K and L of 20.6.6.25 NMAC. The NMP shall identify the method(s) of crop removal to be employed. The NMP shall be developed for the term of the discharge permit, and updated annually; and implemented pursuant to the dairy rule. The NMP shall be developed, signed and dated annually by an individual certified by the American society of agronomy as a certified crop advisor (CCA) or certified professional agronomist (CPAg) or by an individual certified by the New Mexico office of the USDA-NRCS as a nutrient management planner. The permittee may elect to submit an NMP meeting the requirements of this subsection that is incorporated into a broader plan, such as a comprehensive nutrient management plan or a nutrient management plan prepared to meet the requirements of a permit issued by EPA, in which case only the portions of such plan required by this subsection and section 20.6.6.25 NMAC shall be considered for purposes of the dairy rule. For a renewed permit where the NMP was not submitted in an application, the permittee shall submit the initial NMP by May 1 of the first year the permit is in effect, and the permittee shall submit annual updates to the NMP to the department in the monitoring reports due by May 1 of each year.

J. Crop removal - mechanical or grazing. A permittee shall remove crops from fields within the land application area by mechanical harvest unless an alternative proposal for the use of or grazing is submitted with the application for a new, renewed, or modified discharge permit. If grazing is the method proposed for crop removal, the nutrient management plan (NMP) prepared pursuant to Subsection [K] 1 of this section shall include a proposal for the use of grazing for crop removal by means of an actively managed rotational grazing system which promotes uniform grazing and waste distribution throughout the field(s) (and pastures within the field). Proposals shall quantify the degree of nitrogen removal expected to be achieved by grazing, and shall provide scientific documentation supporting the estimated nitrogen removal and justification for the selection of input parameters used in calculations or computer modeling. The NMP proposing grazing for crop removal shall be implemented in its

entirety. Annual updates to the NMP shall include updates to the grazing plan as well as a report of actual weight gains, actual nitrogen uptake of the crop, and estimated crop and nutrient removal from the previous season. An NMP which proposes grazing for crop removal shall also include, at a minimum, estimated values for the following elements.

- (1) The length of the grazing season.
- (2) The size and number of animals to be grazed.
- (3) The estimated weight gain of animals to be grazed, or estimated intake for maintenance or milk production.
- (4) The calculations to determine stocking rates, total acreage needed and residency period.
- (5) The plant species used to establish pastures and the pasture renovation practices to be employed.
- (6) The yield of plant species grown in each pasture and the forage supplied on a monthly basis.
- (7) The grazing management system employed and a map indicating key features of the system including water tanks, fencing, and pasture layout with numbering system and acreage of each pasture.

~~K. Crop removal changes to method(s). If a permittee proposes to change the method(s) (i.e., mechanical versus grazing) of crop removal on any field within the land application area authorized by the discharge permit, the permittee shall apply to modify the discharge permit. The permittee shall submit an application which includes the proposed change(s) pursuant to Subsection I and J of this section. The permittee shall not implement the changes unless the department issues a modified permit approving the changes.~~

L. **Irrigation ditches - inspection and maintenance.** Irrigation ditches used to land apply wastewater or stormwater at a dairy facility shall be concrete-lined and shall be maintained in good repair. The permittee shall visually inspect the ditch system on a monthly basis to ensure proper maintenance. Any damage to a lined ditch shall be repaired within a reasonable time period. A log shall be kept on-site documenting the inspection findings and repairs made, and the log shall be made available to the department upon request.

M. **Backflow prevention.** A permittee shall protect all water wells used within the land application distribution system from contamination by wastewater or stormwater backflow by installing and maintaining backflow prevention methods or devices. Backflow prevention shall be achieved by a total disconnect (physical air gap separation of at least two times the pipe diameter or complete piping separation when wastewater is being pumped) or by the installation of at a minimum a reduced pressure principle backflow prevention assembly (RP) an air/vacuum relief valve and a low pressure drain valve located immediately upstream of a check valve between the fresh irrigation water supply discharge head of the well pump and wastewater and stormwater delivery systems.

(1) A permittee for a new dairy facility shall install backflow prevention methods or devices and submit written confirmation of installation to the department before discharging at the dairy facility.

(2) A permittee for an existing dairy facility that lacks backflow protection as required by this subsection shall install backflow prevention methods or devices within 90 days of the effective date of the discharge permit. The permittee shall submit written confirmation of installation to the department within 180 days of the effective date of the discharge permit.

N. **Backflow prevention by reduced pressure principle check valve backflow prevention assembly device - inspection and maintenance.** A permittee shall inspect each check valve device at least monthly when the well is operating. have each reduced pressure principle backflow prevention assembly (RP) inspected and tested by a person qualified by the manufacturer at the time of installation, repair, or relocation, and at least on an annual schedule thereafter. A malfunctioning RP check valve device shall be repaired or replaced within 30 days of discovery, and use of all wastewater supply lines associated with the RP check valve device shall cease until repair or replacement has been completed. Copies of the inspection and maintenance records and test results for each RP check valve device associated with the backflow prevention program for the previous year shall be submitted to the department annually in the monitoring reports due by May 1.

O. **Supply well protection.** With the exception of monitoring wells, all wells located within the land application area of a dairy facility shall have a surface pad constructed in accordance with the recommendations of Subsection G of 19.27.4.29 NMAC and a permanent well cap or cover pursuant to Subsection I of 19.27.4.29 NMAC.

[20.6.6.21 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.22 ADDITIONAL OPERATIONAL REQUIREMENTS FOR DAIRY FACILITIES DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: Impoundment

evaporative capacity - wastewater and wastewater/stormwater combination. A wastewater or combination wastewater/stormwater impoundment shall be operated and maintained for the purpose of disposing of wastewater or both wastewater and stormwater by evaporation. A permittee shall manage wastewater or combination

wastewater/stormwater impoundments to maintain the capacity and two feet of freeboard as required by Subsection D of 20.6.6.17 NMAC.

[20.6.6.22 NMAC - N, 01/31/2011]

20.6.6.23 GROUND WATER MONITORING REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. Monitoring wells - required locations. A permittee shall monitor ground water quality hydrologically downgradient of each source of ground water contamination: wastewater, stormwater, and combination wastewater/stormwater impoundments, and fields within the land application area at the dairy facility with at least one hydrologically upgradient and two hydrologically downgradient wells. Monitoring wells shall be located pursuant to this section in a location that is protective of the well to detect an exceedance(s) or a trend towards exceedance(s) of the ground water standards at the earliest possible occurrence, so that source control or abatement may be implemented as soon as possible within a reasonable period of time.

(1) ~~Ground water monitoring – installation schedule wastewater impoundments.~~ A minimum of one monitoring well shall be located hydrologically downgradient and within 75 feet (measured as horizontal map distance) of the top inside edge of each wastewater impoundment. For existing dairy facilities, this ground water monitoring requirement additionally applies to wastewater impoundments that received wastewater as authorized by the most recent discharge permit issued prior to the effective date of the dairy rule but are not proposed for use under the first discharge permit renewal following the effective date of the dairy rule.

(a) For a new dairy facility, monitoring wells shall be installed before discharging at the dairy facility.

(b) For an existing dairy facility, any new monitoring wells shall be installed within 120 days of the effective date of the discharge permit, provided that the department may grant a one-time extension of 60 days for good cause shown.

(c) ~~A permittee constructing a new impoundment at an existing dairy facility shall install the monitoring well(s) required to monitor ground water hydrologically downgradient of the impoundments before discharging wastewater to the impoundment or within 120 days of the completion of the impoundment, whichever occurs first.~~

(2) ~~Ground water monitoring – combination wastewater/stormwater impoundments.~~ A minimum of one monitoring well shall be located hydrologically downgradient and within 75 feet (measured as horizontal map distance) of the top inside edge of each combination wastewater/stormwater impoundment. For existing dairy facilities, this ground water monitoring requirement additionally applies to combination wastewater/stormwater impoundments that received wastewater or stormwater as authorized by the most recent discharge permit issued prior to the effective date of the dairy rule but are not proposed for use under the first discharge permit renewal following the effective date of the dairy rule.

(a) ~~For a new dairy facility, monitoring wells shall be installed before placing any livestock at the dairy facility.~~

(b) ~~For an existing dairy facility, monitoring wells shall be installed within 120 days of the effective date of the discharge permit, provided that the department may grant a one-time extension of 60 days for good cause shown.~~

(c) ~~A permittee constructing a new impoundment at an existing dairy facility shall install the monitoring well(s) required to monitor ground water hydrologically downgradient of the impoundment before discharging wastewater to the impoundment, before collecting stormwater in the impoundment or within 120 days of the completion of the impoundment, whichever occurs first.~~

(3) ~~Ground water monitoring – stormwater impoundments.~~ A minimum of one monitoring well shall be located hydrologically downgradient and within 75 feet (measured as horizontal map distance) of the top inside edge of each stormwater impoundment. For existing dairy facilities, this ground water monitoring requirement additionally applies to stormwater impoundments that received stormwater as authorized by the most recent discharge permit issued prior to the effective date of the dairy rule but are not proposed for use under the first discharge permit renewal following the effective date of the dairy rule.

(a) ~~For a new dairy facility, monitoring wells shall be installed before placing any livestock at the dairy facility.~~

(b) ~~For an existing dairy facility, monitoring wells shall be installed within 120 days of the effective date of the discharge permit, provided that the department may grant a one-time extension of 60 days for good cause shown.~~

(c) ~~A permittee constructing a new impoundment at an existing dairy facility shall install the monitoring well(s) required to monitor ground water hydrologically downgradient of the impoundment before~~

collecting stormwater in the impoundment(s) or within 120 days of the completion of the impoundment, whichever occurs first.

~~(4) Ground water monitoring—land application area.~~ Monitoring wells intended to monitor ground water hydrologically downgradient of fields within the land application area shall be installed as follows.

~~(a) Flood irrigation.~~ Ground water monitoring shall be performed hydrologically downgradient of each flood irrigated field or grouping of contiguous flood irrigated fields. For every 40 acres or less of a single flood irrigated field or a single grouping of contiguous flood irrigated fields, a minimum of one monitoring well shall be located hydrologically downgradient and within 50 feet (measured as horizontal map distance) of the downgradient boundary of the single field or single grouping of contiguous fields. Flood irrigated fields separated by ditch irrigation systems, acequias and drains shall be considered contiguous for the purpose of this subsection. For existing dairy facilities, this ground water monitoring requirement additionally applies to single fields or single groupings of contiguous flood irrigated fields that received wastewater or stormwater as authorized by the most recent discharge permit issued prior to the effective date of the dairy rule but are not proposed for use under the first discharge permit renewal following the effective date of the dairy rule.

~~(i)~~ For a new dairy facility, monitoring wells shall be installed before placing livestock at the dairy facility.

~~(ii)~~ For an existing dairy facility, monitoring wells shall be installed within 120 days of the effective date of the discharge permit, provided that the department may grant a one-time extension of 60 days for good cause shown.

~~(iii)~~ A permittee activating a new flood irrigated field at an existing dairy facility shall install the monitoring well(s) required to monitor ground water hydrologically downgradient of the field before applying wastewater or stormwater to the field.

~~(b) Sprinkler or drip irrigation.~~ Ground water monitoring shall be performed hydrologically downgradient of each sprinkler or drip irrigated field, or grouping of contiguous sprinkler or drip irrigated fields. For every 160 acres or less of a single sprinkler or drip irrigated field, or a single grouping of 160 contiguous acres of sprinkler or drip irrigated fields, a minimum of one monitoring well shall be located hydrologically downgradient and within 50 feet (measured as horizontal map distance) of the downgradient boundary of the single field or single grouping of contiguous fields. Sprinkler or drip irrigated fields separated by ditch irrigation systems, acequias and drains shall be considered contiguous for the purpose of this subsection. For existing dairy facilities, this ground water monitoring requirement additionally applies to single fields or single groupings of contiguous sprinkler or drip irrigated fields that received wastewater or stormwater as authorized under the most recent discharge permit issued prior to the effective date of the dairy rule but are not proposed for use under the first discharge permit renewal following the effective date of the dairy rule.

~~(i)~~ For a new dairy facility, monitoring wells shall be installed before placing livestock at the dairy facility.

~~(ii)~~ For an existing dairy facility, monitoring wells shall be installed within 120 days of the effective date of the discharge permit, provided that the department may grant a one-time extension of 60 days for good cause shown.

~~(iii)~~ A permittee activating a new sprinkler or drip irrigated field at an existing dairy facility shall install the monitoring well(s) required to monitor ground water hydrologically downgradient of the field before applying wastewater or stormwater to the field.

~~(c) Crop harvest by grazing.~~ Notwithstanding the requirements of Subparagraphs (a) and (b) of this paragraph, a minimum of one monitoring well(s) shall be located hydrologically downgradient and within 50 feet (measured as horizontal map distance) of the downgradient boundary of each field where grazing is proposed in a nutrient management plan (NMP) as an alternative to, or in conjunction with, crop removal by mechanical harvest.

~~(5) Ground water monitoring—upgradient.~~ A minimum of one monitoring well shall be located hydrologically upgradient of all ground water contamination sources at a dairy facility in order to establish ground water quality conditions at a location not likely to be affected by contamination sources at the dairy facility.

~~(a)~~ For a new dairy facility, monitoring wells shall be installed before placing livestock at the dairy facility.

~~(b)~~ For an existing dairy facility, monitoring wells shall be installed within 120 days of the effective date of the discharge permit, provided that the department may grant a one-time extension of 60 days for good cause shown.

~~(6) Use of existing monitoring wells.~~ A monitoring well approved for use in the previous discharge permit and in existence before the effective date of the dairy rule shall be approved for ground water monitoring at a dairy facility provided all of the following requirements are met.

- ~~_____ (a) The monitoring well is located at the location previously approved by the department.~~
- ~~_____ (b) The monitoring well:~~
 - ~~_____ (i) if intended to monitor ground water quality near a contamination source, is located downgradient of the source based on current hydrologic conditions and is located no more than 100 feet hydrologically downgradient (measured as a horizontal map distance) from the contamination source; or~~
 - ~~_____ (ii) if intended to monitor ground water quality at a location not likely to be affected by contamination sources, is located hydrologically upgradient of sources at the dairy facility.~~
- ~~_____ (c) The monitoring well is constructed with a screen length consistent with the construction requirements of this section or an alternative screen length previously approved by the department, and the screened interval intersects with the most shallow ground water, and~~
 - ~~_____ (i) the alternative screen length is no greater than 30 feet; or~~
 - ~~_____ (ii) the monitoring well has a water column within the screened interval of no more than 25 feet in length based upon the most recent ground water level obtained with a water level measuring device pursuant to 20.6.6.23 NMAC.~~

~~_____ (d) The monitoring well construction log, the scaled dairy facility map and the ground water elevation contour map, and a copy of the department's written approval of an alternate screen length or recent ground water level data, as appropriate, is submitted with the application for a renewed or renewed and modified discharge permit verifying that the requirements of Subparagraphs (a), (b), and (c) of this paragraph are met.~~

(7) **Exceptions to monitoring well requirements.** When appropriate, based on the documented ground water flow direction, one monitoring well may be authorized by a discharge permit to monitor ground water hydrologically downgradient of ~~more than one contamination source~~ the dairy facility under any of the following circumstances.

(a) Contiguous impoundments are oriented along a line that is parallel or approximately parallel to the direction of ground water flow beneath the impoundments.

(b) Adjacent impoundments are oriented along a line that is parallel or approximately parallel to the direction of ground water flow beneath the impoundments and separated by a distance of 50 feet or less as measured from the top inside edge of one impoundment to the nearest top inside edge of the adjacent impoundment.

~~_____ (c) Adjacent or adjacent groupings of contiguous sprinkler or drip irrigated fields are oriented along a line that is parallel or approximately parallel to the direction of ground water flow beneath the fields and the average depth to most shallow ground water measured in on site monitoring wells pursuant to Subsection F of this section is 300 feet or greater. Where monitoring wells do not exist, depth to most shallow ground water shall be determined pursuant to Subsection X of 20.6.6.20 NMAC. A monitoring well(s) installed hydrologically downgradient of a sprinkler or drip irrigated field or a grouping of sprinkler or drip irrigated fields pursuant to Paragraph (4) of this subsection may be authorized by a discharge permit to monitor ground water hydrologically downgradient of not more than two adjacent sprinkler or drip irrigated fields or adjacent groupings of sprinkler or drip irrigated fields.~~

~~_____ (8) **Requirement for third monitoring well.** If fewer than three monitoring wells are needed to satisfy the ground water monitoring requirements of Paragraphs (1) through (7) of this subsection, a third monitoring well shall be installed within 75 feet of the contamination source and in a location alternate to the downgradient monitoring well required by this subsection. The third monitoring well shall be installed in an alternative location that allows for the determination of ground water flow direction pursuant to this section.~~

B. Monitoring wells - location proposals. An applicant or permittee shall identify monitoring well locations in the application for a new, renewed or modified discharge permit pursuant to Subsection A of this section, and shall include the following information.

(1) The location of each monitoring well relative to the ~~contamination source~~ dairy facility it is intended to monitor shall be indicated on the scaled map required by Subsection U of 20.6.6.20 NMAC.

(2) A written description of the specific location for each monitoring well including the horizontal map distance (in feet) and compass bearing of each monitoring well from the top inside edge of the impoundment berm or edge of the field it is intended to monitor.

(3) The ground water flow direction beneath the dairy facility used to determine the monitoring well location(s), including supporting documentation used to determine ground water flow direction.

C. Monitoring wells - identification tags. A permittee shall identify all monitoring wells required by the dairy rule with a well identification tag. For above-grade wells, the tag shall be affixed to the exterior of the steel well shroud ~~using rivets, bolts or a steel band~~. For wells finished below-grade, the tag shall be placed inside the well vault next to the well riser. The tag shall be printed adhesive or metal:

- (1) if metal, made of aluminum;

- (2) at least two inches by four inches in size;
- (3) for monitoring wells installed after the effective date of the dairy rule, the tag shall ~~be engraved~~ with include:

- (a) the discharge permit number;
- (b) the well identification nomenclature specified in a discharge permit;
- (c) the name and New Mexico well driller license number of the well driller who drilled the well; and

- (d) the month and year of well installation; and
- (4) for monitoring wells installed before the effective date of the dairy rule and satisfying the requirements of Paragraph (6) of Subsection A of this section, the tag shall ~~be engraved with~~ include:
 - (a) the discharge permit number;
 - (b) the well identification nomenclature specified in a discharge permit; and
 - (c) if available, the name and New Mexico well driller license number of the well driller who drilled the well, and the month and year of well installation.

D. Monitoring wells - construction and completion ~~new monitoring wells~~. A permittee shall construct monitoring wells pursuant to 19.27.4 NMAC and the following requirements.

(1) All well drilling activities shall be performed by an individual with a current and valid well driller license issued by the state of New Mexico pursuant to 19.27.4 NMAC.

(2) The well driller shall employ drilling methods that allow for accurate determinations of water table locations. All drill bits, drill rods, and down-hole tools shall be thoroughly cleaned immediately before drilling. The borehole diameter shall allow a minimum annular space of two inches between the outer circumference of the well materials (casing or screen) and the borehole wall to allow for the emplacement of sand and sealant.

(3) After completion, the well shall be allowed to stabilize for a minimum of 12 hours before development is initiated.

(4) The well shall be developed so that formation water flows freely through the screen and is not turbid, and all sediment and drilling disturbances are removed from the well.

(5) Schedule 40 (or heavier) polyvinyl chloride (PVC) pipe, stainless steel pipe, or carbon steel pipe shall be used as casing. The casing shall have an inside diameter not less than two inches. The casing material selected for use shall be compatible with the anticipated chemistry of the ground water and appropriate for the contaminants of interest at the dairy facility. The casing material and thickness selected for use shall have sufficient collapse strength to withstand the pressure exerted by grouts used as annular seals and thermal properties sufficient to withstand the heat generated by the hydration of cement-based grouts.

(6) Casing sections shall be joined using welded, threaded, or mechanically locking joints; the method selected shall provide sufficient joint strength for the specific well installation.

(7) The casing shall extend from the top of the screen to at least one foot above ground surface. The top of the casing shall be fitted with a removable cap, and the exposed casing shall be protected by a locking steel well shroud. The shroud shall be large enough in diameter to allow easy access for removal of the cap. Alternatively, monitoring wells may be completed below grade. In this case, the casing shall extend from the top of the screen to six to twelve inches below the ground surface; the monitoring wells shall be sealed with locking, expandable well plugs; a flush-mount, watertight well vault that is rated to withstand traffic loads shall be emplaced around the wellhead; and the cover shall be secured with at least one bolt. The vault cover shall indicate that the wellhead of a monitoring well is contained within the vault.

(8) A 20-foot section (maximum) of continuous well screen shall be installed across the water table. Screen shall consist of continuous-slot, machine slotted, or other manufactured schedule 40 (or heavier) PVC or stainless steel. Screens created by cutting slots into solid casing with saws or other tools shall not be used. The screen material selected for use shall be compatible with the anticipated chemistry of the ground water and appropriate for the contaminants of interest at the dairy facility. The screen slot size shall be selected to retain 90 percent of the filter pack.

(a) Requests for a 30-foot section of continuous well screen may be authorized by a discharge permit when the most recent two years of ground water level data demonstrates a declining water level trend of at least two feet per year. Data supporting ground water levels shall be specific to monitoring wells located at the dairy facility and obtained with a water level measuring device as required by Subsection F of this section.

(b) Requests for a 30-foot section of continuous well screen shall be submitted to the department in the application for a new, renewed or modified discharge permit.

(9) Screen sections shall be joined using welded, threaded, or mechanically locking joints. The method selected shall provide sufficient joint strength for the specific well installation and shall not introduce constituents that may reasonably be considered contaminants of interest at the dairy facility. A cap shall be attached to the bottom of the well screen. Sumps (i.e., casing attached to the bottom of a well screen) shall not be installed.

(10) The bottom of the screen shall be installed no more than 15 feet below the water table, or no more than 25 feet below the water table when additional screen length is authorized by a discharge permit. The top of the well screen shall be positioned not less than five feet above the water table. The well screen slots shall be appropriately sized for the formation materials.

(11) Casing and well screen shall be centered in the borehole by installing centralizers near the top and bottom of the well screen.

(12) A filter pack shall be installed around the screen by filling the annular space from the bottom of the screen to two feet above the top of the screen with clean silica sand. The filter pack shall be properly sized to exclude the entrance of fine sand, silt, and clay from the formation into the monitoring well. For wells deeper than 30 feet, the sand shall be emplaced by a tremmie pipe. The well shall be surged or bailed to settle the filter pack and additional sand added, if necessary, before the bentonite seal is emplaced.

(13) A bentonite seal shall be constructed immediately above the filter pack by emplacing bentonite chips or pellets (three-eighths inch in size or smaller) in a manner that prevents bridging of the chips/pellets in the annular space. The bentonite seal shall be three feet in thickness and hydrated with clean water. Adequate time shall be allowed for expansion of the bentonite seal before installation of the annular space seal.

(14) The annular space above the bentonite seal shall be sealed with cement grout or bentonite-based sealing material acceptable to the state engineer in accordance with 19.27.4 NMAC. A tremmie pipe shall be used to emplace the annular space seal (flow by gravity or pumping through the pipe) if the total depth of the well is greater than 20 feet from the land surface. Annular space seals shall extend from the top of the bentonite seal to the ground surface (for wells completed above grade) or to a level three to six inches below the top of casing (for wells completed below grade).

(15) A concrete pad (two-foot minimum radius, four-inch minimum thickness) shall be poured around the shroud or well vault and wellhead. The concrete and surrounding soil shall be sloped to direct rainfall and runoff away from the wellhead.

E. Monitoring wells - office of the state engineer requirements. Should a well permit for a monitoring well be required by the office of the state engineer, the permittee shall obtain the permit prior to well drilling.

F. Ground water sample collection procedure. A permittee shall perform all ground water sample collection, preservation, transport and analysis according to the following procedure.

(1) Depth-to-most-shallow ground water shall be measured from the top of well casing at point of survey to the nearest 0.01 feet using an electronic water level indicator consisting of dual conductor wire encased in a cable or tape graduated to 0.01 feet, a probe attached to the end of the conductor wire, and a visual or audible indicator.

(2) Monitoring wells shall be purged before sample collection by one of the following methods.

(a) Three well volumes of water shall be purged from the well before sample collection.

(b) The monitoring well shall be purged until measurements of indicator parameters (pH, specific conductance, and temperature) have stabilized. Indicator parameters shall be measured periodically during purging. A parameter stabilization log shall be kept during each sampling event for each monitoring well and include: date; water quality indicator parameter measurements; time for all measurements; and the purge volume extracted. Indicator parameters are considered stable when three consecutive readings made no more than five minutes apart fall within the following ranges: temperature plus or minus 10 percent; pH plus or minus 0.5 units; specific conductance plus or minus 10 percent.

(3) Following purging and immediately before sample collection the following field parameters shall be measured and recorded: pH, specific conductance, and temperature.

(4) In-line flow-through cells shall be disconnected or by-passed during sample collection, if used during purging.

(5) Samples from the well shall be obtained, prepared, preserved and transported to an analytical laboratory for analysis pursuant to the methods authorized by Subsection B of 20.6.6.24 NMAC.

G. Ground water sampling and reporting - routine. A permittee shall collect ground water samples quarterly from all monitoring wells required by Subsection A of this section and Subsection C of 20.6.6.27 NMAC. Samples shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, sulfate and total dissolved solids pursuant to Subsection B of 20.6.6.24 NMAC. A permittee shall submit to the department in the

quarterly monitoring reports the depth-to-most-shallow ground water, the field parameter measurements, the parameter stabilization log (if applicable), the analytical results (including the laboratory quality assurance and quality control summary report) and a map showing the location and number of each well in relation to the contamination source it is intended to monitor.

H. Ground water sampling - new monitoring wells. A permittee shall collect ground water samples from all newly installed monitoring wells. Samples shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, sulfate and total dissolved solids pursuant to Subsection B of 20.6.6.24 NMAC.

(1) Samples shall be collected from the newly installed monitoring wells at new dairy facilities before placing livestock at the dairy facility.

(2) Samples shall be collected from the newly installed monitoring wells at existing dairy facilities within 150 days of the effective date of the discharge permit.

(3) For dairy facilities installing a new monitoring well during the term of a discharge permit, during construction of a new impoundment, or as a result of required corrective actions, samples shall be collected from the newly installed monitoring wells within 30 days of well completion, provided the department may grant an extension for good cause shown.

I. Monitoring well survey and ground water flow determination. A permittee shall survey monitoring wells to a U.S. geological survey (USGS) benchmark and State Plane coordinates. Survey data shall include northing, easting and elevation to the nearest hundredth of a foot or shall be in accordance with the "Minimum Standards for Surveying in New Mexico", 12.8.2 NMAC. A survey elevation shall be established at the top-of-casing, with a permanent marking indicating the point of survey. The survey shall be completed and bear the seal and signature of a licensed New Mexico professional surveyor. Depth-to-most-shallow ground water shall be measured from the point of survey to the nearest hundredth of a foot in all surveyed wells pursuant to Subsection F of this section, and the data shall be used to develop a map showing the location of all monitoring wells and the direction and gradient of ground water flow at the dairy facility.

(1) For a new dairy facility, monitoring wells shall be surveyed before placing livestock at the dairy facility.

(2) For an existing dairy facility, monitoring wells not previously surveyed in a manner consistent with the requirements of this subsection and Subsection B of 20.6.6.17 NMAC shall be surveyed within 150 days of the effective date of the discharge permit.

J. Monitoring well completion report. A permittee shall submit to the department a monitoring well completion report pertaining to all monitoring wells. For a new dairy facility, the report shall be submitted before placing livestock at the dairy facility. For an existing dairy facility, the report shall be submitted within 180 days after the effective date of the discharge permit or within 60 days of completion as specified in a discharge permit. The report shall contain the following information.

(1) Construction and lithologic logs for the new monitoring wells including well record information specified by 19.27.4 NMAC.

(2) Depth-to-most-shallow ground water measured in each new and existing monitoring well.

(3) Survey data and a survey map showing the locations of each new and existing monitoring well and a ground water elevation contour map developed pursuant to Subsection L of this section.

(4) Analytical results of ground water samples collected from the new monitoring wells, including laboratory quality assurance and quality control summary reports, and field parameter measurements.

K. Monitoring well survey report - existing monitoring wells. For a dairy facility required to survey existing monitoring wells pursuant to this section a permittee shall submit the monitoring well survey report to the department within 180 days of the effective date of the discharge permit, provided the department may grant an extension for good cause shown. The report shall contain the depth-to-most-shallow ground water measured in each monitoring well, a surveyed map showing the locations of the monitoring wells, and the direction and gradient of ground water flow at the dairy facility.

L. Ground water elevation contour maps. A permittee shall develop ground water elevation contour maps on a quarterly basis using data associated with all monitoring wells used for ground water monitoring at the dairy facility. Top of casing elevation data, obtained from monitoring well surveys completed pursuant to this section and quarterly depth-to-most-shallow ground water measurements in monitoring wells, shall be used to calculate ground water elevations at monitoring well locations. Ground water elevations between monitoring well locations shall be estimated using common interpolation methods. Ground water elevations shall be expressed in feet. A contour interval appropriate to the data shall be used, but in no case shall the interval be greater than two feet. Ground water elevation contour maps shall depict the ground water flow direction, using arrows, based on the orientation of the ground water elevation contours, and the location and identification of each monitoring well,

impoundment, and field within the land application area. A permittee shall submit ground water elevation contour maps to the department in the quarterly monitoring reports.

M. Monitoring well inspection. The department may perform downhole inspections of all monitoring wells. At least 60 days before the inspection, the department shall provide written notice to the permittee by certified mail stating the inspection date and identifying the monitoring wells to be inspected; the 60 day notification period shall start upon the date of postal notice. At least 48 hours before the department's inspection, the permittee shall remove all existing dedicated pumps to allow adequate settling time of sediment agitated from pump removal. If a permittee decides to install a dedicated pump in a monitoring well, the permittee shall notify the department so that the department may have the opportunity to perform a downhole well inspection before pump installation. Alternatively, a permittee may employ a third party to perform downhole monitoring well inspections, provided the department is given at least 60 days written notice by certified mail so that a department representative may be on-site to observe the inspection.

(1) The third party shall make a video recording of the monitoring well inspection using a downhole camera and perform the inspection in accordance with the following requirements:

(a) Depth to most shallow ground water shall be obtained from the well using an electronic water level indicator pursuant to Subsection F of this section, prior to inspection with a downhole camera. Care shall be taken when obtaining this measurement so as to not disturb sediments in the well.

(b) If ground water sample collection is planned during the inspection event, the downhole camera shall be used to inspect a monitoring well prior to sampling the well.

(c) Prior to well inspection with a downhole camera, at the top of the well casing, the totalizing reading on the downhole camera shall be zeroed, or a value other than zero shall be recorded as an initial reading.

(d) All measurements and totalizing readings (with the exception of depth to most shallow ground water obtained pursuant to Subsection F of this section shall be obtained to the nearest 0.1 feet. Downhole cameras that use a measurement system other than 0.1-foot increments are authorized for use; however the permittee shall report the direct measurement/reading obtained and the calculated conversion in 0.1 feet on the written log.

(e) All measurements and totalizing readings shall be obtained at the top of the well casing.

(f) The downhole camera shall be lowered into the monitoring well at a consistent speed that allows for clear video capture and does not disturb sediments in the well.

(g) Lowering of the downhole camera shall be paused long enough to clearly identify totalizing readings at the following points: depth to most shallow ground water; depth of the top of the screened interval; depth of the bottom of screened interval; and the bottom of the well.

(2) The permittee shall submit written and video monitoring well camera logs for every monitoring well viewed with a downhole camera, along with a copy of an up-to-date facility map showing the location and identification of each monitoring well. The permittee shall submit the logs to the department within 60 days following the date of the well inspection.

(a) The written monitoring well camera log shall include the following general information: name of the dairy facility; discharge permit number; permittee's name; monitoring well identification; date and time of the monitoring well camera inspection; location of the monitoring well relative to a source or facility landmark; camera manufacturer and model; names of camera operator and any technical assistants; diameter of the casing (in inches); and a description of the physical condition of the well's concrete pad, shroud, casing and screened interval. The written log shall include measurements of distance from top of the well casing to the surface of the concrete pad; height from ground surface to the top of the concrete pad; and depth to most shallow ground water measured using an electronic water level indicator pursuant to Subsection F of this section. The written log shall also include totalizing readings obtained from the downhole camera including the initial reading at the top of the well casing; depth to most shallow ground water using the borehole camera; depth of the top of the screened interval; depth of the bottom of screened interval; and the bottom of the well (total depth). The length of the screened interval shall be calculated by subtracting the depth of the top of the screened interval from the depth of the bottom of screened interval and recorded on the log.

(b) The video monitoring well camera log shall display the name of the dairy facility; discharge permit number; permittee's name; monitoring well identification; date and time of the monitoring well camera inspection; and the totalizing readings required by Subparagraph (g) of Paragraph (1) of this subsection. The permittee shall submit the video to the department in Motion Picture Experts Group (MPEG) video format on a compact disc (CD) or digital versatile disc (DVD).

NM. Proposed location of monitoring wells - dispute resolution. If the department provides a notice of technical deficiency pursuant to Subsection G of 20.6.6.10 NMAC due to a disagreement with the number or location of monitoring wells proposed in the application, or if the department notifies a permittee to replace a

monitoring well pursuant to Subsection C of 20.6.6.27 NMAC, the applicant or permittee may notify the secretary by certified mail, sent within 30 days after the date of postal notice of the department's notice, that the applicant or permittee invokes dispute resolution under this subsection. Upon such notice, the department, as represented by the secretary, deputy secretary, or division director and the applicant or permittee shall meet in person within 30 days and shall attempt in good faith to resolve the dispute.

[20.6.6.23 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.24 MONITORING REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. Monitoring reports - schedule of submittal. A permittee shall submit monitoring reports to the department on a quarterly schedule and shall contain monitoring data and information collected pursuant to the dairy rule. Quarterly monitoring reports shall be submitted according to the following schedule:

- (1) January 1 through March 31 (first quarter) - report due by May 1;
- (2) April 1 through June 30 (second quarter) - report due by August 1;
- (3) July 1 through September 30 (third quarter) - report due by November 1; and
- (4) October 1 through December 31 (fourth quarter) - report due by February 1.

B. Sampling and analysis methods. A permittee shall sample and analyze water pursuant to Subsection B of 20.6.2.3107 NMAC. Analysis of water for total sulfur shall be accomplished pursuant to environmental protection agency method 200.7 or equivalent. Sampling and analysis of soil shall be conducted in accordance with "*methods of soil analysis: part 1. physical and mineralogical methods*," 1986 edition; "*methods of soil analysis: part 2. microbiological and biochemical properties*," 1994 edition; and "*methods of soil analysis: part 3. chemical methods*," 1996 edition, published by the American society of agronomy.

C. Wastewater volume measurement and reporting. A permittee shall measure the volume of all wastewater discharged to the wastewater or combination wastewater/stormwater impoundment(s) using flow meters. Meter readings shall be recorded at intervals not to exceed ~~seven days~~ monthly. The average daily discharge volume for each recording interval shall be calculated by dividing the difference between the meter readings by the number of days between meter readings. The permittee shall provide the meter readings including the date, time and units of each measurement, and calculations for the average daily volumes of wastewater discharged to the impoundments, reported in gallons per day, in the quarterly monitoring reports submitted to the department.

D. Stormwater sampling and reporting. A permittee shall collect stormwater samples on a quarterly basis from each stormwater impoundment ~~unless the stormwater will be transferred. The samples shall be collected as soon as possible after a storm event and before transferring the stormwater~~ to a wastewater impoundment(s) ~~or before being sent to the land application area.~~ The samples shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, total sulfur and total dissolved solids pursuant to this section. The permittee shall include analytical results, or a statement that stormwater runoff did not occur, in the quarterly monitoring reports submitted to the department.

~~**E. Flow meter field calibration.** All flow meters shall be capable of having their accuracy ascertained under actual working (field) conditions. A field calibration method shall be developed for each flow meter and that method shall be used to check the accuracy of each respective meter. Field calibrations shall be performed upon installation and, at a minimum, annually thereafter. Flow meters shall be calibrated to within plus or minus 10 percent of actual flow, as measured under field conditions. Field calibrations shall be performed by an individual knowledgeable in flow measurement and in the installation/operation of the particular device in use. The permittee shall submit the results of annual field calibrations to the department annually in the monitoring reports due by May 1. The flow meter calibration report shall include the following:~~

- ~~(1) The location and meter identification nomenclature identified by the department through a discharge permit.~~
- ~~(2) The method of flow meter field calibration employed.~~
- ~~(3) The measured accuracy of each flow meter prior to adjustment indicating the positive or negative offset as a percentage of actual flow as determined by an in-field calibration check.~~
- ~~(4) The measured accuracy of each flow meter following adjustment, if necessary, indicating the positive or negative offset as a percentage of actual flow of the meter.~~
- ~~(5) Any flow meter repairs made during the previous year or during field calibration.~~

[20.6.6.24 NMAC - N, 01/31/2011]

20.6.6.25 ADDITIONAL MONITORING REQUIREMENTS FOR DAIRY FACILITIES WITH A LAND APPLICATION AREA:

A. Volume of wastewater and wastewater/stormwater land applied - measurement and

reporting. A permittee shall measure all wastewater discharges from a wastewater or combination wastewater/stormwater impoundment to each field within the land application area using flow meters. A permittee shall maintain a log recording the date and location of each discharge, flow meter readings immediately prior to and after each discharge, and the calculated total volume of each discharge reported in gallons and acre-feet. A permittee shall submit a copy of the log entries including units of measurement to the department in the quarterly monitoring reports.

B. Volume of stormwater land applied - measurement and reporting. A permittee shall measure all stormwater applications from a stormwater impoundment to each field within the land application area using flow meters. A permittee shall maintain a log recording the date and location of each application, flow meter readings immediately prior to and after each application, and the calculated total volume of each application reported in gallons and acre-feet. A permittee shall submit a copy of the log entries including units of measurement to the department in the quarterly monitoring reports.

C. Wastewater to be land applied - sampling and reporting. A permittee shall collect and analyze wastewater samples on a ~~quarterly~~ annual basis for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, total sulfur and total dissolved solids pursuant to Subsection B of 20.6.6.24 NMAC. Representative samples shall be collected from the wastewater impoundments unless an alternative method is approved for good cause, including safety. The representative samples shall consist of eight samples taken from eight different locations evenly distributed throughout the impoundment or using an alternative method approved by the department for good cause. A permittee shall submit the analytical results to the department in the quarterly monitoring reports.

D. Manure solids - nitrogen content. The nitrogen content of the manure solids applied to each field within the land application area shall be estimated at 25 pounds of nitrogen per ton. Should a permittee choose to use actual nitrogen content values of on-site manure solids, the permittee shall collect a composite sample on an annual basis. The composite sample shall consist of a minimum of 30 sub-samples collected on the same day and thoroughly mixed. Manure samples shall be analyzed for total Kjeldahl nitrogen and moisture content. The permittee shall submit the analytical results to the department in the quarterly monitoring reports.

E. Irrigation water - sampling, volume applied, and reporting. A permittee shall monitor irrigation wells used to supply fresh water to the fields within the land application area to account for additional potential nitrogen supplied to the land application area in the following manner.

(1) Each irrigation well shall be identified in association with the field(s) to which it supplies fresh water.

(2) ~~An annual~~ A sample of irrigation water supplied from each well or a group of wells if more than one well supplies a field shall be collected and analyzed for nitrate as nitrogen and total Kjeldahl nitrogen at least once every five years, pursuant to Subsection B of 20.6.6.24 NMAC.

(3) The annual volume of irrigation water applied to each field within the land application area shall be estimated ~~for each well.~~

(4) The permittee shall submit the analytical results and the estimated annual volume of irrigation water applied ~~from each well~~ to each field within the land application area to the department in the monitoring reports due by May 1.

F. Fertilizer application reporting. A permittee shall maintain a log of all additional fertilizer(s) applied to each field within the land application area. The log shall contain the date of fertilizer application, the type and form of fertilizer, fertilizer analysis, the amount of fertilizer applied in pounds per acre to each field, and the amount of nutrients applied in pounds per acre to each field. The permittee shall submit a copy of the log entries to the department in the quarterly monitoring reports.

G. Land application data sheets. A permittee shall complete land application data sheets for each field within the land application area to document the crop grown and amount of total nitrogen applied from wastewater, stormwater, manure solids, composted material, irrigation water and other additional fertilizer(s), and the residual soil nitrogen and nitrogen credits from leguminous crops. The permittee shall submit a land application data sheet or a statement that land application did not occur to the department in the quarterly monitoring reports. The land application data sheet shall include the following elements ~~from the previous six quarters.~~

(1) The total monthly volume, reported in acre-feet, of wastewater and stormwater applied to each field within the land application area. Total monthly volumes shall be obtained from flow meter readings of each application pursuant to Subsections A and B of this section.

(2) The total nitrogen concentration of wastewater and stormwater obtained from the corresponding quarterly analyses collected pursuant to Subsection C of this section and Subsection D of 20.6.6.24 NMAC.

(3) The total monthly volume, reported in tons per acre, of manure solids applied to each field within the land application area.

(4) The total nitrogen content of the manure solids estimated at 25 pounds of nitrogen per ton or determined from analysis of manure solids samples collected pursuant to Subsection D of this section.

(5) The total nitrogen concentration within the irrigation water and the amount of irrigation water applied pursuant to Subsection E of this section.

(6) The amount of nitrogen reported in pounds per acre from additional fertilizer(s) applied pursuant to Subsection F of this section.

(7) The amount of residual soil nitrogen and nitrogen from leguminous crops credited to each field within the land application area pursuant to Subsections K and L of this section.

H. Crop yield documentation. A permittee shall submit crop yield documentation and plant and harvest dates of each crop grown to the department in the quarterly monitoring reports. Crop yield documentation shall consist of copies of scale-weight tickets or harvest summaries based on scale-weights.

I. Nitrogen concentration of harvested crop. A permittee shall determine the total nitrogen concentration of each harvested crop. A composite sample consisting of 15 sub-samples of plant material shall be taken from each field during the final harvest of each crop grown per year. Samples shall be analyzed for percent total nitrogen and percent dry matter. A permittee shall submit the analytical reports to the department in the quarterly monitoring reports.

J. Nitrogen removal summary of harvested crop. A permittee shall develop a nitrogen removal summary to determine total nitrogen removed by each crop grown on each field within the land application area. Nitrogen removal shall be determined using crop yield and total nitrogen concentration information collected pursuant to Subsections H and I of this section. A permittee shall submit the summary to the department in the quarterly monitoring reports.

K. Soil sampling - initial event in a discharge permit term. A permittee shall collect composite soil samples from each field within the land application area for the first soil sampling event during the first year following the effective date of the discharge permit. Composite soil samples shall be collected ~~in the five-month period between September 1 and January 31~~ for all fields regardless of whether the field is cropped, remains fallow, or has received wastewater or stormwater. One surface composite soil sample (first-foot) and two sub-surface composite soil samples (second-foot and third-foot) shall be collected from each field. Composite soil samples shall be collected and analyzed according to the following procedure.

(1) Each surface and sub-surface soil sample shall consist of a single composite of 15 soil cores collected randomly throughout each field. Should a field consist of different soil textures (i.e., sandy and silty clay), a composite soil sample shall be collected from each soil texture within each field.

(2) Surface soil samples (first-foot) shall be collected from a depth of 0 to 12 inches.

(3) Each second-foot sub-surface soil sample shall be collected from a depth of 12 to 24 inches.

(4) Each third-foot sub-surface soil sample shall be collected from a depth of 24 to 36 inches.

(5) Each surface and sub-surface composite sample shall be analyzed for pH, electrical conductivity, total Kjeldahl nitrogen, nitrate as nitrogen, chloride, organic matter, potassium, phosphorus, sodium, calcium, magnesium, sulfate, soil texture, and sodium adsorption ratio.

(6) pH, electrical conductivity, sodium, calcium, magnesium, and sulfate shall be analyzed using a saturated paste extract in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC. Phosphorus shall be analyzed using the Olsen sodium bicarbonate method in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC. Nitrate as nitrogen shall be analyzed by a 2 molar KCl extract in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC. Total Kjeldahl nitrogen, chloride, organic matter, potassium, soil texture, and sodium adsorption ratio shall be analyzed in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC.

(7) The permittee shall submit the analytical results and a map showing the fields and the sampling locations within each field to the department in the monitoring report due by May 1 following the effective date of the discharge permit.

L. Soil sampling - routine. Beginning in the year following the initial soil sampling required by this section, the permittee shall collect annual soil samples from each field within the land application area that has received or is actively receiving wastewater or stormwater. ~~Composite soil samples shall be collected in the five-month period between September 1 and January 31.~~ For those fields that have never before received wastewater, the permittee shall collect soil samples immediately before initial wastewater application and annually thereafter. Once a field has received wastewater it shall be sampled annually regardless of whether the field is cropped, remains fallow, or has recently received wastewater or stormwater. One surface composite soil sample (first-foot) and two sub-surface composite soil samples (second-foot and third-foot) shall be collected from each field. Composite soil samples shall be collected and analyzed according to the following procedure.

(1) Each surface and sub-surface soil sample shall consist of a single composite of 15 soil cores collected randomly throughout each field. Should a field consist of different soil textures (i.e., sandy and silty clay), a composite soil sample shall be collected from each soil texture within each field.

(2) Surface soil samples (first-foot) shall be collected from a depth of 0 to 12 inches.

(3) Each second-foot sub-surface soil sample shall be collected from a depth of 12 to 24 inches.

(4) Each third-foot sub-surface soil sample shall be collected from a depth of 24 to 36 inches.

(5) Surface soil samples shall be analyzed for pH, electrical conductivity, nitrate as nitrogen, chloride, organic matter, potassium, phosphorus, sodium, calcium, magnesium, and sodium adsorption ratio.

(6) Sub-surface soil samples shall be analyzed for electrical conductivity, nitrate as nitrogen, and chloride.

(7) pH, electrical conductivity, sodium, calcium, and magnesium shall be analyzed using a saturated paste extract in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC. Phosphorus shall be analyzed using the Olsen sodium bicarbonate method in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC. Nitrate as nitrogen shall be analyzed by a 2 molar KCl extract in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC. Chloride, organic matter, potassium, and sodium adsorption ratio shall be analyzed in accordance with the analytical methodology required by Subsection B of 20.6.6.24 NMAC.

(8) The permittee shall submit the analytical results and a map showing the fields and the sampling locations within each field to the department in the monitoring report due by May 1.

[20.6.6.25 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.26 ADDITIONAL MONITORING REQUIREMENTS FOR DAIRY FACILITIES

DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: Wastewater to be evaporated - sampling and reporting. A permittee shall collect a composite wastewater sample on a semi-annual (once every six months) basis from each wastewater or combination wastewater/stormwater impoundment used for disposal by evaporation. ~~The composite sample from each impoundment shall consist of a minimum of six sub-samples collected around the entire perimeter of each impoundment and thoroughly mixed.~~ Samples shall be analyzed for nitrate as nitrogen, total Kjeldahl nitrogen, chloride, total sulfur and total dissolved solids pursuant to Subsection B of 20.6.6.24 NMAC. A permittee shall submit the analytical results to the department in the monitoring reports due by May 1 and November 1.

[20.6.6.26 NMAC - N, 01/31/2011]

20.6.6.27 CONTINGENCY REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. Exceedance of ground water standards - all monitoring wells ~~except impoundment monitoring wells~~. If the constituent concentration in a ground water sample and in the next ground water sample collected from the same monitoring well intended to monitor a contamination source other than an impoundment exceeds one or more of the ground water standards of 20.6.2.3103 NMAC and exceeds the concentration of such constituent(s) in a ground water sample collected from the upgradient monitoring well, then the permittee shall take the following actions. For the purpose of this subsection, ground water samples obtained from the source monitoring well and the upgradient monitoring well that are used for comparison of constituent concentrations shall be collected within two days of each other, provided that if there is sufficient ground water quality data to demonstrate that samples from different periods should be compared, the department may allow such a comparison. If ground water quality data for the upgradient monitoring well are not submitted by the permittee, the ground water standards of 20.6.2.3103 NMAC shall be the applicable standard used to determine if the requirements of this subsection must be met. The contingency requirements of Paragraphs (1) and (2) of this subsection shall not apply if corrective action previously has been taken to address ground water contamination and constituent concentrations have stabilized or improved, but this exception shall no longer apply if a constituent concentration increases for two consecutive sampling events and exceeds its standard or the upgradient concentration. Once enacted the contingency requirements of this subsection apply until the permittee has fulfilled the requirements of this subsection and ground water monitoring pursuant to 20.6.6.23 NMAC confirms for a minimum of eight consecutive ground water sampling events that the standards of 20.6.2.3103 NMAC are not exceeded and the total nitrogen concentration in ground water is less than or equal to 10 milligrams per liter or until the department requires an abatement plan pursuant to Paragraph (3) of this subsection.

(1) A corrective action plan shall be submitted within 120 days of the subsequent sample analysis date unless a petition for variance is filed in accordance with Paragraph (2) of this subsection. The corrective action plan shall describe any repairs made to address the cause of the exceedance, and propose source control measures

and a schedule for implementation. The implementation schedule shall include a schedule of all proposed corrective action activities and the date that corrective action will be completed. The department shall approve or disapprove the corrective action plan within 60 days of receipt. Within 30 days of the date of postal notice of the department's approval of the corrective action plan, the permittee shall initiate implementation of the plan. If the department does not approve the corrective action plan, the department shall notify the permittee of the deficiencies by certified mail. The permittee shall submit a revised corrective action plan to the department within 60 days of the date of postal notice of the notice of deficiency. The department shall approve or disapprove the corrective action plan within 60 days of receipt. If the department does not approve the revised corrective action plan, or if the permittee fails to submit a revised plan as required by this subsection, the department may pursue enforcement actions authorized by Section 74-6-10 NMSA 1978.

(2) The permittee may investigate potential sources of contamination that may have caused a standard(s) to be exceeded. If such an investigation indicates that the source of the contamination is not the source intended to be monitored by the well, the permittee may petition within 120 days of the subsequent sample analysis date for a variance from the requirements of this section in accordance with 20.6.2.1210 NMAC. It is the permittee's burden to prove any claim that the source of the contamination is not the source intended to be monitored by the well. If the petition is denied the permittee shall submit a corrective action plan meeting the requirements of Paragraph (1) of this subsection within 60 days of the denial.

(3) The permittee may be required to submit an abatement plan proposal pursuant to 20.6.2.4106 NMAC within 60 days of written notice from the department. Abatement shall be performed pursuant to 20.6.2.4101, 20.6.2.4103, 20.6.2.4104, and 20.6.2.4106 through 20.6.2.4115 NMAC.

~~**B. Exceedance of ground water standards—impoundment monitoring well.** If the constituent concentration in a ground water sample and in the next ground water sample collected from a monitoring well intended to monitor an impoundment(s) exceeds one or more of the ground water standards of 20.6.2.3103 NMAC and exceeds the concentration of such constituent(s) in a ground water sample collected from the upgradient monitoring well, then the permittee shall enact one of the following measures. For the purpose of this subsection, ground water samples obtained from the impoundment monitoring well and the upgradient monitoring well that are used for comparison of constituent concentrations shall be collected within two days of each other, provided that if there is sufficient ground water quality data to demonstrate that samples from different periods should be compared, the department may allow such a comparison. If ground water quality data for the upgradient monitoring well are not submitted by the permittee, the ground water standard(s) of 20.6.2.3103 NMAC shall be the applicable standard(s) used to determine if the requirements of this subsection must be met. The contingency requirements of Subparagraphs (a) through (c) of Paragraph (1) and Sub-subparagraphs (i) through (iii) of Sub-paragraph (a) of Paragraph (2) of this subsection shall not apply if corrective action previously has been taken to address ground water contamination and constituent concentrations have stabilized or improved, but this exception shall no longer apply if a constituent concentration increases for two consecutive sampling events and exceeds its standard or the upgradient concentration. Once enacted the contingency requirements of this subsection apply until the permittee has fulfilled the requirements of this subsection and ground water monitoring pursuant to 20.6.6.23 NMAC confirms for a minimum of eight consecutive ground water sampling events that the standards of 20.6.2.3103 NMAC are not exceeded and the total nitrogen concentration in ground water is less than or equal to 10 milligrams per liter or until the department requires an abatement plan pursuant to Subparagraph (d) of Paragraph (1) or Sub-subparagraph (iv) of Subparagraph (a) of Paragraph (2) of this subsection.~~

~~(1) Pre dairy rule liner not composed of 40/30 mil HDPE (minimum) or equivalent.~~ For impoundments using a liner installed prior to the effective date of the dairy rule and composed of a material that is not, at a minimum, 40 mil unreinforced HDPE, 30 mil reinforced HDPE, (or other material having equivalent characteristics with regard to permeability, resistance to degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and puncture resistance), the following actions shall be taken:

~~(a) A corrective action plan shall be submitted within 120 days of the subsequent sample analysis date unless a petition for variance is filed in accordance with Subparagraph (c) of this paragraph. The corrective action plan shall describe any repairs or changes in practices made to address the cause of the exceedance, and propose source control measures and a schedule for implementation. The implementation schedule shall include a schedule of all proposed corrective action activities and the date that corrective action will be completed. The department shall approve or disapprove the corrective action plan within 60 days of receipt. If the corrective action plan proposes actions to correct deficiencies with the liner, the proposed actions shall include the following items:~~

~~(i) A proposal for reconstruction and relining of an existing impoundment, or construction and lining of a new impoundment. Reconstruction or new construction shall be completed pursuant to~~

20.6.6.17 NMAC within one year of the subsequent sample analysis date. If a new impoundment is constructed, the existing impoundment shall be permanently closed pursuant to 20.6.6.30 NMAC.

(ii) Reconstruction or construction plans and specifications for the impoundment shall be completed pursuant to 20.6.6.17 NMAC.

(b) Within 30 days of the date of postal notice of the department's approval of the corrective action plan, the permittee shall initiate implementation of the plan. If the department does not approve the corrective action plan, the department shall notify the permittee of the deficiencies by certified mail. The permittee shall submit a revised correction action plan to the department within 60 days of the date of postal notice of the notice of deficiency. The department shall approve or disapprove the revised corrective action plan within 60 days of receipt. If the department does not approve the revised corrective action plan, or if the permittee fails to submit a revised plan as required by this subsection, the department may pursue enforcement actions authorized by Section 74-6-10 NMSA 1978.

(c) The permittee may investigate potential sources of contamination that may have caused a standard(s) to be exceeded. If such an investigation indicates that the source of the contamination is not the impoundment intended to be monitored by the well, the permittee may petition within 120 days of the subsequent sample analysis date for a variance from the requirements of this section in accordance with 20.6.2.1210 NMAC. It is the permittee's burden to prove any claim that the source of the contamination is not the impoundment intended to be monitored by the well. If the variance is denied the permittee shall submit a corrective action plan meeting the requirements of Subparagraph (a) of this paragraph within 60 days of the denial.

(d) The permittee may be required to submit an abatement plan proposal pursuant to 20.6.2.4106 NMAC within 60 days of written notice from the department. Abatement shall be performed pursuant to 20.6.2.4101, 20.6.2.4103, 20.6.2.4104, and 20.6.2.4106 through 20.6.2.4115 NMAC.

(2) **Dairy rule liner or pre-dairy rule liner composed of 40/30 mil (minimum) HDPE or equivalent.** For impoundments using a liner installed after the effective date of the dairy rule and composed of a material that is, at a minimum, 60 mil HDPE (or other material having equivalent characteristics with regard to permeability, resistance to degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and puncture resistance), or impoundments using a liner installed prior to the effective date of the dairy rule and composed of a material that is, at a minimum, 40 mil unreinforced HDPE, 30 mil reinforced HDPE, (or other material having equivalent characteristics with regard to permeability, resistance to degradation by ultraviolet light, compatibility with the liquids anticipated to be collected in the impoundment, tensile strength, and tear and puncture resistance), the following actions shall be taken.

(a) **Initial liner.** For impoundments where the existing liner is the initial liner installed, the following actions shall be taken.

(i) A corrective action plan shall be submitted within 120 days of the subsequent sample analysis date unless a petition for variance is filed in accordance with Sub-subparagraph (iii) of this subparagraph. The corrective action plan shall describe any repairs or changes in practices made to address the cause of the exceedance, and propose source control measures and a schedule for implementation. The implementation schedule shall include a schedule of all proposed corrective action activities and the date that corrective action will be completed. The department shall approve or disapprove the corrective action plan within 60 days of receipt. If the corrective action plan proposes actions to correct deficiencies with the liner, the proposed actions shall include repair or replacement of the existing liner, or construction and lining of a new impoundment. If liner repair is practicable, repairs shall be made pursuant to 20.6.6.17 NMAC or using a material that is equivalent to the existing liner with respect to material thickness and composition. Repairs shall be completed within 240 days of the subsequent sample analysis date. If liner repair is not practicable, the corrective action plan shall propose reconstruction and relining of the impoundment pursuant to 20.6.6.17 NMAC or construction and lining of a new impoundment pursuant to 20.6.6.17 NMAC within one year of the subsequent sample analysis date. Reconstruction or construction plans and specifications for the impoundment shall be completed pursuant to 20.6.6.17 NMAC and submitted with the corrective action plan. If a new impoundment is constructed the existing impoundment shall be closed pursuant to 20.6.6.30 NMAC.

(ii) Within 30 days of the date of postal notice of the department's approval of the corrective action plan, the permittee shall initiate implementation of the plan. If the department does not approve the corrective action plan, the department shall notify the permittee of the deficiencies by certified mail. The permittee shall submit a revised corrective action plan to the department within 60 days of the date of postal notice of the notice of deficiency. The department shall approve or disapprove the revised corrective action plan within 60 days of receipt. If the department does not approve the revised corrective action plan, or if the permittee fails to

submit a revised plan as required by this subsection, the department may pursue enforcement actions authorized by Section 74-6-10 NMSA 1978.

~~(iii) The permittee may investigate potential sources of contamination that may have caused a standard(s) to be exceeded. If such an investigation indicates that the source of the contamination is not the impoundment intended to be monitored by the well, the permittee may petition within 120 days of the subsequent sample analysis date for a variance from the requirements of this section in accordance with 20.6.2.1210 NMAC. It is the permittee's burden to prove any claim that the source of the contamination is not the impoundment intended to be monitored by the well. If the variance is denied the permittee shall submit a corrective action plan meeting the requirements of Sub-subparagraph (i) of this subparagraph within 60 days of the denial.~~

~~(iv) The permittee may be required to submit an abatement plan proposal pursuant to 20.6.2.4106 NMAC within 60 days of written notification from the department. Abatement shall be performed pursuant to 20.6.2.4101, 20.6.2.4103, 20.6.2.4104, and 20.6.2.4106 through 20.6.2.4115 NMAC.~~

~~(b) **Replacement liner.** If source control measures have been previously implemented such that the existing liner replaced a previously installed liner in an impoundment and ground water standard(s) of 20.6.2.3103 NMAC continue to be exceeded, such impoundments are authorized to continue to receive wastewater or stormwater pursuant to the following requirements:~~

~~(i) The permittee may be required to submit an abatement plan proposal pursuant to 20.6.2.4106 NMAC within 60 days of written notice from the department if abatement has not been previously implemented. Abatement shall be performed pursuant to 20.6.2.4101, 20.6.2.4103, 20.6.2.4104, and 20.6.2.4106 through 20.6.2.4115 NMAC.~~

~~(ii) If the results of abatement activities indicate that the replacement liner does not successfully control the source of contamination, the department may modify the discharge permit pursuant to Subsection E of 20.6.2.3109 NMAC and include additional conditions pursuant to Subsection H of 20.6.6.10 NMAC. The additional conditions shall address, but are not limited to, further source control measures. The requirements of 20.6.6.15 NMAC shall apply to hearing requests on the proposed additional discharge permit conditions.~~

CB. Monitoring well replacement. If information available to the department indicates that a monitoring well(s) required by 20.6.6.23 NMAC is not located hydrologically downgradient of the ~~contamination source~~dairy facility it is intended to monitor, is not completed pursuant to 20.6.6.23 NMAC or contains insufficient water to ~~effectively~~ monitor ground water quality effectively, a permittee shall install a replacement monitoring well(s). The replacement monitoring well(s) shall be installed within 120 days of the date of postal notice of notification from the department and a survey of the replacement monitoring well(s) shall be performed within 150 days of the date of postal notice of notification from the department, provided the department may grant an extension for good cause shown. The replacement monitoring well(s) shall be located, installed, completed, surveyed and sampled pursuant to 20.6.6.23 NMAC. The permittee shall develop a monitoring well completion report pursuant to Subsection J of 20.6.6.23 NMAC and submit it to the department within 180 days of the date of postal notice of notification from the department, provided the department may grant an extension for good cause shown.

DC. Exceedances of permitted maximum daily discharge volume. If the maximum daily discharge volume authorized by the discharge permit is exceeded by more than ten percent for any four average daily discharge volumes within any 12-week period, the permittee shall submit within 60 days of the fourth exceedance: a corrective action plan for reducing the discharge volume; or an application for a modified or renewed and modified discharge permit pursuant to 20.6.6.10 NMAC. Within 30 days of postal notice of department approval, the permittee shall initiate implementation of the corrective action plan.

ED. Insufficient impoundment capacity. If a survey, capacity calculations, or settled solids thickness measurements, indicate an existing impoundment is not capable of meeting the capacity requirements required by Subsection D of 20.6.6.17 NMAC, then within 90 days of the effective date of the discharge permit the permittee shall submit a corrective action plan for department approval. The plan may include, but is not limited to, proposals for constructing an additional impoundment, reducing the discharge volume, removing accumulated solids, changing wastewater or stormwater management practices, or installing an advanced treatment system. The corrective action plan shall include a schedule for implementation through completion of corrective actions. The corrective action plan schedule shall propose completion not to exceed one year from the submittal date of the initial corrective action plan. Within 30 days of the date of postal notice of the department's approval of the corrective action plan, the permittee shall initiate implementation of the plan. Should the corrective action plan include removal of accumulated solids, solids shall be removed from the impoundment in a manner that is protective of the impoundment liner. The plan shall include the method of removal, and locations and methods for storage and

disposal of the solids-slurry. If the plan proposes land application of the solids-slurry, the plan must also include the analytical results of total Kjeldahl nitrogen and chloride obtained from a representative sample of the solids-slurry to be applied. Notwithstanding Paragraph (6) of Subsection D of 20.6.6.17 NMAC, if a corrective action plan required under this subsection calls for construction of a new wastewater impoundment or improvement of an existing wastewater impoundment, and ground water quality standards have not been exceeded in monitoring wells installed to monitor the existing impoundment for the four quarters preceding submission of the corrective action plan, the permittee may propose and the department may approve a liner for the new wastewater impoundment or improvement of the existing impoundment consistent with the liner design approved by the department at the time of the last discharge permit issued by the department before the effective date of the dairy rule.

FE. Inability to preserve required freeboard. If a minimum of two feet of freeboard cannot be preserved in the wastewater impoundment, the permittee shall submit a corrective action plan to the department for approval. The corrective action plan shall be submitted within 30 days of the date of the initial exceedance of the freeboard requirement. The plan may include, but is not limited to, proposals for constructing an additional impoundment, reducing the maximum daily discharge volume, changing wastewater management practices, or installing an advanced wastewater treatment system. The corrective action plan shall include actions to be immediately implemented to regain and maintain a minimum of two feet of freeboard until permanent corrective actions have been completed. The corrective action plan shall include a schedule for implementation through completion of corrective actions. The corrective action plan schedule shall propose completion not to exceed one year from the submittal date of the initial corrective action plan. Within 30 days of the date of postal notice of the department's approval of the corrective action plan, the permittee shall initiate implementation of the plan. Notwithstanding Paragraph (6) of Subsection D of 20.6.6.17 NMAC, if a corrective action plan required under this subsection calls for construction of a new wastewater impoundment or improvement of an existing wastewater impoundment, and ground water quality standards have not been exceeded in monitoring wells installed to monitor the existing impoundment for the four quarters preceding submission of the corrective action plan, then the permittee may propose and the department may approve a liner for the new wastewater impoundment or improvement of the existing impoundment consistent with the liner design approved by the department at the time of the last discharge permit issued by the department before the effective date of the dairy rule.

GF. Impoundment - structural integrity compromised. Within 24 hours of discovery, a permittee shall report to the department, any damage to the berms or the liner of an impoundment or any condition that exists that may compromise the structural integrity of the impoundment. Within 15 days of the reported discovery, the permittee shall submit to the department a corrective action plan describing any actions taken or proposed to be taken to repair the damage or condition. Within 30 days of receipt, the department shall respond to the proposed corrective action plan. Repairs to the impoundment liner or berms shall be completed pursuant to 20.6.6.17 NMAC. The corrective action plan shall include a schedule for implementation through completion of corrective actions. The corrective action plan schedule shall propose completion not to exceed one year from the submittal date of the initial corrective action plan. The schedule of corrective actions shall be commensurate to the magnitude and scope of the activities to be completed. Within 30 days of the date of postal notice of the department's approval of the corrective action plan, the permittee shall initiate implementation of the plan. Notwithstanding Paragraph (6) of Subsection D of 20.6.6.17 NMAC, if a corrective action plan required under this subsection calls for construction of a new wastewater impoundment or improvement of an existing wastewater impoundment, and ground water quality standards have not been exceeded in monitoring wells installed to monitor the existing impoundment for the four quarters preceding submission of the corrective action plan, then the permittee may propose and the department may approve a liner for the new wastewater impoundment or improvement of the existing impoundment consistent with the liner design approved by the department at the time of the last discharge permit issued by the department before the effective date of the dairy rule.

HG. Unauthorized discharge - reporting and correction. In the event of a spill or release that is not authorized by the discharge permit, the permittee shall notify the department and take corrective actions pursuant to 20.6.2.1203 NMAC. Wastewater or stormwater shall be contained and pumped to a permitted sump, impoundment, or land application area pursuant to the dairy rule. Wastewater or stormwater applied to the land application area shall conform to the requirements of 20.6.6.21 and 20.6.6.25 NMAC. The permittee shall repair or replace failed components within 48 hours from the time of failure or as soon as practicable.
[20.6.6.27 NMAC - N, 01/31/2011; A, 12/31/2011]

20.6.6.28 [RESERVED]

20.6.6.29 ADDITIONAL CONTINGENCY REQUIREMENTS FOR DAIRY FACILITIES

DISCHARGING TO AN EVAPORATIVE WASTEWATER DISPOSAL SYSTEM: Inability to maintain required freeboard. If a combination wastewater/stormwater impoundment used for disposal by evaporation does not have free capacity below the two-foot freeboard level required by Subsection D of 20.6.6.17 NMAC, then within seven days of the date of discovery of insufficient free capacity the permittee shall submit a corrective action plan for department approval. The plan shall include, but is not limited to, a request for temporary permission to discharge to allow immediate removal and disposal of combined wastewater and stormwater; a proposal for long-term corrective actions which may include constructing an additional impoundment; reducing the discharge volume; changing wastewater or stormwater management practices; or installing an advanced treatment system. The corrective action plan shall include schedule for implementation to complete corrective actions within one year from the submittal date of the initial corrective action plan. Upon department approval, the permittee shall initiate implementation of the corrective action plan.

[20.6.6.29 NMAC - N, 01/31/2011]

20.6.6.30 CLOSURE REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. Permanent closure of dairy facility or impoundments. The following closure actions shall be performed at dairy facilities.

(1) For permanent closure of a dairy facility.

(a) The department shall be notified no later than 30 days after wastewater discharge has permanently ceased at the dairy facility.

(b) Installation of ~~all~~ any additional monitoring wells shall be completed pursuant to 20.6.6.23 NMAC.

(c) All wastewater and combination wastewater/stormwater impoundments shall be emptied within six months of permanently ceasing wastewater discharge at the dairy facility; combination wastewater/stormwater impoundments may continue to receive stormwater after removal of the impounded wastewater/stormwater. All stormwater and combination wastewater /stormwater impoundments shall be emptied of stormwater within one year of ~~removing all livestock from the dairy facility~~ cessation of wastewater discharge. Wastewater and stormwater removed from impoundments shall be applied to the designated land application area, as authorized by a discharge permit. In the event that land application is not authorized by a discharge permit, a disposal plan shall be submitted for department approval and the plan implemented upon department approval.

(d) Manure solids and compost shall be removed from surface areas at the dairy facility and applied to the designated land application area, as authorized by a discharge permit, or transferred off-site for proper disposal ~~within one year of removing all livestock from the facility~~.

(e) Complete removal of manure solids from the wastewater impoundment(s) shall be achieved within two years of permanently ceasing wastewater discharge. Complete removal of manure solids from the stormwater and combination wastewater/stormwater impoundment(s) shall be achieved within two years of ~~removing all livestock from the dairy facility~~ cessation of wastewater discharge. Manure solids shall be applied to the designated land application area, as authorized by a discharge permit. In the event that land application is not authorized by a discharge permit, a disposal plan shall be submitted for department approval and the plan implemented upon department approval.

(f) Impoundment liners shall be perforated or removed and the impoundments shall be re-graded with clean fill to blend with surface topography to prevent ponding within two years of permanently ceasing wastewater discharge ~~and removing all livestock from the facility~~.

(2) For closure of an impoundment at a facility not undergoing permanent closure (e.g., existing impoundment replaced with new impoundment).

(a) Impoundments shall be emptied of wastewater and stormwater within six months of ceasing receipt of wastewater or stormwater into the impoundments. Wastewater and stormwater removed from impoundments shall be applied to the designated land application area, as authorized by a discharge permit. If land application is not authorized by a discharge permit, a disposal plan shall be submitted for department approval and the plan implemented upon department approval.

(b) Complete removal of manure solids from impoundments shall be achieved within two years of ceasing receipt of wastewater or stormwater into the impoundments. Manure solids shall be applied to the designated land application area, as authorized by a discharge permit. If land application is not authorized by a discharge permit, a disposal plan shall be submitted for department approval and the plan implemented upon department approval.

(c) Liners in impoundments shall be perforated or removed and the impoundments shall be regraded with clean fill to blend with surface topography to prevent ponding within two years of ceasing receipt of wastewater or stormwater into the impoundments.

B. Post-closure ground water sampling and reporting. Following completion and confirmation by the department of the requirements of Subsection A of this section, ground water monitoring shall continue pursuant to 20.6.6.23 NMAC until a minimum of eight consecutive ground water sampling events confirm that the standards of 20.6.2.3103 NMAC are not exceeded and the total nitrogen concentration in ground water is less than or equal to 10 milligrams per liter. If monitoring results show that one or more of the standards of 20.6.2.3103 NMAC is exceeded or the total nitrogen concentration in ground water is greater than 10 milligrams per liter, the permittee shall implement contingency requirements pursuant to 20.6.6.27 NMAC. Upon notification from the department that post-closure ground water monitoring may cease, the permittee shall abandon all monitoring wells and submit a report to the department pursuant to Subsection C of this section.

C. Monitoring well abandonment. Upon notification from the department, the permittee shall abandon monitoring wells pursuant to 19.27.4 NMAC and the following requirements.

(1) The well casing shall be removed and neat cement grout, bentonite based plugging material, or other sealing material approved by the state engineer in accordance with 19.27.4 NMAC shall be placed from the bottom of the borehole to the ground surface using a tremmie pipe.

(2) If the casing cannot be removed, neat cement grout, bentonite based plugging material, or other sealing material approved by the state engineer in accordance with 19.27.4 NMAC shall be emplaced in the well using a tremmie pipe from the bottom of the well to the ground surface.

(3) A well abandonment report shall be prepared by the permittee and shall provide information equivalent to the plugging record requirements of 19.27.4 NMAC. The well abandonment report shall be submitted to the department within 60 days of completion of well plugging activities.

~~**D. Discontinuance of ground water monitoring—former impoundments.** Ground water monitoring conducted at previously used impoundments pursuant to Subsection A of 20.6.6.23 NMAC may be discontinued following closure of the impoundment pursuant to Subsection A of this section. Upon the achievement of a minimum of eight consecutive ground water sampling events following completion of closure confirming the conditions of Paragraphs (1) and (2) of this subsection, the permittee may request approval to discontinue ground water monitoring at previously used impoundments. Upon approval from the department, the permittee shall abandon the monitoring wells pursuant to Subsection C of this section.~~

~~(1) Ground water samples from the monitoring wells used to monitor the former impoundments confirm that the standards of 20.6.2.3103 NMAC are not exceeded.~~

~~(2) The total nitrogen concentration in ground water samples from monitoring wells used to monitor the former impoundments confirm that the total nitrogen concentration in ground water does not exceed 10 milligrams per liter.~~

~~**E. Discontinuance of ground water monitoring—former fields.** Ground water monitoring conducted at previously used fields within a land application area pursuant to Subsection A of 20.6.6.23 NMAC may be discontinued following cessation of land application of wastewater or stormwater to the field(s). Upon the achievement of a minimum of eight consecutive ground water sampling events following cessation of land application of wastewater or stormwater confirming the conditions of Paragraphs (1) and (2) of this subsection, the permittee may request approval to discontinue ground water monitoring at previously used fields. Upon approval from the department, the permittee shall abandon the monitoring wells pursuant to Subsection C of this section.~~

~~(1) Ground water samples from the monitoring wells used to monitor the former fields confirm that the standards of 20.6.2.3103 NMAC are not exceeded.~~

~~(2) The total nitrogen concentration in ground water samples from monitoring wells used to monitor the former fields confirm that the total nitrogen concentration in ground water does not exceed 10 milligrams per liter.~~

[20.6.6.30 NMAC - N, 01/31/2011]

20.6.6.31 [RESERVED]

20.6.6.32 [RESERVED]

20.6.6.33 RECORD RETENTION REQUIREMENTS FOR ALL DAIRY FACILITIES:

A. A permittee shall retain a written record at the dairy facility of all data and information related to field measurements, sampling, and analysis conducted pursuant to the dairy rule and the discharge permit. The

following information shall be recorded and shall be made available to the department upon request.

- (1) The dates, exact place and times of sampling or field measurements.
- (2) The name and job title of the individuals who performed each sample collection or field measurement.
- (3) The date of the analysis of each sample.
- (4) The name and address of the laboratory and the name and job title of the person that performed the analysis of each sample.
- (5) The analytical technique or method used to analyze each sample or take each field measurement.
- (6) The results of each analysis or field measurement, including raw data.
- (7) The results of any split, spiked, duplicate or repeat sample.
- (8) A description of the quality assurance and quality control procedures used.

B. A permittee shall retain a written record at the dairy facility of any spills, seeps, or leaks of effluent, and of leachate or process fluids not authorized by the discharge permit. Records shall be made available to the department upon request.

C. A permittee shall retain a written record at the dairy facility of the operation, maintenance, and repair of all features/equipment used to treat, store or dispose of wastewater, measure flow rates, monitor water quality, or collect other data. Records shall include repair, replacement or calibration of any monitoring equipment and repair or replacement of any equipment used in the waste or wastewater treatment and disposal system. Records shall be made available to the department upon request.

D. A permittee shall retain records of all monitoring information at the dairy facility, including all calibration and maintenance records, copies of all reports, and the application for the discharge permit. Records shall be retained for a period of at least 10 years from the date of the sample collection, measurement, report or application.

[20.6.6.33 NMAC - N, 01/31/2011]

20.6.6.34 TRANSFER OF DAIRY DISCHARGE PERMITS:

A. Transfer of discharge permits for dairy facilities shall be made pursuant to 20.6.2.3111 NMAC and this section.

B. The transferee(s) shall notify the department, in writing, of the date of transfer of ownership and provide contact information for the new owner(s) pursuant to Subsection B of 20.6.6.11 NMAC and Subsection B of 20.6.6.12 NMAC. Notification shall be submitted to the department of the transfer within 30 days of the ownership transfer date.

[20.6.6.34 NMAC - N, 01/31/2011]

20.6.6.35 CONTINUING EFFECT OF PRIOR ACTIONS DURING TRANSITION:

A. A discharge permit issued pursuant to 20.6.2.3109 NMAC that has not expired on or before the effective date of the dairy rule shall remain in effect and enforceable pursuant to the conditions of the discharge permit and for its term as designated by Section 74-6-5 NMSA 1978. If an effective discharge permit contains a permit condition with a time period for submittal of a renewal application that is different from the time period contained in Subsection A of 20.6.6.10 NMAC that condition will remain in effect for two years following the effective date of the dairy rule.

B. An application for a new discharge permit or an application for a renewed or modified discharge permit submitted to the department before the effective date of the dairy rule shall be processed by the department if the application has been deemed administratively complete and the requirements of Subsection D of 20.6.2.3108 NMAC have been satisfied. The applicant shall submit a permit fee payment equal to one-half of the applicable permit fee from table 1 of 20.6.2.3114 NMAC within 90 days of the effective date of the dairy rule.

C. If a discharge permit for a dairy facility is expired on the effective date of the dairy rule and an application for renewal has not been received by the department, the permittee, owner of record of the dairy facility or the holder of the expired discharge permit:

(1) shall within 90 days of the effective date of the dairy rule submit to the department an application for a discharge permit renewal, renewal and modification or closure pursuant to 20.6.6.10 NMAC and a filing fee and permit fee payment pursuant to 20.6.6.9 NMAC; or

(2) if the dairy facility has not been constructed or operated, the permittee, the owner of record of the dairy facility or the holder of the expired discharge permit may submit a statement to the department instead of an application for renewal certifying that the facility has not been constructed or operated and that no discharges have occurred. Upon the department's verification of the certification, the department shall retire the discharge permit

number from use.

D. The department shall process submissions meeting the requirements of Subsections B and C of this section according to the following schedule and subject to the public notice requirements of 20.6.2.3108 NMAC. If the department issues a discharge permit, the permittee shall have ninety days from the effective date of the discharge permit to submit all the necessary information to comply with 20.6.6.10 through 20.6.6.13 NMAC.

(1) For a new discharge permit application or for a renewal application for a discharge permit whose term ended on or before December 31, 2005, the department shall propose approval of a discharge permit or disapproval of an application within 90 days of the effective date of the dairy rule. The department shall notify the applicant of the proposed action by certified mail.

(2) For a renewal application for a discharge permit whose term ended in calendar year 2006, the department shall propose approval of a discharge permit or disapproval of an application within 180 days of the effective date of the dairy rule. The department shall notify the applicant of the proposed action by certified mail.

(3) For a renewal application for a discharge permit whose terms ended in calendar year 2007, the department shall propose approval of a discharge permit or disapproval of an application within 270 days of the effective date of the dairy rule. The department shall notify the applicant of the proposed action by certified mail.

(4) For a renewal application for a discharge permit whose terms ended in calendar year 2008, the department shall propose approval of a discharge permit or disapproval of an application within 360 days of the effective date of the dairy rule. The department shall notify the applicant of the proposed action by certified mail.

(5) For a renewal application for a discharge permits whose term ended in calendar year 2009, the department shall propose approval of a discharge permit or disapproval of an application within 450 days of the effective date of the dairy rule. The department shall notify the applicant of the proposed action by certified mail.

(6) For a renewal application for a discharge permit whose term ended on or after January 1, 2010, but before the effective date of the dairy rule, the department shall propose approval of a discharge permit or disapproval of an application within 540 days of the effective date of the dairy rule. The department shall notify the applicant of the proposed action by certified mail.

E. Any dairy facility discharging, capable of recommencing discharging, or that has ceased discharging within the term of its most recent discharge permit shall continue all monitoring and submittal of monitoring reports as prescribed in the most recent discharge permit until the department issues a renewed or renewed and modified discharge permit.

F. Any discharge permit proposed for approval (i.e., draft discharge permit) by the department pursuant to 20.6.2.3109 NMAC, but not made final before the effective date of the dairy rule, is withdrawn. Any permit fee submitted before the withdrawal of such a draft discharge permit shall be applied towards the permit fee for the permit issued pursuant to the dairy rule.

[20.6.6.35 NMAC - N, 01/31/2011]

HISTORY of 20.6.6 NMAC: [RESERVED]